


# RF EXPOSURE EVALUATION REPORT

**FCC ID** : Q3K-5XACULCHG  
**Equipment** : 5 GHz Outdoor PtP/PtMP High Gain Radio Unit  
**Brand Name** : RADWIN 2000, RADWIN 5000  
**Model Name** : Alpha INT, SU-Air INT, SU-Pro INT  
**Applicant** : Radwin Ltd.  
Habarzel 27 Tel Aviv ISRAEL  
**Manufacturer** : Radwin Ltd.  
Habarzel 27 Tel Aviv ISRAEL  
**Standard** : 47 CFR Part 1.1310

We, SPORTON INTERNATIONAL INC., have evaluated the device in accordance with 47 CFR Part 1.1310. The device complies with the required limit.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

<b>1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....</b>	<b>4</b>
<b>2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS .....</b>	<b>5</b>
<b>3. RF EXPOSURE LIMIT INTRODUCTION .....</b>	<b>6</b>
<b>4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....</b>	<b>6</b>
4.1. Standalone Power Density Calculation .....	6





**1. Description of Equipment Under Test (EUT)**

Product Feature & Specification	
EUT Type	5 GHz Outdoor PtP/PtMP High Gain Radio Unit
Brand Name	RADWIN 2000, RADWIN 5000
Model Name	Alpha INT, SU-Air INT, SU-Pro INT
FCC ID	Q3K-5XACULCHG
Wireless Technology and Frequency Range	WLAN 5.3GHz Band: 5260 MHz ~ 5330 MHz WLAN 5.5GHz Band: 5490 MHz ~ 5705 MHz
Mode	WLAN 5GHz: 20MHz/40MHz/80MHz
EUT Stage	Identical Prototype
<b>Remark:</b> 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. 2. Enable WLAN 5.3GHz/5.5GHz RF Exposure Evaluation, and the other frequency band please refer to Sporton Report No.: FA803134.	

**Reviewed by: Jason Wang**

**Report Producer: Daisy Peng**



**2. Maximum RF average output power among production units**

Band / Channel / Frequency (MHz)		Average Power (dBm)		
5.3GHz WLAN (U-NII-2A)	Ch.BW	20MHz	40MHz	80MHz
	5260	6		
	5270		8	
	5290			8
	5295			8
	5300	6	8	5
	5320		8	
	5330	6		

Band / Channel / Frequency (MHz)		Average Power (dBm)		
5.5GHz WLAN (U-NII-2C)	Ch.BW	20MHz	40MHz	80MHz
	5490	6		
	5500		8	
	5525			8
	5560			8
	5580		8	
	5590	6		
	5675			5
	5695		5	
	5705	4		



### **3. RF Exposure Limit Introduction**

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 70 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

### **4. Radio Frequency Radiation Exposure Evaluation**

#### **4.1. Standalone Power Density Calculation**

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 70cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
5.3GHz WLAN	5260.0	22.00	8.00	30.000	1.000	1000.000	0.016	1.000
5.5GHz WLAN	5490.0	22.00	8.00	30.000	1.000	1000.000	0.016	1.000

#### **Conclusion:**

According to 47 CFR §1.1310, the RF exposure analysis concludes that the RF Exposure is FCC compliant.