



REGULATORY COMPLIANCE REPORT

FCC CFR 47 Part 1.1310

Report No.: RDWN92-U3 Rev A (FCC MPE)

Company: Radwin

Model Name: AP0263510, AP0263511, AP0263530,
AP0263540, AP0279700, AP0279710, AP0279720,
SUAG00

REGULATORY COMPLIANCE REPORT

Company Name: Radwin

Model Name: AP0263510, AP0263511, AP0263530, AP0263540, AP0279700,
AP0279710, AP0279720, SUAG00

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN92-U3 Rev A (FCC MPE)

This report supersedes: NONE

Applicant: Radwin
27 Habarzel Street
Tel Aviv, 6971039
Israel

Issue Date: 21st September 2023

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

1. MAXIMUM PERMISSIBLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the Occupational/Controlled Exposure the limit of power density is 5 mW/cm².

The calculations in the table below use the highest conducted power values together with the lowest and highest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
4940-4990	15.0	31.62	25.14	326.59	2.05	5.0	12.82
4940-4990	32.0	1584.89	23.99	250.61	79.02	5.0	79.51

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310 for Occupational/Controlled Exposure.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com