

Company: RADWIN Ltd.

Test of: RADWIN 2000 Jet, RADWIN 5000 Jet

To: FCC CFR 47 Part 1.1310

Report No.: RDWN47-U4\_MPE\_FCC Rev A (non-DFS)

**MPE/RF EXPOSURE TEST REPORT**



# MPE/RF EXPOSURE TEST REPORT

FROM



Test of: RADWIN 2000 Jet, RADWIN 5000 Jet

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN47-U4\_MPE\_FCC Rev A

This report supersedes: NONE

Applicant: Radwin Ltd.  
27 Habarzel Street  
Tel Aviv 69710  
Israel

Issue Date: 26<sup>th</sup> November 2017

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4*\pi*d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10 ^ (G \text{ (dBi)}/10)$$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Maximum Permissible Exposure

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm <sup>2</sup> ) @ Safe Distance
5150.00 – 5250.00	11.00	12.59	23.54	225.94	0.566	1.00	15.05	1.00
5725.00 – 5850.00	11.00	12.59	29.99	997.70	2.499	1.00	31.62	1.00

Note: for mobile or fixed location transmitters the minimum separation distance is 20m, even if calculations indicate the MPE distance to be less.

### Specification - Maximum Permissible Exposure Limits (MPE)

**TABLE 1—LIMITS**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	--	--	f/300	6
1,500-100,000	--	--	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	--	--	f/1500	30
1,500-100,000	--	--	1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)