

Company: RADWIN Ltd.

Test of: RADWIN 5000 JET 5.x GHz

To: FCC Part 15 Subpart E 15.407 & ISSED RSS-247 Issue 2

Report No.: RDWN65-U2 Rev B (non-DFS Bands)

**TEST REPORT**



# COMBINED TEST REPORT

FROM



Test of: RADWIN 5000 JET 5.x GHz

To: FCC CFR 47 Part 15 Subpart E 15.407 & ISED RSS-247 Issue 2

Test Report Serial No.: RDWN65-U2 Rev B (non-DFS Bands)

This report supersedes: RDWN65-U4 Rev A (non-DFS Bands)

Applicant: RADWIN Ltd.  
27 Habarzel Street  
Tel Aviv 69710  
Israel

Product Function: 5 GHz Beamforming Outdoor  
Radio Device

Issue Date: 21<sup>st</sup> January 2022

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



---

## Table of Contents

<b>1. ACCREDITATION, LISTINGS &amp; RECOGNITION</b> .....	<b>4</b>
1.1. TESTING ACCREDITATION.....	4
1.2. RECOGNITION .....	5
1.3. PRODUCT CERTIFICATION .....	6
<b>2. DOCUMENT HISTORY</b> .....	<b>7</b>
<b>3. TEST RESULT CERTIFICATE</b> .....	<b>8</b>
<b>4. REFERENCES AND MEASUREMENT UNCERTAINTY</b> .....	<b>9</b>
4.1. Normative References .....	9
4.2. Test and Uncertainty Procedure .....	10
<b>5. PRODUCT DETAILS AND TEST CONFIGURATIONS</b> .....	<b>11</b>
5.1. Technical Details .....	11
5.2. Scope Of Test Program .....	12
5.3. Equipment Model(s) and Serial Number(s) .....	13
5.4. Antenna Details .....	13
5.5. Cabling and I/O Ports .....	13
5.6. Test Configurations.....	13
5.7. Equipment Modifications .....	14
5.8. Deviations from the Test Standard .....	14
<b>6. TEST SUMMARY</b> .....	<b>15</b>
<b>7. TEST EQUIPMENT CONFIGURATION(S)</b> .....	<b>16</b>
7.1. Radiated Emissions - 3m Chamber .....	16
<b>8. MEASUREMENT AND PRESENTATION OF TEST DATA</b> .....	<b>18</b>
<b>9. TEST RESULTS</b> .....	<b>19</b>
9.1. 26 dB & 99% Bandwidth .....	19
9.2. 6 dB & 99% Bandwidth .....	24
9.3. Peak Transmit Power .....	29
9.4. Power Spectral Density .....	39
9.5. Radiated .....	49
9.5.1. <i>TX Spurious &amp; Restricted Band Emissions</i> .....	52
9.5.1.1. RADWIN Ltd. SA0183620 11 dBi.....	52
9.5.1.2. RADWIN Ltd. SA0183620 20.50 dBi.....	58
9.5.2. <i>Restricted Edge &amp; Band-Edge Emissions</i> .....	61
9.5.2.3. RADWIN Ltd. SA0183620 11 dBi.....	61
9.5.2.4. RADWIN Ltd. SA0183620 20.50 dBi.....	74
<b>A. APPENDIX - GRAPHICAL IMAGES</b> .....	<b>83</b>
A.1. 26 dB & 99% Bandwidth .....	84
A.2. 6 dB & 99% Bandwidth .....	95
A.3. Power Spectral Density .....	107
A.4. Radiated .....	153
A.4.1. <i>TX Spurious &amp; Restricted Band Emissions</i> .....	153
A.4.1.1. RADWIN Ltd. SA0183620 11 dBi .....	153
A.4.1.2. RADWIN Ltd. SA0183620 20.5 dBi .....	159
A.4.2. <i>Restricted Edge &amp; Band-Edge Emissions</i> .....	162
A.4.2.3. RADWIN Ltd. SA0183620 11 dBi .....	162
A.4.2.4. RADWIN Ltd. SA0183620 20.5 dBi .....	173

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

## 1. ACCREDITATION, LISTINGS & RECOGNITION

### 1.1. TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard ISO/IEC 17025:2005. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



## Accredited Laboratory

A2LA has accredited

**MICOM LABS**

Pleasanton, CA

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 14<sup>th</sup> day of January 2022.



Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 2381.01  
Valid to November 30, 2023

*For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.*

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



## 1.2. RECOGNITION

MiCOM Labs, Inc has widely recognized wireless testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA countries. MiCOM Labs test reports are accepted globally.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	US0159 Listing #: 4143A-2 4143A-3
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	APEC MRA 2	RCB 210
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

EU MRA – European Union Mutual Recognition Agreement.

NB – Notified Body

APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement. Recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

### 1.3. PRODUCT CERTIFICATION

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard ISO/IEC 17065:2012. The company is accredited by the American Association for Laboratory Accreditation (A2LA) [www.a2la.org](http://www.a2la.org) test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



## Accredited Product Certification Body

A2LA has accredited

**MiCOM LABS**

Pleasanton, CA

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC 17065:2012 *Requirements for bodies certifying products, processes and services*. This product certification body also meets the A2LA R322 – *Specific Requirements – Notified Body Accreditation Requirements* and A2LA R308 - *Specific Requirements - ISO-IEC 17065 - Telecommunication Certification Body Accreditation Program*. This accreditation demonstrates technical competence for a defined scope and the operation of a management system.



Presented this 14<sup>th</sup> day of January 2022



Vice President, Accreditation Services  
For the Accreditation Council  
Certificate Number 2381.02  
Valid to November 30, 2023

*For the product certification schemes to which this accreditation applies, please refer to the organization's Product Certification Scope of Accreditation.*

United States of America – Telecommunication Certification Body (TCB)  
Industry Canada – Certification Body, CAB Identifier – US0159  
Europe – Notified Body (NB), NB Identifier - 2280  
Japan – Recognized Certification Body (RCB), RCB Identifier - 210

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 7 of 181

## 2. DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft	12 <sup>th</sup> December	Device pcb was updated and as a result the Digital and ac Wireline Emission profile changed. A retest of these parameters was required.  Client supplied third-party report covering updated emission retest. The following Sections of the previous test report (RDWN47-U4 Rev B) were removed and the report re-issued as RDWN65-U2.  Section 9.5.3 Digital Emissions
Rev A	17 <sup>th</sup> December 2019	This report supersedes RDWN47-U4 Rev B
Rev B	21 <sup>st</sup> January 2022	Report amendment per ISED request, retesting performed with verified results V's original test program.
This report was originally issued as RDWN47-U4 Rev B for a module		
Draft	2 <sup>nd</sup> November 2017	Program undertaken to test the following; a).. Full testing 5725 – 5850 MHz band test for compliance to new FCC mask b).. add new antennas
Draft #2	15 <sup>th</sup> November 2017	
Rev A	26 <sup>th</sup> November 2017	Initial Release
Rev B	30 <sup>th</sup> November 2017	Updated Section 5.4 Antenna Details
This report was originally issued as RDWN39-U8 for a module		
Rev A	8 <sup>th</sup> December 2015	Initial Release

In the above table the latest report revision will replace all earlier versions.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 8 of 181

### 3. TEST RESULT CERTIFICATE

<b>Manufacturer:</b> Radwin 27 Habarzel Street Tel Aviv 69710 Israel	<b>Tested By:</b> MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
<b>Model:</b> RADWIN 5000 JET 5.x GHz	<b>Telephone:</b> +1 925 462 0304
<b>Equipment Type:</b> 5 GHz Beamforming Outdoor Radio Device	<b>Fax:</b> +1 925 462 0306
<b>S/N's:</b> Prototype	
<b>Test Date(s):</b> 23 <sup>rd</sup> to 26 <sup>th</sup> October 2017 Verification testing 19-20 <sup>th</sup> January 2022	<b>Website:</b> www.micomlabs.com

STANDARD(S)	TEST RESULTS
FCC CFR 47 Part 15 Subpart E 15.407 & ISSED RSS-247 (non-DFS Bands)	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

#### Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

**Approved & Released for MiCOM Labs, Inc. by:**



Graeme Grieve  
Quality Manager MiCOM Labs, Inc.

Gordon Hurst  
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



## 4. REFERENCES AND MEASUREMENT UNCERTAINTY

### 4.1. Normative References

REF.	PUBLICATION	YEAR	TITLE
I	KDB 662911 D01 & D02	Oct 31 2013	Guidance for measurement of output emission of devices that employ single transmitter with multiple outputs or systems with multiple transmitters operating simultaneously in the same frequency band
II	KDB 905462 D07 v02	22nd August 2016	Test guidance to demonstrate compliance for U-NII devices subject to DFS requirements.
III	KDB 926956 D01 v02	22nd August 2016	U-NII Device Transition Plan
IV	A2LA	5th October 2020	R105 - Requirement's When Making Reference to A2LA Accreditation Status
V	ANSI C63.10	2013	American National Standard for Testing Unlicensed Wireless Devices
VI	ANSI C63.4	2014	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
VII	CISPR 32	2015	Electromagnetic compatibility of multimedia equipment - Emission requirements
VIII	ETSI TR 100 028	2001-12	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
IX	FCC 06-96	Jun 30 2006	Memorandum Opinion and Order
X	FCC 47 CFR Part 15.407	2020	Radio Frequency Devices; Subpart E –Unlicensed National Information Infrastructure Devices
XI	ICES-003	Issue 7; October 15,2020	Information Technology Equipment (Including Digital Apparatus)
XII	M 3003	Edition 3 Nov.2012	Expression of Uncertainty and Confidence in Measurements
XIII	RSS-247 Issue 2	Feb 2017	Digital Transmission Systems (DTSs), Frequency Hopping System (FHSs) and License-Exempt Local Area Network (LE-LEN) Devices
XIV	RSS-Gen Issue 5	2018	General Requirements for Compliance of Radio Apparatus. With Amendments 1: March 2019 and 2: Feb 2021.
XV	FCC 47 CFR Part 2.1033	2020	FCC requirements and rules regarding photographs and test setup diagrams.
XVI	KDB 905462 D02 v02	April 8 2016	Compliance Measurement Procedures for Unlicensed National Information Infrastructure devices operating in the 5250 to 5350 MHz and 5470 to 5725 MHz bands incorporating Dynamic Frequency Selection.
XVII	KDB 789033 D02 V02r01	14th December, 2017	Guidelines For Compliance Testing Of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 10 of 181

---

#### **4.2. Test and Uncertainty Procedure**

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor  $k = 2$ , providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 11 of 181

## 5. PRODUCT DETAILS AND TEST CONFIGURATIONS

### 5.1. Technical Details

Details	Description
Purpose:	Test of the RADWIN 5000 JET 5.x GHz to FCC CFR 47 Part 15 Subpart E 15.407 and ISSED RSS-247 Issue 2. Compliance Measurement Procedures for Unlicensed National Information Infrastructure devices operating in the 5150 to 5250 MHz and 5725 to 5850 MHz bands.
Applicant:	RADWIN Ltd. 27 Habarzel Street Tel Aviv .69710 Israel
Manufacturer:	As applicant
Laboratory performing the tests:	MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Test report reference number:	RDWN65-U2
Date EUT received:	16 <sup>th</sup> October 2017
Standard(s) applied:	FCC CFR 47 Part 15 Subpart E 15.407, RSS-247 Issue 2
Dates of test (from - to):	23 <sup>rd</sup> – 26 <sup>th</sup> October 2017, Verified 19-20 <sup>th</sup> January 2022
No of Units Tested:	1
Product Family Name:	RADWIN JET
Model(s):	RADWIN 5000 JET 5.x GHz
Location for use:	Indoor & Outdoors
Declared Frequency Range(s):	5150 - 5250 MHz; 5725 - 5850 MHz;
Type of Modulation:	BPSK, QPSK, 16QAM, 64QAM, 256QAM
EUT Modes of Operation:	Bandwidths 10 MHz, 20 MHz, 40 MHz, 80 MHz
Declared Nominal Output Power (dBm):	30
Transmit/Receive Operation:	Transceiver
Rated Input Voltage and Current:	POE 55 Vdc 1 A
Operating Temperature Range:	-40°C to +60°C
ITU Emission Designator:	10 MHz 10M0W7W 20 MHz 20M0W7W 40 MHz 40M0W7W 80 MHz 80M0W7W
Equipment Dimensions:	13.9 / 9.0 / 2.6 in
Weight:	11.6 lb
Hardware Rev:	Prototype
Software Rev:	Prototype

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 12 of 181

---

## **5.2. Scope Of Test Program**

### **RADWIN 5000 JET 5.x GHz**

The scope of the test program was to test the RADWIN 5000 JET 5.X GHZ configurations in the frequency ranges 5150 - 5250 MHz; 5725 - 5850 MHz; for compliance against the following specification:

The following antennas were tested to 5725-5850MHz for transmitter spurious and band edge integral antenna 20.5 dBi and integral antenna 11 dBi

The following antennas were tested to 5150-5250 MHz for transmitter spurious and band edge: integral antenna 11 dBi

For band 5150-5250 MHz covering the integral antenna 20.5 dBi please refer to the following report:  
**RDWN39-U8 Rev A Radwin AP0158770 AP 5150-5250 MHz FCC 15.407**

### **FCC CFR 47 Part 15 Subpart E 15.407**

Compliance Measurement Procedures for Unlicensed National Information Infrastructure devices operating in the 5150 to 5250 MHz and 5725 to 5850 MHz bands.

### **ISSED RSS-247**

Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

Results Verified 19-20<sup>th</sup> January 2022

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 13 of 181

### 5.3. Equipment Model(s) and Serial Number(s)

Type	Description	Manufacturer	Model	Serial no.	Delivery Date
EUT	5 GHz Beamforming Outdoor Radio Device	Radwin Ltd.	RADWIN 5000 JET 5.X GHZ	Prototype	16 <sup>th</sup> October 2017

### 5.4. Antenna Details

Type	Manufacturer	Model	Family	Gain (dBi)	BF Gain	Dir BW	X-Pol	Frequency Band (MHz)
integral	RADWIN Ltd.	SA0183620	Flat Panel	11.0	9.5	9.4	Yes	5150 – 5850
integral	RADWIN Ltd.	SA0183620	Sector	11.0	--	60	Yes	5150 – 5850

BF Gain - Beamforming Gain  
Dir BW - Directional BeamWidth  
X-Pol - Cross Polarization

### 5.5. Cabling and I/O Ports

Port Type	Max Cable Length	# of Ports	Screened	Conn Type	Data Type	Bit Rate
Ethernet	>30m	1	Yes	RJ45	Packet Data	10/100/1000

### 5.6. Test Configurations

Results for the following configurations are provided in this report:

Channel Bandwidth(s)	Data Rate MBit/s	Channel Frequency (MHz)		
		Low	Mid	High
<b>5150-5250 MHz</b>				
10MHz	3.25	5162	5200	5245
20MHz	6.50	5165	5200	5240
40MHz	13.50	5172	5200	5230
80MHz	29.30	5194	--	5210
<b>5725 - 5850 MHz</b>				
10MHz	3.25	5730	5787	5845
20MHz	6.50	5735	5787	5840
40MHz	13.50	5745	5787	5830
80MHz	29.30	5765	5787	5810

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 14 of 181

---

### **5.7. Equipment Modifications**

The following modifications were required to bring the equipment into compliance:

1. NONE

### **5.8. Deviations from the Test Standard**

The following deviations from the test standard were required in order to complete the test program:

1. NONE

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 15 of 181

## 6. TEST SUMMARY

### List of Measurements

Test Header	Result	Data Link
Radiated	Complies	-
6 dB & 99% Bandwidth	Complies	<a href="#">View Data</a>
26 dB & 99% Bandwidth	Complies	<a href="#">View Data</a>
Peak Transmit Power	Complies	<a href="#">View Data</a>
Power Spectral Density	Complies	<a href="#">View Data</a>
TX Spurious & Restricted Band Emissions	Complies	-
RADWIN Ltd. SA0183620 11 dBi	Complies	<a href="#">View Data</a>
RADWIN Ltd. SA0183620 20.5 dBi	Complies	<a href="#">View Data<sup>1</sup></a>
Restricted Edge & Band-Edge Emissions	Complies	-
RADWIN Ltd. SA0183620 11 dBi	Complies	<a href="#">View Data</a>
RADWIN Ltd. SA0183620 20.5 dBi	Complies	<a href="#">View Data<sup>1</sup></a>
Digital Emissions	Complies	<a href="#">View Data</a>
Conducted Emissions AC mains	Complies <sup>2</sup>	
Note1: 5150-5250 MHz Transmitter Spurious and Band Edge Data for the 20.5 dBi antenna refer to report "RDWN39-U8 Rev A"		
Note2: Please refer to report "RDWN39-U3 Rev A Radwin AP0158770 AP 5725-5850 MHz FCC 15.407" for the following test results.		
Note 3: Results Verified 19-20 <sup>th</sup> January 2022		


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

## 7. TEST EQUIPMENT CONFIGURATION(S)

### 7.1. Radiated Emissions - 3m Chamber

The following tests were performed using the radiated test set-up shown in the diagram below. Radiated emissions above 1GHz.

Radiated Emissions Above 1GHz Test Setup



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 17 of 181

A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.

Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
158	Barometer/Thermometer	Control Company	4196	E2846	30 Nov 2017
170	Video System Controller for Semi Anechoic Chamber	Panasonic	WV-CU101	04R08507	Not Required
287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	2 May 2018
338	Sunol 30 to 3000 MHz Antenna	Sunol	JB3	A052907	5 Oct 2018
341	900MHz Notch Filter	EWT	EWT-14-0199	H1	30 Oct 2017
397	Amp 10 - 2500MHz	MiCOM Labs	Amp 10 - 2500 MHz	NA	30 Oct 2017
399	ETS 1-18 GHz Horn Antenna	ETS	3117	00154575	30 Oct 2017
406	Amplifier for Radiated Emissions	MiCOM Labs	40dB 1 to 18GHz Amp	0406	30 Oct 2017
410	Desktop Computer	Dell	Inspiron 620	WS38	Not Required
411	Mast/Turntable Controller	Sunol Sciences	SC98V	060199-1D	Not Required
412	USB to GPIB Interface	National Instruments	GPIB-USB HS	11B8DC2	Not Required
413	Mast Controller	Sunol Science	TWR95-4	030801-3	Not Required
415	Turntable Controller	Sunol Sciences	Turntable Controller	None	Not Required
416	Gigabit ethernet filter	ETS-Lingren	Gigafoil 260366	None	Not Required
447	MiTest Rad Emissions Test Software	MiCOM	Rad Emissions Test Software Version 1.0	447	Not Required
462	Schwarzbeck cable from Antenna to Amplifier.	Schwarzbeck	AK 9513	462	30 Oct 2017
463	Schwarzbeck cable from Amplifier to Bulkhead.	Schwarzbeck	AK 9513	463	30 Oct 2017
464	Schwarzbeck cable from Bulkhead to Receiver	Schwarzbeck	AK 9513	464	30 Oct 2017
480	Cable - Bulkhead to Amp	SRC Haverhill	157-3050360	480	30 Oct 2017
481	Cable - Bulkhead to Receiver	SRC Haverhill	151-3050787	481	30 Oct 2017
482	Cable - Amp to Antenna	SRC Haverhill	157-3051574	482	30 Oct 2017

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

## 8. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing for conducted RF testing.



The MiCOM Labs "[MiTest](#)" Automated Test System" (Patent Pending)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 19 of 181

## 9. TEST RESULTS

### 9.1. 26 dB & 99% Bandwidth

Conducted Test Conditions for 26 dB and 99% Bandwidth			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	26 dB and 99 % Bandwidth	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		

**Test Procedure for 26 dB and 99% Bandwidth Measurement**  
The bandwidth at 26 dB and 99 % is measured radiated, in a 3 meter chamber, while EUT is operating in transmission mode at the appropriate center frequency. The Resolution Bandwidth was set to approximately 1% of the emission bandwidth. Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported. In this case Vertical a (V) and Horizontal for port b (H).

Test configuration and setup used for the measurement was per the Radiated Test Set-up section specified in this document.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 20 of 181

**Equipment Configuration for 26 dB & 99% Occupied Bandwidth**

<b>Variant:</b>	10 MHz Bandwidth	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

Test Frequency	Measured 26 dB Bandwidth (MHz)		26 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5162.0	-	<a href="#">11.70</a>	11.70	11.70		
5200.0	-	<a href="#">11.50</a>	11.50	11.50		
5245.0	-	<a href="#">11.50</a>	11.50	11.50		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5162.0	-	<a href="#">8.98</a>	8.98	8.98		
5200.0	-	<a href="#">8.98</a>	8.98	8.98		
5245.0	-	<a href="#">8.98</a>	8.98	8.98		

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 21 of 181

**Equipment Configuration for 26 dB & 99% Occupied Bandwidth**

<b>Variant:</b>	20 MHz Bandwidth	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 26 dB Bandwidth (MHz)		26 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5165.0	-	<a href="#">22.53</a>	22.53	22.53		
5200.0	-	<a href="#">21.80</a>	21.80	21.80		
5240.0	-	<a href="#">22.53</a>	22.53	22.53		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5165.0	-	<a href="#">17.88</a>	17.88	17.88		
5200.0	-	<a href="#">17.88</a>	17.88	17.88		
5240.0	-	<a href="#">17.88</a>	17.88	17.88		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 22 of 181

**Equipment Configuration for 26 dB & 99% Occupied Bandwidth**

<b>Variant:</b>	40 MHz Bandwidth	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 26 dB Bandwidth (MHz)		26 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5172.0	-	<a href="#">43.89</a>	43.89	43.89		
5200.0	-	<a href="#">45.03</a>	45.03	45.03		
5230.0	-	<a href="#">45.15</a>	45.15	45.15		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5172.0	-	<a href="#">36.67</a>	36.67	36.67		
5200.0	-	<a href="#">36.87</a>	36.87	36.87		
5230.0	-	<a href="#">36.87</a>	36.87	36.87		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 23 of 181

**Equipment Configuration for 26 dB & 99% Occupied Bandwidth**

<b>Variant:</b>	80MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 26 dB Bandwidth (MHz)		26 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5194.0	-	<a href="#">87.03</a>	87.03	87.03		
5210.0	-	<a href="#">88.32</a>	88.32	88.32		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5194.0	-	<a href="#">76.31</a>	76.31	76.31		
5210.0	-	<a href="#">76.31</a>	76.31	76.31		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 24 of 181

## 9.2. 6 dB & 99% Bandwidth

Conducted Test Conditions for 6 dB and 99% Bandwidth			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	6 dB and 99 % Bandwidth	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		
<b>Test Procedure for 6 dB and 99% Bandwidth Measurement</b> The bandwidth at 6 dB and 99 % is measured radiated, in a 3 meter chamber, while EUT is operating in transmission mode at the appropriate center frequency. The Resolution Bandwidth was set to approximately 1% of the emission bandwidth. Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported. In this case Vertical a (V) and Horizontal for port b (H).  Test configuration and setup used for the measurement was per the Radiated Test Set-up section specified in this document.			

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 25 of 181

**Equipment Configuration for 6 dB & 99% Bandwidth**

<b>Variant:</b>	10 MHz Bandwidth	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 6 dB Bandwidth (MHz)		6 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5730.0	<a href="#">9.14</a>	-	9.14	9.14		
5787.0	<a href="#">8.86</a>	-	8.86	8.86		
5845.0	<a href="#">9.14</a>	-	9.14	9.14		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5730.0	<a href="#">9.98</a>	-	9.98	9.98		
5787.0	<a href="#">9.90</a>	-	9.90	9.90		
5845.0	<a href="#">10.02</a>	-	10.02	10.02		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 26 of 181

**Equipment Configuration for 6 dB & 99% Bandwidth**

<b>Variant:</b>	20MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 6 dB Bandwidth (MHz)		6 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5735.0	<a href="#">17.88</a>	-	17.88	17.88		
5787.0	<a href="#">17.80</a>	-	17.80	17.80		
5840.0	<a href="#">17.96</a>	-	17.96	17.96		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5735.0	<a href="#">18.23</a>	-	18.23	18.23		
5787.0	<a href="#">18.36</a>	-	18.36	18.36		
5840.0	<a href="#">18.52</a>	-	18.52	18.52		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 27 of 181

**Equipment Configuration for 6 dB & 99% Bandwidth**

<b>Variant:</b>	40MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 6 dB Bandwidth (MHz)		6 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5745.0	<a href="#">36.67</a>	-	36.67	36.67		
5787.0	<a href="#">36.76</a>	-	36.76	36.76		
5830.0	<a href="#">36.44</a>	-	36.44	36.44		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5745.0	<a href="#">36.67</a>	-	36.67	36.67		
5787.0	<a href="#">36.67</a>	-	36.67	36.67		
5830.0	<a href="#">36.67</a>	-	36.67	36.67		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 28 of 181

**Equipment Configuration for 6 dB & 99% Bandwidth**

<b>Variant:</b>	80MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	OC
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured 6 dB Bandwidth (MHz)		6 dB Bandwidth (MHz)			
	H	V	Highest	Lowest		
5765.0	<a href="#">76.74</a>	-	76.74	76.74		
5787.0	<a href="#">76.74</a>	-	76.74	76.74		
5810.0	<a href="#">76.42</a>	-	76.42	76.42		

Test Frequency	Measured 99% Bandwidth (MHz)		99% Bandwidth (MHz)			
	H	V	Highest	Lowest		
5765.0	<a href="#">75.99</a>	-	75.99	75.99		
5787.0	<a href="#">75.99</a>	-	75.99	75.99		
5810.0	<a href="#">76.31</a>	-	76.31	76.31		

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

The above values are representative of the worst case value between polarities and based on the power measurements.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



### 9.3. Peak Transmit Power

Conducted Test Conditions for Maximum Conducted Output Power			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Maximum Conducted Output Power	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	KDB 789033 - D02 General UNII Test Procedures New Rules v01		

#### Test Procedure for Maximum Output Power Measurement

Spectrum Analyzer Method. KDB 789033 defines a methodology using spectrum analyzer. Where power shall be calculated by integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99% occupied bandwidth of the signal. However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with Section 15.407(a). Testing was performed under ambient conditions at nominal voltage.

Test configuration and setup used for the measurement was per the Radiated Test Set-up section specified in this document. Supporting KDB's referenced below.

#### KDB 662911 D01 & KDB 662911 D02, KDB 558074 D01

Radiated measurements used for compliance with conducted limits, the following steps are required to ensure that the total emission power is determined for equipment driving cross polarized antennas:

- (1) Measure radiated emissions with vertical and horizontal polarizations of the measurement antenna;
- (2) Convert each radiated measurement to transmit power based on the antenna gain;

EIRP level to an equivalent electric field strength using the following relationship:  
 $E = \text{EIRP} - 20 \cdot \log(D) + 104.8$

Where:

E = electric field strength in dB $\mu$ V/m,  
EIRP = equivalent isotropic radiated power in dBm  
D = specified measurement distance in meters.

- (3) Sum the powers across the two polarizations to compare the resultant electric field strength level to the applicable limit.

Calculated Power = A + G + Y + 10 log (1/x) dBm

A = Total Power [10\*Log10 (10<sup>a/10</sup> + 10<sup>b/10</sup> + 10<sup>c/10</sup> + 10<sup>d/10</sup>)]

G = Antenna Gain

Y = Beamforming Gain

x = Duty Cycle (average power measurements only)

#### Limits Maximum Conducted Output Power

##### Operating Frequency Band 5150-5250 MHz

15.407 (a)(1)

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 30 of 181

spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5250-5350 and 5470 – 5725 MHz**

##### **15. 407 (a)(2)**

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Operating Frequency Band 5725 – 5850 MHz**

##### **15. 407 (a)(3)**

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 31 of 181

The following Data for 5150-5250 falls under FCC Part 15.407 Only

Equipment Configuration for RF Output Power			
<b>Variant:</b>	10MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5162	11.62	15.79	17.97	30	-12.03	1.5
5200	17.59	21.2	23.54	30	-6.46	8.5
5245	17.92	19.01	22.28	30	-7.72	6.0

Traceability to Industry Recognized Test Methodologies	
<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 32 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	20MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	6.50MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5165	6.46	11.45	13.42	30	-16.58	-2.0
5200	17.05	20.61	22.97	30	-7.03	8.5
5240	17.07	18.46	21.60	30	-8.40	6.0

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 33 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	40MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5172	-0.81	3.69	5.78	30	-16.58	-11.0
5200	16.54	19.01	21.73	30	-7.03	8.5
5230	15.58	17.96	20.71	30	-8.40	6.0

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 34 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	80MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5194	5.33	8.63	11.07	30	-18.93	-3.0
5210	14.86	17.83	20.38	30	-9.62	6.0

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 35 of 181

The following data falls under FCC Part 15.407 & IC RSS-247

Equipment Configuration for RF Output Power			
<b>Variant:</b>	10MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

Test Measurement Results
--------------------------

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin		EUT Power Setting Numeric
	H	V			Numeric	Numeric	
5730	25.94	26.13	29.82	30.00	-0.18	15.0	
5787	27.07	24.15	29.63	30.00	-0.37	16.5	
5845	26.79	23.99	29.39	30.00	-0.61	18.5	

Traceability to Industry Recognized Test Methodologies	
<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 36 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	20MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5735	25.95	25.76	29.64	30.00	-0.36	15.5
5787	26.95	24.03	29.51	30.00	-0.49	17.0
5840	27.47	24.43	29.99	30.00	-0.01	19.00

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 37 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	40MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5745	25.4	25.3	29.13	30.00	-0.87	15.5
5787	26.82	24.48	29.59	30.00	-0.41	17.5
5830	26.95	24.63	29.73	30.00	-0.27	17.5

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 38 of 181

**Equipment Configuration for RF Output Power**

<b>Variant:</b>	80MHz	<b>Duty Cycle (%):</b>	99
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11.0
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency MHz	Measured Output Power		Calculated Total Power dBm	Limit dB	Margin Numeric	EUT Power Setting Numeric
	H	V				
5765	26.09	25.79	29.73	30.00	-0.27	16.0
5787	26.55	24.2	29.31	30.00	-0.69	16.5
5810	26.83	25.21	29.88	30.00	-0.12	18.0

**Traceability to Industry Recognized Test Methodologies**

<b>Work Instruction:</b>	WI-01 MEASURING RF OUTPUT POWER
<b>Uncertainty:</b>	±1.33 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



## 9.4. Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	24.0 - 27.5
<b>Test Heading:</b>	Power Spectral Density	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (a)	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	KDB 789033 - D02 General UNII Test Procedures New Rules v01		

### Test Procedure for Power Spectral Density

The In-Band power spectral density was measured using the measure and sum approach per FCC KDB 662911 (D01 Multiple Transmitter Output v01.)

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with N transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were calculated on a computer, and the results read back into the spectrum analyzer as a data file to produce a representative plot of total spectral power density.

Calculated Power = A + 10 log (1/x) dBm

A = Total Power Spectral Density [10 Log<sub>10</sub> (10<sup>a</sup>/10 + 10<sup>b</sup>/10 + 10<sup>c</sup>/10 + 10<sup>d</sup>/10)]

x = Duty Cycle

Test configuration and setup used for the measurement was per the Radiated Test Set-up section specified in this document. Supporting KDB's referenced below.

### **KDB 662911 D01 & KDB 662911 D02, KDB 558074 D01**

Radiated measurements used for compliance with conducted limits, the following steps are required to ensure that the total emission power s determined for equipment driving cross polarized antennas:

- (1) Measure radiated emissions with vertical and horizontal polarizations of the measurement antenna;
- (2) Convert each radiated measurement to transmit power based on the antenna gain;

EIRP level to an equivalent electric field strength using the following relationship:

E = EIRP – 20\*log (D) + 104.8

Where:

E = electric field strength in dBμV/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- (3) Sum the powers or PSDs across the two polarizations to compare the resultant electric field strength level to the applicable limit.

Calculated Power = A + G + Y+ 10 log (1/x) dBm

A = Total Power [10\*Log<sub>10</sub> (10<sup>a</sup>/10 + 10<sup>b</sup>/10 + 10<sup>c</sup>/10 + 10<sup>d</sup>/10)]

G = Antenna Gain

Y = Beamforming Gain

x = Duty Cycle (average power measurements only)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



### Limits Maximum Power Spectral Density

#### Operating Frequency Band 5150-5250 MHz

##### 15. 407 (a)(1)

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Operating Frequency Band 5250-5350 and 5470 – 5725 MHz

##### 15. 407 (a)(2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### Operating Frequency Band 5725 – 5850 MHz

##### 15. 407 (a)(3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 41 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	10 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.0 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5162.0	<a href="#">-10.49</a>	<a href="#">-6.01</a>	-3.91	17.0	-20.91
5200.0	<a href="#">-3.42</a>	<a href="#">0.00</a>	2.40	17.0	-14.60
5245.0	<a href="#">-3.43</a>	<a href="#">-2.03</a>	1.11	17.0	-15.89

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 42 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	20 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.0 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5165.0	<a href="#">-16.70</a>	<a href="#">-12.55</a>	-10.36	17.0	-27.36
5200.0	<a href="#">-6.54</a>	<a href="#">-4.00</a>	-1.30	17.0	-18.30
5240.0	<a href="#">-6.65</a>	<a href="#">-5.11</a>	-2.03	17.0	-19.03

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 43 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	40 MHz	<b>Duty Cycle (%):</b>	100.0
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5172.0	<a href="#">-27.35</a>	<a href="#">-23.16</a>	-20.99	17.0	-37.99
5200.0	<a href="#">-11.56</a>	<a href="#">-10.89</a>	-7.43	17.0	-24.43
5230.0	<a href="#">-11.87</a>	<a href="#">-9.46</a>	-6.72	17.0	-23.72

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 44 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	80 MHz	<b>Duty Cycle (%):</b>	100.0
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	JMH
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5194.0	<a href="#">-24.81</a>	<a href="#">-22.36</a>	-19.63	17.0	-36.63
5210.0	<a href="#">-16.20</a>	<a href="#">-14.07</a>	-11.22	17.0	-28.22

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 45 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	10 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	3.25 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5730.0	<a href="#">4.83</a>	<a href="#">3.90</a>	8.17	30.00	-21.83
5787.0	<a href="#">5.96</a>	<a href="#">2.20</a>	8.26	30.00	-21.74
5845.0	<a href="#">6.23</a>	<a href="#">2.78</a>	8.62	30.00	-21.38

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 46 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	20 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	6.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5735.0	<a href="#">1.96</a>	<a href="#">0.72</a>	5.17	30.00	-24.83
5787.0	<a href="#">4.73</a>	<a href="#">1.52</a>	7.20	30.00	-22.80
5840.0	<a href="#">4.49</a>	<a href="#">0.53</a>	6.73	30.00	-23.27

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 47 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	40 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	13.50 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5745.0	<a href="#">-2.25</a>	<a href="#">-3.33</a>	1.03	30.00	-28.97
5787.0	<a href="#">0.12</a>	<a href="#">-3.25</a>	2.54	30.00	-27.46
5830.0	<a href="#">0.64</a>	<a href="#">-4.31</a>	2.62	30.00	-27.38

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 48 of 181

**Equipment Configuration for Power Spectral Density**

<b>Variant:</b>	80 MHz	<b>Duty Cycle (%):</b>	100
<b>Data Rate:</b>	29.30 MBit/s	<b>Antenna Gain (dBi):</b>	11.00
<b>Modulation:</b>	OFDM	<b>Beam Forming Gain (Y)(dB):</b>	Not Applicable
<b>TPC:</b>	Not Applicable	<b>Tested By:</b>	SB
<b>Engineering Test Notes:</b>			

**Test Measurement Results**

Test Frequency	Measured Power Spectral Density		Summation Peak Marker + DCCF (+0.00 dB)	Limit	Margin
	(dBm/MHz)				
MHz	H	V	dBm/MHz	dBm/MHz	dB
5765.0	<a href="#">-7.11</a>	<a href="#">-5.81</a>	-2.63	30.00	-32.63
5787.0	<a href="#">-7.15</a>	<a href="#">-8.96</a>	-4.18	30.00	-34.18
5810.0	<a href="#">-5.47</a>	<a href="#">-8.00</a>	-2.77	30.00	-32.77

**Traceability to Industry Recognized Test Methodologies**

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

DCCF - Duty Cycle Correction Factor

Note: click the links in the above matrix to view the graphical image (plot).

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





## 9.5. Radiated

Radiated Test Conditions for Radiated Spurious and Band-Edge Emissions			
<b>Standard:</b>	FCC CFR 47:15.407	<b>Ambient Temp. (°C):</b>	20.0 - 24.5
<b>Test Heading:</b>	Radiated Spurious and Band-Edge Emissions	<b>Rel. Humidity (%):</b>	32 - 45
<b>Standard Section(s):</b>	15.407 (b), 15.205, 15.209	<b>Pressure (mBars):</b>	999 - 1001
<b>Reference Document(s):</b>	See Normative References		

### Test Procedure for Radiated Spurious and Band-Edge Emissions

Radiated emissions for restricted bands above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned.

Measurements on any restricted band frequency or frequencies above 1 GHz are based on the use of measurement instrumentation employing peak and average detectors. All measurements were performed using a resolution bandwidth of 1 MHz.

Test configuration and setup for Undesirable Measurement were per the Radiated Test Set-up specified in this document.

15.407 (b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
- (7) The provisions of §15.205 apply to intentional radiators operating under this section.
- (8) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

### Limits for Restricted Bands (15.205, 15.209)

**Peak emission: 68.23 dBuV/m**

**Average emission: 54 dBuV/m**

### Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

**FS = R + AF + CORR - FO**

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



where:

**FS = Field Strength**  
**R = Measured Spectrum analyzer Input Amplitude**  
**AF = Antenna Factor**  
**CORR = Correction Factor = CL – AG + NFL**  
**CL = Cable Loss**  
**AG = Amplifier Gain**  
**FO = Distance Falloff Factor**  
**NFL = Notch Filter Loss**

**Example:**

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength (dBµV/m);

$$E = 1000000 \times \sqrt{\frac{30P}{3}} \mu\text{V/m}$$

where P is the EIRP in Watts

Therefore: -27 dBm/MHz equates to 68.23 dBuV/m

Conversion between dBmV/m (or dBmV) and mV/m (or mV) are as follows:  
 Level (dBmV/m) = 20 \* Log (level (mV/m))

40 dBmV/m = 100 mV/m  
 48 dBmV/m = 250 mV/m

**Restricted Bands of Operation (15.205)**

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Frequency Band			
MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 51 of 181

---

12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

(b) Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e) of this section, regardless of the field strength limits specified elsewhere in this subpart, the provisions of this section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a) of this section, the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a) of this section, and the fundamental emission is outside of the bands listed in paragraph (a) of this section more than 99% of the time the device is actively transmitting, without compensation for duty cycle.
- (2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.
- (3) Cable locating equipment operated pursuant to §15.213.
- (4) Any equipment operated under the provisions of §15.253, 15.255, and 15.256 in the frequency band 75-85 GHz, or §15.257 of this part.
- (5) Biomedical telemetry devices operating under the provisions of §15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.
- (6) Transmitters operating under the provisions of subparts D or F of this part.
- (7) Devices operated pursuant to §15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.
- (8) Devices operated in the 24.075-24.175 GHz band under §15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in §15.245(b).
- (9) Devices operated in the 24.0-24.25 GHz band under §15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in §15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of §15.245 shall not exceed the limits specified in §15.245(b).

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 52 of 181

## 9.5.1. TX Spurious & Restricted Band Emissions

### 9.5.1.1. RADWIN Ltd. SA0183620 11 dBi

#### Equipment Configuration for TX Spurious & Restricted Band Emissions

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5162.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	1.5	<b>Tested By:</b>	JMH

#### Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5165.52	71.15	3.08	-14.39	59.84	Fundamental	Vertical	151	8	--	--	
#2	10324.28	40.61	4.44	0.11	45.16	Peak (NRB)	Horizontal	151	0	--	--	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 53 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5200.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	8.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5202.67	89.18	3.09	-14.25	78.02	Fundamental	Vertical	151	0	--	--	
#2	6163.52	59.82	3.20	-11.97	51.05	Peak (NRB)	Horizontal	151	0	--	--	Pass
#3	6216.44	59.51	3.26	-11.81	50.96	Peak (NRB)	Horizontal	151	0	--	--	Pass
#4	10402.63	61.94	4.41	0.00	66.35	Max Peak	Horizontal	165	50	68.2	-1.9	Pass
#5	15601.96	53.29	5.58	1.30	60.17	Max Peak	Vertical	162	34	68.2	-8.1	Pass
#6	15601.96	38.24	5.58	1.30	45.12	Max Avg	Vertical	162	34	54.0	-8.9	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 54 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5245.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	6	<b>Tested By:</b>	JMH

**Test Measurement Results**

**1000.00 - 18000.00 MHz**

Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5245.12	87.14	3.15	-14.40	75.89	Fundamental	Vertical	151	9	--	--	
#2	10490.94	63.16	4.46	0.33	67.95	Max Peak	Horizontal	158	26	68.2	-0.3	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 55 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5730.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	15.0	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5726.82	71.01	3.16	-12.86	61.31	Fundamental	Vertical	150	0	--	--	
#2	6068.05	57.35	3.24	-11.92	48.67	Peak (NRB)	Horizontal	150	0	--	--	Pass
#3	11453.49	59.90	4.64	-0.80	63.74	Max Peak	Horizontal	167	48	68.2	-4.5	Pass
#4	11453.49	43.79	4.64	-0.80	47.63	Max Avg	Horizontal	167	48	54.0	-6.4	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 56 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5787.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	16.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5787.78	75.59	3.21	-12.78	66.02	Fundamental	Horizontal	151	0	--	--	
#2	6072.79	59.32	3.25	-11.75	50.82	Peak (NRB)	Horizontal	151	0	--	--	Pass
#3	11574.29	61.03	4.56	-0.46	65.13	Max Peak	Horizontal	162	44	68.2	-3.1	Pass
#4	11574.29	49.30	4.56	-0.46	53.40	Max Avg	Horizontal	162	44	54.0	-0.6	Pass
#5	17363.87	55.45	5.99	0.79	62.23	Max Peak	Horizontal	151	70	68.2	-6.0	Pass
#6	17363.87	39.01	5.99	0.79	45.79	Max Avg	Horizontal	151	70	54.0	-8.2	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 57 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5845.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	18.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5841.37	72.41	3.22	-13.00	62.63	Fundamental	Horizontal	151	0	--	--	
#2	6101.68	60.32	3.24	-11.89	51.67	Peak (NRB)	Horizontal	151	0	--	--	Pass
#3	11685.48	60.91	4.95	-0.46	65.40	Max Peak	Horizontal	154	82	68.2	-2.8	Pass
#4	11685.48	46.48	4.95	-0.46	50.97	Max Avg	Horizontal	154	82	54.0	-3.0	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 58 of 181

### 9.5.1.2. RADWIN Ltd. SA0183620 20.50 dBi

#### Equipment Configuration for TX Spurious & Restricted Band Emissions

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5730.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	8.5	<b>Tested By:</b>	JMH

#### Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5729.26	71.19	3.17	-12.84	61.52	Fundamental	Vertical	151	8	--	--	
#2	6072.79	57.33	3.25	-11.75	48.83	Peak (NRB)	Horizontal	151	8	--	--	Pass
#3	11461.84	57.89	4.62	-0.78	61.73	Max Peak	Horizontal	174	324	68.2	-6.5	Pass
#4	11461.84	42.67	4.62	-0.78	46.51	Max Avg	Horizontal	174	324	54.0	-7.5	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 59 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5787.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	16	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5789.10	75.74	3.21	-12.79	66.16	Fundamental	Horizontal	151	7	--	--	
#2	6070.25	61.85	3.25	-11.84	53.26	Peak (NRB)	Horizontal	151	7	--	--	Pass
#3	6103.72	62.82	3.24	-11.84	54.22	Peak (NRB)	Horizontal	150	0	--	--	Pass
#4	6103.72	56.05	3.24	-11.84	47.45	Max Avg	Horizontal	160	12	54.0	-6.6	Pass
#5	11573.85	62.63	4.54	-0.48	66.69	Max Peak	Horizontal	154	324	68.2	-1.5	Pass
#6	11573.85	49.48	4.54	-0.48	53.54	Max Avg	Horizontal	154	324	54.0	-0.5	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 60 of 181

**Equipment Configuration for TX Spurious & Restricted Band Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5845.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	9.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5844.29	69.66	3.21	-12.82	60.05	Fundamental	Horizontal	151	9	--	--	
#2	6099.58	59.54	3.24	-11.94	50.84	Peak (NRB)	Horizontal	151	9	--	--	Pass
#3	11686.91	54.02	4.98	-0.48	58.52	Max Peak	Horizontal	149	59	68.2	-9.7	Pass
#4	11686.91	38.62	4.98	-0.48	43.12	Max Avg	Horizontal	149	59	54.0	-10.9	Pass

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



## 9.5.2. Restricted Edge & Band-Edge Emissions

### 9.5.2.3. RADWIN Ltd. SA0183620 11 dBi

#### RESULTS SUMMARY FOR RADIATED BAND-EDGE EMISSIONS

##### 5150 - 5250 MHz

RADWIN Ltd. SA0183620 11 dBi		Band-Edge Freq	Limit 68.2dB $\mu$ V/m	Limit 54.0dB $\mu$ V/m	Power Setting
Channel Bandwidth(s)	Operating Frequency (MHz)	MHz	dB $\mu$ V/m	dB $\mu$ V/m	
10 MHz	5162.00	5150.00	67.72	49.81	1.5
20 MHz	5165.00	5150.00	67.48	48.24	-2
40 MHz	5172.00	5150.00	68.19	49.07	-11
80 MHz	5194.00	5150.00	66.97	48.58	-3

##### 5725 MHz Radiated Lower Band-Edge Emissions

RADWIN Ltd. SA0183620 11 dBi		Band-Edge Freq	Limit 68.2dB $\mu$ V/m	Limit 122.2dB $\mu$ V/m	Power Setting
Channel Bandwidth(s)	Operating Frequency (MHz)	MHz	dB $\mu$ V/m	dB $\mu$ V/m	
10 MHz	5730.00	5725.00	67.30	116.79	15.5
20 MHz	5735.00	5725.00	67.58	109.22	15.5
40 MHz	5745.00	5725.00	66.89	102.11	15.5
80 MHz	5785.00	5725.00	67.93	99.80	16.0

##### 5850 MHz Radiated Higher Band-Edge Emissions

RADWIN Ltd. SA0183620 11 dBi		Band-Edge Freq	Limit 68.2dB $\mu$ V/m	Limit 122.2dB $\mu$ V/m	Power Setting
Channel Bandwidth(s)	Operating Frequency (MHz)	MHz	dB $\mu$ V/m	dB $\mu$ V/m	
10 MHz	5845.00	5850.00	67.78	118.35	18.5
20 MHz	5840.00	5850.00	67.99	109.34	19.0
40 MHz	5830.00	5850.00	67.79	103.58	17.5
80 MHz	5810.00	5850.00	68.18	100.93	18.0

Click on the links to view the data.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 62 of 181

**Equipment Configuration for Restricted Lower Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5162.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	1.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5150.00	11.35	3.06	35.40	49.81	Max Avg	Vertical	155	8	54.0	-4.2	Pass
#2	5150.00	29.26	3.06	35.40	67.72	Max Peak	Vertical	155	8	68.2	-0.5	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 63 of 181

**Equipment Configuration for Restricted Lower Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	20 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5165.00	<b>Data Rate:</b>	6.50 MBit/s
<b>Power Setting:</b>	-2	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**4500.00 - 5250.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5150.00	9.78	3.06	35.40	48.24	Max Avg	Vertical	155	8	54.0	-5.8	Pass
#2	5150.00	29.02	3.06	35.40	67.48	Max Peak	Vertical	155	8	68.2	-0.8	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 64 of 181

**Equipment Configuration for Restricted Lower Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	40 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5172.00	<b>Data Rate:</b>	13.50 MBit/s
<b>Power Setting:</b>	-11	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5150.00	10.61	3.06	35.40	49.07	Max Avg	Vertical	155	8	54.0	-4.9	Pass
#2	5150.00	29.73	3.06	35.40	68.19	Max Peak	Vertical	155	8	68.2	0.0	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 65 of 181

**Equipment Configuration for Restricted Lower Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	80 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5194.00	<b>Data Rate:</b>	29.30 MBit/s
<b>Power Setting:</b>	-3	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**4500.00 - 5250.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5150.00	10.12	3.06	35.40	48.58	Max Avg	Vertical	155	8	54.0	-5.4	Pass
#2	5150.00	28.51	3.06	35.40	66.97	Max Peak	Vertical	155	8	68.2	-1.3	Pass
#3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 66 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5730.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	15.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5643.22	27.82	3.18	36.30	67.30	Max Peak	Horizontal	155	11	68.2	-0.9	Pass
#2	5725.00	77.12	3.17	36.50	116.79	Max Peak	Horizontal	155	11	122.2	-5.4	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 67 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	20 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5735.00	<b>Data Rate:</b>	6.50 MBit/s
<b>Power Setting:</b>	15.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5648.99	28.07	3.21	36.30	67.58	Max Peak	Horizontal	155	11	68.2	-0.7	Pass
#2	5725.00	69.55	3.17	36.50	109.22	Max Peak	Horizontal	155	11	122.2	-13.0	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 68 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	40 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5745.00	<b>Data Rate:</b>	13.50 MBit/s
<b>Power Setting:</b>	15.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5634.63	27.39	3.20	36.30	66.89	Max Peak	Horizontal	155	11	68.2	-1.3	Pass
#2	5725.00	62.44	3.17	36.50	102.11	Max Peak	Horizontal	155	11	122.2	-20.1	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 69 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	80 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5765.00	<b>Data Rate:</b>	29.30 MBit/s
<b>Power Setting:</b>	16	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5646.10	28.43	3.20	36.30	67.93	Max Avg	Horizontal	155	11	68.2	-0.3	Pass
#2	5725.00	60.13	3.17	36.50	99.80	Max Avg	Horizontal	155	11	122.2	-22.4	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 70 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5845.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	20.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5850.00	78.45	3.20	36.70	118.35	Max Peak	Horizontal	155	11	122.2	-3.8	Pass
#3	5924.99	27.79	3.19	36.80	67.78	Max Peak	Horizontal	155	11	68.2	-0.5	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 71 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	20 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5840.00	<b>Data Rate:</b>	6.50 MBit/s
<b>Power Setting:</b>	20.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5850.00	69.44	3.20	36.70	109.34	Max Peak	Horizontal	155	11	122.2	-12.9	Pass
#3	5926.37	28.00	3.19	36.80	67.99	Max Peak	Horizontal	155	11	68.2	-0.2	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 72 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	40 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5830.00	<b>Data Rate:</b>	13.50 MBit/s
<b>Power Setting:</b>	20.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5850.00	63.68	3.20	36.70	103.58	Max Peak	Horizontal	155	11	122.2	-18.7	Pass
#3	5934.21	27.80	3.19	36.80	67.79	Max Peak	Horizontal	155	11	68.2	-0.4	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 73 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	80 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	Not Applicable	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5810.00	<b>Data Rate:</b>	29.30 MBit/s
<b>Power Setting:</b>	19.5	<b>Tested By:</b>	JMH

**Note:** The above power setting may be higher than the result reported under Section 9.3 Peak Transmit Power. The power setting reported in Section 9.3 always takes precedence

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5850.00	61.03	3.20	36.70	100.93	Max Peak	Horizontal	155	11	68.2	-21.3	Pass
#3	5927.29	28.19	3.19	36.80	68.18	Max Peak	Horizontal	155	11	68.2	-0.1	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



#### 9.5.2.4. RADWIN Ltd. SA0183620 20.50 dBi

#### RESULTS SUMMARY FOR RADIATED BAND-EDGE EMISSIONS

##### 5725 MHz Radiated Lower Band-Edge Emissions

RADWIN Ltd. SA0183620 20.5 dBi		Band-Edge Freq	Limit 68.2dB $\mu$ V/m	Limit 122.2dB $\mu$ V/m	Power Setting
Channel Bandwidth(s)	Operating Frequency (MHz)	MHz	dB $\mu$ V/m	dB $\mu$ V/m	
10 MHz	5730.00	5725.00	65.79	118.18	8.5
20 MHz	5735.00	5725.00	66.50	109.73	8.5
40 MHz	5745.00	5725.00	66.89	102.77	6.5
80 MHz	5785.00	5725.00	66.40	99.60	7

##### 5850 MHz Radiated Higher Band-Edge Emissions

RADWIN Ltd. SA0183620 20.5 dBi		Band-Edge Freq	Limit 68.23dB $\mu$ V/m	Limit 122.2dB $\mu$ V/m	Power Setting
Channel Bandwidth(s)	Operating Frequency (MHz)	MHz	dB $\mu$ V/m	dB $\mu$ V/m	
10 MHz	5845.00	5850.00	66.41	116.49	9.5
20 MHz	5840.00	5850.00	66.99	108.39	9.5
40 MHz	5830.00	5850.00	66.89	102.77	9.5
80 MHz	5810.00	5850.00	66.40	99.60	9.5

Click on the links to view the data.

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 75 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5730.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	8.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5645.74	26.29	3.20	36.30	65.79	Max Peak	Horizontal	155	11	68.2	-2.4	Pass
#2	5725.00	78.51	3.17	36.50	118.18	Max Peak	Horizontal	155	11	122.2	-4.0	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 76 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	20 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5735.00	<b>Data Rate:</b>	6.50 MBit/s
<b>Power Setting:</b>	8.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5647.18	27.00	3.20	36.30	66.50	Max Peak	Horizontal	155	11	68.2	-1.7	Pass
#2	5725.00	70.06	3.17	36.50	109.73	Max Peak	Horizontal	155	11	122.2	-12.5	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 77 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	40 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5745.00	<b>Data Rate:</b>	13.50 MBit/s
<b>Power Setting:</b>	6.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5625.18	27.25	3.19	36.30	66.74	Max Peak	Horizontal	155	11	68.2	-1.5	Pass
#2	5725.00	61.43	3.17	36.50	101.10	Max Peak	Horizontal	155	11	122.2	-21.1	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 78 of 181

**Equipment Configuration for 5725 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	80 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5765.00	<b>Data Rate:</b>	29.30 MBit/s
<b>Power Setting:</b>	7	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5600.00 - 5780.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5605.34	27.69	3.24	36.30	67.23	Max Peak	Horizontal	155	11	68.2	-1.0	Pass
#2	5725.00	58.79	3.17	36.50	98.46	Max Peak	Horizontal	155	11	122.2	-23.7	Pass
#3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 79 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	10 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5845.00	<b>Data Rate:</b>	3.25 MBit/s
<b>Power Setting:</b>	9.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5850.00	76.59	3.20	36.70	116.49	Max Peak	Horizontal	155	11	122.2	-5.7	Pass
#3	5926.37	26.42	3.19	36.80	66.41	Max Peak	Horizontal	155	11	68.2	-1.8	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 80 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	20 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5840.00	<b>Data Rate:</b>	6.50 MBit/s
<b>Power Setting:</b>	9.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5850.00	68.49	3.20	36.70	108.39	Max Peak	Horizontal	155	11	68.2	-13.8	Pass
#3	5976.15	26.81	3.28	36.90	66.99	Max Peak	Horizontal	155	11	68.2	-1.2	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 81 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	40 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5830.00	<b>Data Rate:</b>	13.50 MBit/s
<b>Power Setting:</b>	9.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	5850.00	62.87	3.20	36.70	102.77	Max Peak	Horizontal	155	11	68.2	-19.5	Pass
#3	5960.02	26.83	3.26	36.80	66.89	Max Peak	Horizontal	155	11	68.2	-1.3	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 82 of 181

**Equipment Configuration for 5850 MHz Radiated Band-Edge Emissions**

<b>Antenna:</b>	RADWIN Ltd. SA0183620	<b>Variant:</b>	80 MHz
<b>Antenna Gain (dBi):</b>	11.00	<b>Modulation:</b>	OFDM
<b>Beam Forming Gain (Y):</b>	9.50	<b>Duty Cycle (%):</b>	99
<b>Channel Frequency (MHz):</b>	5810.00	<b>Data Rate:</b>	29.30 MBit/s
<b>Power Setting:</b>	9.5	<b>Tested By:</b>	JMH

**Test Measurement Results**

**5770.00 - 6000.00 MHz**

Num	Frequency MHz	Raw dB $\mu$ V	Cable Loss dB	AF dB	Level dB $\mu$ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB $\mu$ V/m	Margin dB	Pass /Fail
#1	5850.00	59.70	3.20	36.70	99.60	Max Peak	Horizontal	155	11	122.2	-22.6	Pass
#3	5930.06	26.42	3.18	36.80	66.40	Max Peak	Horizontal	155	11	68.2	-1.8	Pass
#2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

Test Notes: EUT powered by POE and connected to laptop outside chamber

Results Verified 19-20th January 2022

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 83 of 181

---

## **A. APPENDIX - GRAPHICAL IMAGES**

---

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



### A.1. 26 dB & 99% Bandwidth


#### 26 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5162.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	100 kHz	RF Att	0 dB
130 dB $\mu$ V	0.59 dB	VBW	300 kHz		
87 dB $\mu$ V	11.70340681 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 10:37:14

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5157.53106 MHz : 107.02 dB $\mu$ V T2 : 5166.50902 MHz : 114.54 dB $\mu$ V OBW : 8.98 MHz	Measured 26 dB Bandwidth: 11.70 MHz Measured 99% Bandwidth: 8.98 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5200.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	100 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.84 dB	VBW	300 kHz		
87 dB $\mu$ V	11.50300601 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 10:43:23

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5195.53106 MHz : 106.58 dB $\mu$ V T2 : 5204.50902 MHz : 106.35 dB $\mu$ V OBW : 17.555 MHz	Measured 26 dB Bandwidth: 11.50 MHz Measured 99% Bandwidth: 8.98 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5245.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	100 kHz	RF Att	0 dB
130 dB $\mu$ V	-1.08 dB	VBW	300 kHz		
87 dB $\mu$ V	11.50300601 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 10:47:19

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5240.53106 MHz : 105.78 dB $\mu$ V T2 : 5249.50902 MHz : 107.85 dB $\mu$ V OBW : 8.98 MHz	Measured 26 dB Bandwidth: 11.50 MHz Measured 99% Bandwidth: 8.98 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5165.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	200 kHz	RF Att	0 dB
130 dB $\mu$ V	0.09 dB	VBW	1 MHz		
87 dB $\mu$ V	22.52505010 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 10:54:54

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5156.06212 MHz : 109.86 dB $\mu$ V T2 : 5173.93788 MHz : 110.44 dB $\mu$ V OBW : 17.88 MHz	Measured 26 dB Bandwidth: 22.53 MHz Measured 99% Bandwidth: 17.88 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5200.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	200 kHz	RF Att	0 dB
130 dB $\mu$ V	0.59 dB	VBW	1 MHz		
87 dB $\mu$ V	21.80360721 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 10:57:28

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5191.06212 MHz : 108.77 dB $\mu$ V T2 : 5208.93788 MHz : 108.22 dB $\mu$ V OBW : 17.88 MHz	Measured 26 dB Bandwidth: 21.80 MHz Measured 99% Bandwidth: 17.88 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






26 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5240.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	200 kHz	RF Att	0 dB
130 dB $\mu$ V	0.02 dB	VBW	1 MHz		
87 dB $\mu$ V	22.52505010 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:00:37

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5231.06212 MHz : 107.60 dB $\mu$ V T2 : 5248.93788 MHz : 110.95 dB $\mu$ V OBW : 17.88 MHz	Measured 26 dB Bandwidth: 22.53 MHz Measured 99% Bandwidth: 17.88 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5172.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.35 dB	VBW	3 MHz		
87 dB $\mu$ V	43.88777555 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:17:42

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5153.86373 MHz : 112.03 dB $\mu$ V T2 : 5190.53707 MHz : 109.96 dB $\mu$ V OBW : 36.67 MHz	Measured 26 dB Bandwidth: 43.89 MHz Measured 99% Bandwidth: 36.67 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5200.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.23 dB	VBW	3 MHz		
87 dB $\mu$ V	45.03406814 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:22:04

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5181.66333 MHz : 108.58 dB $\mu$ V T2 : 5218.53707 MHz : 109.78 dB $\mu$ V OBW : 36.87 MHz	Measured 26 dB Bandwidth: 45.03 MHz Measured 99% Bandwidth: 36.87 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5230.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.23 dB	VBW	3 MHz		
87 dB $\mu$ V	45.15030060 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:26:07

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5211.66333 MHz : 108.58 dB $\mu$ V T2 : 5248.53707 MHz : 109.78 dB $\mu$ V OBW : 36.87 MHz	Measured 26 dB Bandwidth: 45.15 MHz Measured 99% Bandwidth: 36.87 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 80MHz, Channel: 5194.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	1 MHz	RF Att	0 dB
130 dB $\mu$ V	2.05 dB	VBW	3 MHz		
87 dB $\mu$ V	87.03406814 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:33:30

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5156.00401 MHz : 108.22 dB $\mu$ V T2 : 5232.31663 MHz : 108.96 dB $\mu$ V OBW : 76.31 MHz	Measured 26 dB Bandwidth: 87.03 MHz Measured 99% Bandwidth: 76.31 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




26 dB & 99% BANDWIDTH



Variant: 802.11 80MHz, Channel: 5210.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	1 MHz	RF Att	0 dB
130 dB $\mu$ V	-2.53 dB	VBW	3 MHz		
87 dB $\mu$ V	88.31663327 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 11:38:07

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5172.00401 MHz : 109.07 dB $\mu$ V T2 : 5248.31663 MHz : 108.95 dB $\mu$ V OBW : 76.31 MHz	Measured 26 dB Bandwidth: 88.32 MHz Measured 99% Bandwidth: 76.31 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



## A.2. 6 dB & 99% Bandwidth


6 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5730.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.35 dB	VBW	2 MHz		
87 dB $\mu$ V	9.13827655 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:06:00

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5725.01002 MHz : 108.17 dB $\mu$ V T2 : 5734.98998 MHz : 109.69 dB $\mu$ V OBW : 9.98 MHz	Measured 6 dB Bandwidth: 9.14 MHz Measured 99% Bandwidth: 9.98 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5787.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.18 dB	VBW	2 MHz		
87 dB $\mu$ V	8.85771543 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:08:14

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5782.09018 MHz : 104.44 dB $\mu$ V T2 : 5791.98998 MHz : 106.93 dB $\mu$ V OBW : 9.90 MHz	Measured 6 dB Bandwidth: 8.86 MHz Measured 99% Bandwidth: 9.90 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






6 dB & 99% BANDWIDTH



Variant: 802.11 10MHz, Channel: 5845.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-1.12 dB	VBW	2 MHz		
87 dB $\mu$ V	9.13827655 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:11:21

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5840.01002 MHz : 102.44 dB $\mu$ V T2 : 5850.03006 MHz : 102.58 dB $\mu$ V OBW : 10.02 MHz	Measured 6 dB Bandwidth: 9.14 MHz Measured 99% Bandwidth: 10.02 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5735.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	0.10 dB	VBW	2 MHz		
87 dB $\mu$ V	17.87575150 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:14:05

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5725.82164 MHz : 107.74 dB $\mu$ V T2 : 5744.09820 MHz : 107.36 dB $\mu$ V OBW : 18.28 MHz	Measured 6 dB Bandwidth: 17.88 MHz Measured 99% Bandwidth: 18.28 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5787.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.47 dB	VBW	2 MHz		
87 dB $\mu$ V	17.79559118 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:16:28

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5777.82164 MHz : 105.56 dB $\mu$ V T2 : 5796.17836 MHz : 102.44 dB $\mu$ V OBW : 18.36 MHz	Measured 6 dB Bandwidth: 17.80 MHz Measured 99% Bandwidth: 18.36 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 20MHz, Channel: 5840.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	1.63 dB	VBW	2 MHz		
87 dB $\mu$ V	17.95591182 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:19:48

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5830.74148 MHz : 101.76 dB $\mu$ V T2 : 5849.25852 MHz : 102.24 dB $\mu$ V OBW : 18.52 MHz	Measured 6 dB Bandwidth: 17.96 MHz Measured 99% Bandwidth: 18.52 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5745.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-2.09 dB	VBW	2 MHz		
87 dB $\mu$ V	36.67334669 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:23:53

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5726.66333 MHz : 108.71 dB $\mu$ V T2 : 5763.33667 MHz : 106.62 dB $\mu$ V OBW : 36.67 MHz	Measured 6 dB Bandwidth: 36.67 MHz Measured 99% Bandwidth: 36.67 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5787.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.18 dB	VBW	2 MHz		
87 dB $\mu$ V	36.75751503 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:27:20

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5768.66333 MHz : 104.54 dB $\mu$ V T2 : 5805.33667 MHz : 104.36 dB $\mu$ V OBW : 36.67 MHz	Measured 6 dB Bandwidth: 36.76 MHz Measured 99% Bandwidth: 36.67 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 40MHz, Channel: 5830.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.97 dB	VBW	2 MHz		
87 dB $\mu$ V	36.44288577 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:31:27

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5811.66333 MHz : 103.61 dB $\mu$ V T2 : 5848.33667 MHz : 103.76 dB $\mu$ V OBW : 36.67 MHz	Measured 6 dB Bandwidth: 36.44 MHz Measured 99% Bandwidth: 36.67 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 80MHz, Channel: 5765.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	-0.31 dB	VBW	2 MHz		
87 dB $\mu$ V	76.74348697 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:35:01

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5727.00401 MHz : 106.87 dB $\mu$ V T2 : 5802.99599 MHz : 106.38 dB $\mu$ V OBW : 75.99 MHz	Measured 6 dB Bandwidth: 76.74 MHz Measured 99% Bandwidth: 75.99 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






6 dB & 99% BANDWIDTH



Variant: 802.11 80MHz, Channel: 5787.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	0.49 dB	VBW	2 MHz		
87 dB $\mu$ V	76.74348697 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:37:15

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5749.00401 MHz : 104.37 dB $\mu$ V T2 : 5824.99599 MHz : 103.82 dB $\mu$ V OBW : 75.99 MHz	Measured 6 dB Bandwidth: 76.74 MHz Measured 99% Bandwidth: 75.99 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




6 dB & 99% BANDWIDTH



Variant: 802.11 80MHz, Channel: 5810.00 MHz, Temp: 20, Voltage: 120 Vac



Max/Ref Lvl	Delta 3 [T1]	RBW	500 kHz	RF Att	0 dB
130 dB $\mu$ V	0.76 dB	VBW	2 MHz		
87 dB $\mu$ V	76.42284569 MHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 25.OCT.2017 14:40:52

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 0 Trace Mode = MAX HOLD	T1 : 5772.00401 MHz : 104.61 dB $\mu$ V T2 : 5848.31663 MHz : 103.11 dB $\mu$ V OBW : 76.31 MHz	Measured 6 dB Bandwidth: 76.42 MHz Measured 99% Bandwidth: 76.31 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



### A.3. Power Spectral Density


#### POWER SPECTRAL DENSITY



Variat: 10 MHz, Channel: 5162.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	96.51 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.16354309 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 11:41:30

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5163.54 MHz : 96.51 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 10 MHz, Channel: 5162.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	100.99 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.15949499 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 11:33:08

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5159.49 MHz :100.99 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5200.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	103.58 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.20250501 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 11:49:40

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5202.51 MHz : 103.58 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 110 of 181


POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5200.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	107.00 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.20150301 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:03:04

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5201.50 MHz : 107.00 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 111 of 181


POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5245.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	103.57 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.24173347 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:06:11

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5241.73 MHz : 103.57 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5245.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	104.97 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.24269539 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:04:59

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5242.70 MHz : 104.97 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5165.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	90.30 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.17276553 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:11:20

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5172.77 MHz : 90.30 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 114 of 181


POWER SPECTRAL DENSITY



Variat: 20 MHz, Channel: 5165.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	94.45 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.16845691 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:12:23

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5168.46 MHz :94.45 dBuV/m	Limit: $\leq$ 17.00 dBm, 124 dBuVm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 115 of 181


POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5200.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	100.46 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.19283567 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:16:41

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5192.84 MHz : 100.46 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5200.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	103.00 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.19433868 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:15:42

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5194.34 MHz : 103.00 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 20 MHz, Channel: 5240.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	100.35 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.23684369 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:18:11

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5236.84 MHz : 100.35 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5240.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	101.89 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.24235471 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:19:04

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5242.35 MHz : 101.89 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 40 MHz, Channel: 5172.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	79.64 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.18051703 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:25:43

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5180.52 MHz : 79.64 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 40 MHz, Channel: 5172.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	83.84 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.18071743 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:23:05

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5180.72 MHz :83.84 dBuV/m	Limit: $\leq$ 17.00 dBm, 124 dBuVm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.





**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 121 of 181


POWER SPECTRAL DENSITY



Variation: 40 MHz, Channel: 5200.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	95.44 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.19208417 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:30:08

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5192.08 MHz : 95.44 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 122 of 181


POWER SPECTRAL DENSITY



Variants: 40 MHz, Channel: 5200.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	96.11 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.19428858 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:27:47

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5194.29 MHz : 96.11 dBuV/m	Limit: $\leq$ 17.00 dBm, 124 dBuVm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 40 MHz, Channel: 5230.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	95.13 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.23571142 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:31:40

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5235.71 MHz : 95.13 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 124 of 181


POWER SPECTRAL DENSITY



Variant: 40 MHz, Channel: 5230.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	97.54 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.22749499 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:32:32

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5227.49 MHz : 97.54 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5194.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	82.19 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.22237675 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:36:43

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5222.37 MHz : 82.19 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5194.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	84.60 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.18870942 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:36:00

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5188.71 MHz : 84.60 dBuV/m	Limit: ≤ 17.00 dBm, 124 dBuV/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5210.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	90.80 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.23100200 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:38:27

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5231.00 MHz : 90.80 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5210.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
140 dB $\mu$ V	92.93 dB $\mu$ V	VBW	3 MHz		
97 dB $\mu$ V	5.21496994 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 12:39:35

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5214.50 MHz : 92.93 dB $\mu$ V/m	Limit: $\leq$ 17.00 dBm, 124 dB $\mu$ V/m

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






POWER SPECTRAL DENSITY



Variat: 10 MHz, Channel: 5730.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	111.83 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.72733467 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 16:46:41

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5261.71 MHz : 111.83 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 10 MHz, Channel: 5730.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	110.90 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.72805611 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 16:53:52

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5257.34 MHz :110.90 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 10 MHz, Channel: 5787.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	112.96 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.78778156 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:03:00

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5296.57 MHz :112.96 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5787.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	109.20 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.78814228 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 16:59:33

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5301.70 MHz : 109.20 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 10 MHz, Channel: 5845.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	113.23 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.84674349 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:04:41

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5339.2 MHz : 113.23 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 10 MHz, Channel: 5845.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	109.78 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.84862725 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:05:36

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5339.22 MHz : 109.78 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5735.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	108.96 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.73544088 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 16:36:35

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5265.72 MHz : 108.96 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 20 MHz, Channel: 5735.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dBμV	107.72 dBμV	VBW	2 MHz		
97 dBμV	5.72894790 GHz	SWT	5 ms	Unit	dBμV



Date: 24.OCT.2017 16:38:31

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5271.58 MHz :107.72 dBuV/m	Limit: ≤ 6.00 dBm, 113 dBuVm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






POWER SPECTRAL DENSITY



Variation: 20 MHz, Channel: 5787.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	111.73 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.78872345 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:10:09

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5295.55 MHz : 111.73 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5787.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	108.52 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.78231062 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:09:00

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5293.07 MHz : 108.52 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 20 MHz, Channel: 5840.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	111.49 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.83258517 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:12:56

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5342.29 MHz : 111.48 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 20 MHz, Channel: 5840.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	107.53 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.83258517 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:14:37

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5332.99 MHz : 107.53 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 40 MHz, Channel: 5745.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	104.75 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.72886774 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:17:43

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5280.31 MHz : 104.74 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 40 MHz, Channel: 5745.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	103.67 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.72966934 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:16:49

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5285.52 MHz :103.67 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 40 MHz, Channel: 5787.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dBμV	107.12 dBμV	VBW	2 MHz		
97 dBμV	5.79551703 GHz	SWT	5 ms	Unit	dBμV



Date: 24.OCT.2017 17:18:56

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5307.72 MHz : 107.12 dBuV/m	Limit: ≤ 6.00 dBm, 113 dBuVm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 40 MHz, Channel: 5787.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	103.75 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.77367335 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:19:56

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5312.92 MHz : 103.75 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






POWER SPECTRAL DENSITY



Variation: 40 MHz, Channel: 5830.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	107.64 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.81847695 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:22:03

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5335.12 MHz : 107.64 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 40 MHz, Channel: 5830.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	102.69 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.84472946 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:21:17

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5318.48 MHz : 102.69 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 147 of 181


POWER SPECTRAL DENSITY



Variat: 80 MHz, Channel: 5765.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	99.89 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.74463928 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:23:38

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5323.19 MHz : 99.89 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 80 MHz, Channel: 5765.00 MHz, Polarity V Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	101.19 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.75041082 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:24:24

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5304.91 MHz :101.18 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variation: 80 MHz, Channel: 5787.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	99.85 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.75573747 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:26:23

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5312.99 MHz : 99.85 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variat: 80 MHz, Channel: 5787.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	98.04 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.76856313 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:25:36

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5297.27 MHz : 98.04 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5810.00 MHz, Polarity H, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl	Marker 1 [T1]	RBW	500 kHz	RF Att	0 dB
140 dB $\mu$ V	101.53 dB $\mu$ V	VBW	2 MHz		
97 dB $\mu$ V	5.77841683 GHz	SWT	5 ms	Unit	dB $\mu$ V



Date: 24.OCT.2017 17:27:31

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5330.41 MHz : 101.53 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




POWER SPECTRAL DENSITY



Variant: 80 MHz, Channel: 5810.00 MHz, Polarity V, Temp: 20, Voltage: 48 Vdc



Max/Ref Lvl      Marker 1 [T1]      RBW    500 kHz    RF Att    0 dB  
 140 dB $\mu$ V                      99.00 dB $\mu$ V      VBW    2 MHz  
 97 dB $\mu$ V                      5.79188377 GHz    SWT    5 ms      Unit      dB $\mu$ V



Date: 24.OCT.2017 17:28:35

Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = Average Sweep Count = 100 RF Atten (dB) = 0 Trace Mode = VIEW	M1 : 5287.49 MHz : 99.00 dB $\mu$ V/m	Limit: $\leq$ 6.00 dBm, 113 dB $\mu$ Vm

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






## A.4. Radiated

### A.4.1. TX Spurious & Restricted Band Emissions

#### A.4.1.1. RADWIN Ltd. SA0183620 11 dBi



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5165.52	71.15	3.08	-14.39	59.84	Fundamental	Vertical	151	8	--	--	
2	10324.28	40.61	4.44	0.11	45.16	Peak (NRB)	Horizontal	151	0	--	--	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5200.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 8.5, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5202.67	89.18	3.09	-14.25	78.02	Fundamental	Vertical	151	0	--	--	
2	6163.52	59.82	3.20	-11.97	51.05	Peak (NRB)	Horizontal	151	0	--	--	Pass
3	6216.44	59.51	3.26	-11.81	50.96	Peak (NRB)	Horizontal	151	0	--	--	Pass
4	10402.63	61.94	4.41	0.00	66.35	Max Peak	Horizontal	165	50	68.2	-1.9	Pass
5	15601.96	53.29	5.58	1.30	60.17	Max Peak	Vertical	162	34	68.2	-8.1	Pass
6	15601.96	38.24	5.58	1.30	45.12	Max Avg	Vertical	162	34	54.0	-8.9	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 155 of 181

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5245.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 6, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5245.12	87.14	3.15	-14.40	75.89	Fundamental	Vertical	151	9	--	--	
2	10490.94	63.16	4.46	0.33	67.95	Max Peak	Horizontal	158	26	68.2	-0.3	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 156 of 181

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5730.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 15.5, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5726.82	71.01	3.16	-12.86	61.31	Fundamental	Vertical	150	0	--	--	
2	6068.05	57.35	3.24	-11.92	48.67	Peak (NRB)	Horizontal	150	0	--	--	Pass
3	11453.49	59.90	4.64	-0.80	63.74	Max Peak	Horizontal	167	48	68.2	-4.5	Pass
4	11453.49	43.79	4.64	-0.80	47.63	Max Avg	Horizontal	167	48	54.0	-6.4	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 157 of 181

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5787.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 23.5, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5787.78	75.59	3.21	-12.78	66.02	Fundamental	Horizontal	151	0	--	--	
2	6072.79	59.32	3.25	-11.75	50.82	Peak (NRB)	Horizontal	151	0	--	--	Pass
3	11574.29	61.03	4.56	-0.46	65.13	Max Peak	Horizontal	162	44	68.2	-3.1	Pass
4	11574.29	49.30	4.56	-0.46	53.40	Max Avg	Horizontal	162	44	54.0	-0.6	Pass
5	17363.87	55.45	5.99	0.79	62.23	Max Peak	Horizontal	151	70	68.2	-6.0	Pass
6	17363.87	39.01	5.99	0.79	45.79	Max Avg	Horizontal	151	70	54.0	-8.2	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 158 of 181

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5845.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 20.5, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5841.37	72.41	3.22	-13.00	62.63	Fundamental	Horizontal	151	0	--	--	
2	6101.68	60.32	3.24	-11.89	51.67	Peak (NRB)	Horizontal	151	0	--	--	Pass
3	11685.48	60.91	4.95	-0.46	65.40	Max Peak	Horizontal	154	82	68.2	-2.8	Pass
4	11685.48	46.48	4.95	-0.46	50.97	Max Avg	Horizontal	154	82	54.0	-3.0	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**A.4.1.2. RADWIN Ltd. SA0183620 20.5 dBi**

**TX SPURIOUS & RESTRICTED BAND EMISSIONS**



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5729.26	71.19	3.17	-12.84	61.52	Fundamental	Vertical	151	8	--	--	
2	6072.79	57.33	3.25	-11.75	48.83	Peak (NRB)	Horizontal	151	8	--	--	Pass
3	11461.84	57.89	4.62	-0.78	61.73	Max Peak	Horizontal	174	324	68.2	-6.5	Pass
4	11461.84	42.67	4.62	-0.78	46.51	Max Avg	Horizontal	174	324	54.0	-7.5	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5787.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 16, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5789.10	75.74	3.21	-12.79	66.16	Fundamental	Horizontal	151	7	--	--	
2	6070.25	61.85	3.25	-11.84	53.26	Peak (NRB)	Horizontal	151	7	--	--	Pass
3	6103.72	62.82	3.24	-11.84	54.22	Peak (NRB)	Horizontal	150	0	--	--	Pass
4	6103.72	56.05	3.24	-11.84	47.45	Max Avg	Horizontal	160	12	54.0	-6.6	Pass
5	11573.85	62.63	4.54	-0.48	66.69	Max Peak	Horizontal	154	324	68.2	-1.5	Pass
6	11573.85	49.48	4.54	-0.48	53.54	Max Avg	Horizontal	154	324	54.0	-0.5	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 161 of 181

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: 10 MHz, Test Freq: 5845.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 9.5, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5844.29	69.66	3.21	-12.82	60.05	Fundamental	Horizontal	151	9	--	--	
2	6099.58	59.54	3.24	-11.94	50.84	Peak (NRB)	Horizontal	151	9	--	--	Pass
3	11686.91	54.02	4.98	-0.48	58.52	Max Peak	Horizontal	149	59	68.2	-9.7	Pass
4	11686.91	38.62	4.98	-0.48	43.12	Max Avg	Horizontal	149	59	54.0	-10.9	Pass

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**A.4.2. Restricted Edge & Band-Edge Emissions**

**A.4.2.3. RADWIN Ltd. SA0183620 11 dBi**



**RESTRICTED LOWER BAND-EDGE EMISSIONS**

Variant: 10 MHz, Test Freq: 5162.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 1.5



4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5150.00	11.35	3.06	35.40	49.81	Max Avg	Vertical	155	8	54.0	-4.2	Pass
2	5150.00	29.26	3.06	35.40	67.72	Max Peak	Vertical	155	8	68.2	-0.5	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 163 of 181



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 20 MHz, Test Freq: 5165.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: -2



4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5150.00	9.78	3.06	35.40	48.24	Max Avg	Vertical	155	8	54.0	-5.8	Pass
2	5150.00	29.02	3.06	35.40	67.48	Max Peak	Vertical	155	8	68.2	-0.8	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 40 MHz, Test Freq: 5172.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: -11



4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5150.00	10.61	3.06	35.40	49.07	Max Avg	Vertical	155	8	54.0	-4.9	Pass
2	5150.00	29.73	3.06	35.40	68.19	Max Peak	Vertical	155	8	68.2	0.0	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



RESTRICTED LOWER BAND-EDGE EMISSIONS

Variant: 80 MHz, Test Freq: 5194.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: -3



4500.00 - 5250.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5150.00	10.12	3.06	35.40	48.58	Max Avg	Vertical	155	8	54.0	-5.4	Pass
2	5150.00	28.51	3.06	35.40	66.97	Max Peak	Vertical	155	8	68.2	-1.3	Pass
3	5150.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 10 MHz, Test Freq: 5730.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 15.5, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5643.22	27.82	3.18	36.30	67.30	Max Peak	Horizontal	155	11	68.2	-0.9	Pass
2	5725.00	77.12	3.17	36.50	116.79	Max Peak	Horizontal	155	11	122.2	-5.4	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 20 MHz, Test Freq: 5735.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 15.5, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5648.99	28.07	3.21	36.30	67.58	Max Peak	Horizontal	155	11	68.2	-0.7	Pass
2	5725.00	69.55	3.17	36.50	109.22	Max Peak	Horizontal	155	11	122.2	-13.0	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 168 of 181

5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 40 MHz, Test Freq: 5745.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 15.5, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5634.63	27.39	3.20	36.30	66.89	Max Peak	Horizontal	155	11	68.2	-1.3	Pass
2	5725.00	62.44	3.17	36.50	102.11	Max Peak	Horizontal	155	11	122.2	-20.1	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.






5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 80 MHz, Test Freq: 5765.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 16, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5646.10	28.43	3.20	36.30	67.93	Max Avg	Horizontal	155	11	68.2	-0.3	Pass
2	5725.00	60.13	3.17	36.50	99.80	Max Avg	Horizontal	155	11	122.2	-22.4	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 170 of 181

5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 20 MHz, Test Freq: 5840.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 20.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	69.44	3.20	36.70	109.34	Max Peak	Horizontal	155	11	122.2	-12.9	Pass
3	5926.37	28.00	3.19	36.80	67.99	Max Peak	Horizontal	155	11	68.2	-0.2	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 40 MHz, Test Freq: 5830.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 20.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	63.68	3.20	36.70	103.58	Max Peak	Horizontal	155	11	122.2	-18.7	Pass
3	5934.21	27.80	3.19	36.80	67.79	Max Peak	Horizontal	155	11	68.2	-0.4	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 172 of 181

5850 MHz RADIATED BAND-EDGE EMISSIONS




Variant: 80 MHz, Test Freq: 5810.00 MHz, Antenna: RADWIN Ltd. SA0183620 11 dBi, Power Setting: 19.5, Duty Cycle (%): 99

Measurement Distance: 3m

Sweep Time: 10.0 s

RBW: 1 MHz  
VBW: 3 MHz

Date: 20 Oct 2017 -



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	61.03	3.20	36.70	100.93	Max Peak	Horizontal	155	11	68.2	-21.3	Pass
3	5927.29	28.19	3.19	36.80	68.18	Max Peak	Horizontal	155	11	68.2	-0.1	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



**A.4.2.4. RADWIN Ltd. SA0183620 20.5 dBi**

5725 MHz RADIATED BAND-EDGE EMISSIONS



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5645.74	26.29	3.20	36.30	65.79	Max Peak	Horizontal	155	11	68.2	-2.4	Pass
2	5725.00	78.51	3.17	36.50	118.18	Max Peak	Horizontal	155	11	122.2	-4.0	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 20 MHz, Test Freq: 5735.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 8.5, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5647.18	27.00	3.20	36.30	66.50	Max Peak	Horizontal	155	11	68.2	-1.7	Pass
2	5725.00	70.06	3.17	36.50	109.73	Max Peak	Horizontal	155	11	122.2	-12.5	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 40 MHz, Test Freq: 5745.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 6.5, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5625.18	27.25	3.19	36.30	66.74	Max Peak	Horizontal	155	11	68.2	-1.5	Pass
2	5725.00	61.43	3.17	36.50	101.10	Max Peak	Horizontal	155	11	122.2	-21.1	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 176 of 181

5725 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 80 MHz, Test Freq: 5765.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 7, Duty Cycle (%): 99



5600.00 - 5780.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5605.34	27.69	3.24	36.30	67.23	Max Peak	Horizontal	155	11	68.2	-1.0	Pass
2	5725.00	58.79	3.17	36.50	98.46	Max Peak	Horizontal	155	11	122.2	-23.7	Pass
3	5725.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 10 MHz, Test Freq: 5845.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 9.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	76.59	3.20	36.70	116.49	Max Peak	Horizontal	155	11	122.2	-5.7	Pass
3	5926.37	26.42	3.19	36.80	66.41	Max Peak	Horizontal	155	11	68.2	-1.8	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




**Title:** RADWIN 5000 JET 5.x GHz  
**To:** FCC Part 15.407 & ISSED RSS-247  
**Serial #:** RDWN65-U2 Rev B (non-DFS Bands)  
**Issue Date:** 21<sup>st</sup> January 2022  
**Page:** 178 of 181

5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 20 MHz, Test Freq: 5840.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 9.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	68.49	3.20	36.70	108.39	Max Peak	Horizontal	155	11	68.2	-13.8	Pass
3	5976.15	26.81	3.28	36.90	66.99	Max Peak	Horizontal	155	11	68.2	-1.2	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 40 MHz, Test Freq: 5830.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 9.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	62.87	3.20	36.70	102.77	Max Peak	Horizontal	155	11	68.2	-19.5	Pass
3	5960.02	26.83	3.26	36.80	66.89	Max Peak	Horizontal	155	11	68.2	-1.3	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

5850 MHz RADIATED BAND-EDGE EMISSIONS



Variant: 80 MHz, Test Freq: 5810.00 MHz, Antenna: RADWIN Ltd. SA0183620 20.5 dBi, Power Setting: 9.5, Duty Cycle (%): 99



5770.00 - 6000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	5850.00	59.70	3.20	36.70	99.60	Max Peak	Horizontal	155	11	122.2	-22.6	Pass
3	5930.06	26.42	3.18	36.80	66.40	Max Peak	Horizontal	155	11	68.2	-1.8	Pass
2	5850.00	--	--	--	--	Band-Edge	--	--	--	--	--	--

**Test Notes:** EUT powered by POE and connected to laptop outside chamber

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)