

Company: Radwin Ltd.

Test of: RADWIN JET DUO

To: FCC CFR 47 Part 1.1310

Report No.: RDWN50-U6\_MPE Rev A

**MPE/RF EXPOSURE TEST REPORT**



# MPE/RF EXPOSURE TEST REPORT

FROM



Test of: RADWIN JET DUO

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN50-U6\_MPE Rev A

This report supersedes: NONE

Applicant: Radwin Ltd.  
27 Habarzel Street  
Tel Aviv 69710  
Israel

Issue Date: 26<sup>th</sup> December 2017

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10^{(G \text{ (dBi)})/10}$$

The RADWIN JET DUO has two antenna chains. The peak power in the table below is calculated by assuming a worst-case scenario for the maximum gain antenna and output power. The calculated separation distance is worst case found (Operational mode 40 MHz, channel 3675.00 MHz). Calculation was performed using the 17 dBi antenna gain.

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

Freq. Band (MHz)	Antenna Gain (dBi)	Numeric Gain (numeric)	Max Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density @ 20cm	Distance (cm)	
						Calculated Safe Distance @ 1mW/cm <sup>2</sup> Limit(cm)	Minimum Separation Distance (cm)
3,675.0	17	50.12	+28.79	756.83	7.55	55	55

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification

#### Maximum Permissible Exposure Limits

**§90.1217** Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency levels in excess of the Commission's guidelines. See §1.1307 (b)(1) of this chapter.

Limit = 1 mW / cm<sup>2</sup> from 1.310 Table 1

#### Laboratory Measurement Uncertainty for Power Measurements

Measurement uncertainty	±1.33dB
-------------------------	---------



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)