

REGULATORY COMPLIANCE TEST REPORT

FCC CFR 47 Part 1.1310

Report No.: RDWN77-U5 Rev A (FCC MPE)

Company: Radwin

Model Name: RADWIN 2000 EC00, RADWIN 2000 E100



REGULATORY COMPLIANCE TEST REPORT

Company Name: Radwin

Model Name: RADWIN 2000 EC00, RADWIN 2000 E100

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: RDWN77-U5 Rev A (FCC MPE)

This report supersedes: NONE

Applicant: Radwin 27 Habarzel Street Tel Aviv, 6971039 Israel

Issue Date: 22nd December 2022

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA Phone: +1 (925) 462-0304 Fax: +1 (925) 462-0306 www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels Power Density = Pd (mW/cm²) = EIRP/(4* π *d²) EIRP = P * G P = Peak output power (mW) G = Antenna numeric gain (numeric) d = Separation distance (cm) Numeric Gain = 10 ^ (G (dBi)/10)

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Client declared there is no simultaneous transmission in the following frequency bands therefore each band is kept separate for MPE calculation purposes.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm ²) @ 20cm	Power Density Limit (mW/cm ²)	Min Calculated safe distance for Limit (cm)
5150.0 - 5250.0	24.00	251.19	27.97	626.94	31.31	1.0	111.92
5725.0 - 5850.0	24.00	251.19	29.10	812.83	40.619	1.0	127.47
5150.0 - 5250.0	32.00	1584.89	19.97	99.31	31.313	1.0	111.92
5725.0 - 5850.0	32.00	1584.89	28.07	641.21	202.176	1.0	284.38

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.





575 Boulder Court Pleasanton, California 94566, USA Tel: +1 (925) 462 0304 Fax: +1 (925) 462 0306 www.micomlabs.com