



# WinLink™ 1000 Family

## Carrier-Class License Exempt Radio System



### Features

- High data rate of up to 48Mbps
- Long range of up to 80 Km
- Integrated solution for n x E1/T1s and Ethernet interfaces
- Carrier-class solution
- Compliant with FCC, IC and ETSI regulations

### Description

WinLink1000 family of products is a carrier-class, high capacity and low cost Point to Point broadband wireless transmission system. It packs Legacy TDM and Ethernet services over 2.4GHz and 5.x GHz unlicensed bands and is suitable for deployment in FCC or ESTI regulated countries.

WinLink1000, which provides high capacity connectivity of up to 48 Mbps, allows for the rapid deployment of E1/T1s and Ethernet links at a fraction of alternatives cost.

WinLink1000 is the right solution for customers requiring immediate deployment of affordable carrier-class high capacity connectivity in the license exempt frequencies.

### Benefits

#### Short Time to Service

- License exempt frequencies remove regulatory delays

- Wireless connectivity instead of private line leasing from service providers
- Compact integrated solution that is simple to install and operate


#### Carrier Class Solution

- High reliability and availability based on robust air-interface
- TDM transmission complies with all Telecom requirements.

### Typical Applications

#### Remote Sites' Connectivity

WinLink1000 is offered to enterprises with multiple sites that require a cost effective and transparent connection of their LAN and PBX systems across their various campuses



#### Broadband Access

WinLink1000 provides broadband access services, such broadband Ethernet and Leased Lines, to Small and Medium Enterprises (SME).

#### Backhauling

WinLink1000 backhauls traffic from cellular base stations, Hotspots or point of presence (POP) of wireless ISP's to backbone network.



## Specifications

### Configuration

- **Architecture**  
Indoor Unit (IDU) and  
Outdoor Unit (ODU)
- **IDU to ODU Interface**  
Outdoor CAT-5 cable  
Maximum length of  
100m

### Radio

- **Frequency**  
5.725 – 5.850 GHz  
5.470 – 5.725 GHz  
2.400-2.483 GHz (specific spectrum band  
is country dependent)
- **Data Rate**  
Configurable up to 48Mbps
- **Channel BW**  
20MHz
- **Duplex Technique**  
TDD
- **System Gain**  
160dB
- **Modulation**  
OFDM - BPSK, QPSK,  
16QAM, 64QAM
- **Transmit Power**  
FCC: 18dBm (max)  
ETSI: 7dbm (Max, limited by the  
regulation)
- **Received Dynamic range**  
>60dB

### Antennas

	2.400-2.483 GHz	5.725-5.850 GHz
<b>Integrated</b>		
Gain	17dBi	22dBi
Beam width	20	9 <sup>o</sup>
Polarization	Linear	Linear
<b>External, 2-foot</b>		
Gain	24dBi	28dBi
Beam width	8	4.5 <sup>o</sup>
Polarization	Linear	Linear

### LAN Interface

- **Type**  
10/100BaseT,  
Auto-negotiation
- **Framing/Coding**  
IEEE 802.3/U
- **Bridging**  
Self-learning up to 2000 MAC  
addresses
- **Traffic Handling**  
MAC layer bridging, self-learning
- **Data Latency**  
2msec typical
- **Line Impedance**  
100Ω
- **VLAN Support**  
Transparent
- **Connector**  
RJ-45

### E1/T1 Interface

- **Framing**  
Unframed (Transparent)
- **Timing**  
Plesynchronous (Independent Tx and  
Rx timing)
- **Latency**  
8 msec
- **Line Impedance**  
120/100Ohm, balanced
- **Number of Ports**  
1, 2, 4, 6
- **Connector**  
RJ-45
- **Jitter & Wander**  
G.823, G.824

### Management

- **Protocol**  
SNMP based
- **Network Management**  
Based on SNMPC
- **Management Interface**  
Ethernet 10/100BT  
RS-232
- **Upgrade Capabilities**  
Local and over the air remote software  
download
- **Diagnostic**  
Local and Remote  
loopback testing



## Mechanics

- **ODU Dimensions (with Integrated Antenna)**  
Height: 12 in  
Width: 12 in  
Depth: 2.3 in  
Weight: 3.3 lb
- **IDU-E Dimensions**  
Height: 1.7 in  
Width: 9.3 in  
Depth: 6.5 in  
Weight: 1.1 lb

## General

- **Power Feeding**  
110/220 VAC  
50/60Hz; 48VDC
- **Power Consumption**  
25W max
- **Mounting**  
Pole and Wall

## Environmental

- **Outdoor Unit Enclosure**  
All-weather cases
- **ODU Temperatures**  
-35 – 60°C  
-31–140°F

- **IDU Temperatures**  
-5 – 45°C  
23 - 113°F
- **Humidity**  
Up to 90%  
Non-condensing

## Standards

	2.400-2.483 GHz	5.725-5.85 GHz
<b>Radio</b>		
FCC	47CFR Part 15, subpart C	47CFR Part 15, subpart C
IC	RSS-210	RSS-210
ETSI	EN 300 328	N.A.
<b>Safety</b>		
TUV	60950, according to UL 60950	
CAN-CSA	C22.2 No. 60950	
<b>EMC</b>		
FCC	47CFR Part 15, §15.247 and subpart B	
ETSI	EN 300 386 EN 301 489-1	
<b>Environmental</b>		
ETSI	IEC 60721-3-4 Class 4M5	
	IP 67	

**Radwin Ltd**  
32 Habarzel st,  
Tel-Aviv 69710, Israel  
Tel: +972 3 6455577  
Fax: +972 3 7668777  
Web site: [www.radwin.com](http://www.radwin.com)