

# AT9520 Series

## Multilayer Chip Antenna

### Features

- ❖ Monolithic SMD with small, low-profile and light-weight type.
- ❖ Wide bandwidth

### Applications

- ❖ 2.4GHz WLAN, Home RF, Bluetooth Modules, etc.



### Specifications

Part Number	Frequency Range (MHz)	Peak Gain (XZ-V)	Average Gain (XZ-V)	VSWR	Impedance
<b>AT9520-B2R4HAA_</b>	2400~2500	3.0 dBi typ.	1.0 dBi typ.	2 max.	50 Ω


Q'ty/Reel (pcs) : 1000pcs  
 Operating Temperature Range : -40 ~ +85 °C  
 Storage Temperature Range : -40 ~ +85 °C  
 Power Capacity : 3W max.

### Part Number

**AT**   **9520**   -   **B**   **2R4**   **HAA**   **□**  
 ①   ②   ③   ④   ⑤   ⑥

① Type	AT : Antenna	② Dimensions ( L x W )	9.5x 2.0 mm
③ Material Code	B	④ Frequency Range	2R4=2400MHz
⑤ Specification Code	HAA	⑥ Packaging	T: Tape & Reel B: Bulk


### Terminal Configuration



No.	Terminal Name	No.	Terminal Name
①	Feeding Point	②	NC


**Dimensions and Recommended PC Board Pattern**

Unit : mm




Mark	L	W	T	a
Dimensions	9.5±0.2	2.0±0.2	1.2+ 0.1/-0.2	0.5±0.3

(a) Without Matching Circuits (Moderate Bandwidth)



(b) With Matching Circuits (Wide Bandwidth)




(Matching circuit and component values will be different, depending on PCB layout)

\*Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.



**Typical Electrical Characteristics (T=25°C)**

❖ Test Board





❖ Return Loss

(a) Without Matching Circuits





(b) With Matching Circuits





❖ Radiation Patterns



XY-V/XY-H



XZ-V/XZ-H



YZ-V/YZ-H



**Advanced Ceramic X Corp.**

16 Tzu Chiang Road, Hsinchu Industrial District Hsinchu Hsien 303, Taiwan

TEL:886-3-5987008 FAX:886-3-5987001

E-mail: [acx@acxc.com.tw](mailto:acx@acxc.com.tw) <http://www.acxc.com.tw>