



Test report No.: 2360754R-RFUSV22S-A

TEST REPORT

Product Name	Mobile Computer
Trademark	CIPHERLAB
Model and /or type reference	RK26
FCC Applicant's name / address	CipherLab Co., Ltd. 12F, 333, Dunhua S.Rd., Sec.2, Taipei, Taiwan
IC Applicant's name / address	CIPHERLAB CO. LTD. 12F, 333, Dunhua S.Rd., Sec.2, Taipei, Taiwan
Manufacturer's name	CIPHERLAB CO. LTD.
Test method requested, standard	FCC CFR Title 47 Part 22 ; Part 24 ; Part 27 RSS-132 Issue 4, RSS-133 Issue 6+A1, RSS-139 Issue 4
Test reference	FCC CFR Title 47 Part 2, TIA/EIA 603-E 2016, KDB 971168 D01v03r01, ANSI C63.26 2015, RSS-GEN Issue 5+A2
FCC ID	Q3N-RK26
IC	5121A-RK26
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / April Chen)	<i>April Chen</i>
Tested By (Engineer / Daniel Wu)	<i>Daniel Wu</i>
Approved By (Manager / Tim Sung)	<i>Tim Sung</i>
Date of Receipt	2023/06/28
Date of Issue	2023/09/08
Report Version	V1.0

INDEX

	Page
1. General Information.....	6
1.1. EUT Description.....	6
1.2. Antenna List	7
1.3. Operational Description.....	7
1.4. Configuration of tested System	8
1.5. EUT Setup Procedures.....	8
1.6. Test Facility	9
2. Technical Test	10
2.1. Summary of test result.....	10
2.2. List of test Equipment.....	12
2.3. Measurement Uncertainty.....	13
3. Conducted Output Power Measurement.....	14
3.1. Test Specification	14
3.2. Test Setup	14
3.3. Limits.....	14
3.4. Test Procedure	14
3.5. Test Result of Maximum Power Output and ERP/EIRP Power	15
4. Occupied Bandwidth	20
4.1. Test Specification	20
4.2. Test Setup	20
4.3. Test Procedure	20
4.4. Test Result of Occupied Bandwidth	21
5. Spurious Emission At Antenna Terminals (+/-1MHz).....	27
5.1. Test Specification	27
5.2. Setup	27
5.3. Limits.....	27
5.4. Test Procedure	27
5.5. Test Result of Spurious Emission At Antenna Terminals (+/-1MHz).....	28
6. Spurious Emission	31
6.1. Test Specification	31
6.2. Test Setup	31
6.3. Limits.....	32

6.4.	Test Procedure	32
6.5.	Test Result of Spurious Emission.....	33
7.	Frequency Stability Under Temperature & Voltage Variations	55
7.1.	Test Specification	55
7.2.	Test Setup	55
7.3.	Limits.....	55
7.4.	Test Procedure	55
7.5.	Test Result of Frequency Stability Under Temperature Variations.....	56
8.	Peak to Average Ratio	61
8.1.	Test Specification	61
8.2.	Test Setup	61
8.3.	Limits.....	61
8.4.	Test Procedure	61
8.5.	Test Result of Peak to Average Ratio.....	62

Appendix 1: EUT Test Photographs

Appendix 2: Product Photos - Please refer to the file: 2360754R-Product Photos

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
2360754R-RFUSV22S-A	V1.0	Initial issue of report.	2023/09/08

1. General Information

1.1. EUT Description

Product Name	Mobile Computer
Model No.	RK26
Trade Name	CIPHERLAB
IMEI No.	35453833
FCC ID	Q3N-RK26
IC	5121A-RK26
EUT Rated Voltage	AC 100-240V / 50-60Hz (Power by Adapter) DC 3.8V (Power by Battery)
EUT Test Voltage	AC 120V / 60Hz and DC 5V (Power by Adapter) DC 3.8V (Power by Battery)
TX Frequency	GSM 850: 824.2 MHz ~ 848.8 MHz GSM 1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band 2: 1852.4 MHz ~ 1907.6 MHz WCDMA Band 4: 1712.4 MHz ~ 1752.6 MHz WCDMA Band 5: 826.4 MHz ~ 846.6 MHz
RX Frequency	GSM 850: 869.2 MHz ~ 893.8 MHz GSM 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band 2: 1932.4 MHz ~ 1987.6 MHz WCDMA Band 4: 2112.4 MHz ~ 2152.6 MHz WCDMA Band 5: 871.4 MHz ~ 891.6 MHz
Function	GSM / GPRS / EDGE / WCDMA / HSDPA / HSUPA
Type of Modulation	GMSK / 8PSK / QPSK
Power Cable (Optional)	MFR: CIPHERLAB, M/N: RK25 SNAP ON Non-Shielded, 1.5m, with one ferrite core bonded.
Power Adapter #1 (Optional)	MFR: Sunny, M/N: SYS1561-1005 Input: AC 100-240V~ 1.0A MAX, 50-60Hz Output: +5.0V==2.0A
Power Adapter #2 (Optional)	MFR: CWT, M/N: 2AEA010BC3D Input: AC 100-240V~ 0.35A, 50-60Hz Output: 5.0V==2.0A, 10.0W
Supported Unit	
Type C Cable	MFR: SUNCA, M/N: 1Q11512211-XJ, Shielded, 1m

1.2. Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	Auden	KZLT0LS260011 (LTE Main, TX/RX)	PIFA	2.6 dBi for GSM850 1.4 dBi for GSM1900 1.4 dBi for WCDMA Band 2 2.8 dBi for WCDMA Band 4 2.6 dBi for WCDMA Band 5
2	Auden	KZLT0LS260011 (LTE Aux, RX)	PIFA	-5.0 dBi for GSM850 -3.5 dBi for GSM1900 -3.5 dBi for WCDMA Band 2 -3.6 dBi for WCDMA Band 4 -5.0 dBi for WCDMA Band 5

Note: The antenna gain as by the manufacturer provided.

1.3. Operational Description

The EUT provide all functions described as above. The EUT is tested with maximum rated TX power via the Base Station simulator. DEKRA has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:


Test Mode	Mode 1: GSM 850 Mode 2: GSM 1900 Mode 3: WCDMA Band 2 Mode 4: WCDMA Band 4 Mode 5: WCDMA Band 5
-----------	---

Note:


1. Regards to the frequency band operation; the lowest, middle and highest frequency of channel were selected to perform the test, and then shown on this report.
2. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in VOICE mode for GSM, and RMC mode for WCDMA, and show the worst case in the test report.
3. Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
4. The EUT was performed at X axis, Y axis and Z axis position for radiated spurious emission tests. The worst case was found at Z axis, so the measurement will follow this same test configuration

1.4. Configuration of tested System

(a) Configuration of Radiated measurement



(b) Configuration of Conducted measurement



1.5. EUT Setup Procedures

1	Setup the EUT and simulators as shown on 1.4
2	Turn on the power of all equipment.
3	The EUT was set to communicate with Base Station simulator.
4	Repeat the above procedure (3).

1.6. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Actual	Test Date
Radiated Emission	Temperature (°C)	24.5°C	2023/07/18 ~ 2023/09/01
	Humidity (%RH)	58.3 %	
Conductive	Temperature (°C)	25.0°C	
	Humidity (%RH)	65.0 %	

USA	FCC Registration Number: TW0033
Site Description	Accredited by TAF
	Accredited Number: 3023
Test Laboratory	DEKRA Testing and Certification Co., Ltd
Address	No. 5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

2. Technical Test

2.1. Summary of test result

Test Item	FCC Reference section	FCC Limit	Result
Conducted Output Power	§2.1046	<7 Watts for §22.913(a) <2 Watts for §24.232(c) <1 Watts for §27.50(d)	Pass
	§22.913(a)		
	§24.232(c)		
	§27.50(d)		
Occupied Bandwidth	§2.1049	Within the frequency range	Pass
	§22.863		
	§24.238(b)		
	§27.53(h)		
Spurious Emission at Antenna Terminals	§2.1051	<-13dBm	Pass
	§22.917(a)		
	§24.238(a)		
	§27.53(h)		
Conducted Emission	§2.1051	<-13dBm	Pass
	§22.917(a)		
	§24.238(a)		
	§27.53(h)		
Field Strength of Spurious Radiation	§2.1053	<-13dBm	Pass
	§22.917(a)		
	§24.238(a)		
	§27.53(h)		
Frequency Stability for Temperature & Voltage	§2.1055	<±2.5 ppm for §22.355 Within the frequency range for §24.235, §27.54	Pass
	§22.355		
	§24.235		
	§27.54		
Peak to Average Ratio	§22.913 (d)	<13dB	Pass
	§24.232 (d)		
	§27.50 (d)		

Test Item	IC Reference section	IC Limit	Result
Conducted Output Power	RSS GEN §6.12	<11.5 Watts for RSS 132 §5.4 <2 Watts for RSS 133 §6.4 <1 Watts for RSS 139 §6.5	Pass
	RSS 132 §5.4		
	RSS 133 §6.4		
	RSS 139 §6.5		
Occupied Bandwidth	RSS GEN §6.7	Within the frequency range	Pass
	RSS 132 §5.3		
	RSS 133 §6.3		
	RSS 139 §6.4		
Spurious Emission at Antenna Terminals	RSS GEN §6.13	<-13dBm	Pass
	RSS 132 §5.5		
	RSS 133 §6.5		
	RSS 139 §6.6		
Conducted Emission	RSS GEN §6.13	<-13dBm	Pass
	RSS 132 §5.5		
	RSS 133 §6.5		
	RSS 139 §6.6		
Field Strength of Spurious Radiation	RSS GEN §6.13	<-13dBm	Pass
	RSS 132 §5.5		
	RSS 133 §6.5		
	RSS 139 §6.6		
Frequency Stability for Temperature & Voltage	RSS GEN §6.11	<±2.5 ppm for RSS 132 §5.3, RSS 133 §6.3 Within the frequency range for RSS 139 §6.4	Pass
	RSS 132 §5.3		
	RSS 133 §6.3		
	RSS 139 §6.4		
Peak to Average Ratio	RSS 132 §5.4	<13dB	Pass
	RSS 133 §6.4		
	RSS 139 §6.5		

2.2. List of test Equipment

Conducted / HY-SR03

Instrument Description	Manufacturer	Model No.	Serial No.	Last Calibration	Next Calibration
Spectrum Analyzer	Agilent	N9010A	MY53470892	2022/11/07	2023/11/06
Standard Temperature & Humidity Chamber	K SON	THS-D4T-100	A0606	2022/08/23	2023/08/22
DC Power Supply	Keysight	E36234A	MY59001234	2022/10/31	2023/10/30
Universal Radio communication tester	R&S	CMU200	113574	2023/07/07	2024/07/07

Radiated / HY-CB03

Instrument Description	Manufacturer	Model No.	Serial No.	Last Calibration	Next Calibration
Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0678	2021/09/23	2023/09/22
Horn Antenna	Com-Power	AH-840	101100	2021/10/04	2023/10/03
Horn Antenna	RF SPIN	DRH18-E	210507A18ES	2023/05/11	2024/05/10
Pre-Amplifier	SGH	0301	20211007-10	2023/01/10	2024/01/09
Pre-Amplifier	SGH	PRAMP118	20200701	2023/01/10	2024/01/09
Pre-Amplifier	EMCI	EMC05820SE	980310	2023/01/10	2024/01/09
Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
Coaxial Cable	EMCI	EMC102-KM-K M-600	1160314		
Coaxial Cable	EMCI	EMC102-KM-K M-7000	170242		
Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
Coaxial Cable	SGH	SGH18	2021005-1	2023/01/10	2024/01/09
Coaxial Cable	SGH	SGH18	202108-4		
Coaxial Cable	SGH	HA800	GD20110223-1		
Coaxial Cable	SGH	HA800	GD20110222-3		
Universal Radio communication tester	R&S	CMU200	113574	2023/07/07	2024/07/07

2.3. Measurement Uncertainty

Uncertainties have been calculated according to the DEKRA internal document with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95 % confidence level based on a coverage factor ($k=2$).


Test Item	Uncertainty
Conducted Output Power	± 1.58 dB
Occupied Bandwidth	± 1580.61 Hz
Peak to Average Ratio	± 2.14 dB
Conducted Band Edge	± 2.14 dB
Conducted Spurious Emissions	± 2.14 dB
Radiated Spurious Emissions	30MHz~1GHz: ± 5.88 dB 1GHz~18GHz: ± 3.11 dB 18GHz~40GHz: ± 3.09 dB
Frequency Stability	± 0.42 ppm

3. Conducted Output Power Measurement

3.1. Test Specification

According to Part 2.1046, 22.913, 24.232, 27.50, RSS-GEN, RSS-132, RSS-133, RSS-139.

3.2. Test Setup



3.3. Limits

Band	Limit
850	ERP < 7 W
1900	EIRP < 2 W
AWS(1700)	EIRP < 1 W

3.4. Test Procedure

The EUT is tested with maximum rated TX power via the Base Station simulator, and the output power was measured at the antenna terminals of the EUT.

3.5. Test Result of Maximum Power Output and ERP/EIRP Power

$$\text{EIRP} = \text{PT} + \text{GT} - \text{LC} = \text{ERP} + 2.15 \text{ dB}, \text{ERP} = \text{EIRP} - 2.15 \text{ dB}$$

PT = transmitter output power in dBm

GT = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

GSM 850						
Test Mode	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (W)	ERP Limit (W)
Voice	824.2	34.34	2.6	34.790	3.013	7
	836.6	34.38	2.6	34.830	3.041	7
	848.8	34.00	2.6	34.450	2.786	7
GPRS 850 (↑)	824.2	33.78	2.6	34.230	2.649	7
	836.6	33.81	2.6	34.260	2.667	7
	848.8	33.73	2.6	34.180	2.618	7
GPRS 850 (↑↑)	824.2	33.22	2.6	33.670	2.328	7
	836.6	33.23	2.6	33.680	2.333	7
	848.8	33.57	2.6	34.020	2.523	7
GPRS 850 (↑↑↑)	824.2	31.90	2.6	32.350	1.718	7
	836.6	31.93	2.6	32.380	1.730	7
	848.8	31.91	2.6	32.360	1.722	7
GPRS 850 (↑↑↑↑)	824.2	30.71	2.6	31.160	1.306	7
	836.6	30.80	2.6	31.250	1.334	7
	848.8	30.76	2.6	31.210	1.321	7
EGPRS 850 (↑)	824.2	27.48	2.6	27.930	0.621	7
	836.6	27.40	2.6	27.850	0.610	7
	848.8	27.49	2.6	27.940	0.622	7
EGPRS 850 (↑↑)	824.2	27.36	2.6	27.810	0.604	7
	836.6	27.30	2.6	27.750	0.596	7
	848.8	27.40	2.6	27.850	0.610	7
EGPRS 850 (↑↑↑)	824.2	27.20	2.6	27.650	0.582	7
	836.6	27.14	2.6	27.590	0.574	7
	848.8	27.26	2.6	27.710	0.590	7
EGPRS 850 (↑↑↑↑)	824.2	27.02	2.6	27.470	0.558	7
	836.6	26.95	2.6	27.400	0.550	7
	848.8	27.04	2.6	27.490	0.561	7

GSM 1900						
Test Mode	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	EIRP Limit (W)
Voice	1850.2	30.95	1.4	32.350	1.718	2
	1880.0	30.97	1.4	32.370	1.726	2
	1909.8	30.84	1.4	32.240	1.675	2
GPRS 1900 (↑)	1850.2	30.82	1.4	32.220	1.667	2
	1880.0	30.85	1.4	32.250	1.679	2
	1909.8	30.56	1.4	31.960	1.570	2
GPRS 1900 (↑↑)	1850.2	27.58	1.4	28.980	0.791	2
	1880.0	27.84	1.4	29.240	0.839	2
	1909.8	27.69	1.4	29.090	0.811	2
GPRS 1900 (↑↑↑)	1850.2	26.31	1.4	27.710	0.590	2
	1880.0	26.45	1.4	27.850	0.610	2
	1909.8	26.38	1.4	27.780	0.600	2
GPRS 1900 (↑↑↑↑)	1850.2	25.14	1.4	26.540	0.451	2
	1880.0	25.24	1.4	26.640	0.461	2
	1909.8	25.20	1.4	26.600	0.457	2
EGPRS 1900 (↑)	1850.2	25.45	1.4	26.850	0.484	2
	1880.0	25.32	1.4	26.720	0.470	2
	1909.8	25.26	1.4	26.660	0.463	2
EGPRS 1900 (↑↑)	1850.2	24.77	1.4	26.170	0.414	2
	1880.0	24.86	1.4	26.260	0.423	2
	1909.8	24.75	1.4	26.150	0.412	2
EGPRS 1900 (↑↑↑)	1850.2	22.46	1.4	23.860	0.243	2
	1880.0	22.54	1.4	23.940	0.248	2
	1909.8	22.49	1.4	23.890	0.245	2
EGPRS 1900 (↑↑↑↑)	1850.2	20.19	1.4	21.590	0.144	2
	1880.0	20.23	1.4	21.630	0.146	2
	1909.8	20.22	1.4	21.620	0.145	2

WCDMA Band 2						
Test Mode	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	EIRP Limit (W)
Voice	1852.4	23.07	1.4	24.470	0.280	2
	1880	23.04	1.4	24.440	0.278	2
	1907.6	23.15	1.4	24.550	0.285	2
RMC	1852.4	23.19	1.4	24.590	0.288	2
	1880	23.34	1.4	24.740	0.298	2
	1907.6	23.32	1.4	24.720	0.296	2
HSUPA Subtest 1	1852.4	21.88	1.4	23.280	0.213	2
	1880	21.40	1.4	22.800	0.191	2
	1907.6	21.38	1.4	22.780	0.190	2
HSUPA Subtest 2	1852.4	20.52	1.4	21.920	0.156	2
	1880	20.72	1.4	22.120	0.163	2
	1907.6	20.68	1.4	22.080	0.161	2
HSUPA Subtest 3	1852.4	21.13	1.4	22.530	0.179	2
	1880	21.27	1.4	22.670	0.185	2
	1907.6	21.21	1.4	22.610	0.182	2
HSUPA Subtest 4	1852.4	20.51	1.4	21.910	0.155	2
	1880	20.68	1.4	22.080	0.161	2
	1907.6	20.20	1.4	21.600	0.145	2
HSUPA Subtest 5	1852.4	21.09	1.4	22.490	0.177	2
	1880	21.25	1.4	22.650	0.184	2
	1907.6	21.14	1.4	22.540	0.179	2
HSDPA Subtest 1	1852.4	21.77	1.4	23.170	0.207	2
	1880	21.95	1.4	23.350	0.216	2
	1907.6	21.96	1.4	23.360	0.217	2
HSDPA Subtest 2	1852.4	21.78	1.4	23.180	0.208	2
	1880	21.85	1.4	23.250	0.211	2
	1907.6	21.95	1.4	23.350	0.216	2
HSDPA Subtest 3	1852.4	21.76	1.4	23.160	0.207	2
	1880	21.98	1.4	23.380	0.218	2
	1907.6	21.89	1.4	23.290	0.213	2
HSDPA Subtest 4	1852.4	21.76	1.4	23.160	0.207	2
	1880	21.94	1.4	23.340	0.216	2
	1907.6	21.89	1.4	23.290	0.213	2

WCDMA Band 4						
Test Mode	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (W)	EIRP Limit (W)
Voice	1712.4	20.56	2.8	23.360	0.217	1
	1732.6	20.59	2.8	23.390	0.218	1
	1752.6	20.44	2.8	23.240	0.211	1
RMC	1712.4	20.63	2.8	23.430	0.220	1
	1732.6	20.75	2.8	23.550	0.226	1
	1752.6	20.60	2.8	23.400	0.219	1
HSUPA Subtest 1	1712.4	19.59	2.8	22.390	0.173	1
	1732.6	19.80	2.8	22.600	0.182	1
	1752.6	19.56	2.8	22.360	0.172	1
HSUPA Subtest 2	1712.4	18.19	2.8	20.990	0.126	1
	1732.6	18.26	2.8	21.060	0.128	1
	1752.6	18.09	2.8	20.890	0.123	1
HSUPA Subtest 3	1712.4	18.66	2.8	21.460	0.140	1
	1732.6	18.80	2.8	21.600	0.145	1
	1752.6	18.58	2.8	21.380	0.137	1
HSUPA Subtest 4	1712.4	17.71	2.8	20.510	0.112	1
	1732.6	17.83	2.8	20.630	0.116	1
	1752.6	17.76	2.8	20.560	0.114	1
HSUPA Subtest 5	1712.4	19.72	2.8	22.520	0.179	1
	1732.6	19.75	2.8	22.550	0.180	1
	1752.6	19.51	2.8	22.310	0.170	1
HSDPA Subtest 1	1712.4	19.53	2.8	22.330	0.171	1
	1732.6	19.69	2.8	22.490	0.177	1
	1752.6	19.50	2.8	22.300	0.170	1
HSDPA Subtest 2	1712.4	19.09	2.8	21.890	0.155	1
	1732.6	19.26	2.8	22.060	0.161	1
	1752.6	19.02	2.8	21.820	0.152	1
HSDPA Subtest 3	1712.4	19.06	2.8	21.860	0.153	1
	1732.6	19.23	2.8	22.030	0.160	1
	1752.6	19.07	2.8	21.870	0.154	1
HSDPA Subtest 4	1712.4	19.08	2.8	21.880	0.154	1
	1732.6	19.24	2.8	22.040	0.160	1
	1752.6	19.08	2.8	21.880	0.154	1


WCDMA Band 5						
Test Mode	Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (W)	ERP Limit (W)
Voice	826.4	24.13	2.6	24.580	0.287	7
	836.6	24.14	2.6	24.590	0.288	7
	846.6	24.02	2.6	24.470	0.280	7
RMC	826.4	24.73	2.6	25.180	0.330	7
	836.6	24.87	2.6	25.320	0.340	7
	846.6	24.79	2.6	25.240	0.334	7
HSUPA Subtest 1	826.4	23.13	2.6	23.580	0.228	7
	836.6	23.29	2.6	23.740	0.237	7
	846.6	23.22	2.6	23.670	0.233	7
HSUPA Subtest 2	826.4	21.59	2.6	22.040	0.160	7
	836.6	21.72	2.6	22.170	0.165	7
	846.6	21.67	2.6	22.120	0.163	7
HSUPA Subtest 3	826.4	22.21	2.6	22.660	0.185	7
	836.6	22.25	2.6	22.700	0.186	7
	846.6	22.13	2.6	22.580	0.181	7
HSUPA Subtest 4	826.4	21.57	2.6	22.020	0.159	7
	836.6	21.74	2.6	22.190	0.166	7
	846.6	21.63	2.6	22.080	0.161	7
HSUPA Subtest 5	826.4	23.08	2.6	23.530	0.225	7
	836.6	23.24	2.6	23.690	0.234	7
	846.6	23.20	2.6	23.650	0.232	7
HSDPA Subtest 1	826.4	23.58	2.6	24.030	0.253	7
	836.6	23.82	2.6	24.270	0.267	7
	846.6	23.78	2.6	24.230	0.265	7
HSDPA Subtest 2	826.4	23.07	2.6	23.520	0.225	7
	836.6	23.18	2.6	23.630	0.231	7
	846.6	23.18	2.6	23.630	0.231	7
HSDPA Subtest 3	826.4	23.01	2.6	23.460	0.222	7
	836.6	23.11	2.6	23.560	0.227	7
	846.6	23.14	2.6	23.590	0.229	7
HSDPA Subtest 4	826.4	23.15	2.6	23.600	0.229	7
	836.6	23.14	2.6	23.590	0.229	7
	846.6	23.16	2.6	23.610	0.230	7

4. Occupied Bandwidth

4.1. Test Specification

According to Part 2.1049, 22.863, 24.238, 27.53, RSS-GEN, RSS-132, RSS-133, RSS-139.

4.2. Test Setup



4.3. Test Procedure

The EUT is tested with maximum rated TX power via the Base Station simulator, and the occupied bandwidth was measured at the antenna terminals of the EUT. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. The plots below show the resultant display from the Spectrum Analyser.

4.4. Test Result of Occupied Bandwidth


GSM 850				
BW	Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
VOICE	128	824.2	244.24	309.8
VOICE	189	836.4	245.67	313.9
VOICE	251	848.8	244.25	314.1
EGPRS	128	824.2	244.01	309.3
EGPRS	189	836.4	242.09	314.3
EGPRS	251	848.8	244.97	314.5

GSM 1900				
BW	Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
VOICE	512	1850.2	247.44	310.6
VOICE	661	1880	245.26	310.7
VOICE	810	1909.8	249.32	316.8
EGPRS	512	1850.2	246.08	315.6
EGPRS	661	1880	248.12	317.0
EGPRS	810	1909.8	247.88	313.0


WCDMA Band 2				
BW	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
RMC	9262	1852.4	4.1061	4.677
RMC	9400	1880	4.1212	4.692
RMC	9538	1907.6	4.1128	4.685

WCDMA Band 4				
BW	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
RMC	1312	1712.4	4.1102	4.689
RMC	1413	1732.6	4.1030	4.684
RMC	1513	1752.6	4.1051	4.697


WCDMA Band 5				
BW	Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
RMC	4132	826.4	4.1122	4.691
RMC	4183	836.6	4.1088	4.702
RMC	4233	846.6	4.1030	4.689




OCC 2G850 CH128 VOICE




OCC 2G850 CH189 VOICE




OCC 2G850 CH251 VOICE




OCC 2G850 CH128 EGPRS




OCC 2G850 CH189 EGPRS




OCC 2G850 CH251 EGPRS




OCC 2G1900 CH512 VOICE




OCC 2G1900 CH661 VOICE




OCC 2G1900 CH810 VOICE





OCC 2G1900 CH512 EGPRS



OCC 2G1900 CH661 EGPRS





OCC 2G1900 CH810 EGPRS





OCC B2 CH9262 RMC

OCC B2 CH9400 RMC




OCC B2 CH9538 RMC

OCC B4 CH1312 RMC




OCC B4 CH1413 RMC


OCC B4 CH1513 RMC



OCC B5 CH4132 RMC



OCC B5 CH4183 RMC




OCC B5 CH4233 RMC

5. Spurious Emission At Antenna Terminals (+/-1MHz)

5.1. Test Specification

According to Part 2.1051, 22.917, 24.238, 27.53, RSS-GEN, RSS-132, RSS-133, RSS-139.

5.2. Setup




5.3. Limits

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


5.4. Test Procedure

In accordance with Part 22.917, 24.238, 27.53, at least 1% of the emission bandwidth was used for the resolution and video bandwidths up to 1MHz away from the Block Edge. At greater than 1MHz, the resolution and video bandwidth were set 3 x RBW. The reference power and path losses of all channels used for testing in each frequency block were measured.


5.5. Test Result of Spurious Emission At Antenna Terminals (+/-1MHz)




Bandedge 2G850 CH128 VOICE




Bandedge 2G850 CH251 VOICE




Bandedge 2G850 CH128 EGPRS




Bandedge 2G850 CH251 EGPRS




Bandedge 2G1900 CH512 VOICE





Bandedge 2G1900 CH810 VOICE



Bandedge 2G1900 CH512 EGPRS





Bandedge 2G1900 CH810 EGPRS





Bandedge B2 CH9262 RMC

Bandedge B2 CH9538 RMC



Bandedge B4 CH1312 RMC

Bandedge B4 CH1513 RMC



Bandedge B5 CH4132 RMC

Bandedge B5 CH4233 RMC


6. Spurious Emission

6.1. Test Specification


According to Part 2.1051, 2.1053, 22.917, 24.238, 27.53, RSS-GEN, RSS-132, RSS-133, RSS-139.

6.2. Test Setup

Spurious emissions at antenna terminals



Field strength of spurious radiation



6.3. Limits

Limit	<-13dBm
-------	---------

$43 + 10\text{Log}(P)$ down on the carrier where P is the power in Watts.

6.4. Test Procedure

In accordance with Part 2.1051/2.1053, the spurious emissions from the EUT were measured. The transmitter output power was attenuated using a combination of filters and attenuators and the frequency spectrum investigated from 30MHz to 20GHz. The EUT was set to transmit on full power. The resolution and video bandwidth was set to 1MHz and 3 x RBW. In accordance with Part 22.917 & 24.238, 27.53. The spectrum analyzer detector was set to Max Hold. In addition, measurements were made up to the 10th harmonic of the fundamental. The device was then replaced with a substitution antenna, which input signal was adjusted until the received level matched that of the previously detected emission.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.


The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to TIA/EIA 603-E on radiated measurement.


6.5. Test Result of Spurious Emission




CSE 2G850 CH128 VOICE 30M-1G




CSE 2G850 CH128 VOICE 1G-10G




CSE 2G850 CH128 EGPRS 30M-1G




CSE 2G850 CH128 EGPRS 1G-10G




CSE 2G850 CH189 VOICE 30M-1G




CSE 2G850 CH189 VOICE 1G-10G




CSE 2G850 CH189 EGPRS 30M-1G




CSE 2G850 CH189 EGPRS 1G-10G




CSE 2G850 CH251 VOICE 30M-1G




CSE 2G850 CH251 VOICE 1G-10G




CSE 2G850 CH251 EGPRS 30M-1G




CSE 2G850 CH251 EGPRS 1G-10G




CSE 2G1900 CH512 VOICE 30M-1G




CSE 2G1900 CH512 VOICE 1G-20G




CSE 2G1900 CH512 EGPRS 30M-1G




CSE 2G1900 CH512 EGPRS 1G-20G




CSE 2G1900 CH661 VOICE 30M-1G




CSE 2G1900 CH661 VOICE 1G-20G




CSE 2G1900 CH661 EGPRS 30M-1G




CSE 2G1900 CH661 EGPRS 1G-20G




CSE 2G1900 CH810 VOICE 30M-1G




CSE 2G1900 CH810 VOICE 1G-20G




CSE 2G1900 CH810 EGPRS 30M-1G




CSE 2G1900 CH810 EGPRS 1G-20G




CSE B2 CH9262 RMC 30M-1G




CSE B2 CH9262 RMC 1G-20G




CSE B2 CH9400 RMC 30M-1G




CSE B2 CH9400 RMC 1G-20G




CSE B2 CH9538 RMC 30M-1G




CSE B2 CH9538 RMC 1G-20G




CSE B4 CH1312 RMC 30M-1G




CSE B4 CH1312 RMC 1G-18G




CSE B4 CH1413 RMC 30M-1G




CSE B4 CH1413 RMC 1G-18G




CSE B4 CH1513 RMC 30M-1G




CSE B4 CH1513 RMC 1G-18G




CSE B5 CH4132 RMC 30M-1G




CSE B5 CH4132 RMC 1G-10G




CSE B5 CH4183 RMC 30M-1G







CSE B5 CH4183 RMC 1G-10G




CSE B5 CH4233 RMC 30M-1G



CSE B5 CH4233 RMC 1G-10G




Site :HY-CB03
 Condition :3m Horizontal
 Mode :2G_GSM850_Link_CH251
 Test BY :Gavin Wu



No.	Frequency MHz	Level dBm	Limit dBm	Over Limit dB	Read Level dBm	Factor dB	Remark
1	1697.600	-40.85	-13.00	-27.85	-27.74	-13.11	Peak
2	2546.400	-40.51	-13.00	-27.51	-29.01	-11.50	Peak
3	3395.200	-53.24	-13.00	-40.24	-41.10	-9.14	Peak
4	4244.000	-50.08	-13.00	-37.08	-44.23	-5.85	Peak
5	5092.800	-47.58	-13.00	-34.58	-45.75	-1.83	Peak
6	5941.600	-49.22	-13.00	-36.22	-50.02	0.80	Peak

Note:
 1. Level = Read Level + Factor
 2. Factor = Antenna Factor + Cable Loss - Preamp Factor + Aux Factor
 3. Over Limit = Level - Limit Line
 4. Aux Factor = Convert E (dBuVm) to EIRP (dBm)
 $= 107 + 20\log(3) - 104.8 = 11.8$ dB
 5. The other emission levels were very low against the limit.
 6. The emission under 1GHz was not included since the emission levels are very low against the limit.


Site :HY-CB03
 Condition :3m Vertical
 Mode :2G_GSM850_Link_CH251
 Test BY :Gavin Wu



No.	Frequency MHz	Level dBm	Limit dBm	Over Limit dB	Read Level dBm	Factor dB	Remark
1	1697.600	-43.33	-13.00	-30.33	-30.22	-13.11	Peak
2	2546.400	-39.57	-13.00	-26.57	-28.07	-11.50	Peak
3	3395.200	-54.00	-13.00	-41.00	-44.86	-9.14	Peak
4	4244.000	-50.64	-13.00	-37.64	-44.79	-5.85	Peak
5	5092.800	-48.28	-13.00	-35.28	-46.45	-1.83	Peak
6	5941.600	-50.32	-13.00	-37.32	-51.12	0.80	Peak

Note:
 1. Level = Read Level + Factor
 2. Factor = Antenna Factor + Cable Loss - Preamp Factor + Aux Factor
 3. Over Limit = Level - Limit Line
 4. Aux Factor = Convert E (dBuVm) to EIRP (dBm)
 $= 107 + 20\log(3) - 104.8 = 11.8$ dB
 5. The other emission levels were very low against the limit.
 6. The emission under 1GHz was not included since the emission levels are very low against the limit.


Site :HY-CB03
 Condition :3m Horizontal
 Mode :2G_GSM1900_Link_CH512
 Test BY :Gavin Wu



No.	Frequency MHz	Level dBm	Limit dBm	Over Limit dB	Read Level dBm	Factor dB	Remark
1	3700.400	-45.48	-13.00	-32.48	-38.50	-6.98	Peak
2	5550.600	-45.50	-13.00	-32.50	-45.20	-0.30	Peak
3	7400.800	-32.06	-13.00	-19.06	-37.18	5.12	Peak





Note:
 1. Level = Read Level + Factor
 2. Factor = Antenna Factor + Cable Loss - Preamp Factor + Aux Factor
 3. Over Limit = Level - Limit Line
 4. Aux Factor = Convert E (dBuVm) to EIRP (dBm)
 $= 107 + 20\log(3) - 104.8 = 11.8$ dB
 5. The other emission levels were very low against the limit.
 6. The emission under 1GHz was not included since the emission levels are very low against the limit.





Site :HY-CB03
 Condition :3m Vertical
 Mode :2G_GSM1900_Link_CH512
 Test BY :Gavin Wu











No.	Frequency MHz	Level dBm	Limit dBm	Over Limit dB	Read Level dBm	Factor dB	Remark
1	3700.400	-44.98	-13.00	-31.98	-38.00	-6.98	Peak
2	5550.600	-45.04	-13.00	-32.04	-44.59	-0.45	Peak
3	7400.800	-36.01	-13.00	-23.01	-41.13	5.12	Peak





Note:
 1. Level = Read Level + Factor
 2. Factor = Antenna Factor + Cable Loss - Preamp Factor + Aux Factor
 3. Over Limit = Level - Limit Line
 4. Aux Factor = Convert E (dBuVm) to EIRP (dBm)
 $= 107 + 20\log(3) - 104.8 = 11.8$ dB
 5. The other emission levels were very low against the limit.
 6. The emission under 1GHz was not included since the emission levels are very low against the limit.




























































7. Frequency Stability Under Temperature & Voltage Variations

7.1. Test Specification

According to Part 2.1055, 22.355, 24.235, 27.54, RSS-GEN, RSS-132, RSS-133, RSS-139.

7.2. Test Setup



7.3. Limits

Limit	< ± 2.5 ppm
-------	-------------

7.4. Test Procedure

The frequency stability of transmitter is measured by:

- (a) Temperature: The temperature is varied from -30 °C to 50 °C in 10 °C increment using a standard temperature & Humidity chamber.
- (b) Primary Supply Voltage: The primary supply voltage is varied 85 % to 115 % of the nominal value for non-hand-carried equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating endpoint which shall be specified by the manufacturer.

The EUT was connected via the base station simulator. Universal Radio Communication Tester, was used to measure The Frequency Error. The maximum result of measurements was recorded.

7.5. Test Result of Frequency Stability Under Temperature Variations

GSM 850

Temperature Variations

Temperature Interval(°C)	Test Channel	Deviation (kHz)		Limit (kHz)
		VOICE	EGPRS	
-30	Low	0.005	0.006	±2.09
-20	Low	0.006	0.008	±2.09
-10	Low	0.007	0.005	±2.09
0	Low	0.005	0.006	±2.09
10	Low	0.008	0.007	±2.09
20	Low	0.009	0.005	±2.09
30	Low	0.005	0.008	±2.09
40	Low	0.006	0.008	±2.09
50	Low	0.010	0.009	±2.09
-30	High	-0.005	-0.004	±2.09
-20	High	-0.007	-0.009	±2.09
-10	High	0.006	0.008	±2.09
0	High	0.008	-0.004	±2.09
10	High	0.004	0.006	±2.09
20	High	-0.007	0.008	±2.09
30	High	-0.009	0.009	±2.09
40	High	-0.011	0.015	±2.09
50	High	0.010	0.013	±2.09

Voltage Variations

DC Voltage (V)	Test Channel	Deviation (kHz)		Limit (kHz)
		VOICE	EGPRS	
4.35	Low	0.008	0.009	±2.09
3.8	Low	0.009	0.005	±2.09
3.6	Low	0.008	0.006	±2.09
4.35	High	-0.004	0.005	±2.09
3.8	High	-0.007	0.008	±2.09
3.6	High	-0.006	0.007	±2.09

GSM 1900

Temperature Variations

Temperature Interval(°C)	Test Channel	Deviation (kHz)		Limit (kHz)
		VOICE	EGPRS	
-30	Low	0.008	0.015	±4.77
-20	Low	0.009	0.014	±4.77
-10	Low	0.009	0.016	±4.77
0	Low	0.008	0.015	±4.77
10	Low	0.012	0.015	±4.77
20	Low	0.011	0.017	±4.77
30	Low	0.009	0.016	±4.77
40	Low	-0.010	0.018	±4.77
50	Low	0.008	0.016	±4.77
-30	High	-0.023	-0.022	±4.77
-20	High	-0.021	-0.021	±4.77
-10	High	-0.022	-0.018	±4.77
0	High	-0.021	-0.019	±4.77
10	High	-0.021	-0.017	±4.77
20	High	-0.017	-0.014	±4.77
30	High	-0.015	-0.015	±4.77
40	High	-0.013	-0.013	±4.77
50	High	-0.020	-0.018	±4.77

Voltage Variations

DC Voltage (V)	Test Channel	Deviation (kHz)		Limit (kHz)
		VOICE	EGPRS	
4.35	Low	0.008	0.017	±4.77
3.8	Low	0.011	0.017	±4.77
3.6	Low	0.012	0.016	±4.77
4.35	High	-0.016	-0.014	±4.77
3.8	High	-0.017	-0.014	±4.77
3.6	High	-0.014	-0.016	±4.77

WCDMA Band 2

Temperature Variations

Temperature Interval(°C)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
-30	Low	0.0062	±4.71
-20	Low	0.0058	±4.71
-10	Low	0.0048	±4.71
0	Low	0.0062	±4.71
10	Low	0.0072	±4.71
20	Low	0.0055	±4.71
30	Low	0.0058	±4.71
40	Low	0.0067	±4.71
50	Low	0.0075	±4.71
-30	High	-0.0055	±4.71
-20	High	-0.0064	±4.71
-10	High	-0.0055	±4.71
0	High	-0.0057	±4.71
10	High	-0.0049	±4.71
20	High	-0.0067	±4.71
30	High	-0.0063	±4.71
40	High	-0.0085	±4.71
50	High	-0.0096	±4.71

Voltage Variations

DC Voltage (V)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
4.35	Low	0.0062	±4.71
3.8	Low	0.0055	±4.71
3.6	Low	0.0068	±4.71
4.35	High	-0.0073	±4.71
3.8	High	-0.0067	±4.71
3.6	High	-0.0057	±4.71

WCDMA Band 4

Temperature Variations

Temperature Interval(°C)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
-30	Low	0.0107	±4.33
-20	Low	0.0097	±4.33
-10	Low	0.0101	±4.33
0	Low	0.0119	±4.33
10	Low	0.0124	±4.33
20	Low	0.0166	±4.33
30	Low	0.0175	±4.33
40	Low	0.0211	±4.33
50	Low	0.0244	±4.33
-30	High	0.0116	±4.33
-20	High	0.0119	±4.33
-10	High	0.0099	±4.33
0	High	0.0101	±4.33
10	High	0.0097	±4.33
20	High	-0.0160	±4.33
30	High	-0.0169	±4.33
40	High	-0.0193	±4.33
50	High	-0.0251	±4.33

Voltage Variations

DC Voltage (V)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
4.35	Low	0.0172	±4.33
3.8	Low	0.0166	±4.33
3.6	Low	0.0156	±4.33
4.35	High	0.0168	±4.33
3.8	High	-0.0160	±4.33
3.6	High	0.0162	±4.33

WCDMA Band 5

Temperature Variations

Temperature Interval(°C)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
-30	Low	0.0028	±2.09
-20	Low	0.0034	±2.09
-10	Low	0.024	±2.09
0	Low	0.033	±2.09
10	Low	0.039	±2.09
20	Low	0.036	±2.09
30	Low	0.042	±2.09
40	Low	0.039	±2.09
50	Low	0.047	±2.09
-30	High	-0.0026	±2.09
-20	High	-0.0029	±2.09
-10	High	-0.0034	±2.09
0	High	-0.0025	±2.09
10	High	-0.0023	±2.09
20	High	-0.0037	±2.09
30	High	-0.0046	±2.09
40	High	0.0043	±2.09
50	High	-0.0045	±2.09

Voltage Variations


DC Voltage (V)	Test Channel	Deviation (kHz)	Limit (kHz)
		RMC	
4.35	Low	0.0039	±2.09
3.8	Low	0.0036	±2.09
3.6	Low	0.0042	±2.09
4.35	High	-0.0044	±2.09
3.8	High	-0.0037	±2.09
3.6	High	0.0050	±2.09

8. Peak to Average Ratio

8.1. Test Specification

According to Part 22.913, 24.232, 27.50, RSS-GEN, RSS-132, RSS-133, RSS-139.

8.2. Test Setup




8.3. Limits

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure.


8.4. Test Procedure

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval as follows:
 - 1) for continuous transmissions, set to 1 ms,
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- e) Record the maximum PAPR level associated with a probability of 0.1 %.


8.5. Test Result of Peak to Average Ratio




PTAR 2G850 CH128 VOICE




PTAR 2G850 CH189 VOICE




PTAR 2G850 CH251 VOICE




PTAR 2G850 CH128 EGPRS




PTAR 2G850 CH189 EGPRS




PTAR 2G850 CH251 EGPRS




PTAR 2G1900 CH512 VOICE




PTAR 2G1900 CH661 VOICE




PTAR 2G1900 CH810 VOICE



PTAR 2G1900 CH661 VOICE




PTAR 2G1900 CH810 VOICE




PTAR 2G1900 CH512 EGPRS


PTAR 2G1900 CH661 EGPRS




PTAR B2 CH9262 RMC




PTAR B2 CH9400 RMC




PTAR B2 CH9538 RMC




PTAR B4 CH1312 RMC




PTAR B4 CH1413 RMC




PTAR B4 CH1513 RMC



PTAR B5 CH4132 RMC



PTAR B5 CH4183 RMC



PTAR B5 CH4233 RMC