



欣技資訊股份有限公司

CIPHERLAB CO.,LTD.

12F, 333 Dunhua S. Rd., Sec.2, Taipei, Taiwan R.O.C.

TEL : 886-2-8647-1166 FAX : 886-2-8732-2255

Declaration - MIF for HAC RF Interference Evaluation

To whom it may concern:

This device, with FCC ID: Q3N-RS30: Hearing Aid Compatibility Requirement is going to be certified under ANSI C63.19 2011 version per Part 20.19.

The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in HAC test report exhibit and adding the MIF value in dB (V/m) using pre-determined values provided by Speag.

SPEAG UID	UID Version	Communication System	MIF (dB)
10021	DAB (06.02.2014)	GSM-FDD (TDMA, GMSK)	3.63
10011	CAB (16.01.2014)	UMTS-FDD (WCDMA)	-27.23

The Speag –reference documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, DASY5 Manual V5.2, December 2012

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely,

Herbie Jiang

Manager

Tel: 886-2-86471166 EXT 2277

Fax: 886-2-87322255

E-mail: herbie.jiang@cipherlab.com.tw