

# RF EXPOSURE REPORT

### **CERTIFICATE OF CONFORMITY**

FCC Rule Part: FCC Part 2 (Section 2.1091)

FCC Part 2 (Section 2.1093)

Report No.: MFBCFP-WTW-P22100655

FCC ID: Q3V-MRS32C

Product: MRS Tubular Motor

Model No.: MRS-32C

**Received Date: 2022/10/25** 

Test Date: 2022/11/17 Issued Date: 2022/12/13

Applicant: Nien Made Enterprise Co., Ltd.

Address: 23F.-1, No. 98, Shizheng N. 7th Rd., Xitun Dist., Taichung City 407, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan **Test Location:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration / 198487 / TW2021

**Designation Number:** 

Jeremy Lin / Project Engineer

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by: Jessica Cheng / Senior Specialist



## **Table of Contents**

Relea	se Control Record	3
1	Certificate	4
	Applicable RF Exposure Limit	
	Applicable Evaluation Criteria	
4	Test Results	7
4.1	RF Exposure	7
5	Conclusion	7
6	Information of the Testing Laboratories	8



## **Release Control Record**

Issue No.	Description	Date Issued
MFBCFP-WTW-P22100655	Original release.	2022/12/13

Report No.: MFBCFP-WTW-P22100655 Page No. 3 / 8 Report Format Version: 7.1.0 Reference No.: BCFP-WTW-P22100655



#### 1 Certificate

Product: MRS Tubular Motor

Test Model: MRS-32C

Sample Status: Engineering sample

Applicant: Nien Made Enterprise Co., Ltd.

**Test Date:** 2022/11/17

FCC Rule Part: FCC Part 2 (Section 2.1091)

FCC Part 2 (Section 2.1093)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



### 2 Applicable RF Exposure Limit

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

#### (e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)		
	Limits For General Population / Uncontrolled Exposure					
0.3-1.34	614	1.63	(100)*	30		
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

f = frequency in MHz. \* = Plane-wave equivalent power density.

Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)		
	Limits For General Population / Uncontrolled Exposure					
0.3-3.0	614	1.63	*(100)	≤6		
3.0-30	1842/f	4.89/f	*(900/f²)	<6		
30-300	61.4	0.163	1.0	<6		
300-1,500			f/300	<6		
1,500-100,000			5	<6		

f = frequency in MHz. \* = Plane-wave equivalent power density.

Report No.: MFBCFP-WTW-P22100655 Reference No.: BCFP-WTW-P22100655 Page No. 5 / 8 Report Format Version: 7.1.0



## 3 Applicable Evaluation Criteria

### **Exemption Evaluation**

1 mW Blanket Exemption - §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in <a href="mailto:paragraph (b)(3)(ii)(A)">paragraph (b)(3)(ii)(A)</a> of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

Report No.: MFBCFP-WTW-P22100655 Page No. 6 / 8 Report Format Version: 7.1.0 Reference No.: BCFP-WTW-P22100655



Report Format Version: 7.1.0

### 4 Test Results

#### 4.1 RF Exposure

Environmental Conditions:	25°C, 76% RH	Tested By:	Dalen Dai
---------------------------	--------------	------------	-----------

1 mW Blanket Exemption						
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Limit (mW)	Test Result
GFSK	2415-2459	0.002223	2.8	0.002582	1	Pass

Note:

Calculate the ERP of GFSK from the radiated field strength:

ERP (dBm) = Radiated field strength (dBuV/m) + 20 x Log(d) - 104.77 - 2.15

d is the measurement distance, in 3 m.

ERP =  $71.5 + 20 \times Log(3) - 104.77 - 2.15 = -25.88 \text{ dBm } (0.002582 \text{ mW})$ 

Average Power = ERP (dBm) - Antenna Gain (dBi) + 2.15 = -26.53 dBm (0.002223 mW)

#### 5 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBCFP-WTW-P22100655 Page No. 7 / 8
Reference No.: BCFP-WTW-P22100655



### 6 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@bureauveritas.com">service.adt@bureauveritas.com</a>.
Web Site: <a href="mailto:http://ee.bureauveritas.com.tw">http://ee.bureauveritas.com.tw</a>

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBCFP-WTW-P22100655 Reference No.: BCFP-WTW-P22100655 Page No. 8 / 8

Report Format Version: 7.1.0