

Date : 2006-05-12 **TEST REPORT** Page 1 of 17

No.: HM156573

Applicant: New-Ray Toys Co., Ltd.

Unit 9, 12/F., Houston Centre, 63 Mody Road, T.S.T. East,

Kowloon, Hong Kong.

Description of Samples: Model name: Radio Control Formula One

Model no.: 89923A

Brand name: New-Ray Toys Co., Ltd.

FCC ID: Q4S89923A

Date Samples Received: 2006-05-02

Date Tested: 2006-05-09

Investigation Requested: FCC Part 15 Subpart C

Conclusions: The submitted product COMPLIED with the requirements of

Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on

Section 2.2 in this Test Report.

Remarks: ----

LEE Kam Chuen, EMD For and on behalf of

The Hong Kong Standards and Testing Centre Ltd.



Date: 2006-05-12 Page 2 of 17

No.: HM156573

CONTENT:

	Cover Content	Page 1 of 17 Page 2-3 of 17
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 4 of 17
1.2	Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer	Page 4 of 17
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 5 of 17
1.4	Date of Order	Page 5 of 17
1.5	Submitted Samples	Page 5 of 17
1.6	Test Duration	Page 5 of 17
1.7	Country of Origin	Page 5 of 17
<u>2.0</u>	Technical Details	
2.1	Investigations Requested	Page 6 of 17
2.2	Test Standards and Results Summary	Page 6 of 17
<u>3.0</u>	Test Results	
3.1	Emission	Page 7-10 of 17
3.2	Bandwidth Measurement	Page 11-12 of 17



Date: 2006-05-12 Page 3 of 17

No.: HM156573

Appendix A

List of Measurement Equipment Page 13 of 17

Appendix B

Duty Cycle Correction During 100 msec Page 14-15 of 17

Appendix C

Photographs Page 16-17 of 17



Date: 2006-05-12 Page 4 of 17

No.: HM156573

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone: 852 2666 1888 Fax: 852 2664 4353

1.2 Applicant Details

Applicant

New-Ray Toys Co., Ltd.
Unit 9, 12/F., Houston Centre, 63 Mody Road,
T.S.T. East, Kowloon, Hong Kong.

Manufacturer

New-Ray Toys Co., Ltd.
Unit 9, 12/F., Houston Centre, 63 Mody Road, T.S.T. East, Kowloon, Hong Kong.



Date: 2006-05-12 Page 5 of 17

No.: HM156573

1.3 Equipment Under Test [EUT] Description of Sample

Model Name: Radio Control Formula One
Manufacturer: New-Ray Toys Co., Ltd.
Brand Name: New-Ray Toys Co., Ltd.

Model Number: 89923A

Rating: 9Vd.c ("6FF" size battery x 1)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is a New-Ray Toys Co., Ltd., Radio Control Formula One. The transmitter is a 2 joystick transmitter. The EUT continues to transmit while joystick is being pressed, It is pulse transmitter, Modulation by IC, and type is pulse modulation.

1.4 Date of Order

2006-05-02

1.5 Submitted Sample(s):

1 Samples per model

1.6 Test Duration

2006-05-09

1.7 Country of Origin

China

The Hong Kong Standards and Testing Centre Ltd.



Date: 2006-05-12 Page 6 of 17

No.: HM156573

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary								
Test Condition Test Requirement Test Method Class / Test Result								
			Severity	Pass	Failed	N/A		
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.227	ANSI C63.4:2003	N/A	\boxtimes				
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.4:2003	N/A	\boxtimes				
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	N/A					

Note: N/A - Not Applicable



Date: 2006-05-12 Page 7 of 17

No.: HM156573

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions (30 – 1000MHz)


Test Requirement: FCC 47CFR 15.227
Test Method: ANSI C63.4:2003
Test Date: 2006-05-09
Mode of Operation: Tx mode

Test Method:

The sample was placed 0.8m above the ground plane on a standard radiated emission test site *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: On a standard radiated emission test site located at HKSTC with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.

Test Setup:



The Hong Kong Standards and Testing Centre Ltd.



Date: 2006-05-12 Page 8 of 17

No.: HM156573

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of Fundamental	Field Strength of Fundamental Emission	Field Strength of Fundamental Emission
[MHz]	[Peak] [μV/m]	[Average] [μV/m]
26.96-27.28	100,000	10,000

Results:

	Field Strength of Fundamental Emissions Peak Value								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	dΒμV	dB/m	dBμV/m	μV/m	μV/m				
27.15	62.50	8.9	71.4	3,715.4	100,000	Vertical			

Field Strength of Fundamental Emissions Average									
Frequency	Measured	Adjusted by	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Duty Cycle	Factor	Strength	Strength		Polarity		
MHz	dΒμV	dB	dB/m	dBµV/m	μV/m	μV/m			
27.15	57.8	-4.7	8.9	66.7	2,162.7	10,000	Vertical		

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Remarks:

Correction Factor includes Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Date: 2006-05-12 Page 9 of 17

No.: HM156573

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results:

Radiated Emissions									
	Quasi-Peak Quasi-Peak								
Frequency	Measured	Correction		Field		Field	Limit @3m	E-Field	
	Level @3m	Factor	St	Strength		trength		Polarity	
MHz	dΒμV	dB/m	dBµV/m		//m μV/m		μV/m		
54.29	< 1.0	10.1	<	11.1	<	3.6	100	Vertical	
81.44	< 1.0	9.5	<	10.5	<	3.3	100	Vertical	
108.58	< 1.0	10.7	<	11.7	<	3.8	150	Vertical	
135.73	< 1.0	10.2	<	11.2	<	3.6	200	Vertical	
162.87	< 1.0	11.9	<	12.9	<	4.4	200	Vertical	
190.02	< 1.0	12.4	<	13.4	<	4.7	200	Vertical	
217.16	< 1.0	13.2	<	14.2	<	5.1	200	Vertical	
244.31	< 1.0	15.0	<	16.0	<	6.3	200	Vertical	
271.45	< 1.0	16.1	<	17.1	<	7.2	200	Vertical	

Remarks:

Correction Factor includes Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz ±4.1dB



Date: 2006-05-12 Page 10 of 17

No.: HM156573

3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.207 Test Method: ANSI C63.4:2003

Test Date: N/A
Mode of Operation: N/A

Results: N/A

The EUT is operated by a single source of internal battery power [located in the battery compartment], therefore power line conducted emission was deemed unnecessary.

The Hong Kong Standards and Testing Centre Ltd.



Date: 2006-05-12 Page 11 of 17

No.: HM156573

3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.227

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date: 2006-05-09 Mode of Operation: On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.




Date: 2006-05-12 Page 12 of 17

No.: HM156573

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	20dB Bandwidth [KHz]	FCC Limits [MHz]
27.145	19.3	within 26.96-27.28

20dB Bandwidth of Fundamental Emission





Date: 2006-05-12 Page 13 of 17

No.: HM156573

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	27/06/05
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	27/06/05
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	27/06/05
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	27/06/05
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	27/06/05
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	27/06/05
EM020	HORN ANTENNA	ETS-Linggren	3115	4032	30/07/03
EM022	LOOP ANTENNA	ETS-Linggren	6502	1189-2424	19/09/03
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/12/05
EM131	EMC ANALYZER	HEWLETT PACKARD	8595EM	3710A00155	14/03/06
EM145	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESCS 30	830245/021	04/10/04
EM195	ANTENNA POSITIONING MAST	ETS-Linggren	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	ETS-Linggren	2090	1662	N/A
EM215	MULTIDEVICE CONTROLER	ETS-Linggren	2090	00024676	N/A
EM216	MINI MAST SYSTEM	ETS-Linggren	2075	00026842	N/A
EM217	ELECTRIC POWERED TURNTABLE	ETS-Linggren	2088	00029144	N/A
EM218	ANECHOIC CHAMBER	ETS-Linggren	FACT-3		19/03/04
EM219	BICONILOG ANTENNA	ETS-Linggren	3142C	00029071	01/02/06
EM229	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB40	100248	04/02/05

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	12/01/06
EM119	LISN	ROHDE & SCHWARZ	ESH3-Z5	0831.5518.52	14/10/04
EM127	ISOLATION TRANSFORMER 220 TO 300V	WING SUN	N/A	N/A	CM
EM233	PULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	100314	09/01/06
EM181	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESIB7	100072	17/03/06
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	12/01/06
EM197	LISN	ETS-Linggren	4825/2	1193	27/06/05
EM213	DIGITAL POWER METER	VICNOBL	VIP120	00277	14/09/04

Remarks:-

CM Corrective Maintenance
N/A Not Applicable or Not Available

TBD To Be Determined



Date: 2006-05-12 Page 14 of 17

No.: HM156573

Appendix B


Duty Cycle Correction During 100msec

Each function key sends a different series of characters, but each packet period (42msec) never exceeds a series of 4 long (17msec) and 29 short (600µsec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered 4x1.7msec+29x600µsec per 42msec=57.6% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = 20Log(0.576) =-4.7dB

The following figures [Figure A to Figure C] show the characteristics of the pulse train for one of these functions.




The Hong Kong Standards and Testing Centre Ltd.




Date: 2006-05-12 Page 15 of 17

No.: HM156573

Figure B [Long Pulse] MARKER 4 1.7000 msec .07 dB LOG REF 77.0 dBpV 10 dB/ #ATN 0 dB VA SB SC FC CORR CENTER 27.148 MHz Figure B [Long Pulse] ACTV DET: PEAK QP AVG MKRA 1.7000 msec .07 dB ACTV DET: PEAK QP AVG MKRA 1.7000 msec .07 dB SC FC CORR SPAN 0 Hz





The Hong Kong Standards and Testing Centre Ltd.



Date: 2006-05-12 Page 16 of 17

No.: HM156573

Appendix C

Photographs of EUT

Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



The Hong Kong Standards and Testing Centre Ltd. 10 Dai Wang Street, Taipo Industrial Estate, N.T., Hong Kong


Tel: (852) 2666 1888 Fax: (852) 2664 4353 Homepage: www.hkstc.org E-mail: hkstc@hkstc.org



Date: 2006-05-12 Page 17 of 17

No.: HM156573

Photographs of EUT



***** End of Test Report *****