

Appendix B:SAR Measurement Results-Front of face

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
GPRS 2Tx slots	Front (T60)	128	824.2	33.41	33.50	1.021	0.16	0.345	0.352	-
		190	836.6	33.46	33.50	1.009	-0.10	0.364	0.367	1
		251	848.8	33.10	33.50	1.096	0.09	0.324	0.355	-
GPRS 2Tx slots	Front (T65)	128	824.2	33.41	33.50	1.021	-	-	-	-
		190	836.6	33.46	33.50	1.009	0.12	0.358	0.361	-
		251	848.8	33.10	33.50	1.096	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
GPRS 2Tx slots	Front (T60)	512	1850.2	29.28	30.00	1.180	-0.09	0.115	0.136	-
		661	1880.0	29.75	30.00	1.059	-0.10	0.132	0.140	2
		810	1909.8	29.50	30.00	1.122	0.07	0.119	0.134	-
GPRS 2Tx slots	Front (T65)	512	1850.2	29.28	30.00	1.180	-	-	-	-
		661	1880.0	29.75	30.00	1.059	0.04	0.128	0.136	-
		810	1909.8	29.50	30.00	1.122	-	-	-	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	9262	1852.4	23.10	23.50	1.096	-0.07	0.122	0.134	-
		9400	1880.0	23.35	23.50	1.035	-0.12	0.146	0.151	3
		9538	1907.6	23.05	23.50	1.109	0.11	0.117	0.130	-
RMC 12.2Kbps	Front (T65)	9262	1852.4	23.10	23.50	1.096	-	-	-	-
		9400	1880.0	23.35	23.50	1.035	0.05	0.139	0.144	-
		9538	1907.6	23.05	23.50	1.109	-	-	-	-

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	1312	1712.4	23.09	23.50	1.099	-	-	-	-
		1413	1732.6	23.09	23.50	1.099	-	-	-	-
		1513	1752.6	23.22	23.50	1.067	-0.09	0.691	0.737	-
RMC 12.2Kbps	Front (T65)	1312	1712.4	23.09	23.50	1.099	-	-	-	-
		1413	1732.6	23.09	23.50	1.099	-	-	-	-
		1513	1752.6	23.22	23.50	1.067	0.03	0.746	0.796	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	4132	826.4	22.25	23.00	1.189	0.07	0.175	0.208	-
		4183	836.6	22.80	23.00	1.047	-0.06	0.218	0.228	5
		4233	846.6	22.41	23.00	1.146	-0.11	0.179	0.205	-
RMC 12.2Kbps	Front (T65)	4132	826.4	22.25	23.00	1.189	-	-	-	-
		4183	836.6	22.80	23.00	1.047	0.10	0.201	0.210	-
		4233	846.6	22.41	23.00	1.146	-	-	-	-

Appendix B:SAR Measurement Results-Front of face

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	18700	1860.0	23.38	24.00	1.153	0.16	0.133	0.153	-
		18900	1880.0	23.53	24.00	1.114	0.07	0.139	0.155	-
		19100	1900.0	23.75	24.00	1.059	-0.12	0.159	0.168	6
20M QPSK 50RB	Front (T60)	18700	1860.0	22.40	23.00	1.148	-	-	-	-
		18900	1880.0	22.48	23.00	1.127	-	-	-	-
		19100	1900.0	22.63	23.00	1.089	0.05	0.113	0.123	-
20M QPSK 1RB	Front (T65)	18700	1860.0	23.38	24.00	1.153	-	-	-	-
		18900	1880.0	23.53	24.00	1.114	-	-	-	-
		19100	1900.0	23.75	24.00	1.059	0.09	0.148	0.157	-

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	20050	1720.0	23.14	24.00	1.219	-0.01	0.102	0.124	-
		20175	1732.5	23.42	24.00	1.143	0.07	0.116	0.133	-
		20300	1745.0	23.59	24.00	1.099	-0.21	0.124	0.136	7
20M QPSK 50RB	Front (T60)	20050	1720.0	22.22	22.50	1.067	-	-	-	-
		20175	1732.5	22.07	22.50	1.104	-	-	-	-
		20300	1745.0	22.24	22.50	1.062	-0.08	0.102	0.108	-
20M QPSK 1RB	Front (T65)	20050	1720.0	23.14	24.00	1.219	-	-	-	-
		20175	1732.5	23.42	24.00	1.143	-	-	-	-
		20300	1745.0	23.59	24.00	1.099	-0.07	0.117	0.129	-

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	20450	829.0	24.20	25.00	1.202	0.08	0.167	0.201	-
		20525	836.5	24.52	25.00	1.117	0.01	0.188	0.210	8
		20600	844.0	23.90	25.00	1.288	-0.11	0.152	0.196	-
10M QPSK 25RB	Front (T60)	20450	829.0	23.41	23.50	1.021	-	-	-	-
		20525	836.5	23.42	23.50	1.019	-0.06	0.106	0.108	-
		20600	844.0	23.08	23.50	1.102	-	-	-	-
10M QPSK 1RB	Front (T65)	20450	829.0	24.20	25.00	1.202	-	-	-	-
		20525	836.5	24.52	25.00	1.117	0.13	0.176	0.197	-
		20600	844.0	23.90	25.00	1.288	-	-	-	-

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	20850	2510.0	23.09	24.00	1.233	0.06	0.074	0.091	-
		21100	2535.0	23.88	24.00	1.028	-0.17	0.101	0.104	9
		21350	2560.0	23.86	24.00	1.033	0.01	0.082	0.085	-
20M QPSK 50RB	Front (T60)	20850	2510.0	21.97	23.00	1.268	-	-	-	-
		21100	2535.0	22.92	23.00	1.019	-0.11	0.069	0.070	-
		21350	2560.0	22.42	23.00	1.143	-	-	-	-
20M QPSK 1RB	Front (T65)	20850	2510.0	23.09	24.00	1.233	-	-	-	-
		21100	2535.0	23.88	24.00	1.028	0.06	0.094	0.097	-
		21350	2560.0	23.86	24.00	1.033	-	-	-	-

Appendix B:SAR Measurement Results-Front of face

LTE Band 12										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	23060	704.0	23.51	24.00	1.119	-0.17	0.065	0.073	-
		23095	707.5	23.81	24.00	1.045	0.13	0.081	0.085	10
		23130	711.0	23.57	24.00	1.104	0.06	0.069	0.076	-
10M QPSK 25RB	Front (T60)	23060	704.0	22.52	23.00	1.117	-	-	-	-
		23095	707.5	22.53	23.00	1.114	0.05	0.064	0.071	-
		23130	711.0	22.66	23.00	1.081	-	-	-	-
10M QPSK 1RB	Front (T65)	23060	704.0	23.51	24.00	1.119	-	-	-	-
		23095	707.5	23.81	24.00	1.045	0.08	0.072	0.075	-
		23130	711.0	23.57	24.00	1.104	-	-	-	-

LTE Band 13										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	23230	782.0	23.86	24.00	1.033	0.00	0.157	0.162	11
10M QPSK 25RB	Front (T60)	23230	782.0	22.98	23.00	1.005	0.05	0.124	0.125	-
10M QPSK 1RB	Front (T65)	23230	782.0	23.86	24.00	1.033	-0.12	0.144	0.149	-

LTE Band 25										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	26140	1860.0	23.45	24.00	1.135	0.14	0.132	0.150	-
		26365	1882.5	23.36	24.00	1.159	-0.17	0.127	0.147	-
		26590	1905.0	23.59	24.00	1.099	-0.05	0.144	0.158	12
20M QPSK 50RB	Front (T60)	26140	1860.0	22.21	22.50	1.069	-	-	-	-
		26365	1882.5	22.27	22.50	1.054	-	-	-	-
		26590	1905.0	21.93	22.50	1.140	-0.09	0.091	0.104	-
20M QPSK 1RB	Front (T65)	26140	1860.0	23.45	24.00	1.135	-	-	-	-
		26365	1882.5	23.36	24.00	1.159	-	-	-	-
		26590	1905.0	23.59	24.00	1.099	0.11	0.131	0.144	-

LTE Band 26										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
15M QPSK 1RB	Front (T60)	26765	821.5	24.05	24.50	1.109	0.15	0.177	0.196	-
		26865	831.5	24.10	24.50	1.096	-0.04	0.182	0.200	13
		26965	841.5	23.74	24.50	1.191	-0.09	0.152	0.181	-
15M QPSK 38RB	Front (T60)	26765	821.5	23.15	23.50	1.084	-	-	-	-
		26865	831.5	23.44	23.50	1.014	0.06	0.142	0.144	-
		26965	841.5	22.74	23.50	1.191	-	-	-	-
15M QPSK 1RB	Front (T65)	26765	821.5	24.05	24.50	1.109	-	-	-	-
		26865	831.5	24.10	24.50	1.096	0.19	0.173	0.190	-
		26965	841.5	23.74	24.50	1.191	-	-	-	-

Appendix B:SAR Measurement Results-Front of face

WIFI 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11b	Front (T60)	1	2412	12.48	12.50	1.005	97.60%	1.025	0.11	0.023	0.024	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	-0.14	0.027	0.028	14
		11	2462	12.77	13.00	1.054	97.60%	1.025	0.06	0.024	0.026	-
802.11b	Front (T65)	1	2412	12.48	12.50	1.005	97.60%	1.025	-	-	-	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	0.11	0.023	0.024	-
		11	2462	12.77	13.00	1.054	97.60%	1.025	-	-	-	-

WIFI 5G U-NII-1												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11n (HT20)	Front (T60)	36	5180	9.97	10.00	1.007	86.38%	1.158	0.11	0.042	0.049	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	0.03	0.061	0.074	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	-0.17	0.074	0.095	15
802.11n (HT20)	Front (T65)	36	5180	9.97	10.00	1.007	86.38%	1.158	-	-	-	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	-	-	-	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	0.12	0.062	0.080	-

WIFI 5G U-NII-2A												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11a	Front (T60)	52	5260	10.67	11.00	1.079	87.15%	1.147	-0.16	0.057	0.071	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	0.05	0.060	0.075	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	-0.10	0.078	0.090	16
802.11a	Front (T65)	52	5260	10.67	11.00	1.079	87.15%	1.147	-	-	-	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	-	-	-	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	0.07	0.071	0.082	-

WIFI 5G U-NII-2C												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11n (HT40)	Front (T60)	102	5510	9.65	10.00	1.084	76.02%	1.315	-0.07	0.085	0.121	17
		110	5550	9.55	10.00	1.109	76.02%	1.315	0.01	0.077	0.112	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	-0.11	0.042	0.061	-
802.11n (HT40)	Front (T65)	102	5510	9.65	10.00	1.084	76.02%	1.315	0.11	0.079	0.113	-
		110	5550	9.55	10.00	1.109	76.02%	1.315	-	-	-	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	-	-	-	-

WIFI 5G U-NII-3												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11a	Front (T60)	149	5745	11.10	12.00	1.230	87.23%	1.146	0.15	0.094	0.133	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	-0.09	0.105	0.144	18
		165	5825	10.49	11.00	1.125	87.15%	1.147	0.07	0.072	0.093	-
802.11a	Front (T65)	149	5745	11.10	12.00	1.230	87.23%	1.146	-	-	-	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	0.06	0.094	0.129	-
		165	5825	10.49	11.00	1.125	87.15%	1.147	-	-	-	-

Appendix B:SAR Measurement Results-Front of face

Bluetooth												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
EDR GFSK	Front (T60)	0	2402	10.11	10.50	1.094	76.91%	1.300	0.19	0.010	0.014	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	0.07	0.007	0.009	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	-0.04	0.014	0.018	19
EDR GFSK	Front (T65)	0	2402	10.11	10.50	1.094	76.91%	1.300	-	-	-	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	-	-	-	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	0.09	0.011	0.014	-

Appendix B:SAR Measurement Results-Body

GSM850										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
GPRS 2Tx slots	Front (T60)	128	824.2	33.41	33.50	1.021	-	-	-	-
		190	836.6	33.46	33.50	1.009	-0.04	0.723	0.730	-
		251	848.8	33.10	33.50	1.096	-	-	-	-
	Rear (T60)	128	824.2	33.41	33.50	1.021	-	-	-	-
		190	836.6	33.46	33.50	1.009	0.11	0.765	0.772	-
		251	848.8	33.10	33.50	1.096	-	-	-	-
	Rear (With Belt clip) (T60)	128	824.2	33.41	33.50	1.021	0.05	0.862	0.880	-
		190	836.6	33.46	33.50	1.009	-0.07	1.060	1.070	20
		251	848.8	33.10	33.50	1.096	-0.09	0.778	0.853	-
GPRS 2Tx slots	Front (T65)	128	824.2	33.41	33.50	1.021	-	-	-	-
		190	836.6	33.46	33.50	1.009	0.06	0.711	0.718	-
		251	848.8	33.10	33.50	1.096	-	-	-	-

PCS1900										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
GPRS 2Tx slots	Front (T60)	512	1850.2	29.28	30.00	1.180	-	-	-	-
		661	1880.0	29.75	30.00	1.059	-0.03	0.712	0.754	-
		810	1909.8	29.50	30.00	1.122	-	-	-	-
	Rear (T60)	512	1850.2	29.28	30.00	1.180	-	-	-	-
		661	1880.0	29.75	30.00	1.059	-0.11	0.742	0.786	-
		810	1909.8	29.50	30.00	1.122	-	-	-	-
	Rear (With Belt clip) (T60)	512	1850.2	29.28	30.00	1.180	0.08	0.801	0.945	-
		661	1880.0	29.75	30.00	1.059	-0.17	0.898	0.951	21
		810	1909.8	29.50	30.00	1.122	0.12	0.805	0.903	-
GPRS 2Tx slots	Front (T65)	512	1850.2	29.28	30.00	1.180	-	-	-	-
		661	1880.0	29.75	30.00	1.059	-0.15	0.699	0.740	-
		810	1909.8	29.50	30.00	1.122	-	-	-	-

WCDMA Band II										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	9262	1852.4	23.10	23.50	1.096	-	-	-	-
		9400	1880.0	23.35	23.50	1.035	-0.05	0.677	0.701	-
		9538	1907.6	23.05	23.50	1.109	-	-	-	-
	Rear (T60)	9262	1852.4	23.10	23.50	1.096	-	-	-	-
		9400	1880.0	23.35	23.50	1.035	0.09	0.756	0.783	-
		9538	1907.6	23.05	23.50	1.109	-	-	-	-
	Rear (With Belt clip) (T60)	9262	1852.4	23.10	23.50	1.096	0.08	0.997	1.093	-
		9400	1880.0	23.35	23.50	1.035	-0.01	1.090	1.128	22
		9538	1907.6	23.05	23.50	1.109	-0.13	0.952	1.056	-
RMC 12.2Kbps	Front (T65)	9262	1852.4	23.10	23.50	1.096	-	-	-	-
		9400	1880.0	23.35	23.50	1.035	0.14	0.658	0.681	-
		9538	1907.6	23.05	23.50	1.109	-	-	-	-

Appendix B:SAR Measurement Results-Body

WCDMA Band IV										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	1312	1712.4	23.09	23.50	1.099	-	-	-	-
		1413	1732.6	23.09	23.50	1.099	-	-	-	-
		1513	1752.6	23.22	23.50	1.067	-0.09	0.691	0.737	-
	Rear (T60)	1312	1712.4	23.09	23.50	1.099	-	-	-	-
		1413	1732.6	23.09	23.50	1.099	-	-	-	-
		1513	1752.6	23.22	23.50	1.067	0.03	0.746	0.796	-
	Rear (With Belt clip) (T60)	1312	1712.4	23.09	23.50	1.099	0.03	0.961	1.056	-
		1413	1732.6	23.09	23.50	1.099	-0.05	0.974	1.070	-
		1513	1752.6	23.22	23.50	1.067	-0.10	1.040	1.109	23
RMC 12.2Kbps	Front (T65)	1312	1712.4	23.09	23.50	1.099	-	-	-	-
		1413	1732.6	23.09	23.50	1.099	-	-	-	-
		1513	1752.6	23.22	23.50	1.067	0.03	0.677	0.722	-

WCDMA Band V										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
RMC 12.2Kbps	Front (T60)	4132	826.4	22.25	23.00	1.189	-	-	-	-
		4183	836.6	22.80	23.00	1.047	0.05	0.388	0.406	-
		4233	846.6	22.41	23.00	1.146	-	-	-	-
	Rear (T60)	4132	826.4	22.25	23.00	1.189	-	-	-	-
		4183	836.6	22.80	23.00	1.047	0.03	0.515	0.539	-
		4233	846.6	22.41	23.00	1.146	-	-	-	-
	Rear (With Belt clip) (T60)	4132	826.4	22.25	23.00	1.189	0.09	0.507	0.603	-
		4183	836.6	22.80	23.00	1.047	-0.08	0.589	0.617	24
		4233	846.6	22.41	23.00	1.146	0.15	0.511	0.585	-
RMC 12.2Kbps	Front (T65)	4132	826.4	22.25	23.00	1.189	-	-	-	-
		4183	836.6	22.80	23.00	1.047	0.19	0.369	0.386	-
		4233	846.6	22.41	23.00	1.146	-	-	-	-

LTE Band 2										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	18700	1860.0	23.38	24.00	1.153	-	-	-	-
		18900	1880.0	23.53	24.00	1.114	-	-	-	-
		19100	1900.0	23.75	24.00	1.059	-0.08	0.684	0.725	-
	Rear (T60)	18700	1860.0	23.38	24.00	1.153	-	-	-	-
		18900	1880.0	23.53	24.00	1.114	-	-	-	-
		19100	1900.0	23.75	24.00	1.059	0.05	0.735	0.779	-
	Rear (With Belt clip) (T60)	18700	1860.0	23.38	24.00	1.153	-0.13	0.995	1.148	-
		18900	1880.0	23.53	24.00	1.114	0.08	1.030	1.148	-
		19100	1900.0	23.75	24.00	1.059	0.11	1.150	1.218	25
20M QPSK 50RB	Front (T60)	18700	1860.0	22.40	23.00	1.148	-	-	-	-
		18900	1880.0	22.48	23.00	1.127	-	-	-	-
		19100	1900.0	22.63	23.00	1.089	0.05	0.592	0.645	-
	Rear (T60)	18700	1860.0	22.40	23.00	1.148	-	-	-	-
		18900	1880.0	22.48	23.00	1.127	-	-	-	-
		19100	1900.0	22.63	23.00	1.089	-0.06	0.645	0.702	-
	Rear (With Belt clip) (T60)	18700	1860.0	22.40	23.00	1.148	0.11	0.665	0.764	-
		18900	1880.0	22.48	23.00	1.127	0.05	0.728	0.821	-
		19100	1900.0	22.63	23.00	1.089	0.07	0.825	0.898	-
20M QPSK 100RB	Rear (With Belt clip) (T60)	18700	1860.0	22.30	23.00	1.175	0.09	0.675	0.793	-
		18900	1880.0	22.50	23.00	1.122	0.12	0.736	0.826	-
		19100	1900.0	22.46	23.00	1.132	0.05	0.744	0.843	-
20M QPSK 1RB	Front (T65)	18700	1860.0	23.38	24.00	1.153	-	-	-	-
		18900	1880.0	23.53	24.00	1.114	-	-	-	-
		19100	1900.0	23.75	24.00	1.059	0.15	0.671	0.711	-

Appendix B:SAR Measurement Results-Body

LTE Band 4										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	20050	1720.0	23.14	24.00	1.219	-	-	-	-
		20175	1732.5	23.42	24.00	1.143	-	-	-	-
		20300	1745.0	23.59	24.00	1.099	-0.06	0.675	0.742	-
	Rear (T60)	20050	1720.0	23.14	24.00	1.219	-	-	-	-
		20175	1732.5	23.42	24.00	1.143	-	-	-	-
		20300	1745.0	23.59	24.00	1.099	-0.12	0.720	0.791	-
	Rear (With Belt clip) (T60)	20050	1720.0	23.14	24.00	1.219	0.02	0.915	1.115	-
		20175	1732.5	23.42	24.00	1.143	-0.06	0.977	1.117	-
		20300	1745.0	23.59	24.00	1.099	-0.17	1.080	1.187	26
20M QPSK 50RB	Front (T60)	20050	1720.0	22.22	22.50	1.067	-	-	-	-
		20175	1732.5	22.07	22.50	1.104	-	-	-	-
		20300	1745.0	22.24	22.50	1.062	0.08	0.610	0.648	-
	Rear (T60)	20050	1720.0	22.22	22.50	1.067	-	-	-	-
		20175	1732.5	22.07	22.50	1.104	-	-	-	-
		20300	1745.0	22.24	22.50	1.062	-0.10	0.659	0.700	-
	Rear (With Belt clip) (T60)	20050	1720.0	22.22	22.50	1.067	-0.12	0.638	0.680	-
		20175	1732.5	22.07	22.50	1.104	0.06	0.755	0.834	-
		20300	1745.0	22.24	22.50	1.062	-0.11	0.883	0.937	-
20M QPSK 100RB	Rear (With Belt clip) (T60)	20050	1720.0	22.06	22.50	1.107	-0.09	0.765	0.847	-
		20175	1732.5	22.08	22.50	1.102	0.14	0.771	0.849	-
		20300	1745.0	22.18	22.50	1.076	0.08	0.855	0.920	-
20M QPSK 1RB	Front (T65)	20050	1720.0	23.14	24.00	1.219	-	-	-	-
		20175	1732.5	23.42	24.00	1.143	-	-	-	-
		20300	1745.0	23.59	24.00	1.099	0.16	0.659	0.724	-

LTE Band 5										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	20450	829.0	24.20	25.00	1.202	-	-	-	-
		20525	836.5	24.52	25.00	1.117	0.05	0.319	0.356	-
		20600	844.0	23.90	25.00	1.288	-	-	-	-
	Rear (T60)	20450	829.0	24.20	25.00	1.202	-	-	-	-
		20525	836.5	24.52	25.00	1.117	-0.09	0.356	0.398	-
		20600	844.0	23.90	25.00	1.288	-	-	-	-
	Rear (With Belt clip) (T60)	20450	829.0	24.20	25.00	1.202	0.09	0.449	0.540	-
		20525	836.5	24.52	25.00	1.117	0.03	0.488	0.545	27
		20600	844.0	23.90	25.00	1.288	-0.18	0.412	0.531	-
10M QPSK 25RB	Front (T60)	20450	829.0	23.41	23.50	1.021	-	-	-	-
		20525	836.5	23.42	23.50	1.019	-0.03	0.249	0.254	-
		20600	844.0	23.08	23.50	1.102	-	-	-	-
	Rear (T60)	20450	829.0	23.41	23.50	1.021	-	-	-	-
		20525	836.5	23.42	23.50	1.019	0.16	0.275	0.280	-
		20600	844.0	23.08	23.50	1.102	-	-	-	-
	Rear (With Belt clip) (T60)	20450	829.0	23.41	23.50	1.021	-	-	-	-
		20525	836.5	23.42	23.50	1.019	-0.12	0.315	0.321	-
		20600	844.0	23.08	23.50	1.102	-	-	-	-
10M QPSK 1RB	Front (T65)	20450	829.0	24.20	25.00	1.202	-	-	-	-
		20525	836.5	24.52	25.00	1.117	0.14	0.307	0.343	-
		20600	844.0	23.90	25.00	1.288	-	-	-	-

Appendix B:SAR Measurement Results-Body

LTE Band 7										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	20850	2510.0	23.09	24.00	1.233	-	-	-	-
		21100	2535.0	23.88	24.00	1.028	0.07	0.631	0.649	-
		21350	2560.0	23.86	24.00	1.033	-	-	-	-
	Rear (T60)	20850	2510.0	23.09	24.00	1.233	-	-	-	-
		21100	2535.0	23.88	24.00	1.028	0.05	0.766	0.787	-
		21350	2560.0	23.86	24.00	1.033	-	-	-	-
	Rear (With Belt clip) (T60)	20850	2510.0	23.09	24.00	1.233	0.05	0.735	0.906	-
		21100	2535.0	23.88	24.00	1.028	-0.11	0.917	0.943	28
		21350	2560.0	23.86	24.00	1.033	-0.02	0.876	0.905	-
20M QPSK 50RB	Front (T60)	20850	2510.0	21.97	23.00	1.268	-	-	-	-
		21100	2535.0	22.92	23.00	1.019	0.09	0.589	0.600	-
		21350	2560.0	22.42	23.00	1.143	-	-	-	-
	Rear (T60)	20850	2510.0	21.97	23.00	1.268	-	-	-	-
		21100	2535.0	22.92	23.00	1.019	-0.13	0.645	0.657	-
		21350	2560.0	22.42	23.00	1.143	-	-	-	-
	Rear (With Belt clip) (T60)	20850	2510.0	21.97	23.00	1.268	-	-	-	-
		21100	2535.0	22.92	23.00	1.019	-0.11	0.762	0.776	-
		21350	2560.0	22.42	23.00	1.143	-	-	-	-
20M QPSK 100RB	Rear (With Belt clip) (T60)	20850	2510.0	22.11	23.00	1.227	-	-	-	-
		21100	2535.0	22.80	23.00	1.047	0.09	0.745	0.780	-
		21350	2560.0	22.50	23.00	1.122	-	-	-	-
20M QPSK 1RB	Front (T65)	20850	2510.0	23.09	24.00	1.233	-	-	-	-
		21100	2535.0	23.88	24.00	1.028	0.09	0.617	0.634	-
		21350	2560.0	23.86	24.00	1.033	-	-	-	-

LTE Band 12										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	23060	704.0	23.51	24.00	1.119	-	-	-	-
		23095	707.5	23.81	24.00	1.045	0.08	0.119	0.124	-
		23130	711.0	23.57	24.00	1.104	-	-	-	-
	Rear (T60)	23060	704.0	23.51	24.00	1.119	-	-	-	-
		23095	707.5	23.81	24.00	1.045	-0.04	0.128	0.134	-
		23130	711.0	23.57	24.00	1.104	-	-	-	-
	Rear (With Belt clip) (T60)	23060	704.0	23.51	24.00	1.119	0.07	0.139	0.156	-
		23095	707.5	23.81	24.00	1.045	-0.04	0.159	0.166	29
		23130	711.0	23.57	24.00	1.104	-0.15	0.134	0.148	-
10M QPSK 25RB	Front (T60)	23060	704.0	22.52	23.00	1.117	-	-	-	-
		23095	707.5	22.53	23.00	1.114	-0.09	0.103	0.115	-
		23130	711.0	22.66	23.00	1.081	-	-	-	-
	Rear (T60)	23060	704.0	22.52	23.00	1.117	-	-	-	-
		23095	707.5	22.53	23.00	1.114	-0.05	0.122	0.136	-
		23130	711.0	22.66	23.00	1.081	-	-	-	-
	Rear (With Belt clip) (T60)	23060	704.0	22.52	23.00	1.117	-	-	-	-
		23095	707.5	22.53	23.00	1.114	-0.13	0.142	0.158	-
		23130	711.0	22.66	23.00	1.081	-	-	-	-
10M QPSK 1RB	Front (T65)	23060	704.0	23.51	24.00	1.119	-	-	-	-
		23095	707.5	23.81	24.00	1.045	0.11	0.108	0.113	-
		23130	711.0	23.57	24.00	1.104	-	-	-	-

Appendix B:SAR Measurement Results-Body

LTE Band 13										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
10M QPSK 1RB	Front (T60)	23230	782.0	23.86	24.00	1.033	0.09	0.302	0.312	-
	Rear (T60)	23230	782.0	23.86	24.00	1.033	0.05	0.324	0.335	-
	Rear (With Belt clip) (T60)	23230	782.0	23.86	24.00	1.033	-0.03	0.359	0.371	30
10M QPSK 25RB	Front (T60)	23230	782.0	22.98	23.00	1.005	0.02	0.286	0.287	-
	Rear (T60)	23230	782.0	22.98	23.00	1.005	-0.12	0.315	0.316	-
	Rear (With Belt clip) (T60)	23230	782.0	22.98	23.00	1.005	-0.11	0.342	0.344	-
10M QPSK 1RB	Front (T65)	23230	782.0	23.86	24.00	1.033	0.03	0.297	0.307	-

LTE Band 25										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
20M QPSK 1RB	Front (T60)	26140	1860.0	23.45	24.00	1.135	-	-	-	-
		26365	1882.5	23.36	24.00	1.159	-	-	-	-
		26590	1905.0	23.59	24.00	1.099	0.03	0.638	0.701	-
	Rear (T60)	26140	1860.0	23.45	24.00	1.135	-	-	-	-
		26365	1882.5	23.36	24.00	1.159	-	-	-	-
		26590	1905.0	23.59	24.00	1.099	0.04	0.712	0.782	-
	Rear (With Belt clip) (T60)	26140	1860.0	23.45	24.00	1.135	-0.12	0.936	1.062	-
		26365	1882.5	23.36	24.00	1.159	0.03	0.925	1.072	-
		26590	1905.0	23.59	24.00	1.099	-0.15	1.010	1.110	31
20M QPSK 50RB	Front (T60)	26140	1860.0	22.21	22.50	1.069	-	-	-	-
		26365	1882.5	22.27	22.50	1.054	0.09	0.552	0.582	-
		26590	1905.0	21.93	22.50	1.140	-	-	-	-
	Rear (T60)	26140	1860.0	22.21	22.50	1.069	-	-	-	-
		26365	1882.5	22.27	22.50	1.054	-0.08	0.647	0.682	-
		26590	1905.0	21.93	22.50	1.140	-	-	-	-
	Rear (With Belt clip) (T60)	26140	1860.0	22.21	22.50	1.069	-0.04	0.814	0.870	-
		26365	1882.5	22.27	22.50	1.054	0.08	0.855	0.902	-
		26590	1905.0	21.93	22.50	1.140	-0.13	0.748	0.853	-
20M QPSK 100RB	Rear (With Belt clip) (T60)	26140	1860.0	22.10	22.50	1.096	-0.03	0.775	0.850	-
		26365	1882.5	22.16	22.50	1.081	-0.16	0.791	0.855	-
		26590	1905.0	22.05	22.50	1.109	0.09	0.759	0.842	-
20M QPSK 1RB	Front (T65)	26140	1860.0	23.45	24.00	1.135	-	-	-	-
		26365	1882.5	23.36	24.00	1.159	-	-	-	-
		26590	1905.0	23.59	24.00	1.099	0.15	0.619	0.680	-

Appendix B:SAR Measurement Results-Body

LTE Band 26										
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz					(W/kg)	(W/kg)	
15M QPSK 1RB	Front (T60)	26765	821.5	24.05	24.50	1.109	-	-	-	-
		26865	831.5	24.10	24.50	1.096	-0.02	0.358	0.393	-
		26965	841.5	23.74	24.50	1.191	-	-	-	-
	Rear (T60)	26765	821.5	24.05	24.50	1.109	-	-	-	-
		26865	831.5	24.10	24.50	1.096	-0.09	0.416	0.456	-
		26965	841.5	23.74	24.50	1.191	-	-	-	-
	Rear (With Belt clip) (T60)	26765	821.5	24.05	24.50	1.109	0.08	0.432	0.479	-
		26865	831.5	24.10	24.50	1.096	-0.03	0.459	0.503	32
		26965	841.5	23.74	24.50	1.191	-0.14	0.411	0.490	-
15M QPSK 38RB	Front (T60)	26765	821.5	23.15	23.50	1.084	-	-	-	-
		26865	831.5	23.44	23.50	1.014	0.04	0.322	0.326	-
		26965	841.5	22.74	23.50	1.191	-	-	-	-
	Rear (T60)	26765	821.5	23.15	23.50	1.084	-	-	-	-
		26865	831.5	23.44	23.50	1.014	-0.07	0.385	0.390	-
		26965	841.5	22.74	23.50	1.191	-	-	-	-
	Rear (With Belt clip) (T60)	26765	821.5	23.15	23.50	1.084	-	-	-	-
		26865	831.5	23.44	23.50	1.014	-0.13	0.406	0.412	-
		26965	841.5	22.74	23.50	1.191	-	-	-	-
15M QPSK 1RB	Front (T65)	26765	821.5	24.05	24.50	1.109	-	-	-	-
		26865	831.5	24.10	24.50	1.096	0.06	0.345	0.378	-
		26965	841.5	23.74	24.50	1.191	-	-	-	-

WIFI 2.4G												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11b	Front (T60)	1	2412	12.48	12.50	1.005	97.60%	1.025	0.12	0.064	0.066	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	-0.08	0.083	0.086	33
		11	2462	12.77	13.00	1.054	97.60%	1.025	0.03	0.071	0.077	-
	Rear (T60)	1	2412	12.48	12.50	1.005	97.60%	1.025	-	-	-	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	-0.05	0.004	0.004	-
		11	2462	12.77	13.00	1.054	97.60%	1.025	-	-	-	-
	Rear (With Belt clip) (T60)	1	2412	12.48	12.50	1.005	97.60%	1.025	-	-	-	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	-0.11	0.005	0.005	-
		11	2462	12.77	13.00	1.054	97.60%	1.025	-	-	-	-
802.11b	Front (T65)	1	2412	12.48	12.50	1.005	97.60%	1.025	-	-	-	-
		6	2437	12.97	13.00	1.007	97.60%	1.025	-0.04	0.076	0.078	-
		11	2462	12.77	13.00	1.054	97.60%	1.025	-	-	-	-

Appendix B:SAR Measurement Results-Body

WIFI 5G U-NII-1												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11n (HT20)	Front (T60)	36	5180	9.97	10.00	1.007	86.38%	1.158	0.02	0.101	0.118	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	0.19	0.129	0.156	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	-0.14	0.177	0.227	34
	Rear (T60)	36	5180	9.97	10.00	1.007	86.38%	1.158	-	-	-	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	-	-	-	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	-0.09	0.021	0.027	-
	Rear (With Belt clip) (T60)	36	5180	9.97	10.00	1.007	86.38%	1.158	-	-	-	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	-	-	-	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	-0.05	0.024	0.031	-
802.11n (HT20)	Front (T65)	36	5180	9.97	10.00	1.007	86.38%	1.158	-	-	-	-
		44	5220	11.81	12.00	1.045	86.38%	1.158	-	-	-	-
		48	5240	12.55	13.00	1.109	86.38%	1.158	0.08	0.161	0.207	-

WIFI 5G U-NII-2A												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11a	Front (T60)	52	5260	10.67	11.00	1.079	87.15%	1.147	-0.05	0.135	0.167	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	0.09	0.159	0.199	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	-0.11	0.198	0.229	35
	Rear (T60)	52	5260	10.67	11.00	1.079	87.15%	1.147	-	-	-	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	-	-	-	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	-0.04	0.021	0.024	-
	Rear (With Belt clip) (T60)	52	5260	10.67	11.00	1.079	87.15%	1.147	-	-	-	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	-	-	-	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	-0.08	0.026	0.030	-
802.11a	Front (T65)	52	5260	10.67	11.00	1.079	87.15%	1.147	-	-	-	-
		56	5280	11.11	11.50	1.094	87.22%	1.147	-	-	-	-
		64	5320	11.96	12.00	1.009	87.23%	1.146	0.03	0.185	0.214	-

WIFI 5G U-NII-2C												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11n (HT40)	Front (T60)	102	5510	9.65	10.00	1.084	76.02%	1.315	-0.09	0.169	0.241	36
		110	5550	9.55	10.00	1.109	76.02%	1.315	0.06	0.152	0.222	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	0.15	0.087	0.127	-
	Rear (T60)	102	5510	9.65	10.00	1.084	76.02%	1.315	-0.04	0.015	0.021	-
		110	5550	9.55	10.00	1.109	76.02%	1.315	-	-	-	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	-	-	-	-
	Rear (With Belt clip) (T60)	102	5510	9.65	10.00	1.084	76.02%	1.315	-0.10	0.024	0.034	-
		110	5550	9.55	10.00	1.109	76.02%	1.315	-	-	-	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	-	-	-	-
802.11n (HT40)	Front (T65)	102	5510	9.65	10.00	1.084	76.02%	1.315	0.09	0.155	0.221	-
		110	5550	9.55	10.00	1.109	76.02%	1.315	-	-	-	-
		142	5710	7.56	8.00	1.107	75.94%	1.317	-	-	-	-

Appendix B:SAR Measurement Results-Body

WIFI 5G U-NII-3												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
802.11a	Front (T60)	149	5745	11.10	12.00	1.230	87.23%	1.146	0.02	0.239	0.337	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	-0.09	0.255	0.349	37
		165	5825	10.49	11.00	1.125	87.15%	1.147	0.06	0.174	0.225	-
	Rear (T60)	149	5745	11.10	12.00	1.230	87.23%	1.146	-	-	-	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	-0.06	0.020	0.027	-
		165	5825	10.49	11.00	1.125	87.15%	1.147	-	-	-	-
	Rear (With Belt clip) (T60)	149	5745	11.10	12.00	1.230	87.23%	1.146	-	-	-	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	-0.12	0.026	0.036	-
		165	5825	10.49	11.00	1.125	87.15%	1.147	-	-	-	-
802.11a	Front (T65)	149	5745	11.10	12.00	1.230	87.23%	1.146	-	-	-	-
		157	5785	11.23	12.00	1.194	87.15%	1.147	0.03	0.247	0.338	-
		165	5825	10.49	11.00	1.125	87.15%	1.147	-	-	-	-

Bluetooth												
Mode	Test Position	Frequency		Conducted Power (dBm)	Tune-up limit (dBm)	Tune-up scaling factor	Duty Cycle	Duty Cycle Scaling Factor	Power Drift(dB)	Measured SAR(1g)	Report SAR(1g)	Plot No.
		CH	MHz							(W/kg)	(W/kg)	
EDR GFSK	Front (T60)	0	2402	10.11	10.50	1.094	76.91%	1.300	0.05	0.045	0.064	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	0.12	0.029	0.039	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	-0.09	0.051	0.067	38
	Rear (T60)	0	2402	10.11	10.50	1.094	76.91%	1.300	-	-	-	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	-	-	-	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	0.05	0.002	0.003	-
	Rear (With Belt clip) (T60)	0	2402	10.11	10.50	1.094	76.91%	1.300	-	-	-	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	-	-	-	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	-0.14	0.003	0.004	-
EDR GFSK	Front (T65)	0	2402	10.11	10.50	1.094	76.91%	1.300	-	-	-	-
		39	2441	8.82	9.00	1.042	76.91%	1.300	-	-	-	-
		78	2480	10.45	10.50	1.012	76.91%	1.300	0.12	0.046	0.061	-