



Safe RF Exposure Distance Calculation for Certus H1 Terminal

REVISION 1.1

LEGAL DISCLAIMER AND CONDITIONS OF USE

This document contains information on the Iridium Certus Certification Data Packet Guide for Iridium Partners, VAR, VAM, and is provided “as is.” The purpose of providing such information is to enable Value Added Resellers and Value Added Manufacturers (collectively, “Product Developer(s)”) to understand how to integrate the Partner Product into a wireless voice and/or data solution. Iridium Satellite LLC and its affiliated companies, directors, officers, employees, agents, trustees or consultants (“Iridium”) have made reasonable effort to make the information in this document reliable and consistent with specifications, test measurements and other information. However, Iridium assumes no responsibility for any typographical, technical, content or other inaccuracies in this document. Iridium reserves the right in its sole discretion and without prior written notice to you to change the Iridium Certus Certification Data Packet Guide and materials and/or revise this document or withdraw it at any time. The Product Developer assumes the full risk of using the Product requirements, specifications and any other information provided.

Iridium does not certify or otherwise make any representation or warranty as to the quality, effectiveness, reliability, performance or safety of the certified product.

Your use of the information contained in this Guide is restricted to the development activity authorized under the agreement(s) between you and Iridium, and is otherwise subject to all applicable terms and conditions of such agreement(s) including without limitation, software license, and warranty, conditions of use and confidentiality provisions.

Revision History

Date	Version	Author	Description
4-12-2017	1.0	Jeremy Lavine	
4-18-2017	1.1	Jeremy Lavine	Added mention of FCC bulletin and added peak EIRP and associated minimum distance calculation.

Contents

1	Introduction	5
2	RF Exposure Calculation	5
3	Summary	5

1 Introduction

Certus terminals will transmit various power levels and possess different gain antennas. This implies the Effective Isotropic Radiated Power (EIRP) will be different for the various terminals. In this technical note a “worst case” safe RF exposure distance is calculated based upon a Certus terminal of the greatest EIRP based upon Canadian Safety Code 6 and FCC 47 CFR 1.1310 (previously FCC OET Bulletin No. 65).

2 RF Exposure Calculation

Canadian Safety Code 6, “Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range of 3 KHz to 300 GHz”, states an average power density of 10 Watts per square meter, (W/m^2), as a safe exposure level for humans of the general public.

FCC 47 CFR 1.1310 “Radiofrequency radiation exposure limits” paragraphs (c), (d)(2), (d)(4) and (e) indicate a power density limit of $1mW/cm^2$ averaged over an indefinite time period, i.e. $10W/m^2$ average, the same limit as specified in Canadian Safety Code 6, for the general population.

The power density, PD , can be calculated from the Effective Isotropic Radiated Power (EIRP) as:

$$PD = \frac{EIRP}{4\pi r^2}$$

Rearranging the above equation to solve for r yields:

$$r = \sqrt{EIRP/4\pi PD}$$

The following table shows the maximum peak, bursted, and average EIRP for a Certus H1 terminal and the associated calculated minimum distance r .

Period	Max. EIRP (dBW)	Max. EIRP (Watts)	r (meters)
Instantaneous (peak)	24.7	295	1.53
8.28ms transmit burst	15.2	33.1	0.513
90ms frame (4 bursts per frame) or longer/indefinite	10.9	12.2	0.311

3 Summary

A distance of 0.311 meters or greater from an H1 terminal is sufficient to meet the Canadian Safety Code 6 and FCC 47 CFR 1.1310 maximum limit of $10W/m^2$ average. A distance of 1.53 meters or greater assures that the peak power will meet the $10W/m^2$ average limit, and therefore may be used as a conservative figure.