

FCC Part 15C Measurement and Test Report

For

GUANGDONG STEELMATE SECURITY CO., LTD.

Renan Street, Dongfu Road, Dongfeng Town, Zhongshan, 528425,

China

FCC ID: Q6WBSE083

FCC Rules:	<u>FCC Part 15.231</u>	
Product Description:	<u>Tire Pressure Monitor System</u>	
Tested Model:	<u>TP-70</u>	
Report No.:	<u>STR12058367I</u>	
Tested Date:	<u>2012-06-01 to 2012-06-08</u>	
Issued Date:	<u>2012-06-14</u>	
Tested By:	<u>Susan Su / Engineer</u>	<i>Susan Su</i>
Reviewed By:	<u>Lahm Peng / EMC Manager</u>	<i>Lahm peng</i>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u>	<i>Jandyso</i>
Prepared By:	<p>SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn</p>	

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd

TABLE OF CONTENTS

1. GENERAL INFORMATION.....3

 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3

 1.2 TEST STANDARDS.....4

 1.3 TEST METHODOLOGY.....4

 1.4 TEST FACILITY.....4

 1.5 EUT SETUP AND TEST MODE.....5

2. SUMMARY OF TEST RESULTS6

3. ANTENNA REQUIREMENT7

 3.1 STANDARD APPLICABLE.....7

 3.2 TEST RESULT.....7

4. RADIATED EMISSIONS.....8

 4.1 MEASUREMENT UNCERTAINTY8

 4.2 STANDARD APPLICABLE.....8

 4.3 TEST EQUIPMENT LIST AND DETAILS9

 4.4 TEST PROCEDURE.....9

 4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....10

 4.6 ENVIRONMENTAL CONDITIONS10

 4.7 SUMMARY OF TEST RESULTS/PLOTS10

5. 20DB BANDWIDTH13

 5.1 STANDARD APPLICABLE.....13

 5.2 TEST EQUIPMENT LIST AND DETAILS13

 6.3 TEST PROCEDURE.....13

 5.4 ENVIRONMENTAL CONDITIONS13

 5.5 SUMMARY OF TEST RESULTS/PLOTS13

6. TRANSMISSION TIME.....15

 6.1 STANDARD APPLICABLE.....15

 6.2 TEST EQUIPMENT LIST AND DETAILS15

 6.3 TEST PROCEDURE.....15

 6.4 ENVIRONMENTAL CONDITIONS15

 6.5 SUMMARY OF TEST RESULTS/PLOTS15

7. DUTY CYCLE.....18

 7.1 STANDARD APPLICABLE.....18

 7.2 TEST EQUIPMENT LIST AND DETAILS18

 7.3 TEST PROCEDURE.....18

 7.4 ENVIRONMENTAL CONDITIONS18

 7.5 SUMMARY OF TEST RESULTS/PLOTS18

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: GUANGDONG STEELMATE SECURITY CO., LTD.
 Address of applicant: Renan Street, Dongfu Road, Dongfeng Town, Zhongshan, 528425, China
 Manufacturer: GUANGDONG STEELMATE SECURITY CO., LTD.
 Address of manufacturer: Renan Street, Dongfu Road, Dongfeng Town, Zhongshan, 528425, China

General Description of EUT	
Product Name:	Tire Pressure Monitor System
Trade Name:	Steelmate
Model No.:	TP-70
Rated Voltage:	DC 3V Battery
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	433.916 MHz
Max. Field Strength:	74 dBuV/m (at 3m distance)
Data Rate:	/
Modulation:	FSK
Antenna Type:	Integral Antenna
Antenna Gain:	1dBi
Lowest Internal Frequency of EUT:	18.08MHz
Device Category:	Fixed Device

1.2 Test Standards

The following report is prepared on behalf of the GUANGDONG STEELMATE SECURITY CO., LTD. in accordance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated at continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	With modulation
TM2		
TM3		

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209	Radiated Spurious Emissions	Compliant
§15.231(e)	Deactivation Testing	Compliant
§15.231(e)	Radiated Emissions	Compliant
§15.231(c)	20dB Bandwidth Testing	Compliant

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a permanent antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

4.2 Standard Applicable

According to §15.231(e), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emission (microvolts/meter)
40.66 - 40.70	1,000	100
70 - 130	500	50
130 - 174	500 to 1,500 **	50 to 150 **
174 - 260	1,500	150
260 - 470	1,500 to 5,000 **	150 to 500 **
Above 470	5,000	500

** linear interpolations

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

4.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2012-03-28	2013-03-27
EMI Test Receiver	R&S	ESVB	825471/005	2012-03-28	2013-03-27
Pre-amplifier	Agilent	8447F	3113A06717	2012-03-28	2013-03-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2012-03-28	2013-03-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2012-02-25	2013-02-24
Horn Antenna	ETS	3117	00086197	2012-02-25	2013-02-24
Loop Antenna	SCHWARZECK	HFRA 5165	9365	2012-02-25	2013-02-24

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.231(e) and FCC Part 15.209 Limit.



4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Loss} + \text{Cab. Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.6 Environmental Conditions

Temperature:	21° C
Relative Humidity:	50%
ATM Pressure:	1011 mbar

4.7 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.231 standards, and had the worst margin of:

-9.90 dBμV at 1735.664MHz in the Vertical polarization, Ave Detector, 9 kHz to 5 GHz, 3 Meters

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data

EUT: *Tire Pressure Monitor System*
 Tested Model: *TP-70*
 Operating Condition: *Transmitting*
 Comment: *DC 3V*
 Test Specification: *Horizontal*




No.	Frequency MHz	Reading dBuV/m	Corr. Factor(dB)	Dutycycle Factor (dB)	Result dBuV/m	Limit dBuV/m	Margin (dB)	Deg. (°)	Height (cm)	Remark
1	433.9160	48.97	11.10	N/A	60.07	92.87	-32.80	330	100	peak
	433.9160	/	/	-12.49	47.58	72.87	-25.29	330	100	Ave
2	750.1083	16.19	17.78	N/A	33.97	46.00	-12.03	45	100	peak
3	867.8320	31.76	18.54	N/A	50.30	72.87	-22.57	41	100	peak
	867.8320	/	/	-12.49	37.81	52.87	-15.06	41	100	Ave

Above 1GHz

No.	Frequency MHz	Reading dBuV/m	Corr. Factor (dB)	Dutycycle Factor (dB)	Result dBuV/m	Limit dBuV/m	Margin dB	Deg. (°)	Height (cm)	Remark
1	1301.748	58.41	-13.12	N/A	45.29	74.00	-28.71	45	100	Peak
2	1735.664	62.99	-11.68	N/A	51.31	74.00	-22.69	310	100	Peak
	1301.748	/	/	-12.49	32.80	54.00	-21.20	360	100	Ave
	1735.664	/	/	-12.49	38.82	54.00	-15.18	360	100	Ave

Test Specification: Vertical



No.	Frequency MHz	Reading dBuV/m	Corr. Factor(dB)	Dutycycle Factor(dB)	Result dBuV/m	Limit dBuV/m	Margin (dB)	Deg. (°)	Height (cm)	Remark
1	433.9160	62.90	11.10	N/A	74.00	92.87	-18.87	360	100	peak
	433.9160	/	/	-12.49	61.51	72.87	-11.36	360	100	Ave
2	734.4913	16.70	17.68	N/A	34.38	46.00	-11.62	230	100	peak
3	851.0353	16.99	17.66	N/A	34.65	46.00	-11.35	360	100	peak

Above 1GHz

No.	Frequency MHz	Reading dBuV/m	Corr. Factor(dB)	Dutycycle Factor(dB)	Result dBuV/m	Limit dBuV/m	Margin dB	Deg. (°)	Height (cm)	Remark
1	1301.748	61.13	-13.12	N/A	48.01	74.00	-25.99	45	100	Peak
2	1735.664	67.61	-11.02	N/A	56.59	74.00	-17.41	310	100	Peak
	1301.748	/	/	-12.49	35.52	54.00	-18.48	360	100	Ave
	1735.664	/	/	-12.49	44.10	54.00	-9.90	360	100	Ave

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz..

The fundamental frequency is 433.916MHz, so the fundamental and spurious emissions radiated limit base on the the operating frequency 433.916MHz.

5. 20dB Bandwidth

5.1 Standard Applicable

According to FCC Part 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

5.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2012-03-28	2013-03-27
Attenuator	ATTEN	ATS100-4-20	/	2012-03-28	2013-03-27

6.3 Test Procedure

With the EUT’s antenna attached, the EUT’s 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT’s operation band.

5.4 Environmental Conditions

Temperature:	21° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar


5.5 Summary of Test Results/Plots

Test Frequency MHz	20dB Bandwidth kHz	Limit kHz	Result
433.916	103.388	1084.79	Pass

Limit = Fundamental Frequency X 0.25% = 433.916 MHz X 0.25% = 1084.79 kHz

Please refer to the attached plots.

20dB Bandwidth Test Plot



6. Transmission Time

6.1 Standard Applicable

According to FCC 15.231(e), devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

6.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2012-03-28	2013-03-27
Attenuator	ATTEN	ATS100-4-20	/	2012-03-28	2013-03-27

6.3 Test Procedure

With the EUT’s antenna attached, the EUT’s output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.916MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

6.4 Environmental Conditions

Temperature:	20° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

6.5 Summary of Test Results/Plots

For Normal transmitting under standby (2.5 Bar)


Item	Measured Value	Limit	Result
Transmission Time	23.75 ms	1 s	Pass
Silent Time	237 s	10 s	Pass
Silent Time/Transmission Time	9978.95	30	Pass

For Alarm Transmitting Under Quickly Leak


Item	Measured Value	Limit	Result
Transmission Time	23.50 ms	1 s	Pass
Silent Time	3.95 s	/	Pass
Silent Time/Transmission Time	168.08	/	Pass

Please refer to the attached plots.


Silent Time (Normal transmitting)




Transmission Time



Silent Time (Quickly Leak)



Transmission Time



According to FCC 15.231 a (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition, So the device comply with the requirement of the section for alarm transmitting test mode.

7. Duty Cycle

7.1 Standard Applicable

According to FCC Part 15.231 (b)(2) and 15.35 (c), For pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

7.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Agilent	E4402B	US41192821	2012-03-28	2013-03-27
Attenuator	ATTEN	ATS100-4-20	/	2012-03-28	2013-03-27

7.3 Test Procedure

With the EUT’s antenna attached, the EUT’s output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.916MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

7.4 Environmental Conditions

Temperature:	24° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar


7.5 Summary of Test Results/Plots

Type of Pulse	Width of Pulse ms	Quantity of Pulse number	Transmission Time ms	Total Time (T _{on}) ms
Pulse 1	23.75	1	23.75	23.75
/	/	/	/	

Test Period (T _p) ms	Total Time (T _{on}) ms	Duty Cycle %	Duty Cycle Factor dB
100	23.75	23.75	-12.49

Please refer to the attached test plots

Width of Pulse



***** END OF REPORT *****