Sheet 1 of 2 Sheets FCC ID.: Q72DMA1

MAXIMUM PERMISSIBLE EXPOSURE

Standard Applicable

Section 15.247 (b)(5): Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. *See* § 1.1307(b)(1) of this Chapter.

Section 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time		
(MHz)	Strength (V/m)	Strength (A/m)	(nW/cm^2)	(Minutes)		
(A) Limits for Occupational/control Exposures						
300-1500			F/300	6		
1500-100,000			5	6		
(B) Limits for General Population/Uncontrolled Exposures						
300-1500		F/300		6		
1500-100,000			1	30		

F = Frequency in MHz

Calculations

Friis transmission formula: $P_d = (P_{out} * G) / (4 * pi * r^2)$

Where

 P_d = power density in mW/cm²

 $P_{out} = \text{output power to antenna in } mW$

G = gain of antenna in linear scale

pi = 3.1416

 \mathbf{r} = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

ETC Report No.: ET93S-08-211

Sheet 2 of 2 Sheets
FCC ID.: Q72DMA1

Result

Operation	Power Density	Maximum Peak	Antenna Gain	Minimum allowable Distance
Frequency	Limit	Output Power	(dBi)	®From Skin
(GHz)	(mW/cm^2)	(dBm)		(cm)
2.412	1.0	19.807	2.1	3.51
2.437	1.0	19.222	2.1	3.28
2.462	1.0	19.457	2.1	3.37

The distance **r** calculated from the Friis transmission formula is mush shorter than 20 cm separation requirement. So SAR test is not required.

The **Installation Manual** instructs the user to install the device such that it has a separation of at least 20 cm from persons (see text below) to comply with the FCC's requirements. This separation of 20 cm more than meets the FCC's and Industry Canada RF exposure requirements.

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. The antenna(s) used for this equipment must be installed to provide a separation distance of at least eight inches (20em) from all persons.

This equipment must not be operated in conjunction with any other antenna.

Extract from Installation Manual