



**FCC 47 CFR PART 15 SUBPART C**

**TEST REPORT**

**For**

**IEEE 802.11b/g WLAN mini-PCI Card**

**Model: WLAN TP BG**

**Trade Name: N/A**

*Prepared for*

**CHUNG NAM ELECTRONICS CO., LTD.  
12/F, CHUNG NAM BUILDING,  
NO.1 LOCKHART ROAD  
HONG KONG**

*Prepared by*

**COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.  
NO. 6, JINAO INDUSTRIAL PARK, NO. 35 JUKENG ROAD,  
DASHUIKENG VILLAGE, GUANLAN TOWN, BAOAN  
DISTRICT, SHENZHEN, CHINA**

**TEL: 86-755-28055000**

**FAX: 86-755-28055221**



---

*Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



## TABLE OF CONTENTS

<b>1. TEST RESULT CERTIFICATION.....</b>	<b>3</b>
<b>2. EUT DESCRIPTION .....</b>	<b>4</b>
<b>3. TEST METHODOLOGY .....</b>	<b>5</b>
3.1 EUT CONFIGURATION .....	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.5 DESCRIPTION OF TEST MODES .....	6
<b>4. INSTRUMENT CALIBRATION.....</b>	<b>7</b>
<b>5. FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1 FACILITIES8	
5.2 EQUIPMENT.....	8
5.3 LABORATORY ACCREDITATIONS AND LISTING.....	8
<b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
6.1 SETUP CONFIGURATION OF EUT.....	9
6.2 SUPPORT EQUIPMENT .....	9
<b>7. FCC PART 15.247 REQUIREMENTS.....</b>	<b>10</b>
7.1 6DB BANDWIDTH.....	10
7.2 PEAK POWER.....	16
7.3 BAND EDGES MEASUREMENT .....	22
7.4 PEAK POWER SPECTRAL DENSITY .....	31
7.5 SPURIOUS EMISSIONS.....	37
7.6 POWERLINE CONDUCTED EMISSIONS .....	59
<b>APPENDIX 1 PHOTOGRPHS OF TEST SETUP .....</b>	<b>63</b>



# 1. TEST RESULT CERTIFICATION

**Applicant:** CHUNG NAM ELECTRONICS CO., LTD.  
12F, Chung Nam Building, No.1 Lockhart Rd.,  
| Wanchai, Hongkong

**Equipment Under Test:** IEEE 802.11b/g WLAN mini-PCI Card

**Trade Name:** N/A

**Model:** WLAN TP BG

**Date of Test:** June 28 ~ July 10, 2005

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15 Subpart C	No non-compliance noted

### We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

*Reviewed and Approved by*

---

Clinton Kao  
Manager of the Engineering Dept.  
Compliance Certification Services (ShenZhen) Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	IEEE 802.11b/g WLAN mini-PCI Card
<b>Trade Name</b>	N/A
<b>Model Number</b>	WLAN TP BG
<b>EUT Power Rating</b>	Powered from the host device (via mini-PCI interference)
<b>Frequency Range</b>	802.11b mode: 2412 ~ 2462 MHz 802.11g mode: 2412 ~ 2462 MHz
<b>Transmit Power</b>	802.11b mode: 13.20 dBm 802.11g mode: 13.18 dBm
<b>Modulation Technique</b>	802.11b: DSSS (CCK; DQPSK; DBPSK) 802.11g: OFDM
<b>Transmit Data Rate</b>	802.11b: 11Mbps(CCK) with fall back rates of 5.5, 2, and 1Mbps 802.11g : 54Mbps with fall back rates of 48/36/24/18/12/9/6 Mbps (OFDM)
<b>Number of Channels</b>	11 Channels
<b>Antenna Specification</b>	1.8 dBi (Max)

*Note: This submittal(s) (test report) comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.*



### **3. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4.

### 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 3.5 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

IEEE802.11b: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 11Mbps highest data rate (worst case) are chosen for the final testing.

IEEE802.11g: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 6Mbps data rate (the worst case) are chosen for the final testing.



#### **4. INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



## **5. FACILITIES AND ACCREDITATIONS**

### **5.1 FACILITIES**

All measurement facilities used to collect the measurement data are located at

No. 6, Jinao industrial park, No.35 Jukeng Road, Dashuikeng Village, Guanlan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### **5.3 LABORATORY ACCREDITATIONS AND LISTING**

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200577-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission.





## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### 6.2 SUPPORT EQUIPMENT

Device Type	Brand	Model	FCC ID	Serial No.	Data Cable	Power Cord
Notebook PC	IBM	2672	FCC DoC	992F2VG	Nil	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m

**Notes:**

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*

## 7. FCC PART 15.247 REQUIREMENTS

### 7.1 6dB BANDWIDTH

#### LIMIT


For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

#### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### Test Configuration



#### TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = 20MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.



## **TEST RESULTS**

*No non-compliance noted*

### **Test Data**

**Test mode: IEEE 802.11b**

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Bandwidth (kHz)</b>	<b>Limit (kHz)</b>	<b>Margin (kHz)</b>
Low	2412	12830	>500	PASS
Mid	2437	12800		PASS
High	2462	11600		PASS


**Test mode: IEEE 802.11g**

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Bandwidth (kHz)</b>	<b>Limit (kHz)</b>	<b>Margin (kHz)</b>
Low	2412	16430	>500	PASS
Mid	2437	16400		PASS
High	2462	16370		PASS


**Test Plot**

**802.11b mode**

**6dB Bandwidth (CH Low)**




**6dB Bandwidth (CH Mid)**






### 6dB Bandwidth (CH High)




**802.11g mode**

**6dB Bandwidth (CH Low)**




**6dB Bandwidth (CH Mid)**





### 6dB Bandwidth (CH High)



## **7.2 PEAK POWER**

### **LIMIT**

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **MEASUREMENT EQUIPMENT USED**

<b>Name of Equipment</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Due</b>
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### **Test Configuration**



### **TEST PROCEDURE**

*The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.*





**TEST RESULTS**

*No non-compliance noted*

**Test Data**

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Output Power (dBm)	cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	1.20	1200	13.20	0.02089	1	PASS
Md	2437	1.14	1200	13.14	0.02061		PASS
Hgh	2462	1.16	1200	13.16	0.02070		PASS

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	Output Power (dBm)	cable loss (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	1.18	1200	13.18	0.02080	1	PASS
Md	2437	1.12	1200	13.12	0.02051		PASS
Hgh	2462	-0.40	1200	11.60	0.01445		PASS



**Test Plot**

**802.11b mode**


**Peak power (CH Low)**



**Peak power (CH Mid)**




**Peak power (CH High)**



**802.11g mode**

**Peak power (CH Low)**




**Peak power (CH Mid)**





### Peak power (CH High)



## 7.3 BAND EDGES MEASUREMENT

### LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration



### TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.


### TEST RESULTS

Refer to attach spectrum analyzer data chart.

**Band Edges (802.11b / CH Low)**


**Detector mode: Peak**

**Polarity: Vertical**




**Detector mode: Average**

**Polarity: Vertical**




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal





**Band Edges (802.11b / CH High)**


**Detector mode: Peak**

**Polarity: Vertical**




**Detector mode: Average**

**Polarity: Vertical**




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average


Polarity: Horizontal



**Band Edges (802.11g / CH Low)**


**Detector mode: Peak**

**Polarity: Vertical**




**Detector mode: Average**

**Polarity: Vertical**




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average


Polarity: Horizontal



**Band Edges (802.11g / CH High)**


**Detector mode: Peak**

**Polarity: Vertical**




**Detector mode: Average**

**Polarity: Vertical**




Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal



## 7.4 PEAK POWER SPECTRAL DENSITY

### LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.



**TEST RESULTS**

*No non-compliance noted*

**Test Data**

**Test mode: IEEE 802.11b**

Channel	Frequency	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-23.39	12.00	-11.39	8.00	PASS
Mid	2437	-19.55	12.00	-7.55		PASS
High	2462	-22.86	12.00	-10.86		PASS

**Test mode: IEEE 802.11g**

Channel	Frequency	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-24.37	12.00	-12.37	8.00	PASS
Mid	2437	-27.51	12.00	-15.51		PASS
High	2462	-27.89	12.00	-15.89		PASS


**Factor=cable loss 2dB + attuantor 10dB=12dB**




**Test Plot**

**802.11b mode**


**PPSD (CH Low)**



**PPSD (CH Mid)**




### PPSD (CH High)




**802.11g mode**

**PPSD (CH Low)**




**PPSD (CH Mid)**





### PPSD (CH High)



## 7.5 SPURIOUS EMISSIONS

### 7.5.1 Conducted Measurement

#### LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

#### TEST RESULTS


*No non-compliance noted*




**Test Plot**

**IEEE 802.11b / CH Low**

**30MHz ~ 2.9GHz**




**2.9GHz ~ 26.5GHz**






**IEEE 802.11b / CH Mid**

**30MHz ~ 2.9GHz**




**2.9GHz ~ 26.5GHz**






**IEEE 802.11b / CH High**

**30MHz ~ 2.9GHz**



**2.9GHz ~ 26.5GHz**









**IEEE 802.11g / CH Low**

**30MHz ~ 2.9GHz**




**2.9GHz ~ 26.5GHz**






**IEEE 802.11g / CH Mid**

**30MHz ~ 2.9GHz**




**2.9GHz ~ 26.5GHz**




**IEEE 802.11g / CH High**

**30MHz ~ 2.9GHz**



**2.9GHz ~ 26.5GHz**





### 7.6.2 Radiated Emissions

#### LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

*Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


## MEASUREMENT EQUIPMENT USED

RF CHAMBER II				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US44300399	02/06/2006
EMI Test Receiver	R&S	ESCI	1166.595K03	01/13/2006
Pre-Amplifier	MITEQ	N/A	AFS42-00102650-42-10P-42	02/14/2006
Bilog Antenna	SCHWAZBECK	CBL6143	5082	06/09/2005
Turn Table	EMCO	2081-1.21	N/A	N.C.R
Antenna Tower	CT	N/A	N/A	N.C.R
Controller	CT	N/A	N/A	N.C.R
RF Comm. Test set	HP	8920B	US36142090	N.C.R
Site NSA	C&C	N/A	N/A	09/06/2005
Horn Antenna	TRC	N/A	N/A	03/04/2006


*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration

#### Below 1 GHz



## Above 1 GHz



## TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

**TEST RESULTS****Below 1 GHz****Operation Mode:** TX / IEEE 802.11b / CH Low**Test Date:** July 08, 2005**Temperature:** 20°C**Tested by:** Terry**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
48.5500	V	Peak	50.45	-15.32	35.13	40.00	-4.87
98.3750	V	Peak	58.97	-19.12	39.85	43.50	-3.65
182.8750	V	Peak	52.96	-18.14	34.82	43.50	-8.68
251.0500	V	Peak	53.41	-16.08	37.33	46.00	-8.67
604.7500	V	Peak	46.74	-8.01	38.73	46.00	-7.27
801.5000	V	Peak	49.18	-6.29	42.89	46.00	-3.11
97.8250	H	Peak	55.30	-19.40	35.90	43.50	-7.60
184.9000	H	Peak	57.78	-18.13	39.65	43.50	-3.85
252.0500	H	Peak	56.68	-16.12	40.56	46.00	-5.44
402.7500	H	Peak	50.31	-11.27	39.04	46.00	-6.96
801.5000	H	Peak	44.65	-6.23	38.42	46.00	-7.58
934.5000	H	Peak	43.73	-5.06	38.67	46.00	-7.33

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Operation Mode: TX / IEEE 802.11b / CH Mid

Test Date: July 08, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
163.3000	V	Peak	52.68	-18.23	34.45	43.50	-9.05
184.9000	V	Peak	54.74	-18.18	36.56	43.50	-6.94
252.0500	V	Peak	54.58	-16.12	38.46	46.00	-7.54
485.0000	V	Peak	49.29	-10.10	39.19	46.00	-6.81
668.5000	V	Peak	45.37	-7.84	37.53	46.00	-8.47
918.7500	V	Peak	45.05	-5.32	39.73	46.00	-6.27
97.8250	H	Peak	53.70	-19.40	34.30	43.50	-9.20
192.6500	H	Peak	56.94	-18.14	38.80	43.50	-4.70
256.0500	H	Peak	56.52	-16.12	40.40	46.00	-5.60
402.5500	H	Peak	47.88	-11.29	36.59	46.00	-9.41
803.7500	H	Peak	40.30	-6.34	33.96	46.00	-12.04
934.7800	H	Peak	39.10	-5.08	34.02	46.00	-11.98

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.





Operation Mode: TX / IEEE 802.11b / CH High

Test Date: July 08, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit 3m (dBUV/m)	Safe Margin (dB)
144.85	V	Peak	44.50	-17.21	27.29	43.50	-16.21
168.25	V	Peak	46.39	-17.98	28.41	43.50	-15.09
234.85	V	Peak	50.80	-17.63	33.17	46.00	-12.83
485.0000	V	Peak	47.29	-10.10	37.19	46.00	-8.81
668.5000	V	Peak	43.37	-7.84	35.53	46.00	-10.47
918.7500	V	Peak	40.05	-5.32	34.73	46.00	-11.27
401.33	H	Peak	43.01	-12.18	30.83	46.00	-15.17
502.67	H	Peak	45.67	-9.48	36.19	46.00	-9.81
578.33	H	Peak	42.47	-8.18	34.29	46.00	-11.71
635.83	H	Peak	41.35	-7.05	34.30	46.00	-11.70
799.17	H	Peak	41.19	-4.65	36.54	46.00	-9.46
965.33	H	Peak	39.17	-1.57	37.60	54.00	-16.40

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit 3m (dBUV/m)	Safe Margin (dB)
46.5500	V	Peak	50.36	-15.32	35.04	40.00	-4.96
103.9250	V	Peak	54.16	-18.07	36.09	43.50	-7.41
252.0500	V	Peak	55.26	-16.12	39.14	46.00	-6.86
536.5000	V	Peak	42.28	-8.87	33.41	46.00	-12.59
801.5000	V	Peak	43.83	-6.34	37.49	46.00	-8.51
918.7500	V	Peak	40.43	-5.32	35.11	46.00	-10.89
97.2500	H	Peak	54.42	-19.53	34.89	43.50	-8.61
186.6750	H	Peak	54.67	-18.18	36.49	43.50	-7.01
252.1500	H	Peak	57.47	-16.12	41.35	46.00	-4.65
402.5500	H	Peak	48.65	-11.29	37.36	46.00	-8.64
802.7500	H	Peak	41.85	-6.34	35.51	46.00	-10.49
934.5000	H	Peak	43.88	-5.08	38.80	46.00	-7.20

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit 3m (dBUV/m)	Safe Margin (dB)
48.5500	V	Peak	50.05	-15.32	34.73	40.00	-5.27
106.6500	V	Peak	54.02	-17.87	36.15	43.50	-7.35
181.7800	V	Peak	54.78	-18.05	36.73	43.50	-6.77
252.0550	V	Peak	55.37	-16.12	39.25	46.00	-6.75
532.5000	V	Peak	45.52	-8.87	36.65	46.00	-9.35
932.5000	V	Peak	41.67	-5.05	36.62	46.00	-9.38
97.1500	H	Peak	54.78	-19.53	35.25	43.50	-8.25
182.3250	H	Peak	55.03	-18.17	35.86	43.50	-7.64
249.0500	H	Peak	57.11	-16.12	40.99	46.00	-5.01
402.5500	H	Peak	51.49	-11.29	40.20	46.00	-5.80
801.5500	H	Peak	41.79	-6.34	35.45	46.00	-10.55
934.7800	H	Peak	41.01	-5.08	35.93	46.00	-10.07

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Operation Mode: TX / IEEE 802.11g / CH High

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
48.7500	V	Peak	50.12	-15.45	34.67	40.00	-5.33
108.7250	V	Peak	52.46	-18.05	34.41	43.50	-9.09
184.2350	V	Peak	54.42	-18.18	36.24	43.50	-7.26
260.1530	V	Peak	55.02	-16.02	39.00	46.00	-7.00
678.4550	V	Peak	42.16	-7.65	34.51	46.00	-11.49
932.5000	V	Peak	39.76	-5.08	34.68	46.00	-11.32
95.1750	H	Peak	54.90	-19.65	35.25	43.50	-8.25
183.2550	H	Peak	55.65	-18.05	37.60	43.50	-5.90
253.0500	H	Peak	57.45	-16.20	41.25	46.00	-4.75
402.5000	H	Peak	47.75	-11.29	36.46	46.00	-9.54
802.5000	H	Peak	41.73	-6.34	35.39	46.00	-10.61
934.5000	H	Peak	40.79	-5.07	35.72	46.00	-10.28

Notes:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX / IEEE 802.11b / CH Low**Test Date:** July 08, 2005**Temperature:** 23°C**Tested by:** Terry**Humidity:** 56 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1046.67	V	6.66	---	38.8	45.46	---	74.00	54.00	-28.54	Peak
1256.67	V	5.51	---	39.59	45.10	---	74.00	54.00	-28.90	Peak
2376.67	V	3.89	---	44.32	48.21	---	74.00	54.00	-25.79	Peak
2690.00	V	3.9	---	44.64	48.54	---	74.00	54.00	-25.46	Peak
3675.00	V	6.23	-5.72	47.56	53.36	41.84	74.00	54.00	-12.16	AVG
7450.00	V	2.49	-9.64	56.18	58.67	46.54	74.00	54.00	-7.46	AVG
2090.00	H	3.52	---	42.61	46.13	---	74.00	54.00	-27.87	Peak
2373.33	H	3.23	---	44.29	47.52	---	74.00	54.00	-26.48	Peak
2683.33	H	3.42	---	44.62	48.04	---	74.00	54.00	-25.96	Peak
4825.00	H	1.81	-9.18	50.22	52.03	41.04	74.00	54.00	-12.96	AVG
7258.33	H	2.93	-10.36	55.48	60.41	45.12	74.00	54.00	-8.88	AVG

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

**Operation Mode:** TX / IEEE 802.11b / CH Mid**Test Date:** July 08, 2005**Temperature:** 20°C**Tested by:** Terry**Humidity:** 70 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1043.33	V	6.38	---	38.79	45.17	---	74.00	54.00	-28.83	Peak
1250.00	V	6.83	---	39.57	46.40	---	74.00	54.00	-27.60	Peak
2080.00	V	4.29	---	42.58	46.87	---	74.00	54.00	-27.13	Peak
2370.00	V	4.33	---	44.27	48.60	---	74.00	54.00	-25.40	Peak
4875.00	V	1.99	-9.26	50.51	52.50	41.25	74.00	54.00	-12.75	AVG
7458.33	V	1.4	-10.43	56.17	57.57	45.74	74.00	54.00	-8.26	AVG
1183.33	H	5.55	---	39.4	44.95	---	74.00	54.00	-29.05	Peak
1273.33	H	8.01	---	39.62	47.63	---	74.00	54.00	-26.37	Peak
1506.67	H	7.67	---	40.35	48.02	---	74.00	54.00	-25.98	Peak
4833.33	H	1.89	-9.34	50.27	52.16	40.93	74.00	54.00	-13.07	AVG
7491.67	H	3.57	-7.32	56.13	59.70	48.81	74.00	54.00	-5.19	AVG

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



**Operation Mode:** TX / IEEE 802.11b / CH High

**Test Date:** July 08, 2005

**Temperature:** 20°C

**Tested by:** Terry

**Humidity:** 70 % RH

**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1046.67	V	6.06	---	38.8	44.86	---	74.00	54.00	-29.14	Peak
1246.67	V	5.22	---	39.57	44.79	---	74.00	54.00	-29.21	Peak
2383.33	V	4	---	44.37	48.37	---	74.00	54.00	-25.63	Peak
2610.00	V	3.12	---	44.34	47.46	---	74.00	54.00	-26.54	Peak
4925.00	V	3.15	-8.02	50.8	53.95	33.65	74.00	54.00	-11.22	AVG
7708.33	V	3.63	-8.47	55.89	59.52	36.95	74.00	54.00	-6.58	AVG
2370.00	H	4.32	---	44.27	48.59	---	74.00	54.00	-25.41	Peak
2683.33	H	3.3	---	44.62	47.92	---	74.00	54.00	-26.08	Peak
4958.33	H	2.04	-9.36	50.99	53.03	41.63	74.00	54.00	-12.37	AVG
7708.33	H	3.82	-8.11	55.89	59.71	47.78	74.00	54.00	-6.22	AVG

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



Operation Mode: TX / IEEE 802.11g / CH Low

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2039.10	V	5.46	---	42.6	48.06	---	74.00	54.00	-25.94	Peak
2446.00	V	7.8	---	44.33	52.13	38.21	74.00	54.00	-15.79	Peak
2039.10	H	6.92	---	42.6	49.52	---	74.00	54.00	-24.48	Peak
2446.00	H	10.48	---	44.33	54.81	36.33	74.00	54.00	-17.67	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.





Operation Mode: TX / IEEE 802.11g / CH Mid

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2063.15	V	3.14	---	43.25	46.39	---	74.00	54.00	-27.61	Peak
4841.67	V	1.55	---	50.32	51.87	---	74.00	54.00	-22.13	Peak
2063.15	H	1.86	---	43.75	45.61	---	74.00	54.00	-28.39	Peak
4783.33	H	2.33	---	50.09	52.42	---	74.00	54.00	-21.58	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.



Operation Mode: TX / IEEE 802.11g / CH High

Test Date: July 07, 2005

Temperature: 20°C

Tested by: Terry

Humidity: 70 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
2087.00	V	5.81	---	43.52	49.33	---	74.00	54.00	-24.67	Peak
3042.18	V	1.75	---	45.15	46.90	---	74.00	54.00	-27.10	Peak
2087.00	H	11.15	-9.21	43.57	54.72	34.36	74.00	54.00	-19.64	Peak
3031.12	H	5.28	---	44.84	50.12	---	74.00	54.00	-23.88	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
  - b. AV Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

## 7.6 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power Line, the radio frequency voltage that is conducted back onto the AC power Line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases Linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50


Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power Line (LINE and NEUTRAL) and ground at the power terminals.

### MEASUREMENT EQUIPMENT USED

Conducted Emission Test Site A (10m chamber)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESI26	100068	02/11/2006
EMC Analyzer	Agilent	E7402A	US41160329	02/11/2006
LISN	FCC	FCC-LISN-50-50-2-M	01067	02/11/2006
LISN (EUT)	FCC	FCC-LISN-50-50-2-M	01068	02/11/2006
4-WIRE ISN	R&S	ENY41	830663/024	04/9/2006
TRANSIENT LIMITER	SCHAFFNER	CFL9206	1710	03/15/2006
Double 2-Wire ISN	R&S	ENY22	830661/027	04/9/2006
EMI Monitor control box	FCC	0-SVDC	N/A	N/A

**Remark:** Each piece of equipment is scheduled for calibration once a year.

## Test Configuration



See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

## TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

## TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



**Test Data**

**Model:** Operating

**Test Mode:** Mode 1

**Temperature:** 30°C

**Humidity:** 60% RH

**Tested by:** Terry

**Test Results:** Pass

(The chart below shows the highest readings taken from the final data)

Freq. (MHz)	Peak Raw (dBuV)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Margi n (dB)	Factor (dB)	Remark
0.164	47.96	---	---	65.58	55.58	-7.62	10.32	L1
0.216	45.61	---	---	64.09	54.09	-8.48	10.30	L1
0.536	41.90	---	---	56.00	46.00	-4.10	10.37	L1
1.121	36.69	---	---	56.00	46.00	-9.31	10.49	L1
5.487	38.27	---	---	60.00	50.00	-11.73	11.09	L1
16.709	35.70	---	---	60.00	50.00	-14.30	12.38	L1
0.164	45.10	---	---	65.58	55.58	-10.48	10.40	L2
0.213	41.66	---	---	64.20	54.20	-12.54	10.39	L2
0.535	40.21	---	---	56.00	46.00	-5.79	10.48	L2
1.173	35.62	---	---	56.00	46.00	-10.38	10.59	L2
5.494	37.92	---	---	60.00	50.00	-12.08	11.17	L2
17.046	35.63	---	---	60.00	50.00	-14.37	12.36	L2

L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

**Remark:**

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

**Note:**

Freq. = Emission frequency in KHz

Factor (dB) = cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER (The TRANSIENT LIMITER included 10 dB ATTENUATION)

Amptd dBuV = Uncorrected Analyzer/Receiver reading + cable loss + Insertion loss of LISN+ Insertion loss of TRANSIENT LIMITER, if it > 0.5 dB



*Limit dBuV = Limit stated in standard*

*Margin dB = Reading in reference to limit*

### **Calculation Formula**

*Margin (dB) = Amptd (dBuV) – Limit (dBuV)*

### **Common Mode Conducted Emission**

*Not applicable*

## APPENDIX 1 PHOTOGRPHS OF TEST SETUP

### LINE CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST

