

# RF EXPOSURE

FCC ID: Q78-R8978S2600M

**Applicable standard:** FCC §2.1091 §1.1307

## Limit

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated. Limits for Maximum Permissible Exposure (MPE)

| (B) Limits for General Population/Uncontrolled Exposure |                                   |                                   |                                         |                                                                   |
|---------------------------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------------|-------------------------------------------------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
| 0.3-1.34                                                | 614                               | 1.63                              | (100)*                                  | 30                                                                |
| 1.34-30                                                 | 824/f                             | 2.19/f                            | (180/f <sup>2</sup> )*                  | 30                                                                |
| 30-300                                                  | 27.5                              | 0.073                             | 0.2                                     | 30                                                                |
| 300-1500                                                | --                                | --                                | f/1500                                  | 30                                                                |
| 1500-100,000                                            | --                                | --                                | 1.0                                     | 30                                                                |

## Test Data

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Maximum output power at antenna input terminal: 52.06(dBm) ,the Torrance is  $\pm 2.7$ dB ,the cable loss is 0.6dB.

Predication frequency range: 2496M-2596MHz

Antenna Gain (typical): 17(dBi)

Power density at predication frequency at 1020 cm: 0.9996(mW/cm<sup>2</sup>)

MPE limit for uncontrolled exposure at prediction frequency: 1 (mW/cm<sup>2</sup>)

$$PG=52.06+2.7+17-0.6=71.16\text{dBm}$$


<以上所有信息均为中兴通讯股份有限公司所有，不得外传>

All Rights reserved, No Spreading abroad without Permission of ZTE

---

PG=13061708.88mW  
 $S = PG / 4\pi R^2 < 1(\text{mW}/\text{cm}^2)$   
R=1020cm

**Test Result: pass**



Jennie HE – Certification Engineer

2014-10-25

Date