
ZXHN F660 GPON ONT User Manual



ZTE CORPORATION

ZXHN F660 GPON ONT User Manual

Manual No: SJ-20170123104656-005 Edition Time: 2018-01-30(R1.0)

LEGAL INFORMATION

Copyright © 2017 ZTE CORPORATION.

The contents of this document are protected by copyright laws and international treaties. Any reproduction or distribution of this document or any portion of this document, in any form by any means, without the prior written consent of ZTE CORPORATION is prohibited. Additionally, the contents of this document are protected by contractual confidentiality obligations.

All company, brand and product names are trade or service marks, or registered trade or service marks, of ZTE CORPORATION or of their respective owners.

This document is provided "as is", and all express, implied, or statutory warranties, representations or conditions are disclaimed, including without limitation any implied warranty of merchantability, fitness for a particular purpose, title or non-infringement. ZTE CORPORATION and its licensors shall not be liable for damages resulting from the use of or reliance on the information contained herein.

ZTE CORPORATION or its licensors may have current or pending intellectual property rights or applications covering the subject matter of this document. Except as expressly provided in any written license between ZTE CORPORATION and its licensee, the user of this document shall not acquire any license to the subject matter herein.

ZTE CORPORATION reserves the right to upgrade or make technical change to this product without further notice.

Users may visit ZTE technical support website http://support.zte.com.cn to inquire related information.

The ultimate right to interpret this product resides in ZTE CORPO-RATION.

1 Safety Precautions

NOTE Note:

Before using the device, read the following safety precautions. ZTE bears no liability to the consequences incurred by violation of the safety instructions.

Usage Cautions

- Read all the safety cautions carefully before using the device.
- Only use the accessories included in the package, such as power supply adapter and battery.
- Do not extend the power cord, otherwise the device will not work.
- The power supply voltage must meet the requirements of the device input voltage (The voltage fluctuation range is less than 10%).
- Keep the power plug clean and dry to prevent any risk of electric shock or other dangers.
- Disconnect all the cables during a lightning storm to prevent the device from damage.
- Power off and unplug the power plug when the device is not in use for a long time.
- Do not attempt to open the covers of the device. It is dangerous to do so when the device is powered ON.
- Do not directly stare at the optical interface to prevent any eye injuries.
- Power off and stop using the device under the conditions such as, abnormal sound, smoke, and strange smell. Contact the service provider for maintenance if the device is faulty.

Environment Requirements

- Ensure proper ventilation to the device. Place the device away from direct sunlight and never spill any liquid on the device.
- Do not place any object on the device to prevent any deformation or damage to the device.
- Do not place the device near any source of heat or water.
- Keep the device away from any household appliances with strong magnetic or electric fields, such as microwave oven and refrigerator.

Cleaning Requirements

Before cleaning, power off the device, and unplug all the cables connected to the device, such as power cable, optical fiber, and Ethernet cable. Do not use any liquid or spray to clean the device. Use a soft dry cloth.

Environment Protection

- Do not dispose the device or power adapter improperly.
- Observe the local regulations about the equipment disposal or treatment.

Environmental Information

The equipment you purchased has required the extraction and use of natural resources for its production. It may contain substances that are hazardous to people's health and to the environment. To avoid putting such substances into our environment and to reduce pressure on our natural resources, we ask that you reuse or recycle your end-of-life equipment by using an accredited electronics take-back system.

The symbols below indicate that this product should be reused or recycled and not simply discarded. Please locate and use an appropriate reuse and recycling site.

If you need more information on collection, reuse and recycling systems, contact your local or regional waste administration. You may also contact your equipment provider for more information on the environmental performances of these products.



2 Package Content

Please make sure the ZXHN F660 package contains the following items.

| Item | Quantity |
|----------------------------|----------|
| ZXHN F660 unit | One |
| AC-DC power supply adapter | One |
| RJ-45 Ethernet cable | One |
| User manual | One |



The list is only for reference. The actual contents may vary from the list.

If any of the items included in the package is incorrect, lost or damaged, please contact your service provider. If you need to replace the product, please keep the package and all the items in good condition.

3 Indicator

shows the indicators on the front panel of the ZXHN F660 unit.

Figure 3-1 Indicators on the Front Panel

```
Power PON LOS Internet LANI LAN2 LANI HANA Phone Phone 246-Fi WPS USB
```

describes the indicators on the front panel of the ZXHN F660 unit.

| Table 3-1 Des | criptions of the | Indicators on | the Front Panel |
|---------------|------------------|---------------|-----------------|
|---------------|------------------|---------------|-----------------|

| Indicator | Status | Description | |
|-----------|----------------|--|--|
| Power | Off | No power | |
| Power | Solid green | Power on | |
| | Off | The ONT registration fails or the system is not powered on. | |
| PON | Solid green | The ONT registration is successful. | |
| | Flashing green | The ONT is being registered. | |

| Indicator | Status | Description |
|--------------------|----------------|---|
| | Off | The ONT received optical power is normal. |
| LOS | Solid red | The optical transmitter of the PON interface is powered off. |
| | Flashing red | The ONT received optical power is lower than the optical sensitivity of the receiver. |
| | Off | The device is not powered on or the Ethernet connection does not exit. |
| Internet | Solid green | The internet connection has been established. |
| | Flashing green | The data is transmitted via internet connection. |
| | Off | The device is not powered on or the network link is not established. |
| LAN1 – LAN4 | Solid green | The network link has been established but no data is being transmitted or received. |
| | Flashing green | Data is being transmitted or received. |
| | Off | The device is not powered on or it cannot be registered to the soft switch. |
| Phone1 – Phone2 | Solid green | The device has been registered to the soft switch, but there are no POTS services. |
| | Flashing green | The POTS communication service is being provided. |
| | Off | The device is not powered on or the wireless interface is disabled. |
| Wi-Fi | Solid green | The wireless interface is enabled. |
| | Flashing green | The data is being transmitted or received. |


| Indicator | Status | Description | |
|-----------|----------------|---|--|
| | Solid yellow | The negotiation is being made. | |
| WPS | Solid green | The negotiation is successful. | |
| | Solid red | The session overlapping detection or negotiation fails. | |
| USB | Off | The device is not powered on or the USB interface is not connected. | |
| | Solid green | The USB interface is connected to the USB storage device, or connected to the printing device, but no data is being transmitted or received. | |
| | Flashing green | The data is being transmitted or received. | |



Side Panel

shows the interfaces and buttons on the side panel of the ZXHN F660 unit.

Figure 4-1 Interfaces and Buttons on the Side Panel



describes the interfaces and buttons on the side panel of the ZXHN F660 unit.


Table 4-1 Descriptions of the Interfaces and Buttons on the Side Panel

| Interface/ Button | Description |
|----------------------|--|
| Reset | This button is on the bottom of modem. In the power-on state, you can restore the system to the default configuration by using a thin needle to press this slot for five seconds. |
| USB | USB 2.0 interface. |
| WPS | Wi-Fi protection button. To enable the Wi-Fi protection function, press this button, so that users can access the network without entering their passwords. |
| Wi-Fi | WLAN button for enabling or disabling the WLAN function. |

Rear Panel

shows the interfaces and buttons of the ZXHN F660 unit.

Figure 4-2 Interfaces and Buttons on the Rear Panel



describes the interfaces and buttons on the back panel of the ZXHN F660 unit.

Table 4-2 Descriptions of the Interfaces and Buttons on the Rear Panel

| Interface/Button | Description |
|------------------|--|
| PON | PON interface. |
| | RJ-11 telephone interface, connected to the telephone with RJ-11 telephone cable. |
| LAN1 – LAN4 | RJ-45 Ethernet interface. |

| Interface/Button | Description | |
|------------------|--------------------------|--|
| Power | 12 V DC power connector. | |
| On/Off | Power switch. | |

5 Product Features

Interfaces

- GPON interface: GPON standard, SC/APC, comply with ITU G.984.1–G.984.5 standards.
- Ethernet interface: Four GE interfaces, RJ-45, comply with IEEE 802.3 and IEEE 802.3u standards.
- Phone interface: RJ-11.
- Wi-Fi interface: Complying with IEEE 802.11b/g/n standard.
- USB Interface: Standard USB 2.0 interface.

Technical Features

- Broadband service access: Connected to Internet through the GPON access method.
- Ethernet service access: Provides GE Ethernet interfaces, connected to the Ethernet devices, such as the user PC. Provides the Internet access and IPTV services.
- Phone service access: Supports SIP, H.248 protocol.
- Wi-Fi service access: Provides Internet service for the users through the WLAN method.
- Data sharing, backup and restore: Provides USB 2.0 interface to connect to the USB storage device for file sharing, quick backup, and data restoring.
- Security: Provides multi-level authentication based on the device, user and service, and provides the data channel encryption for safety.
- QoS: Provides QoS services meeting the requirements of various services for the local devices and network
- Network management: Provides multi-mode network management.


6 Product Specifications

| Technical Specifications | | |
|--------------------------|---|--|
| Dimension | 205mm × 120mm × 28mm (Width × Depth × Height, antenna unincluded) | |
| Power adapter | Input: AC 100 V – 240 V, 50 Hz/60 Hz Output: DC 12 V, 1 A | |
| Environment Requirements | | |
| Operation temperature | 0 °C – 40 °C (32 °F – 104 °F) | |
| Operation humidity | 5% – 95% (non-condensing) | |

7 Cable Connection

shows the devices that are connected to the ZXHN F660 device.

Figure 7-1 Entire Connection



After the devices are connected to the ZXHN F660 device, press the power button. When the corresponding indicators on the front panel are On, you can enjoy various services provided by the service provider.

The factors affecting the wireless network coverage range include the location of the product, distance between the product and a wireless terminal, number of obstacles, obstacle material and density, and interference source. It is recommended that you place the product in accordance with the following principles to maximize the strength of wireless signals.

- The product should be far away from the objects affecting wireless signal propagation, for example, an object with a high reflectivity such as a metallic object or a mirror.
- The product should be far away from an electrical appliance with a strong magnetic or electric field, for example, a microwave oven, a refrigerator, a wireless router, a cordless phone, or a Bluetooth product.
- The product should be installed on the same floor as the applied area.
- Do not put other objects on the product. Try to reduce the number of obstacles between the product and a wireless terminal.
- Horizontally place the product in the middle of the applied area and do not put it in a corner.

Do not place the product at a high position while it is placed horizontally. The recommended height is 1.2 to 1.5 meters.

8 Troubleshooting

The Power indicator on the front panel is off after the power button is pressed.

The power adapter is not correctly connected to the device. Be sure to use the power adapter supplied with the device.

The LOS indicator is flashing red or solid red after the device is powered on.

- The optical fiber is not correctly connected to the ONT PON interface.
- The optical fiber is broken or damaged.
- If the indicator is solid red or keeps flashing, please contact the service provider for maintenance.

The PON indicator on the front panel is off or flashing green after the device is powered on.

- The GPON link is not established.
- The ONT is not registered.
- Please contact the service provider for help.

The green LAN indicator on the front panel is off after the device is powered on.

- The corresponding LAN link is not established.
- The Ethernet cable is not correctly connected to the LAN interface.
- The network device connected to the LAN interface is not powered on.

The Phone indicator on the front panel is off after the device is powered on.

The telephone function is abnormal. Please contact the service provider for help.

9 FCC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement

This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be colocated or operating in conjunction with any other antenna or transmitter. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

Caution!

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

| CERTIFICATION |
|---------------|
| CHECKER |
| DATE |
| ZTE |

Address: No.55, Hi-tech Road South, ShenZhen, P.R.China Postcode: 518057 Tel: +86-755-2677 1900 URL: http://support.zte.com.cn E-mail: support@zte.com.cn