


## SAR Exclusion Evaluation Report

Applicant : Mobile Action Technology Inc.  
Product Type : Bluetooth 4.0 Low Energy Wristband  
Trade Name : Q-Watch  
Model Number : Q-77  
Date of Received : Apr. 13, 2016  
Test Period : Apr. 14 ~ Apr. 25, 2016  
Date of Issued : Apr. 27, 2016

### Issue by

Approved By :   
(Bill Hu)

Tested By :   
(Mark Duan)

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade District,  
Taoyuan City 33465, Taiwan (R.O.C)  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



### Revision History

Rev.	Issue Date	Revisions	Revised By
00	Apr. 27, 2016	Initial Issue	Snow Wang



# Contents

<b>1. Description of Equipment under Test (EUT) .....</b>	<b>4</b>
<b>2. Reference Testing Standards .....</b>	<b>4</b>
<b>3. SAR Test Exclusion.....</b>	<b>5</b>
3.1 Conducted Power .....	6
3.2 Antenna Location.....	6
3.3 Evaluation Results .....	7



## 1. Description of Equipment under Test (EUT)

Applicant	Mobile Action Technology Inc. 5F., No.205-3, Sec.3, Beishin Rd., Shindian City Taipei Taiwan 231			
Manufacturer	Heisei Technology Co., Ltd. 2F.,No.5,Aly.8,Ln.45.,Baoxing Rd.,Xindian Dist.,New Taipei City 231,Taiwan,R.O.C.			
Product Type	Bluetooth 4.0 Low Energy Wristband			
Trade Name	Q-Watch			
Model Number	Q-77			
FCC ID	Q7Z-16077R1			
Operate Freq. Band	Frequency Range (MHz)	Modulation Type	Data Rate (Mbps)	Number of Channels
Bluetooth LE	2402 ~ 2480	GFSK	1	40
Antenna information	Type		Max. Gain (dBi)	
	FPC Antenna		-1.14	

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1093. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

## 2. Reference Testing Standards

Standard	Description	Version
ANSI/IEEE C95.1	American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300 KHz to 100 GHz, New York.	1992
IEEE 1528	IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques.	2013
FCC 47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices.	---
FCC KDB 865664 D01	SAR measurement 100 MHz to 6 GHz - describes SAR measurement procedures for devices operating between 100 MHz to 6 GHz	v01r04
FCC KDB 865664 D02	RF Exposure Reporting - provides general reporting requirements as well as certain specific information required to support MPE and SAR compliance.	v01r02
FCC KDB 447498 D01	General RF Exposure Guidance - provides guidance pertaining to RF exposure requirements for mobile and portable device equipment authorizations.	v06



### 3. SAR Test Exclusion

As RF exposure evaluation of portable device, SAR test is not required when the evaluation results. According to KDB 447498 4.3.1, unless excluded by specific FCC test procedures, portable devices shall include SAR data for equipment approval. SAR test necessity will be based on the exclusion result.

The test exclusion refers KDB 447498 as below:

**≤50mm:**

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

**>50mm and <200mm:**

- a)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$  mW, at 100 MHz to 1500 MHz
- b)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$  mW at > 1500 MHz and  $\leq 6$  GHz

### 3.1 Conducted Power


The conducted power turn-up tolerance, please reference manufacturer specification.

Operate Band	Modulation Type	Data Rate (Mbps)	Frequency (MHz)	Average Power (dBm)
Bluetooth LE	GFSK	1	2402	-4.52
			2440	-3.35
			2480	-2.04

### 3.2 Antenna Location

Transmitter and antenna implementation	
Operate Band	Bluetooth Antenna
Bluetooth LE	V

Ant. Used	Antenna to user distance (mm)					
	Side 1	Side 2	Side 3	Side 4	Side 5	Side 6
Bluetooth Antenna	1	3	35	5	6	12





### 3.3 Evaluation Results

The evaluation of SAR test reduction according to KDB447498

SAR test is not required when the results showed "EXEMPT".

Body SAR test reduction										
Ant. Used	Operate Band	Frequency (GHz)	Tune-Power		Calculated threshold value					
			(dBm)	(mW)	Side 1	Side 2	Side 3	Side 4	Side 5	Side 6
Bluetooth Antenna	Bluetooth LE (GFSK)	2.48	-2	1	1.6	0.5	0	0.3	0.3	0.1
					EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT	EXEMPT

#### Exclusion Considerations: SAR is not required

- Note:
1. Calculated Threshold Value include string "mW", that is mean through compare output power with threshold, if the output power more than threshold value the SAR test should be perform.
  2. Calculated Threshold Value only include number format, that is mean through compare output power with threshold, if the threshold value more than 3 the SAR test should be perform.
  3. Otherwise, the SAR test could be exempt.
  4. When an antenna qualifies for the standalone SAR test exclusion of KDB447498 section 4.3.1 and also transmits simultaneously with other antennas, the standalone SAR value must be estimated according to KDB447498 section "4.3.2. Simultaneous transmission SAR test exclusion considerations b) ".
  5. The channel and frequency used highest frequency, that result should be evaluated the worst case.
  6. Power and distance are rounded to the nearest mW and mm before calculation.
  7. The result is rounded to one decimal place for comparison.