

FCC ID: Q7Z-21G120B

## GT-120B Specifications

### Bluetooth GPS Logger GT-120B

#### Specifications

Dimension | Weight : 44.5mm x 28mm x 13.5mm | 21.5g

Built-in GPS Patch Antenna

16M bit Flash Memory to store 65,000 waypoint

Built-in 380 mAh Li-Polymer battery

2 LEDs for On/Off/Charge/Logging status indication

Average acquisition time : Cold Start < 35 seconds

USB 2.0 interface for PC connect and Charging

Bluetooth 5.2 compatible supports long range feature

Water Resistant: IPX7

Operating Temperature: -10 C to 50 C

#### For Bluetooth:

The transmitter of the EUT is powered Build-in Battery, DC5V from USB cable, Support battery charge and data transmission, and employing GFSK modulation with 40 channels in 2.4 GHz Band.

The antenna used in this product is Chip Antenna. BT version is 5.2

Frequency Range: 2402-2480 MHz

Bluetooth Antenna	
Frequency Range	2.4~2.5 GHz
Trade Name	Invax
Model Name	IVX-CA2400-321605
Antenna Type	Chip Antenna
Antenna Gain	2.5dBi

Antenna	Mode	Frequency/Band	Rate/RB/Modulation	Avg with tune-up (dBm)
				Max
Bluetooth	Bluetooth LE	2.4GHz		2.0