FCC ID: Q7Z-BV001R1

Operational Description of the equipment

Install Voiis Panel software on the Voiis software CD. Use Bluetooth Manager to search for Voiis Mini/Phone and connect with it.

Step 1. Install Voiis Panel software

Insert the Voiis software CD to the PC and install the Voiis Panel software.

Step 2. Launch Voiis Panel software.

After the installation completed, you will find the Voiis Panel icon on the Programs menu or desktop of PC. Click Voiis Panel icon to launch Voiis Panel and then click **Bluetooth Manager**.

Step 3. Search and connect Voiis Mini/Phone.

Please make sure Voiis Mini/Phone has been turned on, and enter **Pairing** mode in **Bluetooth** setting.

Click Search and wait for 10 to 20 seconds. Bluetooth Manager will display the Voiis Mini/Phone that has been found. Select the Voiis Mini/Phone that you wish to connect and click **Pair** button.

PRODUCT	Voiis Dongle
MODEL NO.	BV-001
CHARGE POWER	DC 5.0V, 150mA
FREQUENCY BAND	2.402GHz~2.480GHz
CARRIER FREQUENCY	FHSS(Frequency Hopping Spread Spectrum)
NUMBER OF CHANNEL	79
CHANNEL SPACING	1 MHz
RATED RF OUTPUT POWER	+1.9 dBm
MODE OF OPERATION	duplex
MODULATION TYPE	GFSK(1Mbps)
BIT RATE OF TRANSMISSION	Bluetooth V1.2(1Mbps)
ANTENNA TYPE	Mono Pole
ANTENNA GAIN	0dB
OPERATING TEMPERATURE	0~45℃
CHANNEL BANDWIDTH	1MHz