



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:1 of 51  
Date: Apr. 20, 2007

Product Name: Bluetooth Data Suite  
Model Number: MA-730  
Applicant: MOBILE ACTION TECHNOLOGY INC.  
5F., No.205-3, Sec.3, Beishin Rd., Shindian  
City, Taipei, Taiwan  
Date of Receipt: Mar. 30, 2007  
Finished date of Test: Apr. 19, 2007  
Applicable Standards: 47 CFR Part 15, Subpart C  
ANSI C63.4:2003  
FCC Public Notice DA 00-705(March 2000)

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Tested By:

John Yu, Date: 4/20/2007  
(John Yu)

Approved By:

Johnson Ho, Date: 4/20/2007  
(Johnson Ho, Director)



Lab Code: 200099-0



## TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT.....	4
1.1 DOCUMENT POLICY.....	4
1.2 TEST STATEMENT.....	4
1.3 EUT MODIFICATION.....	4
2. DESCRIPTION OF EUT AND TEST MODE.....	5
2.1 GENERAL DESCRIPTION OF EUT.....	5
2.2 DESCRIPTION OF SUPPORT UNIT.....	5
2.3 DESCRIPTION OF TEST MODE.....	6
3. DESCRIPTION OF APPLIED STANDARDS.....	6
4. TECHNICAL CHARACTERISTICS TEST.....	7
4.1 CHANNEL SEPARATION TEST.....	7
4.1.1 LIMIT.....	7
4.1.2 TEST EQUIPMENT.....	7
4.1.3 TEST SET-UP.....	7
4.1.4 TEST PROCEDURE.....	7
4.1.5 EUT OPERATING CONDITION.....	8
4.1.6 TEST RESULT.....	8
4.2 20DB BANDWIDTH.....	12
4.2.1 LIMIT.....	12
4.2.2 TEST EQUIPMENT.....	12
4.2.3 TEST SET-UP.....	12
4.2.4 TEST PROCEDURE.....	12
4.2.5 TEST RESULT.....	13
4.3 QUANTITY OF HOPPING CHANNEL TEST.....	16
4.3.1 LIMIT.....	16
4.3.2 TEST EQUIPMENT.....	16
4.3.3 TEST SET-UP.....	16
4.3.4 TEST PROCEDURE.....	16
4.3.5 EUT OPERATING CONDITION.....	16
4.3.6 TEST RESULT.....	17
4.4 TIME OF OCCUPANCY (DWELL TIME).....	18
4.4.1 LIMIT.....	18
4.4.2 TEST EQUIPMENT.....	18
4.4.3 TEST SET-UP.....	18
4.4.4 TEST PROCEDURE.....	18
4.4.5 EUT OPERATING CONDITION.....	18
4.4.6 TEST RESULT.....	19
4.5 CONDUCTED EMISSION.....	23
4.5.1 LIMIT.....	23
4.5.2 TEST EQUIPMENT.....	23
4.5.3 TEST SETUP.....	24



# TEST REPORT

4.5.4 TEST PROCEDURE .....	24
4.5.5 EUT OPERATING CONDITION .....	24
4.5.6 TEST RESULT .....	25
4.6 RADIATED EMISSION TEST .....	26
4.6.1 LIMIT .....	26
4.6.2 TEST EQUIPMENT .....	27
4.6.3 TEST SET-UP .....	28
4.6.4 TEST PROCEDURE .....	29
4.6.5 EUT OPERATING CONDITION .....	29
4.6.6 RADIATED EMISSION TEST RESULT .....	30
4.7 PEAK POWER TEST .....	37
4.7.1 LIMIT .....	37
4.7.2 TEST EQUIPMENT .....	37
4.7.3 TEST SET-UP .....	38
4.7.4 TEST PROCEDURE .....	38
4.7.5 EUT OPERATING CONDITION .....	38
4.7.6 TEST RESULT .....	38
4.8 BAND EDGE TEST .....	42
4.8.1 LIMIT .....	42
4.8.2 TEST EQUIPMENT .....	42
4.8.3 TEST SET-UP .....	43
4.8.4 TEST PROCEDURE .....	44
4.8.5 EUT OPERATING CONDITION .....	44
4.8.6 TEST RESULT .....	44
5 ANTENNA APPLICATION .....	47
5.1 ANTENNA REQUIREMENT .....	47
5.2 RESULT .....	47
6. PHOTOS OF TESTING .....	48
7. TERMS OF ABBREVIATION .....	51



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:4 of 51  
Date: Apr. 20, 2007

## 1. DOCUMENT POLICY AND TEST STATEMENT

### 1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.

### 1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

### 1.3 EUT MODIFICATION

- No modification in SRT Lab.



## 2. DESCRIPTION OF EUT AND TEST MODE

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Bluetooth Data Suite
<b>MODEL NO.</b>	MA-730
<b>POWER SUPPLY</b>	DC 5.0 V, 50mA
<b>FREQUENCY BAND</b>	2.402GHz ~2.480GHz
<b>CARRIER FREQUENCY</b>	FHSS
<b>NUMBER OF CHANNEL</b>	79
<b>CHANNEL SPACING</b>	1 MHz
<b>RATED RF OUTPUT POWER</b>	+4 dBm
<b>MODULATION TYPE</b>	GFSK (1Mbps), $\pi/4$ -DQPSK (2Mbps), 8-DPSK (3Mbps)
<b>MODE OF OPERATION</b>	duplex
<b>BIT RATE OF TRANSMISSION</b>	Bluetooth V2.0 ( 1 Mbps) DQPSK ( 2 Mbps) 8DPSK ( 3 Mbps)
<b>ANTENNA TYPE</b>	PCB PATCH
<b>ANTENNA GAIN</b>	-8.7 dBi
<b>OPERATING TEMPERATURE</b>	0~45°C
<b>CHANNEL BANDWIDTH</b>	1MHz

#### NOTE :

For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.

### 2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested with a PC system and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

No	Device	Brand	Model #	FCC ID/DoC	Cable
1	NOTEBOOK	DELL	PP01L	DOC	2.0m unshielded power cord
2	PRINTER	HP	HP3325	DOC	1.5m unshielded power cord 1.5m shielded data cord
3	BLUETOOTH DONGLE	MSI	MS-6970A	N/A	N/A

**NOTE :** For the actual test configuration, please refer to the photos of testing.



## 2.3 DESCRIPTION OF TEST MODE

79 channels are provided by EUT. Three channels of lower, medium and higher were chosen for test.

Channel	Frequency (MHz)
0	2402
39	2448
78	2480

### NOTE :

1. Below 1 GHz, the channel 0, 39 and 78 were pre-tested in chamber. The channel 78, worst case one, was chosen for radiated emission test.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually.

## 3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C

ANSI C63.4: 2003

Public Notice DA 00-705 (March 2000)

All tests have been performed and recorded as the above standards.

 <b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A07033002 Report No.: FCCA07033002 FCCID: Q7Z-MA730G1 Page:7 of 51 Date: Apr. 20, 2007
---	----------------------	---

## 4. TECHNICAL CHARACTERISTICS TEST

### 4.1 CHANNEL SEPARATION TEST

#### 4.1.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Frequency Range (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz


#### 4.1.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.1.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

#### 4.1.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:8 of 51  
Date: Apr. 20, 2007

## 4.1.5 EUT OPERATING CONDITION

1. Set the EUT under transmission condition continuously at a specific channel frequency.
2. The EUT was set to the highest available power level.

## 4.1.6 TEST RESULT

Temperature: 25°C Humidity: 65%RH  
Spectrum Detector: PK Tested by: John Yu  
Test Result: PASS Tested Date: Apr. 16, 2007

Channel Number	Channel Frequency (MHz)	Separation Read Value (kHz)	Minimum Limit(20dB Bandwidth) (kHz)
0	2402	1004.000	25
39	2441	1000.000	25
78	2480	1000.000	25










CH78:



Date: 16.APR.2007 19:27:26

 <b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A07033002 Report No.: FCCA07033002 FCCID: Q7Z-MA730G1 Page:12 of 51 Date: Apr. 20, 2007
---	----------------------	--

## 4.2 20dB Bandwidth

### 4.2.2 LIMIT

Frequency Range (MHz)	Quantity of Hopping Channel	Limit(kHz)			
		50	25	15	75
902-928		<250	>250	NA	NA
2400-2483.5		NA	NA	>1000	<1000


### 4.2.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/Facilities	Specifications	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.2.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

### 4.2.4 TEST PROCEDURE

The EUT was operated in hopping mode or any specific channel.  
 Printed out the test result from the spectrum by hard copy function.



**Spectrum Research & Testing Lab., Inc.**  
 No. 101-10, Ling 8,  
 Shan-Tong Li, Chung-Li  
 City, Taoyuan, Taiwan

# TEST REPORT


Reference No.: A07033002  
 Report No.: FCCA07033002  
 FCCID: Q7Z-MA730G1  
 Page:13 of 51  
 Date: Apr. 20, 2007

## 4.2.5 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>60%RH</u>
Spectrum Detector:	<u>PK</u>	Tested by:	<u>John Yu</u>
Test Result:	<u>PASS</u>	Tested Date:	<u>Apr.16, 2007</u>

Channel Number	Channel Frequency (MHz)	20dB Down Bandwidth (kHz)
0	2402	880
39	2441	884
78	2480	880

CH0:



Date: 16.APR.2007 19:40:16




**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:14 of 51  
Date: Apr. 20, 2007


CH39:



Date: 16.APR.2007 19:39:03



CH78:



Date: 16.APR.2007 19:37:57



### 4.3 QUANTITY OF HOPPING CHANNEL TEST

#### 4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (Quantity of Hopping Channel)			
	20dB Bandwidth <250kHz	20dB Bandwidth >250kHz	20dB Bandwidth <1MHz	20dB Bandwidth >1MHz
902-928	50	25	N/A	N/A
2400-2483.5	N/A	N/A	75	15
5725-5850	N/A	N/A	75	N/A


#### 4.3.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/Facilities	Specifications	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

#### 4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

#### 4.3.5 EUT OPERATING CONDITION

1. Set the EUT under frequency hopping transmission condition.
2. The EUT was set to the highest available power level.





**Spectrum Research & Testing Lab., Inc.**  
 No. 101-10, Ling 8,  
 Shan-Tong Li, Chung-Li  
 City, Taoyuan, Taiwan

# TEST REPORT


Reference No.: A07033002  
 Report No.: FCCA07033002  
 FCCID: Q7Z-MA730G1  
 Page:17 of 51  
 Date: Apr. 20, 2007

## 4.3.6 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>65%RH</u>
Spectrum Detector:	<u>PK</u>	Tested by:	<u>John Yu</u>
Test Result:	<u>PASS</u>	Tested Date:	<u>Apr.16,2007</u>

Hopping Channel Frequency Range(MHz)	Quantity of Hopping Channel Read Value	Quantity of Hopping Channel Limit
2402~2480	79	75

CH0-CH78



Date: 16.APR.2007 19:51:53

 <b>Spectrum Research &amp; Testing Lab., Inc.</b> No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A07033002 Report No.: FCCA07033002 FCCID: Q7Z-MA730G1 Page:18 of 51 Date: Apr. 20, 2007
---	----------------------	--

#### 4.4 TIME OF OCCUPANCY (Dwell Time)

##### 4.4.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (ms)		
	20dB Bandwidth <250kHz(50Channel)	20dB Bandwidth >250kHz(25Channel)	20dB Bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

**NOTE:** The “()” is all channel's average time of occupancy.


##### 4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/Facilities	Specifications	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

##### 4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

##### 4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

##### 4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan


# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:19 of 51  
Date: Apr. 20, 2007



## 4.4.6 TEST RESULT

Temperature: 25°C Humidity: 65%RH  
Spectrum Detector: PK Tested by: John Yu  
Test Result: PASS Tested Date: Apr.16,2007

Channel Number	Channel Frequency (MHz)	Pulse Time ( $\mu$ s)	Period Time (s)	Time of Occupancy (Dwell Time) (ms)	Average Time of Occupancy Limit (ms)
0	2402.00	400	31.6	126.400	400
39	2441.00	400	31.6	126.400	400
78	2480.00	398	31.6	125.768	400





Date: 16.APR.2007 20:43:04



Date: 16.APR.2007 19:18:31




Ch39:



Date: 16.APR.2007 19:16:58



CH78:



Date: 16.APR.2007 19:11:53



## 4.5 CONDUCTED EMISSION

### 4.5.1 LIMIT

FREQUENCY (MHz)	Class A (dB $\mu$ V)		Class B (dB $\mu$ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.5 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 4.5.2 TEST EQUIPMENT


The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 KHZ TO 30 MHZ	ROHDE & SCHWARZ	ESHS30/ 826003/008	OCT. 2007 ETC
LISN (for EUT)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01017	OCT. 2007 ETC
LISN (for Peripheral)	50 $\mu$ H, 50 ohm	FCC	FCC-LISN-50-25-2/ 01018	NOV. 2007 ETC
50 ohm TERMINATOR	50 ohm	HP	11593A/ 2	OCT. 2007 ETC
COAXIAL CABLE	5m	SUNCITY	CABLE 05/ #5-5M	NOV. 2007 SRT
ISOLATION TRANSFORMER	N/A	APC	AFC-11015/ F102040016	N/A
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 771	N/A
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	N/A
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	N/A

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



### 4.5.3 TEST SETUP



#### NOTE:

1. The EUT was put on a wooden table with 0.8m height above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 951318.
4. The serial no. of the LISN connected to support units is 924839.

### 4.5.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4: 2003 and CISRP22:2006. The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm/50 $\mu$ H as specified. All readings were quasi-peak and average values with 10 kHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. Both lines of the power mains of EUT were measured and the cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

### 4.5.5 EUT OPERATING CONDITION

Set the EUT under transmission condition continuously at a specific channel frequency.

Under Windows XP ran "EMI TEST" program, PC sent "H" pattern or accessed the following peripherals:

- Printer
- FDD
- HDD





## 4.5.6 TEST RESULT

Temperature:	24°C	Humidity:	70%RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Link
Receiver Detector:	Q.P. and AV.	Tested By:	John Yu
		Tested Date:	Apr. 19, 2007

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.156	0.30	49.30	27.38	49.60	27.68	65.83	55.83	-16.23	-28.15
0.174	0.30	53.02	43.95	53.32	44.25	65.31	55.31	-11.99	-11.06
0.524	0.24	36.66	34.08	36.90	34.32	56.00	46.00	-19.10	-11.68
1.507	0.15	33.34	28.32	33.49	28.47	56.00	46.00	-22.51	-17.53
3.645	0.19	36.54	26.42	36.73	26.61	56.00	46.00	-19.27	-19.39
21.017	0.39	15.72	8.47	16.11	8.86	60.00	50.00	-43.89	-41.14

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB $\mu$ V)		Emission Level (dB $\mu$ V)		Limit (dB $\mu$ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.156	0.30	48.34	27.85	48.64	28.15	65.83	55.83	-17.19	-27.68
0.174	0.30	53.44	44.95	53.74	45.25	65.31	55.31	-11.57	-10.06
0.519	0.24	38.66	35.22	38.90	35.46	56.00	46.00	-17.10	-10.54
1.220	0.14	32.42	21.76	32.56	21.90	56.00	46.00	-23.44	-24.10
1.329	0.15	30.48	29.32	30.63	29.47	56.00	46.00	-25.37	-16.53
18.270	0.28	19.12	10.09	19.40	10.37	60.00	50.00	-40.60	-39.63

### NOTE :

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies were very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.



## 4.6 RADIATED EMISSION TEST

### 4.6.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission measurement for frequency below 1000 MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

FREQUENCY (MHz)	DISTANCE(m)	FIELD STRENGTH (dB $\mu$ V/m)
30 – 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

**NOTE:**

1. In the emission tables above, the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument, antenna, and the closest point of any part of the device or system.

FCC Part 15, Subpart 15.35(b) limit of radiated emission for frequency above 1000MHz

FREQUENCY (MHz)	Class A (dB $\mu$ V/m) (at 3m)		Class B (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
Above 1000	80.0	60.0	74.0	54.0

FCC Part 15, Subpart C Section 15.249. The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

FUNDAMENTAL FREQUENCY (MHz)	FILED STRENGTH OF FUNDAMENTAL (dB $\mu$ V/m) (at 3m)		FIELD STRENGTH OF HARMONICS (dB $\mu$ V/m) (at 3m)	
	PK.	AV.	PK.	AV.
902-928	114	94	74.0	54.0
2400-2483.5	114	94	74.0	54.0
5725-5875	114	94	74.0	54.0
24000-24250	128	108	88	68



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:27 of 51  
Date: Apr. 20, 2007

### 4.6.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test:


EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9kHz TO 2.75 GHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	OCT. 2007 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3143/ 9509-1152	JUN. 2007 SRT
PRE-AMPLIFIER	1 GHz TO 26.5 GHz	HP	8449B/ 3008A01019	AUG. 2007 ETC
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	DEC. 2007 SRT
COAXIAL CABLE	25M	SUNCITY	J400-25M-2NP/ #153-25M	JUN. 2007 SRT
FILTER	2 LINE, 30A	FIL.COIL	FC-943/ 869	N/A
FREQUENCY CONVERTER	N/A	APC	AFC-2KBB/ F100030031	AUG. 2007 SRT

#### NOTE:

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.



## 4.6.3 TEST SET-UP



**NOTE :**

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## **TEST REPORT**

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:29 of 51  
Date: Apr. 20, 2007

### **4.6.4 TEST PROCEDURE**

The EUT was tested according to the requirement of ANSI C63.4:2003 and CISPR 22:2006. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz, all readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak or average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

First, Find the margin or higher points at least 6 points by software, then use manual to find the maximum data. The procedure is referred on the test procedure of SRT LAB.

### **4.6.5 EUT OPERATING CONDITION**

Same as section 4.1.5 of this report.



## 4.6.6 RADIATED EMISSION TEST RESULT

Temperature:	25°C	Humidity:	57%RH
Frequency Range:	30M – 1GHz	Measured Distance:	3m
Receiver Detector:	Q.P. or AV.	Tested Mode:	CH0-TX
Tested By:	John Yu	Tested Date:	Apr. 17, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
178.1920	2.33	9.80	16.5	28.6	43.5	-14.9	310	1.55
240.2775	2.72	11.00	22.9	36.6	46.0	-9.4	100	1.03
335.6675	3.20	14.80	12.4	30.4	46.0	-15.6	190	1.06
365.6770	3.37	15.30	19.1	37.8	46.0	-8.2	10	1.26
430.2775	3.76	16.80	9.8	30.4	46.0	-15.6	40	1.01
527.9800	4.26	18.81	9.3	32.4	46.0	-13.6	30	1.01

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
224.4375	2.64	10.66	21.3	34.6	46.0	-11.4	80	1.3
433.1525	3.78	16.95	15.7	36.4	46.0	-9.6	110	1.2
366.5200	3.38	15.30	18.3	37.0	46.0	-9.0	10	1.02
527.9725	4.26	18.81	7.5	30.6	46.0	-15.4	165	1.08
645.2475	4.74	19.95	7.3	32.0	46.0	-14.0	115	1.01
763.1075	5.23	23.17	5.5	33.9	46.0	-12.1	135	1.03

### NOTE :

1. Measurement uncertainty is +/-2dB.
2. "\*\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



# TEST REPORT

Temperature:	27°C	Humidity:	59%RH
Frequency Range:	30M – 1GHz	Measured Distance:	3m
Receiver Detector:	Q.P. or AV.	Tested Mode:	CH39-TX
Tested By:	John Yu	Tested Date:	Apr. 17, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
225.9400	2.64	10.70	15.8	29.1	46.0	-16.9	70	1.06
299.6750	3.02	13.70	12.3	29.0	46.0	-17.0	25	1.03
365.9850	3.37	15.30	8.2	26.9	46.0	-19.1	140	1.12
499.3750	4.12	18.00	8.5	30.6	46.0	-15.4	80	1.24
576.2250	4.49	19.30	6.2	30.0	46.0	-16.0	170	1.16
615.2550	4.65	19.50	6.7	30.8	46.0	-15.2	56	1.72

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
228.3350	2.65	10.82	10.3	23.8	46.0	-22.2	250	1.3
287.1370	2.96	12.71	7.8	23.5	46.0	-22.5	35	1.16
432.2625	3.77	16.90	13.3	34.0	46.0	-12.0	220	1.07
563.9300	4.43	19.37	6.9	30.7	46.0	-15.3	325	1.02
649.6950	4.76	19.99	6.2	30.9	46.0	-15.1	115	1.25
527.9800	4.26	18.81	7.3	30.4	46.0	-15.6	95	1.03

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



Temperature: 27°C Humidity: 59%RH  
Frequency Range: 30M – 1GHz Measured Distance: 3m  
Receiver Detector: Q.P. or AV. Tested Mode: CH78-TX  
Tested By: John Yu Tested Date: Apr. 17, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
226.6300	2.64	10.74	12.3	25.7	46.0	-20.3	57	1.01
297.1254	3.01	13.50	10.8	27.3	46.0	-18.7	78	1.22
332.5698	3.18	14.74	11.2	29.1	46.0	-16.9	78	1.11
358.2589	3.32	15.28	7.9	26.5	46.0	-19.5	65	1.22
488.2365	4.06	17.98	5.9	27.9	46.0	-18.1	156	1.45
612.8560	4.64	19.44	6.0	30.1	46.0	-15.9	325	1.21

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
245.6984	2.76	11.50	11.2	25.5	46.0	-20.5	63	1.24
254.6325	2.81	12.08	8.7	23.6	46.0	-22.4	112	1.24
365.8965	3.37	15.30	11.2	29.9	46.0	-16.1	152	1.11
430.7375	3.76	16.80	6.0	26.6	46.0	-19.4	185	1.4
609.1452	4.63	19.38	6.1	30.1	46.0	-15.9	147	1.24
647.4675	4.75	19.97	5.0	29.7	46.0	-16.3	159	1.31

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.





Temperature: 27°C Humidity: 59%RH  
Frequency Range: 30M – 1GHz Measured Distance: 3m  
Receiver Detector: Q.P. or AV. Tested Mode: RX  
Tested By: John Yu Tested Date: Apr. 17, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
178.2525	2.33	9.80	15.6	27.7	43.5	-15.8	321	1.03
239.9900	2.71	10.99	13.4	27.1	46.0	-18.9	65	1.11
335.9825	3.20	14.80	8.9	26.9	46.0	-19.1	157	1.15
365.3654	3.37	15.30	7.1	25.8	46.0	-20.2	264	1.21
501.2354	4.13	18.03	5.4	27.6	46.0	-18.4	214	1.12
530.2114	4.27	18.90	5.5	28.7	46.0	-17.3	314	1.14

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
190.2546	2.45	10.70	13.9	27.1	43.5	-16.5	68	1.31
254.6325	2.81	12.08	8.7	23.6	46.0	-22.4	112	1.24
365.8965	3.37	15.30	11.2	29.9	46.0	-16.1	123	1.13
425.3654	3.74	16.60	7.2	27.5	46.0	-18.5	258	1.36
640.3589	4.73	19.90	5.9	30.5	46.0	-15.5	159	1.31
633.5698	4.71	19.76	4.2	28.7	46.0	-17.3	189	1.21

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:34 of 51  
Date: Apr. 20, 2007

Temperature:	<u>27°C</u>	Humidity:	<u>59%RH</u>
Frequency Range:	<u>1 – 12.5GHz</u>	Measured Distance:	<u>3m</u>
Receiver Detector:	<u>PK. or AV.</u>	Tested Mode:	<u>CH0-Link</u>
Tested By:	<u>John Yu</u>	Tested Date:	<u>Apr. 17, 2007</u>

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402.00	-32.16	28.54	92.9	62.3	89.3	58.7	N/A	N/A	N/A	N/A	54.0	1.1
2398.21	-32.17	28.00	51.5	31.7	47.3	27.5	74.0	54.0	-26.7	-26.5	165.0	1.1
2406.10	-32.17	28.01	54.8	33.4	50.6	29.2	74.0	54.0	-23.4	-24.8	273.0	1.3
4804.00	-30.47	33.64	56.4	45.7	59.6	48.9	74.0	54.0	-14.4	-5.1	132.0	1.2
7206.00	-28.90	36.26	43.6	*	51.0	*	74.0	54.0	-23.0	*	204.0	1.02
9608.00	-28.55	37.84	39.5	*	48.8	*	74.0	54.0	-25.2	*	302.0	1.2

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2402.00	-32.16	28.00	93.4	61.7	89.2	57.5	N/A	N/A	N/A	N/A	91.0	1.2
2398.20	-32.17	28.00	54.8	32.4	50.6	28.2	74.0	54.0	-23.4	-25.8	38.0	1.3
2406.18	-32.17	28.01	59.4	34.1	55.2	29.9	74.0	54.0	-18.8	-24.1	32.0	1.6
2426.30	-32.20	28.05	49.5	*	45.4	*	74.0	54.0	-28.6	*	188.0	1.4
4804.00	-30.47	33.64	54.7	34.1	57.9	37.3	74.0	54.0	-16.1	-16.7	127.0	1.2
7206.00	-28.90	36.26	46.4	*	53.8	*	74.0	54.0	-20.2	*	325.0	1

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



# TEST REPORT

Temperature:	27°C	Humidity:	59%RH
Frequency Range:	1 – 12.5GHz	Measured Distance:	3m
Receiver Detector:	PK. Or AV.	Tested Mode:	CH39-Link
Tested By:	John Yu	Tested Date:	Apr. 17, 2007

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441.00	-32.23	28.62	90.7	61.5	87.1	57.9	N/A	N/A	N/A	N/A	54.0	1
2437.30	-32.22	28.07	49.7	*	45.6	*	74.0	54.0	-28.4	*	302.0	1.2
2445.26	-32.23	28.09	52.7	39.0	48.6	34.9	74.0	54.0	-25.4	-19.1	165.0	1.1
2465.31	-32.22	28.13	45.1	*	41.0	*	74.0	54.0	-33.0	*	155.0	1.2
4882.00	-30.26	33.71	53.8	41.6	57.2	45.0	74.0	54.0	-16.8	-9.0	132.0	1.2
7323.00	-29.04	36.36	44.7	*	52.0	*	74.0	54.0	-22.0	*	310.0	1.1

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2441.00	-32.23	28.08	95.8	63.4	91.7	59.3	N/A	N/A	N/A	N/A	91.0	1.1
2437.24	-32.22	28.07	51.6	37.4	47.5	33.3	74.0	54.0	-26.5	-20.7	100.0	1.2
2445.24	-32.23	28.09	58.9	42.7	54.8	38.6	74.0	54.0	-19.2	-15.4	267.0	1.2
2465.25	-32.22	28.13	49.3	*	45.2	*	74.0	54.0	-28.8	*	188.0	1.2
4882.00	-30.26	33.71	57.4	43.2	60.8	46.6	74.0	54.0	-13.2	-7.4	300.0	1.1
7323.00	-29.04	36.36	43.2	*	50.5	*	74.0	54.0	-23.5	*	45.0	1.3

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:36 of 51  
Date: Apr. 20, 2007

Temperature:	<u>27°C</u>	Humidity:	<u>59%RH</u>
Frequency Range:	<u>1 – 12.5GHz</u>	Measured Distance:	<u>3m</u>
Receiver Detector:	<u>PK. Or AV.</u>	Tested Mode:	<u>CH78-Link</u>
Tested By:	<u>John Yu</u>	Tested Date:	<u>Apr. 17, 2007</u>

Antenna Polarization: Horizontal

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00	-32.19	28.73	91.7	60.4	88.2	56.9	N/A	N/A	N/A	N/A	34.0	1.2
2476.30	-32.20	28.15	51.3	33.7	47.3	29.7	74.0	54.0	-26.7	-24.3	302.0	1.1
2484.10	-32.19	28.17	56.8	34.2	52.8	30.2	74.0	54.0	-21.2	-23.8	48.0	1.1
2504.30	-32.13	28.22	47.6	*	43.7	*	74.0	54.0	-30.3	*	273.0	1.1
4960.00	-30.26	33.77	49.2	*	52.7	*	74.0	54.0	-21.3	*	132.0	1.2
7440.00	-28.95	36.45	41.4	*	48.9	*	74.0	54.0	-25.1	*	124.0	1.1

Antenna Polarization: Vertical

Frequency (MHz)	Corret Factor (dB)	Antenna Factor (dB/m)	Reading (dBμV)		Emission (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ(°)	EL(m)
			PK	AV	PK	AV	PK	AV	PK	AV		
2480.00	-32.19	28.16	99.8	62.7	95.8	58.7	N/A	N/A	N/A	N/A	91.0	1.2
2476.06	-32.20	28.15	58.6	34.2	54.6	30.2	74.0	54.0	-19.4	-23.8	38.0	1.1
2484.10	-32.19	28.17	59.4	32.9	55.4	28.9	74.0	54.0	-18.6	-25.1	267.0	1.3
2504.25	-32.13	28.22	49.7	*	45.8	*	74.0	54.0	-28.2	*	140.0	1.3
4960.00	-30.26	33.77	54.6	32.9	58.1	36.4	74.0	54.0	-15.9	-17.6	127.0	1.1
7440.00	-28.95	36.45	44.2	*	51.7	*	74.0	54.0	-22.3	*	280.0	1.4

**NOTE :**

1. Measurement uncertainty is +/-2dB.
2. "\*": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research & Testing Lab., Inc.**  
 No. 101-10, Ling 8,  
 Shan-Tong Li, Chung-Li  
 City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
 Report No.: FCCA07033002  
 FCCID: Q7Z-MA730G1  
 Page:37 of 51  
 Date: Apr. 20, 2007

## 4.7 PEAK POWER TEST

### 4.7.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit(w)				
	Quantity of Hopping Channel	50	25	15	75
902-928		1(30dBm)	0.125(21dBm)	NA	NA
2400-2483.5		NA	NA	0.125(21dBm)	1(30dBm)
5725-5850		NA	NA	NA	1(30dBm)

### 4.7.2 TEST EQUIPMENT


The following test equipment was used during the test :

Equipment/Facilities	Specifications	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	MAR. 2008 ETC
POWER METER	N/A	BOONTON	4232A/ 29001	MAY 2007 ETC
POWER SENSOR	DC-18GHz 0.3 $\mu$ W-100mW 50 $\Omega$	BOONTON	51011-EMC/ 31184	JUN. 2007 ETC

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



### 4.7.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

### 4.7.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.  
 Printed out the test result from the spectrum by hard copy function.  
 Recorded the read value of the power meter.

### 4.7.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

### 4.7.6 TEST RESULT

Temperature:	<u>25°C</u>	Humidity:	<u>65%RH</u>
Spectrum Detector:	<u>PK</u>	Tested by:	<u>John Yu</u>
Test Result:	<u>PASS</u>	Tested Date:	<u>Apr.16,2007</u>

Channel Number	Channel Frequency (MHz)	Peak Output Power (dBm)	Peak Power Limit (dBm)
0	2402.0000	-2.34	30
39	2441.0000	-2.80	30
78	2480.0000	-3.07	30











## 4.8 BAND EDGE TEST

### 4.8.1 LIMIT

FCC Part15, Subpart C Section 15.249 (c), Emission radiated outside of the specified frequency bands, except for harmonics, shall attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Operating Frequency Range (MHz)	Limit (dB $\mu$ V/m)	
	Peak	Average
902-928	74	54
2400-2483.5		
5725-5850		

### 4.8.2 TEST EQUIPMENT

The following test equipment was used during the test :


Equipment/Facilities	Specification	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-7GHz	ROHDE & SCHWARZ	FSP7/ 839511/010	APR. 2008 R&S
EMI TEST RECEIVER	9 kHz TO 2750 MHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	OCT. 2007 ETC
SPECTRUM	9KHz-26.5GHz	HP	8953E/ 3710A03220	MAY 2007 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	NOV. 2007 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	FEB. 2008 SRT
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC. 2007 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	APR. 2008 SRT

**NOTE:** The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.




## 4.8.3 TEST SET-UP

### FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a  $50\Omega$  RF cable.

### FOR RADIATED EMISSION TEST



**NOTE :**

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



#### 4.8.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel.  
Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 10 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

#### 4.8.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

#### 4.8.6 TEST RESULT

Temperature:	<u>26°C</u>	Humidity:	<u>61%RH</u>
Spectrum Detector:	<u>PK &amp; AV</u>	Tested by:	<u>John Yu</u>
Test Result:	<u>PASS</u>	Tested Date:	<u>Apr. 16, 2007</u>




**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:45 of 51  
Date: Apr. 20, 2007


CH0:



Date: 16.APR.2007 20:02:12



CH78:



Date: 16.APR.2007 20:03:48



**Spectrum Research &  
Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## **TEST REPORT**

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:47 of 51  
Date: Apr. 20, 2007

### **5 ANTENNA APPLICATION**

#### **5.1 Antenna requirement**

The EUT's antenna is met the requirement of FCC part15C section15.203 and 15.204.

#### **5.2 Result**

The EUT's antenna used a chip antenna and integrated on PCB. The antenna's gain is -3 dBi and meets the requirement.



## 6. PHOTOS OF TESTING

- Radiated Emission test(1G)







- Radiated Emission test(2G)






**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

# TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:50 of 51  
Date: Apr. 20, 2007

- Conducted Emission test





**Spectrum Research & Testing Lab., Inc.**  
No. 101-10, Ling 8,  
Shan-Tong Li, Chung-Li  
City, Taoyuan, Taiwan

## TEST REPORT

Reference No.: A07033002  
Report No.: FCCA07033002  
FCCID: Q7Z-MA730G1  
Page:51 of 51  
Date: Apr. 20, 2007

### 7. TERMS OF ABBREVIATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction