




# FCC RADIO TEST REPORT

**FCC ID** : Q87-03433  
**Equipment** : LINKSYS MR9000 TRI-BAND WIFI 5 ROUTER,  
LINKSYS MR9000X TRI-BAND WIFI 5 ROUTER,  
LINKSYS MR8900 TRI-BAND WIFI 5 ROUTER,  
LINKSYS MR8950 TRI-BAND WIFI 5 ROUTER  
**Brand Name** : LINKSYS  
**Model Name** : MR9000, MR9000X, MR8900, MR8950  
**Applicant** : Linksys LLC  
121 Theory Drive, Irvine CA 92617, United States  
**Standard** : 47 CFR FCC Part 15.247

The product was received on Apr. 02, 2019, and testing was started from Apr. 02, 2019 and completed on Jun. 03, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1 General Description .....</b>	<b>5</b>
1.1 Information.....	5
1.2 Applicable Standards .....	8
1.3 Testing Location Information .....	8
1.4 Measurement Uncertainty .....	8
<b>2 Test Configuration of EUT .....</b>	<b>9</b>
2.1 Test Channel Mode .....	9
2.2 The Worst Case Measurement Configuration.....	10
2.3 EUT Operation during Test .....	11
2.4 Accessories .....	11
2.5 Support Equipment.....	12
2.6 Test Setup Diagram .....	13
<b>3 Transmitter Test Result .....</b>	<b>15</b>
3.1 AC Power-line Conducted Emissions .....	15
3.2 DTS Bandwidth .....	17
3.3 Maximum Conducted Output Power .....	18
3.4 Power Spectral Density .....	21
3.5 Emissions in Non-restricted Frequency Bands .....	23
3.6 Emissions in Restricted Frequency Bands.....	24
<b>4 Test Equipment and Calibration Data .....</b>	<b>28</b>
<b>Appendix A. Test Results of AC Power-line Conducted Emissions</b>	
<b>Appendix B. Test Results of DTS Bandwidth</b>	
<b>Appendix C. Test Results of Maximum Conducted Output Power</b>	
<b>Appendix D. Test Results of Power Spectral Density</b>	
<b>Appendix E. Test Results of Emissions in Non-restricted Frequency Bands</b>	
<b>Appendix F. Test Results of Emissions in Restricted Frequency Bands</b>	
<b>Appendix G. Test Photos</b>	
<b>Photographs of EUT v01</b>	



## History of this test report

TEL : 886-3-656-9065  
FAX : 886-3-656-9085  
Report Template No.: CB Ver1.0

Page Number : 3 of 29  
Issued Date : Jul. 19, 2019  
Report Version : 01



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Sam Chen**

**Report Producer: Viola Huang**



# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

**Note:**

- ♦ Bluetooth LE uses a GFSK modulation.
- ♦ BWch is the nominal channel bandwidth.
- ♦ Nss-Min is the minimum number of spatial streams.
- ♦ Nant is the number of outputs. e.g., 2(2, 3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

**1.1.2 Antenna Information**

Ant.	Port	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	1	FIT	ANEP5M3-CCG01-EH	Dipole Antenna	I-PEX	Note 1
2	2	FIT	ANEP5M3-CCG00-EH	Dipole Antenna	I-PEX	
3	3	FIT	ANEP5M1-CCG00-EH	Dipole Antenna	I-PEX	
4	4	FIT	ANEP5M1-CCG01-EH	Dipole Antenna	I-PEX	
5	1	FIT	ANTS1M1-CCG00-EH	PIFA Antenna	N/A	

Note 1:

Ant.	Port	Gain (dBi)			
		WLAN 2.4G	WLAN 5G Band 1	WLAN 5G Band 4	BT
1	1	2.84	2.60	2.44	-
2	2	2.36	2.87	2.28	-
3	3	-	-	2.93	-
4	4	-	-	3.01	-
5	1	-	-	-	2.90

Note 2: The above information was declared by manufacturer.

Note 3: The EUT has five antennas.

**<For 2.4GHz Band>****For IEEE 802.11b/g/n/VHT mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

**<For 5GHz Band 1>****For IEEE 802.11a/n/ac mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

**<For 5GHz Band 4>****For IEEE 802.11a/n/ac mode (4TX/4RX)**

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

**<For Bluetooth>****For BT function (1TX/1RX)**

Only Port 1 can be used as transmitting/receiving antenna.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)
BT-LE(1Mbps)	0.621	2.07

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

**1.1.4 EUT Operational Condition**

<b>EUT Power Type</b>	From Power Adapter		
<b>Function</b>	<input checked="" type="checkbox"/> Point-to-multipoint	<input type="checkbox"/> Point-to-point	
<b>Test Software Version</b>	QRCT Version3.0.187.0		
<b>Support Mode</b>	<input checked="" type="checkbox"/> LE 1M PHY: 1 Mb/s		
	<input type="checkbox"/> LE Coded PHY (S=2): 500 Kb/s		
	<input type="checkbox"/> LE Coded PHY (S=8): 125 Kb/s		
	<input type="checkbox"/> LE 2M PHY: 2 Mb/s		

Note: The above information was declared by manufacturer.

**1.1.5 Table for EUT supports function**

Function	Supports type
AP Router	Master

**1.1.6 Table for Multiple Listing**

The four equipment names and four model names in the following table are all refer to the identical product.

Equipment Name	Model Name	Description
LINKSYS MR9000 TRI-BAND WIFI 5 ROUTER	MR9000	Marketing purpose to sell in different retailers.
LINKSYS MR9000X TRI-BAND WIFI 5 ROUTER	MR9000X	
LINKSYS MR8900 TRI-BAND WIFI 5 ROUTER	MR8900	
LINKSYS MR8950 TRI-BAND WIFI 5 ROUTER	MR8950	

From the above models, model: MR9000 was selected as representative model for the test and its data was recorded in this report.



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 558074 D01 v05r02

## 1.3 Testing Location Information

Testing Location				
<input type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	TEL : 886-3-327-3456	FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.	TEL : 886-3-656-9065	FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-CB	Brian Sun	22~24°C / 50~60%	Apr. 18, 2019~May 15, 2019
Radiated	03CH01-CB for below 1GHz 03CH03-CB for above 1GHz	Brian Sun	22~24°C / 50~60%	Apr. 02, 2019~Jun. 03, 2019
AC Conduction	CO01-CB	Wei Li	23~23.6°C / 55~58%	Apr. 11, 2019

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086B with Industry Canada.

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.1 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%
Output Power Measurement	1.33 dB	Confidence levels of 95%
Power Density Measurement	1.27 dB	Confidence levels of 95%
Bandwidth Measurement	9.74 x10 <sup>-8</sup>	Confidence levels of 95%





## **2 Test Configuration of EUT**

### **2.1 Test Channel Mode**

<b>Mode</b>	<b>PowerSetting</b>
BT-LE(1Mbps)	-
2402MHz	Default
2440MHz	Default
2480MHz	Default

## 2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral
<b>Operating Mode</b>	Normal Link
1	EUT + Adapter 2 with US plug
2	EUT + Adapter 1
3	EUT + Adapter 3
Mode 2 generated the worst test result, so it was recorded in this report.	

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
<b>Test Condition</b>	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	Emissions in Restricted Frequency Bands
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
<b>Operating Mode &lt; 1GHz</b>	CTX
	The EUT was performed at Y axis and Z axis position for Emissions in Restricted above 1GHz test, and the worst case was found at Z axis. So the measurement will follow this same test configuration.
1	EUT_2.4GHz in Z axis + Adapter 1
2	EUT_2.4GHz in Z axis + Adapter 2 with US plug
3	EUT_2.4GHz in Z axis + Adapter 3
Mode 2 has been evaluated to be the worst case among Mode 1~3, thus measurement for Mode 4~6 will follow this same test mode.	
4	EUT_5GHz in Z axis + Adapter 2 with US plug
5	EUT_Bluetooth 2.0 in Z axis + Adapter 2 with US plug
6	EUT_Bluetooth 4.0 in Z axis + Adapter 2 with US plug
Mode 2 generated the worst test result, so it was recorded in this report.	



<b>Operating Mode &gt; 1GHz</b>	CTX
	The EUT was performed at Y axis and Z axis position for Emissions in Restricted test, and the worst case was found at Z axis. So the measurement will follow this same test configuration.
1	EUT in Z axis

<b>The Worst Case Mode for Following Conformance Tests</b>	
<b>Tests Item</b>	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
<b>Operating Mode</b>	
1	WLAN 2.4GHz + WLAN 5GHz B1 + WLAN 5GHz B4 + Bluetooth
Refer to Sporton Test Report No.: FA941701 for Co-location RF Exposure Evaluation.	

## 2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting/receiving mode.

For Normal Link:

During the test, the EUT operation to normal function.

## 2.4 Accessories

<b>Accessories</b>			
<b>Equipment Name</b>	<b>Brand Name</b>	<b>Model Name</b>	<b>Rating</b>
Adapter 1 (Fixed plug)	KTEC	KSA-24W-120200HU	INPUT: 100-240V, 50/60Hz 0.6A OUTPUT: 12V, 2.0A
Adapter 2 (Interchangeable plug)	KTEC	KSA-24W-120200D5	INPUT: 100-240V, 50/60Hz 0.6A OUTPUT: 12V, 2.0A
Adapter 3 (Fixed plug)	APD	WB-24J12FU-ABBC	INPUT: 100-240V, 50-60Hz 0.7A Max. OUTPUT: 12V, 2A
<b>Other</b>			
US plug*1 (only for adapter 2 use)			



## 2.5 Support Equipment


For AC Conduction:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	Flash disk3.0	Transcend	JetFlash-700	N/A
B	LAN NB	DELL	E6430	N/A
C	WAN NB	DELL	E6430	N/A
D	2.4G NB	DELL	E6430	N/A
E	5G-1 & BT NB	Apple	A1278	N/A
F	5G-2 NB	DELL	E6430	N/A

For Radiated and RF Conducted test:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A

## 2.6 Test Setup Diagram



**Test Setup Diagram - Radiated Test**


Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	Power cable	No	1.5m



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

### 3.1.4 Test Setup



### 3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A



## 3.2 DTS Bandwidth

### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
<b>Systems using digital modulation techniques:</b>	
▪	6 dB bandwidth $\geq$ 500 kHz.


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

### 3.2.4 Test Setup



### 3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

### 3.3 Maximum Conducted Output Power

#### 3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	▪ Smart antenna system (SAS):
	- Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	- Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi.	


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

**3.3.3 Test Procedures**

Test Method	
▪ Maximum Peak Conducted Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
▪ Maximum Conducted Output Power	
[duty cycle ≥ 98% or external video / power trigger]	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
▪ For conducted measurement.	
▪ If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
▪ If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

### 3.3.4 Test Setup



### 3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
▪ Power Spectral Density (PSD) $\leq 8$ dBm/3kHz

#### 3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures

Test Method	
▪ Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).	
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.2 Method PKPSD. [duty cycle $\geq 98\%$ or external video / power trigger]
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.3 Method AVGPS-1.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.5 Method AVGPS-2.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.7 Method AVGPS-3.
duty cycle $< 98\%$ and average over on/off periods with duty factor	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.4 Method AVGPS-1A. (alternative).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.6 Method AVGPS-2A. (alternative)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10.8 Method AVGPS-3A. (alternative)
▪ For conducted measurement.	
▪ If The EUT supports multiple transmit chains using options given below:	
<input checked="" type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/>	Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,

- |  |  |
|--|--|
|  | <input type="checkbox"/> Option 3: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$ . Or each transmit chains shall be add $10 \log(N)$ to compared with the limit. |
|--|--|

### 3.4.4 Test Setup



### 3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

### 3.5 Emissions in Non-restricted Frequency Bands

#### 3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> <li>Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.</li> </ul>

#### 3.5.4 Test Setup



#### 3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E



### 3.6 Emissions in Restricted Frequency Bands

#### 3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

#### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.







### 3.6.3 Test Procedures

Test Method	
▪ The average emission levels shall be measured in [duty cycle $\geq 98$ or duty factor].	
▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
▪ For the transmitter unwanted emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$ ).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$ ).
	<input type="checkbox"/> Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$ , where T is pulse time.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
▪ For the transmitter band-edge emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

### 3.6.4 Test Setup





### 3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### 3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

### 3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



## 4 Test Equipment and Calibration Data


Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.45GHz	Jan. 28, 2019	Jan. 29, 2020	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-1 6-2	04083	150kHz ~ 100MHz	Dec. 24, 2018	Dec. 23, 2019	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Jan. 11, 2019	Jan. 10, 2020	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	150kHz ~ 30MHz	May 22, 2018	May 21, 2019	Conduction (CO01-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Aug. 27, 2018	Aug. 26, 2019	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 29, 2019	Mar. 28, 2020	Radiation (03CH01-CB)
Horn Antenna	ETS • Lindgren	3115	6821	750MHz~18GHz	Jan. 24, 2019	Jan. 23, 2020	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 28, 2018	Jun. 27, 2019	Radiation (03CH03-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 02, 2018	May 01, 2019	Radiation (03CH01-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 01, 2019	Apr. 30, 2020	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Dec. 20, 2018	Dec. 19, 2019	Radiation (03CH03-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 04, 2018	Jul. 03, 2019	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Jan. 31, 2019	Jan. 30, 2020	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100142	9kHz~40GHz	Dec. 26, 2018	Dec. 25, 2019	Radiation (03CH03-CB)
EMI Test Receiver	R&S	ESCS	100359	9kHz ~ 2.75GHz	Jul. 03, 2018	Jul. 02, 2019	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-16+17	N/A	30 MHz ~ 1 GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	RG402	High Cable-20+27	1GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-27	1GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#1	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-40G#2	18GHz ~ 40 GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH03-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	Feb. 25, 2019	Feb. 24, 2020	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-28	1 GHz –26.5 GHz	Nov. 19, 2018	Nov. 18, 2019	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 05, 2018	Nov. 04, 2019	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.


N.C.R. means Non-Calibration required.





# AC Power-line Conducted Emissions Result

Appendix A





Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	703.75k	1.028M	1M03F1D	690k	1.026M

**Max-N dB** = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;  
**Min-N dB** = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;




**Result**

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	690k	1.028M
2440MHz	Pass	500k	692.5k	1.026M
2480MHz	Pass	500k	703.75k	1.026M


**Port X-N dB** = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

**BT-LE(1Mbps)**
**2402MHz**
**EBW**

15/05/2019


**BT-LE(1Mbps)**
**2440MHz**
**EBW**


15/05/2019



## BT-LE(1Mbps)

2480MHz

15/05/2019



**Summary**

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	5.54	0.00358

**Result**

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.90	3.48	30.00
2440MHz	Pass	2.90	5.02	30.00
2480MHz	Pass	2.90	5.54	30.00

**DG** = Directional Gain; **Port X** = Port X output power

**Summary**

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-10.26

RBW=3 kHz.

**Result**

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	2.90	-11.93	8.00
2440MHz	Pass	2.90	-10.55	8.00
2480MHz	Pass	2.90	-10.26	8.00

**DG** = Directional Gain; RBW=3 kHz;


**PD** = trace bin-by-bin of each transmits port summing can be performed maximum power density; **Port X** = Port X power density;

### BT-LE(1Mbps)

### PSD

2402MHz

15/05/2019




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-11.93	-11.93	-11.93

### BT-LE(1Mbps)

### PSD

2440MHz

15/05/2019




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-10.55	-10.55	-10.55

### BT-LE(1Mbps)

### PSD

2480MHz

15/05/2019



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-10.26	-10.26	-10.26

**Summary**

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.44004G	5.05	-24.95	621.41M	-62.60	2.3992G	-44.32	2.48491G	-60.69	2.55586G	-50.97	1

**Result**



Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.44004G	5.05	-24.95	621.41M	-62.60	2.3992G	-44.32	2.48491G	-60.69	2.55586G	-50.97	1
2440MHz	Pass	2.44004G	5.05	-24.95	531.72M	-62.73	2.39822G	-62.14	2.48496G	-61.72	2.59526G	-48.17	1
2480MHz	Pass	2.44004G	5.05	-24.95	845.78M	-63.11	2.39958G	-62.46	2.48537G	-55.82	2.584G	-52.70	1

BT-LE(1Mbps)

2402MHz

CSE NdB

15/05/2019





Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44004G	5.05	-24.95	621.41M	-62.60	2.39922G	-44.32	2.48491G	-60.69	2.55586G	-50.97	1

BT-LE(1Mbps)

2440MHz

CSE NdB

15/05/2019



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44004G	5.05	-24.95	531.72M	-62.73	2.39822G	-62.14	2.48496G	-61.72	2.59526G	-48.17	1





BT-LE(1Mbps)

2480MHz

CSE NdB


15/05/2019

Port1



RBW (Hz)  
100k  
VBW (Hz)  
300k  
Detector  
Peak

Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44004G	5.05	-24.95	845.78M	-63.11	2.39958G	-62.46	2.48537G	-55.82	2.584G	-52.70	1



**RSE below 1GHz Result**

Operating Mode	2	Polarization	Horizontal
Operating Function	CTX- EUT_2.4GHz in Z axis + Adapter 2 with US plug		

Date: 2019-05-03 Time: 17:20:52

FCC CLASS-B  
6dB

	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	Line	Limit	Level	Loss	Factor	Factor				
	Freq	Level	Line							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg
1	84.32	30.59	40.00	-9.41	47.15	1.12	14.03	31.71	100	360 Peak
2	125.06	35.00	43.50	-8.50	46.55	1.38	18.80	31.73	100	360 Peak
3	132.82	33.41	43.50	-10.09	45.28	1.41	18.45	31.73	100	360 Peak
4	158.04	29.37	43.50	-14.13	42.94	1.59	16.60	31.76	100	360 Peak
5	196.84	31.77	43.50	-11.73	45.85	1.68	16.00	31.76	100	360 Peak
6	238.55	40.29	46.00	-5.71	52.38	1.89	17.83	31.81	100	360 Peak

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



## RSE TX above 1GHz Result

## Appendix F.2


### Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.4835G	48.33	54.00	-5.67	30.96	3	Vertical	286	2.47	-

## BT-LE(1Mbps)

## 2402MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-L-3  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3836G	55.02	74.00	-18.98	30.78	3	Vertical	74	2.93	-				
AV	2.3742G	43.26	54.00	-10.74	30.74	3	Vertical	74	2.93	-				
PK	2.4022G	100.31	Inf	-Inf	30.84	3	Vertical	74	2.93	-				
AV	2.402G	98.73	Inf	-Inf	30.84	3	Vertical	74	2.93	-				

## BT-LE(1Mbps)

## 2402MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-L-3  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3532G	54.12	74.00	-19.88	30.66	3	Horizontal	293	1.01	-				
AV	2.3678G	43.07	54.00	-10.93	30.71	3	Horizontal	293	1.01	-				
PK	2.4024G	99.83	Inf	-Inf	30.84	3	Horizontal	293	1.01	-				
AV	2.402G	98.32	Inf	-Inf	30.84	3	Horizontal	293	1.01	-				

## BT-LE(1Mbps)

## 2402MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-L-3  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.80362G	53.02	74.00	-20.98	3.49	3	Vertical	134	2.57	-				
AV	4.80394G	45.06	54.00	-8.94	3.49	3	Vertical	134	2.57	-				

## BT-LE(1Mbps)

## 2402MHz\_TX

14/05/2019



EUT\_Z\_1TX  
Setting Default  
01-L-3  
FSP(100056)


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.80446G	52.29	74.00	-21.71	3.50	3	Horizontal	282	1.06	-				
AV	4.80403G	44.40	54.00	-9.60	3.49	3	Horizontal	282	1.06	-				



## BT-LE(1Mbps)

## 2440MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3668G	54.75	74.00	-19.25	30.71	3	Vertical	109	2.89	-				
AV	2.366G	43.16	54.00	-10.84	30.71	3	Vertical	109	2.89	-				
PK	2.4396G	102.30	Inf	-Inf	30.90	3	Vertical	109	2.89	-				
AV	2.44G	100.78	Inf	-Inf	30.90	3	Vertical	109	2.89	-				
PK	2.492G	55.07	74.00	-18.93	30.98	3	Vertical	109	2.89	-				
AV	2.492G	43.53	54.00	-10.47	30.98	3	Vertical	109	2.89	-				

## BT-LE(1Mbps)

## 2440MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.3732G	55.90	74.00	-18.10	30.74	3	Horizontal	290	1.19	-				
AV	2.3868G	43.07	54.00	-10.93	30.79	3	Horizontal	290	1.19	-				
PK	2.4396G	102.23	Inf	-Inf	30.90	3	Horizontal	290	1.19	-				
AV	2.44G	100.76	Inf	-Inf	30.90	3	Horizontal	290	1.19	-				
PK	2.4996G	54.75	74.00	-19.25	30.99	3	Horizontal	290	1.19	-				
AV	2.4876G	43.35	54.00	-10.65	30.97	3	Horizontal	290	1.19	-				

## BT-LE(1Mbps)

## 2440MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.87953G	54.78	74.00	-19.22	3.84	3	Vertical	319	1.00	-				
AV	4.87997G	47.90	54.00	-6.10	3.84	3	Vertical	319	1.00	-				

## BT-LE(1Mbps)

## 2440MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.87941G	51.29	74.00	-22.71	3.84	3	Horizontal	291	1.07	-				
AV	4.87982G	42.23	54.00	-11.77	3.84	3	Horizontal	291	1.07	-				

## BT-LE(1Mbps)

## 2480MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.4798G	102.32	Inf	-Inf	30.96	3	Vertical	286	2.47	-				
AV	2.48G	100.84	Inf	-Inf	30.96	3	Vertical	286	2.47	-				
PK	2.4835G	55.98	74.00	-18.02	30.96	3	Vertical	286	2.47	-				
AV	2.4835G	48.33	54.00	-5.67	30.96	3	Vertical	286	2.47	-				

## BT-LE(1Mbps)

## 2480MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	2.4798G	102.62	Inf	-Inf	30.96	3	Horizontal	288	1.37	-				
AV	2.48G	101.10	Inf	-Inf	30.96	3	Horizontal	288	1.37	-				
PK	2.4835G	56.03	74.00	-17.97	30.96	3	Horizontal	288	1.37	-				
AV	2.4835G	48.30	54.00	-5.70	30.96	3	Horizontal	288	1.37	-				

## BT-LE(1Mbps)

## 2480MHz\_TX

14/05/2019




EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.95948G	53.84	74.00	-20.16	4.20	3	Vertical	116	1.71	-				
AV	4.9599G	46.59	54.00	-7.41	4.20	3	Vertical	116	1.71	-				

## BT-LE(1Mbps)

## 2480MHz\_TX

14/05/2019



EUT\_Z\_1TX  
Setting Default  
01-C-5  
FSP(100056)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment				
PK	4.95957G	50.87	74.00	-23.13	4.20	3	Horizontal	285	1.07	-				
AV	4.95985G	41.63	54.00	-12.37	4.20	3	Horizontal	285	1.07	-				