



FCC TEST REPORT

REPORT NO.: RF110907E06

MODEL NO.: E1200

VERSION: 2

FCC ID: Q87-E1200V2

RECEIVED: Sep. 07, 2011

TESTED: Sep. 08 to 20, 2011

ISSUED: Oct. 17, 2011

APPLICANT: Cisco Consumer Products LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617(USA)

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS : No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

TEST LOCATION (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung
Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 80 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

Table of Contents

RELEASE CONTROL RECORD	4
1. CERTIFICATION	5
2. SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	10
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	11
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4 DESCRIPTION OF SUPPORT UNITS.....	15
3.5 CONFIGURATION OF SYSTEM UNDER TEST	16
4. TEST TYPES AND RESULTS	18
4.1 CONDUCTED EMISSION MEASUREMENT	18
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	18
4.1.2 TEST INSTRUMENTS.....	18
4.1.3 TEST PROCEDURES	19
4.1.4 DEVIATION FROM TEST STANDARD	19
4.1.5 TEST SETUP	20
4.1.6 EUT OPERATING CONDITIONS	20
4.1.7 TEST RESULTS (With adapter 1).....	21
4.1.8 TEST RESULTS (With adapter 2).....	23
4.2 RADIATED EMISSION MEASUREMENT	25
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	25
4.2.2 TEST INSTRUMENTS.....	26
4.2.3 TEST PROCEDURES	27
4.2.4 DEVIATION FROM TEST STANDARD	27
4.2.5 TEST SETUP	28
4.2.6 EUT OPERATING CONDITIONS	28
4.2.7 TEST RESULTS	29
4.3 6dB BANDWIDTH MEASUREMENT	58
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	58
4.3.2 TEST INSTRUMENTS.....	58
4.3.3 TEST PROCEDURE.....	58
4.3.4 DEVIATION FROM TEST STANDARD	58
4.3.5 TEST SETUP	58
4.3.6 EUT OPERATING CONDITIONS	58
4.3.7 TEST RESULTS	59
4.4 MAXIMUM PEAK OUTPUT POWER.....	63
4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	63
4.4.2 INSTRUMENTS.....	63



A D T

4.4.3	TEST PROCEDURES	63
4.4.4	DEVIATION FROM TEST STANDARD	63
4.4.5	TEST SETUP	63
4.4.6	EUT OPERATING CONDITIONS	63
4.4.7	TEST RESULTS	64
4.5	POWER SPECTRAL DENSITY MEASUREMENT	65
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	65
4.5.2	TEST INSTRUMENTS.....	65
4.5.3	TEST PROCEDURE.....	65
4.5.4	DEVIATION FROM TEST STANDARD.....	65
4.5.5	TEST SETUP	65
4.5.6	EUT OPERATING CONDITION.....	65
4.5.7	TEST RESULTS	66
4.6	CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	70
4.6.1	LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT.....	70
4.6.2	TEST INSTRUMENTS.....	70
4.6.3	TEST PROCEDURE.....	70
4.6.4	DEVIATION FROM TEST STANDARD.....	70
4.6.5	EUT OPERATING CONDITION.....	70
4.6.6	TEST RESULTS	70
5.	INFORMATION ON THE TESTING LABORATORIES	79
6.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	80



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF110907E06	Original release	Oct. 17, 2011



A D T

1. CERTIFICATION

PRODUCT: Wireless-N Router
BRAND NAME: Cisco
MODEL NO.: E1200
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: Sep. 08 to 20, 2011
APPLICANT: Cisco Consumer Products LLC
STANDARDS: FCC Part 15, Subpart C (Section 15.247)
ANSI C63.4-2003
ANSI C63.10-2009

The above equipment (Model: E1200) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Midoli Peng, **DATE:** Oct. 17, 2011
(Midoli Peng, Specialist)

APPROVED BY : May Chen, **DATE:** Oct. 17, 2011
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -3.04dB at 4.578MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -0.5dB at 2390.0MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Conducted Out-Band Emission Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.



A D T

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.45 dB
Radiated emissions (30MHz-1GHz)	3.89dB
Radiated emissions (1GHz -18GHz)	2.19 dB
Radiated emissions (18GHz -40GHz)	2.56 dB



A D T

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-N Router
MODEL NO.	E1200
FCC ID	Q87-E1200V2
POWER SUPPLY	DC 12V from power adapter
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n (20MHz, 800ns GI): up to 130Mbps 802.11n (40MHz, 800ns GI): up to 270Mbps
FREQUENCY OPERATING	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11 for 802.11b, 802.11g, 802.11n (20MHz) 7 for 802.11n (40MHz)
MAXIMUM OUTPUT POWER	802.11b: 144.5mW 802.11g: 234.4mW 802.11n (20MHz): 437.7mW 802.11n (40MHz): 182.3mW
ANTENNA TYPE	Please see NOTE
DATA CABLE	NA
I/O PORTS	RJ-45 Port x 4 (Ethernet (10, 100Mbps)) RJ-45 Port x 1 (Internet (10, 100Mbps))
ASSOCIATED DEVICES	Adapter x 1

NOTE:

1. There are two antennas provided to this EUT, please refer to the following table:

Transmitter Circuit	Gain (dBi)	Antenna Type	Connector Type
Chain (0)	4	Dipole	NA
Chain (1)	2	Dipole	NA

2. The EUT must be supplied with a power adapter and following two different model names could be chosen:

Adapter 1	
BRAND	HON-KWANG
MODEL	HK-Q106-A12
INPUT POWER	AC 100-240V, 50/60Hz, 0.5A
OUTPUT POWER	DC 12V, 0.5A DC Cable: 1.5m unshielded
Adapter 2	
BRAND	Leader
MODEL	MU08-6120050-A1
INPUT POWER	AC 100-240V, 50/60Hz, 0.3A
OUTPUT POWER	DC 12V, 0.5A DC Cable: 1.5m unshielded

For radiated test, the EUT was pre-tested with above adapters, the worse case was found in adapter 2. Therefore only the test data of the adapter was recorded in this report.

3. The EUT is 2 * 2 spatial MIMO (2Tx & 2Rx) without beam forming function. The 11b/g legacy mode is limited to single transmitter only.
4. When the EUT operating in 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
5. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		



A D T

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
MODE A	√	-	-	-	-	With adapter 1
MODE B	√	√	√	√	√	With adapter 2

Where **PLC**: Power Line Conducted Emission **RE < 1G**: Radiated Emission below 1GHz
RE ≥ 1G: Radiated Emission above 1GHz **APCM**: Antenna Port Conducted Measurement
OB: Conducted Out-Band Emission Measurement

ANTENNA COMBINATION MODE:

COMBINATION MODE	OPERATION MODE	TX CHAIN(0)	TX CHAIN(1)
A	802.11 b	√	-
B	802.11 b	-	√
C	802.11 g	√	-
D	802.11 g	-	√
E	802.11n (20MHz)	√	√
F	802.11n (40MHz)	√	√

Note:
1. The above information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.
2. Mode A, C, E, F the worst modes, was selected as representative mode for the report.

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	E



RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11n (20MHz)	1 to 11	6	OFDM	BPSK	6.5	E

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	F

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 6, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	3 to 9	3, 6, 9	OFDM	BPSK	13.5	F



A D T

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	COMBINATION MODE
802.11b	1 to 11	1, 11	DSSS	DBPSK	1	A
802.11g	1 to 11	1, 11	OFDM	BPSK	6	C
802.11n (20MHz)	1 to 11	1, 11	OFDM	BPSK	6.5	E
802.11n (40MHz)	3 to 9	3, 9	OFDM	BPSK	13.5	F

※ TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
PLC	27deg. C, 62%RH,	120Vac, 60Hz	Eagle Chen
RE ³ 1G	25deg. C, 73%RH	120Vac, 60Hz	Evan Huang
RE<1G	24deg. C, 72%RH	120Vac, 60Hz	Evan Huang
APCM	35deg. C, 60%RH	120Vac, 60Hz	Rex Huang
OB	25deg. C, 73%RH	120Vac, 60Hz	Evan Huang

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



A D T

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


For Conducted Test					
NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP27L	7YLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP27L	6YLB32S	FCC DoC
For other test items					
NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP32LA	FSLB32S	FCC DoC
2	NOTEBOOK COMPUTER	DELL	PP32LA	GSLB32S	FCC DoC
3	HUB	ZyXEL	ES-116P	S060H02000215	FCC DoC

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	UTP Cable (10m)
2	UTP Cable (10m)
3	UTP Cable (10m)


NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST

For Conducted test:



For other test items:





A D T

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Test date: Sep. 08, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver	ESCS 30	100375	Mar. 09, 2011	Mar. 08, 2012
Line-Impedance Stabilization Network (for EUT)	ENV216	100072	Jun. 10, 2011	Jun. 09, 2012
Line-Impedance Stabilization Network (for Peripheral)	ESH3-Z5	848773/004	Nov. 03, 2010	Nov. 02, 2011
RF Cable (JYBAO)	5DFB	COCCAB-002	Aug. 29, 2011	Aug. 28, 2012
50 ohms Terminator	50	3	Oct. 07, 2010	Nov. 02, 2011
Software	BV ADT_Cond_V7.3.7	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS


1. Placed the EUT on testing table.
2. Prepared other computer systems (support units 1~2) to act as communication partners and placed them outside of testing area.
3. The communication partners ran test program “Telnet Paste(E1200V2 command.txt)” to enable EUT under transmission/receiving condition continuously via UTP cables transmission.

4.1.7 TEST RESULTS (With adapter 1)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
--------------	----------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.330	9.70	33.91	24.86	43.61	34.56	59.46
2	0.795	9.70	29.38	17.16	39.08	26.86	56.00	46.00	-16.92	-19.14
3	1.625	9.71	33.45	22.86	43.16	32.57	56.00	46.00	-12.84	-13.43
4	2.156	9.71	29.67	20.52	39.38	30.23	56.00	46.00	-16.62	-15.77
5	2.750	9.73	30.38	20.76	40.11	30.49	56.00	46.00	-15.89	-15.51
6	3.734	9.74	36.25	27.83	45.99	37.57	56.00	46.00	-10.01	-8.43
7	5.441	9.78	35.36	26.85	45.14	36.63	60.00	50.00	-14.86	-13.37
8	7.152	9.82	33.19	25.24	43.01	35.06	60.00	50.00	-16.99	-14.94
9	8.586	9.85	28.23	20.75	38.08	30.60	60.00	50.00	-21.92	-19.40


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
-------	-------------	---------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.689	9.74	30.16	18.49	39.90	28.23	56.00
2	0.834	9.75	28.35	15.63	38.10	25.38	56.00	46.00	-17.90	-20.62
3	1.102	9.75	29.14	21.53	38.89	31.28	56.00	46.00	-17.11	-14.72
4	1.594	9.76	33.86	23.17	43.62	32.93	56.00	46.00	-12.38	-13.07
5	1.809	9.77	33.18	22.31	42.95	32.08	56.00	46.00	-13.05	-13.92
6	2.355	9.78	33.19	22.56	42.97	32.34	56.00	46.00	-13.03	-13.66
7	2.766	9.78	35.19	23.35	44.97	33.13	56.00	46.00	-11.03	-12.87
8	3.449	9.79	38.64	26.43	48.43	36.22	56.00	46.00	-7.57	-9.78
9	3.746	9.80	41.19	29.26	50.99	39.06	56.00	46.00	-5.01	-6.94
10	3.883	9.80	41.77	30.21	51.57	40.01	56.00	46.00	-4.43	-5.99
11	5.258	9.84	40.73	29.52	50.57	39.36	60.00	50.00	-9.43	-10.64
12	5.891	9.86	38.34	27.73	48.20	37.59	60.00	50.00	-11.80	-12.41
13	6.801	9.89	36.68	26.14	46.57	36.03	60.00	50.00	-13.43	-13.97
14	8.160	9.93	35.08	21.68	45.01	31.61	60.00	50.00	-14.99	-18.39
15	10.063	9.99	37.53	31.05	47.52	41.04	60.00	50.00	-12.48	-8.96

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.




4.1.8 TEST RESULTS (With adapter 2)

PHASE	Line (L)	6dB BANDWIDTH	9 kHz
-------	----------	---------------	-------

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.595	9.70	28.27	20.49	37.97	30.19	56.00
2	1.535	9.71	29.46	19.49	39.17	29.20	56.00	46.00	-16.83	-16.80
3	2.469	9.72	31.16	22.25	40.88	31.97	56.00	46.00	-15.12	-14.03
4	2.773	9.73	32.73	24.19	42.46	33.92	56.00	46.00	-13.54	-12.08
5	3.449	9.74	35.79	27.36	45.53	37.10	56.00	46.00	-10.47	-8.90
6	3.891	9.75	36.90	28.52	46.65	38.27	56.00	46.00	-9.35	-7.73
7	4.777	9.77	38.79	30.61	48.56	40.38	56.00	46.00	-7.44	-5.62
8	5.676	9.79	40.15	31.99	49.94	41.78	60.00	50.00	-10.06	-8.22
9	6.113	9.80	40.38	32.56	50.18	42.36	60.00	50.00	-9.82	-7.64
10	7.469	9.83	37.36	29.47	47.19	39.30	60.00	50.00	-12.81	-10.70
11	9.406	9.87	33.96	24.16	43.83	34.03	60.00	50.00	-16.17	-15.97
12	12.996	9.89	27.99	18.35	37.88	28.24	60.00	50.00	-22.12	-21.76

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.






A D T

PHASE	Neutral (N)	6dB BANDWIDTH	9 kHz
--------------	-------------	----------------------	-------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.435	9.74	31.17	23.86	40.91	33.60	57.15
2	1.297	9.76	29.96	20.74	39.72	30.50	56.00	46.00	-16.28	-15.50
3	1.449	9.76	33.26	25.38	43.02	35.14	56.00	46.00	-12.98	-10.86
4	1.730	9.76	31.97	22.45	41.73	32.21	56.00	46.00	-14.27	-13.79
5	2.633	9.78	36.17	25.38	45.95	35.16	56.00	46.00	-10.05	-10.84
6	3.117	9.79	38.31	27.36	48.10	37.15	56.00	46.00	-7.90	-8.85
7	3.828	9.80	41.49	30.88	51.29	40.68	56.00	46.00	-4.71	-5.32
8	4.578	9.82	43.14	32.17	52.96	41.99	56.00	46.00	-3.04	-4.01
9	5.402	9.84	45.13	33.86	54.97	43.70	60.00	50.00	-5.03	-6.30
10	5.770	9.86	45.87	34.26	55.73	44.12	60.00	50.00	-4.27	-5.88
11	6.770	9.89	44.31	33.03	54.20	42.92	60.00	50.00	-5.80	-7.08
12	9.266	9.97	35.29	25.73	45.26	35.70	60.00	50.00	-14.74	-14.30
13	12.848	10.04	27.16	15.79	37.20	25.83	60.00	50.00	-22.80	-24.17

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. The emission levels of other frequencies were very low against the limit.
 3. Margin value = Emission level - Limit value
 4. Correction factor = Insertion loss + Cable loss
 5. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. Section 15.205 restricted bands of operation shall compliance with the limits in Section 15.209.



A D T

4.2.2 TEST INSTRUMENTS

Test date: Sep. 18, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Agilent Spectrum Analyzer	E4446A	MY48250253	Aug. 29, 2011	Aug. 28, 2012
Agilent Pre-Selector	N9039A	MY46520310	Aug. 29, 2011	Aug. 28, 2012
Agilent Signal Generator	N5181A	MY49060347	July 25, 2011	July 24, 2012
LIG NEX1 Test Receiver	ER-265	L09068005	Oct. 25, 2010	Oct. 24, 2011
Mini-Circuits Pre-Amplifier	ZFL-1000VH2B	AMP-ZFL-04	Nov. 16, 2010	Nov. 15, 2011
Agilent Pre-Amplifier	8449B	3008A02465	Feb. 28, 2011	Feb. 27, 2012
Miteq Pre-Amplifier	AFS33-1800265 0-30-8P-44	881786	Nov. 16, 2010	Nov. 15, 2011
SCHWARZBECK Trilog Broadband Antenna	VULB 9168	9168-361	Apr. 14, 2011	Apr. 13, 2012
AISI Horn_Antenna	AIH.8018	0000220091110	Nov. 22, 2010	Nov. 21, 2011
SCHWARZBECK Horn_Antenna	BBHA 9170	9170-424	Oct. 08, 2010	Oct. 07, 2011
RF CABLE	NA	RF104-205 RF104-207 RF104-202	Dec. 28, 2010	Dec. 27, 2011
RF Cable	NA	CHHCAB_001	Oct. 17, 2010	Oct. 16, 2011
Software	ADT_Radiated_V8.7.05	NA	NA	NA
CT Antenna Tower & Turn Table	NA	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

3. The test was performed in 966 Chamber No. H.

4. The FCC Site Registration No. is 797305.

5. The CANADA Site Registration No. is IC 7450H-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	24deg. C, 72%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	155.53	33.0 QP	43.5	-10.5	1.75 H	274	18.59	14.41
2	250.03	35.0 QP	46.0	-11.0	1.50 H	273	21.93	13.04
3	374.97	35.5 QP	46.0	-10.5	1.00 H	304	18.67	16.79
4	500.02	38.5 QP	46.0	-7.5	2.00 H	27	18.96	19.53
5	599.97	39.6 QP	46.0	-6.4	1.50 H	228	17.96	21.60
6	750.01	40.5 QP	46.0	-5.5	1.00 H	317	17.22	23.27
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	64.82	35.2 QP	40.0	-4.8	1.00 V	37	22.49	12.75
2	250.03	36.5 QP	46.0	-9.5	1.00 V	231	23.50	13.04
3	450.05	36.2 QP	46.0	-9.8	1.25 V	306	17.68	18.48
4	500.02	37.6 QP	46.0	-8.4	1.25 V	360	18.11	19.53
5	599.97	36.2 QP	46.0	-9.8	1.75 V	282	14.56	21.60
6	750.01	39.0 QP	46.0	-7.0	1.25 V	353	15.75	23.27

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



A D T

ABOVE 1GHz WORST-CASE DATA

802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.00 H	245	25.79	31.21
2	2390.00	45.3 AV	54.0	-8.7	1.00 H	245	14.09	31.21
3	*2412.00	107.1 PK			1.00 H	244	75.83	31.27
4	*2412.00	104.6 AV			1.00 H	244	73.33	31.27
5	4824.00	51.3 PK	74.0	-22.7	1.51 H	141	11.88	39.42
6	4824.00	47.9 AV	54.0	-6.1	1.51 H	141	8.48	39.42
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	59.3 PK	74.0	-14.7	1.00 V	113	28.09	31.21
2	2390.00	47.8 AV	54.0	-6.2	1.00 V	113	16.59	31.21
3	*2412.00	111.1 PK			1.01 V	115	79.83	31.27
4	*2412.00	108.7 AV			1.01 V	115	77.43	31.27
5	4824.00	53.2 PK	74.0	-20.8	1.20 V	2	13.78	39.42
6	4824.00	50.8 AV	54.0	-3.2	1.20 V	2	11.38	39.42

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	102.6 PK			1.24 H	80	71.26	31.34
2	*2437.00	100.0 AV			1.24 H	80	68.66	31.34
3	4874.00	50.9 PK	74.0	-23.1	1.49 H	131	11.28	39.62
4	4874.00	47.4 AV	54.0	-6.6	1.49 H	131	7.78	39.62
5	7311.00	51.5 PK	74.0	-22.5	1.17 H	40	7.40	44.10
6	7311.00	43.9 AV	54.0	-10.1	1.17 H	40	-0.20	44.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	111.2 PK			1.02 V	113	79.86	31.34
2	*2437.00	108.7 AV			1.02 V	113	77.36	31.34
3	4874.00	54.3 PK	74.0	-19.7	1.32 V	8	14.68	39.62
4	4874.00	52.1 AV	54.0	-1.9	1.32 V	8	12.48	39.62
5	7311.00	54.2 PK	74.0	-19.8	1.56 V	348	10.10	44.10
6	7311.00	48.8 AV	54.0	-5.2	1.56 V	348	4.70	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M



NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.8 PK			1.00 H	246	73.40	31.40
2	*2462.00	102.4 AV			1.00 H	246	71.00	31.40
3	2483.50	57.3 PK	74.0	-16.7	1.00 H	245	25.84	31.46
4	2483.50	45.6 AV	54.0	-8.4	1.00 H	245	14.14	31.46
5	4924.00	51.5 PK	74.0	-22.5	1.45 H	320	11.68	39.82
6	4924.00	48.0 AV	54.0	-6.0	1.45 H	320	8.18	39.82
7	7386.00	51.1 PK	74.0	-22.9	1.53 H	40	6.92	44.18
8	7386.00	39.9 AV	54.0	-14.1	1.53 H	40	-4.28	44.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.7 PK			1.02 V	112	79.30	31.40
2	*2462.00	108.0 AV			1.02 V	112	76.60	31.40
3	2483.50	60.2 PK	74.0	-13.8	1.02 V	112	28.74	31.46
4	2483.50	48.5 AV	54.0	-5.5	1.02 V	112	17.04	31.46
5	4924.00	55.3 PK	74.0	-18.7	1.33 V	14	15.48	39.82
6	4924.00	53.0 AV	54.0	-1.0	1.33 V	14	13.18	39.82
7	7386.00	52.9 PK	74.0	-21.1	1.45 V	246	8.72	44.18
8	7386.00	46.4 AV	54.0	-7.6	1.45 V	246	2.22	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11b MODE, CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE, CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11b MODE,CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11b MODE, CH11, VERTICAL)





A D T

802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.8 PK	74.0	-16.2	1.29 H	14	26.59	31.21
2	2390.00	46.0 AV	54.0	-8.0	1.29 H	14	14.79	31.21
3	*2412.00	106.5 PK			1.00 H	245	75.23	31.27
4	*2412.00	94.8 AV			1.00 H	245	63.53	31.27
5	4824.00	54.3 PK	74.0	-19.7	1.00 H	68	14.88	39.42
6	4824.00	41.1 AV	54.0	-12.9	1.00 H	68	1.68	39.42
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.9 PK	74.0	-5.1	1.00 V	115	37.69	31.21
2	2390.00	52.6 AV	54.0	-1.4	1.00 V	115	21.39	31.21
3	*2412.00	110.5 PK			1.00 V	114	79.23	31.27
4	*2412.00	99.2 AV			1.00 V	114	67.93	31.27
5	4824.00	54.4 PK	74.0	-19.6	1.00 V	338	14.98	39.42
6	4824.00	41.2 AV	54.0	-12.8	1.00 V	338	1.78	39.42

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.2 PK			1.00 H	247	78.86	31.34
2	*2437.00	98.6 AV			1.00 H	247	67.26	31.34
3	4874.00	47.3 PK	74.0	-26.7	1.17 H	65	7.68	39.62
4	4874.00	35.4 AV	54.0	-18.6	1.17 H	65	-4.22	39.62
5	7311.00	53.8 PK	74.0	-20.2	1.17 H	41	9.70	44.10
6	7311.00	40.5 AV	54.0	-13.5	1.17 H	41	-3.60	44.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	115.3 PK			1.00 V	113	83.96	31.34
2	*2437.00	102.7 AV			1.00 V	113	71.36	31.34
3	4874.00	52.0 PK	74.0	-22.0	1.17 V	9	12.38	39.62
4	4874.00	38.6 AV	54.0	-15.4	1.17 V	9	-1.02	39.62
5	7311.00	58.3 PK	74.0	-15.7	1.56 V	335	14.20	44.10
6	7311.00	43.8 AV	54.0	-10.2	1.56 V	335	-0.30	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	104.9 PK			1.00 H	247	73.50	31.40
2	*2462.00	93.5 AV			1.00 H	247	62.10	31.40
3	2483.50	64.0 PK	74.0	-10.0	1.00 H	248	32.54	31.46
4	2483.50	47.2 AV	54.0	-6.8	1.00 H	248	15.74	31.46
5	4924.00	54.1 PK	74.0	-19.9	1.02 H	55	14.28	39.82
6	4924.00	41.1 AV	54.0	-12.9	1.02 H	55	1.28	39.82
7	7386.00	53.8 PK	74.0	-20.2	1.02 H	12	9.62	44.18
8	7386.00	41.8 AV	54.0	-12.2	1.02 H	12	-2.38	44.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	111.1 PK			1.02 V	113	79.70	31.40
2	*2462.00	98.3 AV			1.02 V	113	66.90	31.40
3	2483.50	72.0 PK	74.0	-2.0	1.02 V	113	40.54	31.46
4	2483.50	52.5 AV	54.0	-1.5	1.02 V	113	21.04	31.46
5	4924.00	54.5 PK	74.0	-19.5	1.02 V	330	14.68	39.82
6	4924.00	41.3 AV	54.0	-12.7	1.02 V	330	1.48	39.82
7	7386.00	52.7 PK	74.0	-21.3	1.00 V	215	8.52	44.18
8	7386.00	41.9 AV	54.0	-12.1	1.00 V	215	-2.28	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



RESTRICTED BANDEDGE (802.11g MODE, CH1, HORIZONTAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH1, VERTICAL)





A D T



RESTRICTED BANDEDGE (802.11g MODE, CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11g MODE,CH11, VERTICAL)





A D T

802.11n (20MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.00	64.8 PK	74.0	-9.2	1.38 H	16	33.59	31.21
2	2389.00	47.3 AV	54.0	-6.7	1.38 H	16	16.09	31.21
3	*2412.00	104.9 PK			1.42 H	16	73.63	31.27
4	*2412.00	93.7 AV			1.42 H	16	62.43	31.27
5	4824.00	53.7 PK	74.0	-20.3	1.00 H	69	14.28	39.42
6	4824.00	40.5 AV	54.0	-13.5	1.00 H	69	1.08	39.42
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.6 PK	74.0	-4.4	1.00 V	114	38.39	31.21
2	2390.00	53.1 AV	54.0	-0.9	1.00 V	114	21.89	31.21
3	*2412.00	109.4 PK			1.00 V	114	78.13	31.27
4	*2412.00	97.8 AV			1.00 V	114	66.53	31.27
5	4824.00	53.6 PK	74.0	-20.4	1.00 V	35	14.18	39.42
6	4824.00	41.1 AV	54.0	-12.9	1.00 V	35	1.68	39.42

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.5 PK			1.00 H	248	82.16	31.34
2	*2437.00	102.4 AV			1.00 H	248	71.06	31.34
3	4874.00	49.5 PK	74.0	-24.5	1.63 H	333	9.88	39.62
4	4874.00	37.4 AV	54.0	-16.6	1.63 H	333	-2.22	39.62
5	7311.00	52.7 PK	74.0	-21.3	1.18 H	40	8.60	44.10
6	7311.00	39.7 AV	54.0	-14.3	1.18 H	40	-4.40	44.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.7 PK			1.00 V	279	82.36	31.34
2	*2437.00	102.7 AV			1.00 V	279	71.36	31.34
3	4874.00	54.7 PK	74.0	-19.3	1.16 V	12	15.08	39.62
4	4874.00	41.4 AV	54.0	-12.6	1.16 V	12	1.78	39.62
5	7311.00	55.8 PK	74.0	-18.2	1.70 V	16	11.70	44.10
6	7311.00	41.5 AV	54.0	-12.5	1.70 V	16	-2.60	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.9 PK			1.32 H	9	71.50	31.40
2	*2462.00	90.2 AV			1.32 H	9	58.80	31.40
3	2483.90	66.5 PK	74.0	-7.5	1.32 H	13	35.04	31.46
4	2483.90	46.1 AV	54.0	-7.9	1.32 H	13	14.64	31.46
5	4924.00	53.6 PK	74.0	-20.4	1.06 H	83	13.78	39.82
6	4924.00	40.7 AV	54.0	-13.3	1.06 H	83	0.88	39.82
7	7386.00	54.1 PK	74.0	-19.9	1.05 H	22	9.92	44.18
8	7386.00	41.9 AV	54.0	-12.1	1.05 H	22	-2.28	44.18

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.6 PK			1.04 V	114	78.20	31.40
2	*2462.00	99.1 AV			1.04 V	114	67.70	31.40
3	2483.50	71.4 PK	74.0	-2.6	1.04 V	111	39.94	31.46
4	2483.50	52.4 AV	54.0	-1.6	1.04 V	111	20.94	31.46
5	4924.00	53.3 PK	74.0	-20.7	1.00 V	48	13.48	39.82
6	4924.00	41.0 AV	54.0	-13.0	1.00 V	48	1.18	39.82
7	7386.00	52.7 PK	74.0	-21.3	1.00 V	203	8.52	44.18
8	7386.00	42.0 AV	54.0	-12.0	1.00 V	203	-2.18	44.18

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T



RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, HORIZONTAL)







A D T

RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH1, VERTICAL)





RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, HORIZONTAL)





A D T

RESTRICTED BANDEDGE (802.11n (20MHz) MODE,CH11, VERTICAL)





A D T

802.11n (40MHz) OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2388.50	65.5 PK	74.0	-8.5	1.29 H	166	34.29	31.21
2	2388.50	49.2 AV	54.0	-4.8	1.29 H	166	17.99	31.21
3	*2422.00	99.3 PK			1.29 H	166	68.00	31.30
4	*2422.00	88.0 AV			1.29 H	166	56.70	31.30
5	4844.00	53.4 PK	74.0	-20.6	1.02 H	88	13.90	39.50
6	4844.00	40.6 AV	54.0	-13.4	1.02 H	88	1.10	39.50
7	7266.00	53.8 PK	74.0	-20.2	1.01 H	11	9.74	44.06
8	7266.00	41.7 AV	54.0	-12.3	1.01 H	11	-2.36	44.06
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2389.07	65.2 PK	74.0	-8.8	1.06 V	81	33.99	31.21
2	2389.07	53.2 AV	54.0	-0.8	1.06 V	81	21.99	31.21
3	*2422.00	104.9 PK			1.06 V	81	73.60	31.30
4	*2422.00	93.3 AV			1.06 V	81	62.00	31.30
5	4844.00	53.3 PK	74.0	-20.7	1.02 V	58	13.80	39.50
6	4844.00	40.9 AV	54.0	-13.1	1.02 V	58	1.40	39.50
7	7266.00	52.5 PK	74.0	-21.5	1.01 V	201	8.44	44.06
8	7266.00	42.0 AV	54.0	-12.0	1.01 V	201	-2.06	44.06

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.9 PK	74.0	-1.1	1.00 H	294	41.69	31.21
2	2390.00	52.7 AV	54.0	-1.3	1.00 H	294	21.49	31.21
3	*2437.00	108.1 PK			1.00 H	291	76.76	31.34
4	*2437.00	93.7 AV			1.00 H	291	62.36	31.34
5	2483.50	69.5 PK	74.0	-4.5	1.00 H	296	38.04	31.46
6	2483.50	51.8 AV	54.0	-2.2	1.00 H	296	20.34	31.46
7	4874.00	53.3 PK	74.0	-20.7	1.01 H	89	13.68	39.62
8	4874.00	40.8 AV	54.0	-13.2	1.01 H	89	1.18	39.62
9	7311.00	53.8 PK	74.0	-20.2	1.03 H	4	9.70	44.10
10	7311.00	41.9 AV	54.0	-12.1	1.03 H	4	-2.20	44.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.5 PK	74.0	-0.5	1.04 V	81	42.29	31.21
2	2390.00	52.8 AV	54.0	-1.2	1.04 V	81	21.59	31.21
3	*2437.00	107.4 PK			1.04 V	81	76.06	31.34
4	*2437.00	96.3 AV			1.04 V	81	64.96	31.34
5	2483.50	72.8 PK	74.0	-1.2	1.00 V	112	41.34	31.46
6	2483.50	52.4 AV	54.0	-1.6	1.00 V	112	20.94	31.46
7	4874.00	53.7 PK	74.0	-20.3	1.00 V	49	14.08	39.62
8	4874.00	41.1 AV	54.0	-12.9	1.00 V	49	1.48	39.62
9	7311.00	52.4 PK	74.0	-21.6	1.05 V	214	8.30	44.10
10	7311.00	42.1 AV	54.0	-11.9	1.05 V	214	-2.00	44.10

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 73%RH	TESTED BY	Evan Huang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	98.6 PK			1.00 H	293	67.22	31.38
2	*2452.00	87.3 AV			1.00 H	293	55.92	31.38
3	2484.90	61.8 PK	74.0	-12.2	1.00 H	293	30.34	31.46
4	2484.90	47.2 AV	54.0	-6.8	1.00 H	293	15.74	31.46
5	4904.00	54.2 PK	74.0	-19.8	1.06 H	10	14.46	39.74
6	4904.00	42.2 AV	54.0	-11.8	1.06 H	10	2.46	39.74
7	7356.00	53.7 PK	74.0	-20.3	1.09 H	11	9.55	44.15
8	7356.00	41.9 AV	54.0	-12.1	1.09 H	11	-2.25	44.15

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	105.9 PK			1.01 V	112	74.52	31.38
2	*2452.00	94.3 AV			1.01 V	112	62.92	31.38
3	2484.40	71.3 PK	74.0	-2.7	1.01 V	112	39.84	31.46
4	2484.40	53.2 AV	54.0	-0.8	1.01 V	112	21.74	31.46
5	4904.00	52.5 PK	74.0	-21.5	1.08 V	217	12.76	39.74
6	4904.00	42.3 AV	54.0	-11.7	1.08 V	217	2.56	39.74
7	7356.00	52.5 PK	74.0	-21.5	1.08 V	227	8.35	44.15
8	7356.00	42.2 AV	54.0	-11.8	1.08 V	227	-1.95	44.15

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “: Fundamental frequency.





A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, HORIZONTAL)





RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH3, VERTICAL)







A D T

RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, HORIZONTAL)



RESTRICTED BANDEDGE (802.11n (40MHz) MODE,CH9, VERTICAL)



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Test date: Sep. 20, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.35	0.5	PASS
6	2437	7.86	0.5	PASS
11	2462	8.72	0.5	PASS

CH11






A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	12.63	0.5	PASS
6	2437	14.47	0.5	PASS
11	2462	13.56	0.5	PASS


CH6



802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)		
1	2412	12.67	12.88	0.5	PASS
6	2437	13.87	16.72	0.5	PASS
11	2462	15.39	14.53	0.5	PASS

CHAIN (1):CH6






A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)	PASS / FAIL
		CHAIN(0)	CHAIN(1)		
3	2422	33.96	31.37	0.5	PASS
6	2437	36.49	35.86	0.5	PASS
9	2452	35.87	36.22	0.5	PASS

CHAIN (0):CH6



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Test date: Sep. 20, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Anritsu Power Meter	ML2495A	0824006	May 04, 2011	May 03, 2012
Pulse Power Sensor	MA2411B	0738172	May 03, 2011	May 02, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. The transmitter output was connected to the power meter through an attenuator; the bandwidth of the fundamental frequency was measured with the power meter.
2. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	141.3	21.5	30	PASS
6	2437	144.5	21.6	30	PASS
11	2462	125.9	21.0	30	PASS

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
1	2412	112.2	20.5	30	PASS
6	2437	234.4	23.7	30	PASS
11	2462	125.9	21.0	30	PASS

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
1	2412	20.2	20.5	216.9	23.4	30	PASS
6	2437	23.5	23.3	437.7	26.4	30	PASS
11	2462	19.7	19.6	184.5	22.7	30	PASS

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)		TOTAL PEAK POWER (mW)	TOTAL PEAK POWER (dBm)	PEAK POWER LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)				
3	2422	17.5	16.6	101.9	20.1	30	PASS
6	2437	18.9	20.2	182.3	22.6	30	PASS
9	2452	18.2	18.3	133.7	21.3	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Test date: Sep. 20, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6




A D T

4.5.7 TEST RESULTS

802.11b DSSS MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-5.0	8	PASS
6	2437	-3.6	8	PASS
11	2462	-4.9	8	PASS

CH6






A D T

802.11g OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
1	2412	-11.0	8	PASS
6	2437	-4.4	8	PASS
11	2462	-10.3	8	PASS

CH6






A D T

802.11n (20MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
1	2412	-10.6	-10.5	-7.5	8	PASS
6	2437	-6.9	-7.9	-4.4	8	PASS
11	2462	-10.6	-12.0	-8.2	8	PASS

For Chain(0): CH6






A D T

802.11n (40MHz) OFDM MODULATION:

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)		TOTAL POWER DENSITY (dBm)	MAXIMUM LIMIT (dBm)	PASS / FAIL
		CHAIN(0)	CHAIN(1)			
3	2422	-17.7	-16.7	-14.2	8	PASS
6	2437	-14.3	-14.7	-11.5	8	PASS
9	2452	-15.6	-16.2	-12.9	8	PASS

For Chain(0): CH6



4.6 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Test date: Sep. 20, 2011

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
R&S Spectrum Analyzer	FSP 40	100060	May 11, 2011	May 10, 2012

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set RBW of spectrum analyzer to 100kHz and VBW of spectrum analyzer to 300kHz with suitable frequency span including 100 MHz or 200 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (RBW = 100kHz, VBW = 300kHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.6 TEST RESULTS



The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).



A D T

Performing measurements: Measure and add 10 log(N) dB 802.11b DSSS MODULATION:



CH1





A D T

CH11







A D T

802.11g OFDM MODULATION:

CH1



A D T





A D T



A D T

CH11







A D T

802.11n (20MHz) OFDM MODULATION:



CH1





A D T

CH11







A D T

802.11n (40MHz) OFDM MODULATION:

CH3



A D T





A D T



A D T

CH9





5. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5.phtml.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Email: service.adt@tw.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

6.APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---