



RF EXPOSURE REPORT

REPORT NO.: SA980606H02A

MODEL NO.: E3000

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Cisco-Linksys LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617(USA)

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB LOCATION: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,
Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in our lab, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. Friis Formula

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**

6. Test Results

6.1 Antenna Gain

There are three antennas provided to this EUT, please refer to the following table:

Transmitter / Circuit	Antenna Gain		Antenna Type	Connector
	For 2.4GHz Gain (dBi)	For 5GHz Gain (dBi)		
Chain(0)	4	3.5	PIFA	NA
Chain(1)	4	3.5	PIFA	NA
Chain(2)	4	3.5	PIFA	NA

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For 15.247(2.4GHz) :

For Part 802.11b:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	398.100	0.199	1.0
6	2437	398.100	0.199	1.0
11	2462	309.000	0.154	1.0

For Part 802.11g:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	162.200	0.081	1.0
6	2437	691.800	0.346	1.0
11	2462	100.000	0.050	1.0

DRAFT 802.11n (20MHz) OFDM

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	670.300	0.335	1.0
6	2437	979.800	0.490	1.0
11	2462	284.400	0.142	1.0

DRAFT 802.11n (40MHz) OFDM

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2422	328.100	0.164	1.0
4	2437	583.800	0.292	1.0
7	2452	260.800	0.130	1.0

For 15.247(5GHz) :

For Part 802.11a:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
149	5745	398.1	0.177	1.0
157	5785	389.0	0.173	1.0
165	5825	363.1	0.162	1.0

For DRAFT 802.11n (20MHz) OFDM:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
149	5745	789.7	0.352	1.0
157	5785	737.0	0.328	1.0
165	5825	687.8	0.306	1.0

DRAFT 802.11n (40MHz) OFDM

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
151	5755	743.9	0.331	1.0
159	5795	695.1	0.310	1.0



For 15.407(5GHz) :

For Part 802.11a:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
36	5180	30.9	0.014	1.0
40	5200	31.6	0.014	1.0
48	5240	32.4	0.014	1.0

For DRAFT 802.11n (20MHz) OFDM:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
36	5180	30.6	0.014	1.0
40	5200	32.9	0.015	1.0
48	5240	32.9	0.015	1.0

DRAFT 802.11n (40MHz) OFDM

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
38	5190	42.3	0.019	1.0
46	5230	40.2	0.018	1.0

CONCLUSION:

Both of the 11g and 11a can transmit simultaneously, the formula of calculated the MPE is:

$$CPD_1 / LPD_1 + CPD_2 / LPD_2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

Therefore, the calculation of this situation is $0.490 / 1 + 0.352 / 1 = 0.842$, which is less than the "1" limit.