



# RF EXPOSURE REPORT

**REPORT NO.:** SA110714C16D

**MODEL NO.:** EA4500

**FCC ID:** Q87-EA4500

**APPLICANT:** Cisco Consumer Products LLC

**ADDRESS:** 121 Theory Drive Irvine California 92617 United States

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

**LAB ADDRESS:** No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

This test report consists of 9 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by any government agency. The test results in the report only apply to the tested sample.



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT .....	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION.....	5
5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	7



## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110714C16D	Original release	Jan. 10, 2012



## 1. CERTIFICATION

**PRODUCT:** 802.11 a/b/g/n AP

**MODEL:** EA4500

**BRAND:** Cisco

**APPLICANT:** Cisco Consumer Products LLC

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

IEEE C95.1

The above equipment (Model: EA4500) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Phoenix Huang , **DATE:** Jan. 10, 2012  
( Phoenix Huang, Specialist )

**APPROVED BY** : May Chen , **DATE:** Jan. 10, 2012  
( May Chen, Deputy Manager )

## 2. RF EXPOSURE LIMIT

### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm <sup>2</sup> )	AVERAGE TIME (minutes)
<b>LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE</b>				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

## 5. ANTENNA GAIN

There are six antennas provided to this EUT, please refer to the following table:

<b>For 2.4GHz</b>				
Transmitter Circuit	Freq.(MHz)	Peak Gain (dBi)	Antenna Type	Connector Type
Chain (0)	2400	3.31	PIFA	UFL
	2450	2.27	PIFA	UFL
	2500	2.27	PIFA	UFL
Chain (1)	2400	3.45	PIFA	UFL
	2450	2.99	PIFA	UFL
	2500	2.81	PIFA	UFL
Chain (2)	2400	1.82	PIFA	UFL
	2450	1.96	PIFA	UFL
	2500	1.85	PIFA	UFL
<b>For 5GHz</b>				
Transmitter Circuit	Freq.(MHz)	Peak Gain (dBi)	Antenna Type	Connector Type
Chain (0)	5150	3.71	PIFA	UFL
	5350	3.05	PIFA	UFL
	5600	3.00	PIFA	UFL
	5730	3.39	PIFA	UFL
	5850	3.62	PIFA	UFL
Chain (1)	5150	3.28	PIFA	UFL
	5350	3.60	PIFA	UFL
	5600	3.29	PIFA	UFL
	5730	2.95	PIFA	UFL
	5850	2.65	PIFA	UFL
Chain (2)	5150	3.71	PIFA	UFL
	5350	3.40	PIFA	UFL
	5600	3.71	PIFA	UFL
	5730	4.27	PIFA	UFL
	5850	3.91	PIFA	UFL

The EUT incorporates CDD function with 802.11a, 802.11b, 802.11g.

## 6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

For 15.247(2.4GHz):

802.11b:

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412-2462	314.3	7.7	20	0.368	1.00

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$$

Effective Legacy Gain (dBi) = 7.7

802.11g:

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412-2462	314.9	7.7	20	0.369	1.00

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$$

Effective Legacy Gain (dBi) = 7.7

802.11n(20MHz):

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2412-2462	682.2	3.5	20	0.304	1.00

802.11n(40MHz):

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
2422-2452	171.4	3.5	20	0.076	1.00

**For 15.247(5GHz):**
**802.11a:**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5745 ~ 5825	434.6	8.4	20	0.598	1.00

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20} + 10^{G3/20})^2 / 3]$$

Effective Legacy Gain (dBi) = 8.4

**802.11n(20MHz):**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5745 ~ 5825	431.0	4.3	20	0.231	1.00

**802.11n(40MHz):**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5755 ~ 5795	464.6	4.3	20	0.249	1.00



**For 15.407(5GHz):**

**802.11a:**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5180 ~ 5240	24.6	6.7	20	0.023	1.00

$$\text{Directional gain} = 10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2]$$

Effective Legacy Gain (dBi) = 6.7

**802.11n(20MHz):**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5180 ~ 5240	29.6	3.7	20	0.014	1.00

**802.11n(40MHz):**

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm <sup>2</sup> )
5190 ~ 5230	48.3	3.7	20	0.023	1.00

**CONCLUSION:**

Both of the 2.4GHz and 5GHz WLAN device can transmit simultaneously, the formula of calculated the MPE is:

$$\text{CPD}_1 / \text{LPD}_1 + \text{CPD}_2 / \text{LPD}_2 + \dots \text{etc.} < 1$$

**CPD = Calculation power density**

**LPD = Limit of power density**

Therefore, the worst-case situation is  $0.369 / 1 + 0.598 / 1 = 0.967$ , which is less than "1". This confirmed that the device comply with FCC 1.1310 MPE limit.

**--- END ---**