



RF Exposure Evaluation Report

Equipment : Max-Stream AC1750 MU-MIMO GIGABIT ROUTER
Max-Stream AC1900 MU-MIMO GIGABIT ROUTER

Brand Name : LINKSYS

Model No. : EA7400V2;EA7500V2

FCC ID : Q87-EA7500V2

Standard : 47 CFR Part 2.1091

Applicant : LINKSYS LLC
121 Theory Drive, Irvine ,California,United States,
92617

The product sample received on Jun. 29, 2016 and completely tested on Sep. 02, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Sam Chen
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

| | | |
|----------|---|----------|
| 1 | GENERAL DESCRIPTION | 4 |
| 1.1 | EUT General Information | 4 |
| 1.2 | Table for Multiple Listing | 4 |
| 1.3 | Testing Location | 4 |
| 2 | MAXIMUM PERMISSIBLE EXPOSURE | 5 |
| 2.1 | Limit of Maximum Permissible Exposure | 5 |
| 2.2 | MPE Calculation Method | 5 |
| 2.3 | Calculated Result and Limit..... | 6 |



REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|-------------|---------|-------------------------|---------------|
| FA662319-01 | Rev. 01 | Initial issue of report | Sep. 21, 2016 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

1 General Description

1.1 EUT General Information

| RF General Information | | | |
|------------------------|------------------------|---------------------------|---|
| Evaluation Mode | Frequency Range (MHz) | Operating Frequency (MHz) | Modulation Type |
| 2.4GHz WLAN | 2400-2483.5 | 2412-2462 | 802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) |
| 5GHz WLAN | 5150-5250 5725-5850 | 5180-5240 5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |

1.2 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

| Model Name | Equipment Name | Modulation | Description |
|------------|---|--------------------------------|--|
| EA7400V2 | Max-Stream AC1750 MU-MIMO GIGABIT ROUTER | Without 256QAM in 802.11ac. | All the models are identical, the difference model served as marketing strategy. |
| EA7500V2 | Max-Stream AC1900 MU-MIMO GIGABIT ROUTER | With 256QAM in 802.11ac. | |

From the above models, model: EA7500V2 was selected as representative model for the test and its data was recorded in this report.

1.3 Testing Location

| Testing Location | | |
|-------------------------------------|--------|---|
| <input type="checkbox"/> | HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973 |
| <input checked="" type="checkbox"/> | JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085 |

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 32 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | EIRP (W) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) | Ratio (S/Limit) |
|----------|----------|-------------|------------|----------|---------------|-------------------------|-------------------------------|-----------------|
| 2.4G;G1D | 2.10 | 27.72 | 29.82 | 0.9594 | 32 | 0.07456 | 1 | 0.07456 |
| 5.2G;D1D | 8.35 | 27.64 | 35.98 | 3.96278 | 32 | 0.30796 | 1 | 0.30796 |
| | | | | | | | Sum Ratio | 0.38252 |
| | | | | | | | Ratio Limit | 1 |