



RF Exposure Evaluation Report

Equipment : MAX-STREAM AC4000 MU-MIMO TRI-BAND ROUTER
Brand Name : LINKSYS
Model No. : EA9300, EA9250
FCC ID : Q87-EA9300
Standard : 47 CFR Part 2.1091
Applicant : Linksys LLC
121 Theory Drive, Irvine, CA 92617, USA

The product sample received on Dec. 27, 2016 and completely tested on Jan. 05, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Cliff Chang
SPORTON INTERNATIONAL INC.





TABLE OF CONTENTS

1 GENERAL DESCRIPTION4

1.1 EUT General Information4

1.2 Table for Multiple Model Name4

1.3 Table for Multiple Source4

1.4 Table for Class II Change.....5

1.5 Testing Location5

2 MAXIMUM PERMISSIBLE EXPOSURE6

2.1 Limit of Maximum Permissible Exposure6

2.2 MPE Calculation Method.....6

2.3 Calculated Result and Limit.....7

PHOTOGRAPHS OF EUT V01

1 General Description

1.1 EUT General Information

| RF General Information | | | |
|------------------------|--------------------------------------------------|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode | Frequency Range (MHz) | Operating Frequency (MHz) | Modulation Type |
| 2.4GHz WLAN | 2400-2483.5 | 2412-2462 | 802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |
| 5GHz WLAN | 5150-5250 5250-5350 5470-5725 5725-5850 | 5180-5240 5260-5320 5500-5720 5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) |

1.2 Table for Multiple Model Name

The EUT has two model names which are identical to each other in all aspects except for the following table:

| Model Name | Description |
|------------|---------------------------------------------------------------------------------------|
| EA9300 | All the models are identical, the different model names served as marketing strategy. |
| EA9250 | |

Note: From the above models, model: EA9300 was selected as representative model for the test and its data was recorded in this report.

1.3 Table for Multiple Source

The EUT has two Source names which are identical to each other in all aspects except for the following table:

| Source | Brand Name | VENDORNO | PARTDESC |
|---------------|------------|-----------------|---------------------------------------------------------------------|
| First source | SK HYNIX | H5TC2G63GFR-PBA | MEMORY,SDRAM DDR3,128MX16,FBGA, 96PIN,H5TC2G63GFR-PBA,0~+95,CLASS 2 |
| Second source | WINBOND | W632GU6KB-12 | MEMORY,SDRAM DDR3,128MX16,WBGA, 96PIN,W632GU6KB,0~+85,CLASS 2 |



1.4 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FA6D1310
Below is the table for the change of the product with respect to the original one.

| Modifications |
|--------------------------------------------------------------------------------------------------------------------------|
| Add Band 2 and Band 3 (5250~5350 MHz, 5470~5725 MHz) for this device, and it evaluated for Maximum Permissible Exposure. |

Note: Maximum Permissible Exposure of 2.4GHz Band and 5GHz Band 1/4 are based on original test report.

1.5 Testing Location

| Testing Location | | |
|-------------------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973 |
| <input checked="" type="checkbox"/> | JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085 |

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-100,000 | | | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 32 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tune-up EIRP (dBm) | Tune-up EIRP (W) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) |
|--------------------------|----------|-------------|------------|--------------------|------------------|---------------|-------------------------|-------------------------------|
| 2.4G;G1D (Radio2) | 6.35 | 29.52 | 35.87 | 36.00 | 3.98107 | 32 | 0.30953 | 1.00000 |
| 5.2G;D1D (Band 1/Radio3) | 7.18 | 28.79 | 35.97 | 36.00 | 3.98107 | 32 | 0.30953 | 1.00000 |
| 5.3G;D1D (Band 2/Radio3) | 7.18 | 22.74 | 29.92 | 30.00 | 1.00000 | 32 | 0.07775 | 1.00000 |
| 5.6G;D1D (Band 3/Radio1) | 6.62 | 23.33 | 29.95 | 30.00 | 1.00000 | 32 | 0.07775 | 1.00000 |
| 5.8G;D1D (Band 4/Radio1) | 6.62 | 29.18 | 35.80 | 36.00 | 3.98107 | 32 | 0.30953 | 1.00000 |

| Mode | DG (dBi) | Power (dBm) | EIRP (dBm) | Tune-up EIRP (dBm) | Tune-up EIRP (W) | Distance (cm) | S (mW/cm ²) | S Limit (mW/cm ²) | Ratio (S/Limit) |
|--------------------------|----------|-------------|------------|--------------------|------------------|---------------|-------------------------|-------------------------------|-----------------|
| 2.4G;G1D (Radio2) | 6.35 | 29.52 | 35.87 | 36.00 | 3.98107 | 32 | 0.310 | 1.00000 | 0.30953 |
| 5.2G;D1D (Band 1/Radio3) | 7.18 | 28.79 | 35.97 | 36.00 | 3.98107 | 32 | 0.310 | 1.00000 | 0.30953 |
| 5.8G;D1D (Band 4/Radio1) | 6.62 | 29.18 | 35.80 | 36.00 | 3.98107 | 32 | 0.310 | 1.00000 | 0.30953 |
| | | | | | | | | Sum Ratio | 0.92859 |
| | | | | | | | | Ratio Limit | 1 |