



CH11 БŢ Span 1.5 MHz -17.00 dBm 2.462903000 GHz ¥ Marker 1 [T1] *VBW 30 kHz *SWT 500 s *RBW 3 kHz 145 150 kHz/ đb 30 * Att Center 2.462903 GHz đb 0.5 20.5 dBm Offset -20-01 Ref --50--- 60--02--10--30--40-20 10 1 РК ИТЕМ



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 1MHz and 1kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



4.6.6 TEST RESULTS (A)

The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

For test mode A

NOTE:

The band edge emission plot on the following 1~2 pages show 57.12dB delta between carrier maximum power and local maximum emission in restrict band (2.3898GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 105.50dBuV/m, so the maximum field strength in restrict band is 105.50-57.12=48.38dBuV/m which is under 54dBuV/m limit.

The band edge emission plot on the following 3~4 pages show 56.94dB delta between carrier maximum power and local maximum emission in restrict band (2.4847GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 105.22BuV/m, so the maximum field strength in restrict band is 105.22-56.94=48.28dBuV/m which is under 54dBuV/m limit.


For test mode B

NOTE:


The band edge emission plot on the following 1~2 pages show 57.12dB delta between carrier maximum power and local maximum emission in restrict band (2.3898GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 101.24dBuV/m, so the maximum field strength in restrict band is 101.24-57.12=44.12dBuV/m which is under 54dBuV/m limit.

The band edge emission plot on the following 3~4 pages show 56.94dB delta between carrier maximum power and local maximum emission in restrict band (2.4847GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 101.12dBuV/m, so the maximum field strength in restrict band is 101.12-56.94=44.18dBuV/m which is under 54dBuV/m limit.





















4.6.7 TEST RESULTS (B)

The spectrum plots are attached on the following 4 pages. D2 line indicates the highest level and D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

For test mode A

NOTE:

The band edge emission plot on the following 1~2 pages show 49.72dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 101.60dBuV/m, so the maximum field strength in restrict band is 101.60-49.72=51.88dBuV/m which is under 54dBuV/m limit.

The band edge emission plot on the following 3~4 pages show 49.69dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 103.00dBuV/m, so the maximum field strength in restrict band is 103.00-49.69=53.31dBuV/m which is under 54dBuV/m limit.


For test mode B

NOTE:


The band edge emission plot on the following 1~2 pages show 49.72dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 99.17BuV/m, so the maximum field strength in restrict band is 99.17-49.72=49.45dBuV/m which is under 54dBuV/m limit.

The band edge emission plot on the following 3~4 pages show 49.69B delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 97.23dBuV/m, so the maximum field strength in restrict band is 97.23-49.69=47.54dBuV/m which is under 54dBuV/m limit.





















4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION


The antenna used in this product is Dipole antenna with SMA connector. And the maximum Gain of this antenna is 7dBi.



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST For test mode A










RADIATED EMISSION TEST For test mode A n n n n 930615L08 m m T 930615L0





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP, UL	
Germany	TUV Rheinland	
Japan	VCCI	
Norway	NEMKO	
Canada	INDUSTRY CANADA, CSA	
R.O.C.	CNLA, BSMI, DGT	
Netherlands	Telefication	
Singapore	PSB, GOST-ASIA(MOU)	
Russia	CERTIS(MOU)	

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

<u>www.adt.com.tw/index.5/phtml</u>. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab: Tel: 886-2-26052180 Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab: Tel: 886-3-3183232 Fax: 886-3-3185050

Linko RF Lab. Tel: 886-3-3270910 Fax: 886-3-3270892

Email: <u>service@mail.adt.com.tw</u> Web Site: <u>www.adt.com.tw</u>

The address and road map of all our labs can be found in our web site also.

Report Format Version 1.0