

## RF Exposure Report

**Report No.:** SA140220D03D

**FCC ID:** Q87-LAPAC1200

**Test Model:** LAPAC1200

**Received Date:** May 4, 2016

**Test Date:** May 4 ~ 11, 2016

**Issued Date:** May 19, 2016

**Applicant:** Linksys LLC

**Address:** 121 Theory Drive Irvine California 92617 United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan  
(R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
<b>3 Calculation Result Of Maximum Conducted Power</b> .....	<b>6</b>

### Report Issue History Record

Issue No.	Description	Date Issued
SA140220D03	Original	Apr. 15, 2014
SA140220D03C	Upgraded the standard to section 15.407 under new rule for U-NII-1 and U-NII-3 band.	May 4, 2016
SA140220D03D	Upgraded the standard to section 15.407 under new rule (16-24) for U-NII-1 and U-NII-3 band.	May 19, 2016

### Release Control Record

Issue No.	Description	Date Issued
SA140220D03D	Original release.	May 19, 2016

## 1 Certificate of Conformity

**Product:** AC1200 Dual Band Access Point

**Brand:** Linksys

**Test Model:** LAPAC1200

**Sample Status:** Engineering sample

**Applicant:** Linksys LLC

**Test Date:** May 4 ~ 11, 2016

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D03

KDB 447498 D01

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**



, **Date:**

May 19, 2016

Annie Chang / Senior Specialist

**Approved by :**



, **Date:**

May 19, 2016

Rex Lai / Assistant Manager

## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 25cm away from the body of the user.

So, this device is classified as **Mobile Device**.

### 3 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412 ~ 2462 (Original Approved)	28.90	5.01	25	0.3133	1
5180 ~ 5240	25.75	5.01	25	0.1517	1
5745 ~ 5825	27.36	5.01	25	0.2197	1

**NOTE:** 1. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi}$   
 2. Driver Version: v1.1.00.005

#### CONCLUSION:

Both of the modules can transmit simultaneously, the formula of calculated the MPE is:

$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

$\text{WLAN (2.4G)} + \text{WLAN (5.0G)} = 0.3133/1 + 0.2197/1 = 0.5330$

**Therefore, the maximum calculation of this situation is 0.5330, which is less than the “1” limit.**

--- END ---