



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Linksys LLC
Applicant Address	131 Theory Drive Irvine California 92617 United States
FCC ID	Q87-LAPAC1750PO
Manufacturer's company	Linksys LLC
Manufacturer Address	131 Theory Drive Irvine California 92617 United States

Product Name	AC1750 Pro Dual Band Access Point
Brand Name	Linksys
Model No.	LAPAC1750PRO
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Mar. 11, 2014
Final Test Date	Apr. 23, 2014
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g and IEEE 802.11a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01, KDB 662911 D01 v02r01, KDB644545 D01v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna.....	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes.....	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units	11
3.8. Table for Parameters of Test Software Setting	12
3.9. EUT Operation during Test	14
3.10. Duty Cycle.....	15
3.11. Test Configurations	21
4. TEST RESULT	25
4.1. AC Power Line Conducted Emissions Measurement.....	25
4.2. Maximum Conducted Output Power Measurement.....	29
4.3. Power Spectral Density Measurement	33
4.4. 6dB Spectrum Bandwidth Measurement	56
4.5. Radiated Emissions Measurement	67
4.6. Emissions Measurement	101
4.7. Antenna Requirements	138
5. LIST OF MEASURING EQUIPMENTS	139
6. MEASUREMENT UNCERTAINTY.....	141
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3
APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT	C1 ~ C3

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR431102AA	Rev. 01	Initial issue of report	Apr. 29, 2014



1. CERTIFICATE OF COMPLIANCE

Product Name : AC1750 Pro Dual Band Access Point
Brand Name : Linksys
Model No. : LAPAC1750PRO
Applicant : Linksys LLC
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 11, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'. The signature is written in a cursive style and is positioned above a horizontal line.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	11.01 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.02 dB
4.3	15.247(e)	Power Spectral Density	Complies	2.98 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.12 dB
4.6	15.247(d)	Band Edge Emissions	Complies	1.02 dB
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter or PoE
Modulation	see the below table for IEEE 802.11n/ac
Data Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n/ac
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	<u>For 2.4GHz Band:</u> 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth <u>For 5GHz Band:</u> 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth ; 1 for 80MHz bandwidth
Channel Band Width (99%)	<u>For 2.4GHz Band:</u> MCS0 (HT20): 17.76 MHz ; MCS0 (HT40): 36.32 MHz <u>For 5GHz Band:</u> <For Non-Beamforming Mode> 802.11ac MCS0/Nss1 (VHT20): 27.36 MHz ; 802.11ac MCS0/Nss1 (VHT40): 55.20 MHz ; 802.11ac MCS0/Nss1 (VHT80): 76.48 MHz <For Beamforming Mode> 802.11ac MCS2/Nss1 (VHT80): 77.44 MHz
Maximum Conducted Output Power	<u>For 2.4GHz Band:</u> MCS0 (HT20): 27.48 dBm ; MCS0 (HT40): 18.22 dBm <u>For 5GHz Band:</u> <For Non-Beamforming Mode> 802.11ac MCS0/Nss1 (VHT20): 28.80 dBm ; 802.11ac MCS0/Nss1 (VHT40): 28.67 dBm ; 802.11ac MCS0/Nss1 (VHT80): 24.87 dBm <For Beamforming Mode> 802.11ac MCS2/Nss1 (VHT20): 26.33 dBm ; 802.11ac MCS2/Nss1 (VHT40): 26.22 dBm ; 802.11ac MCS2/Nss1 (VHT80): 25.96 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a/b/g

Items	Description
Product Type	802.11a/b/g: WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From power adapter or PoE
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 10.16 MHz ; 11g: 16.56 MHz ; 11a: 27.68 MHz
Maximum Conducted Output Power	11b: 27.04 dBm ; 11g: 27.36 dBm ; 11a: 28.80 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Items	Description
Beamforming Function	<input checked="" type="checkbox"/> With beamforming for 802.11n/ac in 5GHz. <input type="checkbox"/> Without beamforming

Antenna and Band width

Antenna	Three (TX)		
	20 MHz	40 MHz	80 MHz
IEEE 802.11a	V	X	X
IEEE 802.11b	V	X	X
IEEE 802.11g	V	X	X
IEEE 802.11n	V	V	X
IEEE 802.11ac	V	V	V

IEEE 11n/ac Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS0-23
802.11n (HT40)	3	MCS0-23
802.11ac (VHT20)	3	MCS 0-9/Nss1-3
802.11ac (VHT40)	3	MCS 0-9/Nss1-3
802.11ac (VHT80)	3	MCS 0-9/Nss1-3

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

Power	Brand	Model	Rating
Adapter 1 (Fixed plug)	HON-KWANG	HK-AJ-120A200-US	INPUT: 100-240V~50-60Hz, 0.8A OUTPUT: 12V, 2A
Adapter 2 (Interchangeable plug)	HON-KWANG	HK-AX-120A200-CP	INPUT: 100-240V~50-60Hz, 0.8A OUTPUT: 12V, 2A
Others			
FCC Plug*1 (only for Adapter 2)			
Cradle*1			

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz B4
1	Airgain	M2410DCR-G200U	PIFA Antenna	I-PEX	4.3	-
	Airgain	M2410DCR-G130U	PIFA Antenna	I-PEX	-	4.4
2	Airgain	M2410DCR-G65U	PIFA Antenna	I-PEX	4.4	-
	Airgain	M2410DCR-G65U	PIFA Antenna	I-PEX	-	5.2
3	Airgain	M2410DCR-G130U	PIFA Antenna	I-PEX	4.1	-
	Airgain	M2410DCR-G200U	PIFA Antenna	I-PEX	-	5.0

Note: The EUT has three antennas.

For 2.4GHz

For IEEE 802.11b/g/n mode (3TX/3RX)

Ant. 1, Ant. 2 and Ant. 3 can be used as transmitting/receiving antennas.


Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.

For 5GHz

For IEEE 802.11a/n/ac mode (3TX/3RX)

Ant. 1, Ant. 2 and Ant. 3 can be used as transmitting/receiving antennas.

Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band:

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Power Spectral Density	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
6dB Spectrum Bandwidth	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Band Edge Emissions	11n HT20	MCS0	1/6/11	1+2+3
	11n HT40	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3

For 5GHz Band:

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	11ac VHT20	MCS0/Nss1	149/157/165	1+2+3
	11ac VHT40	MCS0/Nss1	151/159	1+2+3
	11ac VHT80	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Power Spectral Density	11ac VHT20	MCS0/Nss1	149/157/165	1+2+3
	11ac VHT40	MCS0/Nss1	151/159	1+2+3
	11ac VHT80	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
6dB Spectrum Bandwidth	11ac VHT20	MCS0/Nss1	149/157/165	1+2+3
	11ac VHT40	MCS0/Nss1	151/159	1+2+3
	11ac VHT80	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Radiated Emissions Below 1GHz	Normal Link	-	-	-
Radiated Emissions Above 1GHz	11ac VHT20	MCS0/Nss1	149/157/165	1+2+3
	11ac VHT40	MCS0/Nss1	151/159	1+2+3
	11ac VHT80	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3
Band Edge Emissions	11ac VHT20	MCS0/Nss1	149/157/165	1+2+3
	11ac VHT40	MCS0/Nss1	151/159	1+2+3
	11ac VHT80	MCS0/Nss1	155	1+2+3
	11a/BPSK	6 Mbps	149/157/165	1+2+3

Note 1: VHT20/VHT40 covers HT20/HT40, due to same modulation.

Note 2: There are two modes of EUT, one is beamforming mode, and the other is non-beamforming mode for 802.11n/ac in 5GHz, Beamforming mode and non-beamforming mode has been test and record in this test report.

Note 3: VHT20/VHT40 didn't test 6dB Spectrum Bandwidth for beamforming mode, because beamforming mode's output power was less than that of non-beamforming mode in 5GHz band 4.

The following test modes were performed for all tests:

For Conducted Emission test:

Mode 1. EUT + Adapter 1

Mode 2. EUT + Adapter 2

Mode 3. EUT + PoE

Mode 3 is the worst case, so it was selected to record in this test report.

For Radiated Emission test below 1GHz:

Mode 1. Laying of EUT with cradle + Adapter 1

Mode 2. Stand of EUT without cradle + Adapter 1

Mode 2 has been evaluated to be the worst case among Mode 1~2, thus measurement for Mode 3 ~ 4 will follow this same test mode.

Mode 3. Stand of EUT without cradle + Adapter 2

Mode 4. Stand of EUT without cradle + PoE

For Radiated Emission test below 1GHz:

Mode 2 generated the worst test result, so it was recorded in this report.

For Radiated Emission test above 1GHz:

Mode 1. Laying of EUT

Mode 2. Stand of EUT

Mode 2 generated the worst test result, so it was recorded in this report.

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
TEL:	886-3-656-9065			
FAX:	886-3-656-9085			
Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Supporting Units

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook *4	DELL	E6430	DoC
PoE	Linksys	LACP130	N/A

For Test Site No: 03CH01-CB / Below 1GHz

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1340	E2K4965AGNM
Notebook	DELL	E6430	DoC
Notebook	DELL	D420	E2KWM3945ABG
Notebook	DELL	M1330	E2K4965AGNM

For Test Site No: 03CH01-CB / Above 1GHz <For Non-Beamforming Mode>

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1340	E2K4965AGNM

For Test Site No: 03CH01-CB / Above 1GHz <For Beamforming Mode>

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D420	E2KWM3945ABG
Notebook	DELL	M1330	E2K4965AGNM
WLAN AC Dongle	Netgear	A6200	PY31220200

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	DoC

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

<For Non-Beamforming Mode>

For 2.4GHz Band

Power Parameters of IEEE 802.11n MCS0 HT20

Test Software Version	Mtool_2.0.0.6		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 HT20	55	88	56

Power Parameters of IEEE 802.11n MCS0 HT40

Test Software Version	Mtool_2.0.0.6		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 HT40	45	57	53

Power Parameters of IEEE 802.11b/g

Test Software Version	Mtool_2.0.0.6		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	75	88	81
IEEE 802.11g	57	88	56

For 5GHz Band

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

Test Software Version	Mtool_2.0.0.6		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0/Nss1 VHT20	100	100	100

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

Test Software Version	Mtool_2.0.0.6	
Frequency	5755 MHz	5795 MHz
MCS0/Nss1 VHT40	90	100

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

Test Software Version	Mtool_2.0.0.6
Frequency	5775 MHz
MCS0/Nss1 VHT80	84

Power Parameters of IEEE 802.11a

Test Software Version	Mtool_2.0.0.6		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	100	100	100

<For Beamforming Mode>

For 5GHz Band

Power Parameters of IEEE 802.11ac MCS2/Nss1VHT20

Test Software Version	Mtool_2.0.0.6		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS2/Nss1 VHT20	90	90	98

Power Parameters of IEEE 802.11ac MCS2/Nss1 VHT40

Test Software Version	Mtool_2.0.0.6	
Frequency	5755 MHz	5795 MHz
MCS2/Nss1 VHT40	91	91

Power Parameters of IEEE 802.11ac MCS2/Nss1 VHT80

Test Software Version	Mtool_2.0.0.6
Frequency	5775 MHz
MCS2/Nss1 VHT80	91

3.9. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

For Conducted Mode:

The EUT was programmed to be in continuously transmitting mode.

For Radiated Mode:

During the test, the following programs under WIN XP were executed.

The program was executed as follows:


1. During the test, the EUT operation to normal function.
2. Executed command fixed test channel under DOS.
3. Executed "Lantest.exe " to link with the remote workstation to receive and transmit packet by WLAN AC Dongle and transmit duty cycle no less 98%

3.10. Duty Cycle

<For non-beamforming mode>


For 2.4GHz Band:

IEEE 802.11n MCS0 HT20




Date: 1.APR.2014 21:50:09

IEEE 802.11n MCS0 HT40




Date: 1.APR.2014 21:51:26

IEEE 802.11b



Date: 1.APR.2014 21:47:32


IEEE 802.11g



Date: 1.APR.2014 21:48:27


For 5GHz Band:

IEEE 802.11ac MCS0/Nss1 VHT20




Date: 1.APR.2014 21:54:18

IEEE 802.11ac MCS0/Nss1 VHT40




Date: 1.APR.2014 21:55:34

IEEE 802.11ac MCS0/Nss1 VHT80



Date: 1. APR. 2014 21:59:32

IEEE 802.11a




Date: 1. APR. 2014 21:52:53

<For beamforming mode>


For 5GHz Band:

IEEE 802.11ac MCS2/Nss1 VHT20




Date: 1.APR.2014 21:54:18

IEEE 802.11ac MCS2/Nss1 VHT40



Date: 1.APR.2014 21:55:34


IEEE 802.11ac MCS2/Nss1 VHT80



Date: 1.APR.2014 21:59:32

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length(m)
1	Power Cable	No	1.8m
2	RJ-45 Cable	No	0.8m
3	RJ-45 Cable	No	10m
4	RJ-45 Cable	No	10m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz




Item	Connection	Shield	Length(m)
1	Power Cable	No	1.5m
2	RJ-45 Cable	No	10m
3	RJ-45 Cable	No	10m

Test Configuration: above 1GHz <For Non-Beamforming Mode>



Item	Connection	Shield	Length(m)
1	Power Cable	No	1.5m
2	RJ-45 Cable	No	10m

Test Configuration: above 1GHz <For Beamforming Mode>



Item	Connection	Shield	Length(m)
1	Power Cable	No	1.5m
2	RJ-45 Cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	54%
Test Engineer	Sollo Luo	Phase	Line
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.18152	52.76	-11.65	64.42	0.15	52.42	0.19	LINE	QP
2	0.18152	38.99	-15.42	54.42	0.15	38.65	0.19	LINE	AVERAGE
3	0.21055	36.96	-26.22	63.18	0.15	36.61	0.20	LINE	QP
4	0.21055	9.00	-44.18	53.18	0.15	8.65	0.20	LINE	AVERAGE
5	0.22676	46.74	-15.83	62.57	0.15	46.39	0.20	LINE	QP
6	0.22676	36.30	-16.27	52.57	0.15	35.95	0.20	LINE	AVERAGE
7	0.49673	38.58	-17.47	56.05	0.15	38.23	0.20	LINE	QP
8	0.49673	24.13	-21.92	46.05	0.15	23.78	0.20	LINE	AVERAGE
9	0.52934	36.79	-19.21	56.00	0.15	36.44	0.20	LINE	QP
10	0.52934	13.36	-32.64	46.00	0.15	13.01	0.20	LINE	AVERAGE
11	0.54355	41.98	-14.02	56.00	0.15	41.63	0.20	LINE	QP
12	0.54355	28.70	-17.30	46.00	0.15	28.35	0.20	LINE	AVERAGE
13	1.082	34.82	-21.18	56.00	0.16	34.45	0.20	LINE	QP
14	1.082	17.58	-28.42	46.00	0.16	17.21	0.20	LINE	AVERAGE
15	6.878	33.30	-26.70	60.00	0.32	32.67	0.30	LINE	QP
16	6.878	27.06	-22.94	50.00	0.32	26.43	0.30	LINE	AVERAGE

Temperature	24°C	Humidity	54%
Test Engineer	Sollo Luo	Phase	Neutral
Configuration	Normal Link	Test Mode	Mode 3



	Freq	Level	Over Limit	Limit Line	LISN Factor	Read Level	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dB	dBuV	dB		
1	0.18346	40.09	-14.23	54.33	0.07	39.83	0.19	NEUTRAL	AVERAGE
2	0.18346	51.01	-13.31	64.33	0.07	50.75	0.19	NEUTRAL	QP
3	0.49937	41.30	-14.71	56.01	0.07	41.03	0.20	NEUTRAL	QP
4	0.49937	27.46	-18.55	46.01	0.07	27.19	0.20	NEUTRAL	AVERAGE
5	0.79180	42.10	-13.90	56.00	0.08	41.82	0.20	NEUTRAL	QP
6	0.79180	33.34	-12.66	46.00	0.08	33.06	0.20	NEUTRAL	AVERAGE
7	0.83932	34.99	-11.01	46.00	0.08	34.71	0.20	NEUTRAL	AVERAGE
8	0.83932	43.99	-12.01	56.00	0.08	43.71	0.20	NEUTRAL	QP
9	0.86643	43.10	-12.90	56.00	0.08	42.82	0.20	NEUTRAL	QP
10	0.86643	26.98	-19.02	46.00	0.08	26.70	0.20	NEUTRAL	AVERAGE
11	1.203	34.90	-11.10	46.00	0.09	34.61	0.21	NEUTRAL	AVERAGE
12	1.203	44.43	-11.57	56.00	0.09	44.14	0.21	NEUTRAL	QP
13	2.133	32.02	-13.98	46.00	0.11	31.68	0.23	NEUTRAL	AVERAGE
14	2.133	44.00	-12.00	56.00	0.11	43.66	0.23	NEUTRAL	QP
15	6.523	38.05	-11.95	50.00	0.19	37.55	0.31	NEUTRAL	AVERAGE
16	6.523	44.69	-15.31	60.00	0.19	44.19	0.31	NEUTRAL	QP
17	6.841	36.29	-13.71	50.00	0.20	35.79	0.30	NEUTRAL	AVERAGE
18	6.841	43.05	-16.95	60.00	0.20	42.55	0.30	NEUTRAL	QP

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n/ac
Test Date	Apr. 01, 2014		

<For Non-Beamforming Mode>

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	13.49	12.89	13.27	17.99	30.00	Complies
6	2437 MHz	22.88	22.30	22.91	27.48	30.00	Complies
11	2462 MHz	13.53	13.41	13.77	18.34	30.00	Complies

Configuration IEEE 802.11n MCS0 HT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
3	2422 MHz	9.23	8.57	10.06	14.10	30.00	Complies
6	2437 MHz	13.46	13.00	13.85	18.22	30.00	Complies
9	2452 MHz	12.06	11.81	12.74	16.99	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	24.25	23.88	23.95	28.80	30.00	Complies
157	5785 MHz	24.27	23.76	23.85	28.74	30.00	Complies
165	5825 MHz	24.42	23.73	23.81	28.77	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
151	5755 MHz	22.01	21.76	21.81	26.63	30.00	Complies
159	5795 MHz	24.26	23.65	23.77	28.67	30.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
155	5775 MHz	20.00	20.07	20.21	24.87	30.00	Complies

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a/b/g
Test Date	Apr. 01, 2014		

Configuration IEEE 802.11b / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	18.77	18.46	18.49	23.35	30.00	Complies
6	2437 MHz	22.52	21.84	22.41	27.04	30.00	Complies
11	2462 MHz	20.18	19.81	20.57	24.97	30.00	Complies

Configuration IEEE 802.11g / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	13.84	13.55	13.83	18.51	30.00	Complies
6	2437 MHz	22.80	22.05	22.88	27.36	30.00	Complies
11	2462 MHz	13.58	13.26	13.83	18.33	30.00	Complies

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	24.32	23.86	23.87	28.79	30.00	Complies
157	5785 MHz	24.30	23.75	23.78	28.72	30.00	Complies
165	5825 MHz	24.44	23.80	23.80	28.80	30.00	Complies

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac
Test Date	Apr. 21, 2014		

<For Beamforming Mode>

Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	21.72	21.44	21.48	26.32	26.35	Complies
157	5785 MHz	21.88	21.47	21.32	26.33	26.35	Complies
165	5825 MHz	21.69	21.23	21.44	26.23	26.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

=9.65dBi > 6dBi, So Band1 Limit = 30-(9.65-6)=26.35dBm

Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
151	5755 MHz	21.56	21.28	21.38	26.18	26.35	Complies
159	5795 MHz	21.56	21.39	21.39	26.22	26.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

=9.65dBi > 6dBi, So Band1 Limit = 30-(9.65-6)=26.35dBm

Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Power (dBm)				Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
155	5775 MHz	21.25	21.07	21.25	25.96	26.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

=9.65dBi > 6dBi, So Band1 Limit = 30-(9.65-6)=26.35dBm

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD) and KDB 662911 D01 v02r01 section In-Band Power Spectral Density (PSD) Measurements option (b) Measure and sum spectral maximal across the outputs.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n/ac

<For Non-Beamforming Mode>

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	-13.63	-12.85	-15.03	-8.97	8.00	Complies
6	2437 MHz	-4.23	-3.80	-3.37	0.99	8.00	Complies
11	2462 MHz	-12.00	-13.64	-12.94	-8.04	8.00	Complies

Configuration IEEE 802.11n MCS0 HT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
3	2422 MHz	-18.70	-20.16	-19.24	-14.55	8.00	Complies
6	2437 MHz	-15.71	-14.35	-14.76	-10.13	8.00	Complies
9	2452 MHz	-16.62	-17.24	-15.74	-11.72	8.00	Complies

For 5GHz Band

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	-2.04	-3.20	-2.02	2.39	8.00	Complies
157	5785 MHz	-1.53	-3.23	-1.99	2.58	8.00	Complies
165	5825 MHz	-2.74	-3.80	-2.70	1.72	8.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
151	5755 MHz	-6.91	-7.52	-7.56	-2.55	8.00	Complies
159	5795 MHz	-5.91	-6.25	-6.26	-1.37	8.00	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
155	5775 MHz	-10.47	-12.04	-12.45	-6.80	8.00	Complies

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	-3.38	-3.54	-4.21	1.08	8.00	Complies
6	2437 MHz	-0.29	0.94	-0.01	5.02	8.00	Complies
11	2462 MHz	-2.36	-3.66	-1.75	2.25	8.00	Complies

Configuration IEEE 802.11g / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
1	2412 MHz	-11.99	-12.18	-11.26	-7.02	8.00	Complies
6	2437 MHz	-2.26	-3.44	-2.40	2.10	8.00	Complies
11	2462 MHz	-12.19	-12.85	-12.28	-7.66	8.00	Complies

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	-2.26	-2.80	-2.87	2.14	8.00	Complies
157	5785 MHz	-1.81	-2.92	-1.56	2.71	8.00	Complies
165	5825 MHz	-1.57	-3.50	-2.25	2.40	8.00	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac

<For Beamforming Mode>

For 5GHz Band

Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
149	5745 MHz	-4.42	-4.94	-5.44	-0.14	4.35	Complies
157	5785 MHz	-4.60	-4.46	-5.54	-0.07	4.35	Complies
165	5825 MHz	-6.40	-5.84	-6.38	-1.43	4.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

=9.65dBi > 6dBi, So Band 4 Limit = 8-(9.65-6)=4.35dBm/3kHz

Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
151	5755 MHz	-7.29	-7.41	-8.25	-2.86	4.35	Complies
159	5795 MHz	-7.12	-8.50	-8.11	-3.10	4.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$

=9.65dBi > 6dBi, So Band 4 Limit = 8-(9.65-6)=4.35dBm/3kHz

Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)				Power Density Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3	Total		
155	5775 MHz	-8.71	-10.16	-7.71	-3.98	4.35	Complies

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$


=9.65dBi > 6dBi, So Band 4 Limit = 8-(9.65-6)=4.35dBm/3kHz

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.


<For Non-Beamforming Mode>

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Ant. 1




Date: 1.APR.2014 20:49:00

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Ant. 2




Date: 1.APR.2014 20:49:43

Power Density Plot on Configuration IEEE 802.11n MCS0 HT20 / 2437 MHz / Ant. 3




Date: 1.APR.2014 20:50:36

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Ant. 1




Date: 1.APR.2014 21:00:13

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Ant. 2




Date: 1.APR.2014 21:02:57

Power Density Plot on Configuration IEEE 802.11n MCS0 HT40 / 2437 MHz / Ant. 3




Date: 1.APR.2014 21:06:20

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz / Ant. 1




Date: 1.APR.2014 21:25:22

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785MHz / Ant. 2




Date: 1.APR.2014 21:27:53

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz / Ant. 3




Date: 1.APR.2014 21:30:29

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Ant. 1




Date: 1.APR.2014 21:38:29

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Ant. 2




Date: 1.APR.2014 21:35:04

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5795 MHz / Ant. 3




Date: 1.APR.2014 21:33:42

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Ant. 1




Date: 1.APR.2014 21:40:42

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Ant. 2




Date: 1.APR.2014 21:42:09

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz / Ant. 3




Date: 1.APR.2014 21:43:29

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Ant. 1




Date: 1.APR.2014 18:58:39

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Ant. 2




Date: 1.APR.2014 18:57:37

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz / Ant. 3




Date: 1.APR.2014 18:54:09

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 1




Date: 1.APR.2014 19:15:34

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 2




Date: 1.APR.2014 19:16:22

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz / Ant. 3




Date: 1.APR.2014 19:17:08

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 1




Date: 1.APR.2014 21:12:07

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 2



Date: 1.APR.2014 21:15:36


Power Density Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 3



Date: 1.APR.2014 21:18:34


<For Beamforming Mode>

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / 5785 MHz / Ant. 1




Date: 23.APR.2014 15:12:45

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / 5785 MHz / Ant. 2




Date: 23.APR.2014 15:13:37

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / 5785 MHz / Ant. 3




Date: 23.APR.2014 15:14:41

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / 5755 MHz / Ant. 1




Date: 23.APR.2014 15:26:10

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / 5755 MHz / Ant. 2




Date: 23.APR.2014 15:25:02

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / 5755 MHz / Ant. 3




Date: 23.APR.2014 15:23:52

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / 5775 MHz / Ant. 1




Date: 21.APR.2014 20:37:07

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / 5775 MHz / Ant. 2



Date: 21.APR.2014 20:39:05

Power Density Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / 5775 MHz / Ant. 3



Date: 21.APR.2014 20:40:24

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

For Radiated 6dB Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout

For Radiated 6dB Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n/ac

<For Non-Beamforming Mode>

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 HT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	17.68	500	Complies
6	2437 MHz	16.96	17.76	500	Complies
11	2462 MHz	16.72	17.68	500	Complies

Configuration IEEE 802.11n MCS0 HT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.16	36.16	500	Complies
6	2437 MHz	36.32	36.32	500	Complies
9	2452 MHz	35.68	36.32	500	Complies

For 5GHz Band
Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	27.36	500	Complies
157	5785 MHz	16.40	25.76	500	Complies
165	5825 MHz	16.48	26.40	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.32	37.76	500	Complies
159	5795 MHz	36.32	55.20	500	Complies

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	76.16	76.48	500	Complies

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11 a/b/g

Configuration IEEE 802.11b / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.08	10.08	500	Complies
6	2437 MHz	8.16	10.16	500	Complies
11	2462 MHz	8.08	10.08	500	Complies

Configuration IEEE 802.11g / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	13.84	16.32	500	Complies
6	2437 MHz	15.04	16.56	500	Complies
11	2462 MHz	12.96	16.56	500	Complies

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.08	27.68	500	Complies
157	5785 MHz	15.68	26.16	500	Complies
165	5825 MHz	16.32	27.44	500	Complies

Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

Temperature	20°C	Humidity	52%
Test Engineer	Jim Huang	Configurations	IEEE 802.11ac

<For Beamforming Mode>


For 5GHz Band

Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	71.68	77.44	500	Complies


<For Non-Beamforming Mode>

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20 / 2412 MHz / Ant. 1 + Ant. 2 + Ant. 3




Date: 1.APR.2014 22:35:45

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40 / 2452 MHz / Ant. 1 + Ant. 2 + Ant. 3




Date: 1.APR.2014 22:43:13

**6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / 5785 MHz /
Ant. 1 + Ant. 2 + Ant. 3**




Date: 1. APR. 2014 22:48:48

**6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / 5755MHz /
Ant. 1 + Ant. 2 + Ant. 3**




Date: 1. APR. 2014 22:50:50

**6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / 5775 MHz /
Ant. 1 + Ant. 2 + Ant. 3**




Date: 1.APR.2014 22:53:19

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz / Ant. 1 + Ant. 2 + Ant. 3




Date: 1. APR. 2014 22:27:29

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz / Ant. 1 + Ant. 2 + Ant. 3



Date: 1. APR. 2014 22:34:25

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 1 + Ant. 2 + Ant. 3




Date: 1.APR.2014 22:46:13

<For Beamforming Mode>

6 dB Bandwidth Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / 5775 MHz /

Ant. 1 + Ant. 2 + Ant. 3



Date: 21.APR.2014 20:45:20

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	Normal Link
Test Date	Mar. 11, 2014	Test Mode	Mode 2

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	Normal Link
Test Mode	Mode 2		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	31.94	36.88	40.00	-3.12	46.34	0.65	17.69	27.80	Peak	400	0	HORIZONTAL
2	500.45	35.33	46.00	-10.67	43.13	2.67	17.63	28.10	Peak	400	0	HORIZONTAL
3	575.14	36.25	46.00	-9.75	43.07	2.80	18.48	28.10	Peak	400	0	HORIZONTAL
4	625.58	36.37	46.00	-9.63	42.69	2.90	18.85	28.07	Peak	400	0	HORIZONTAL
5	674.08	41.29	46.00	-4.71	47.27	3.04	19.01	28.03	Peak	400	0	HORIZONTAL
6	725.49	38.13	46.00	-7.87	43.62	3.15	19.26	27.90	Peak	400	0	HORIZONTAL

Vertical



Peak	Freq MHz	Level dBuV/m	Limit Line dBuV/m	Over Limit dB	Read Level dBuV	Cable Loss dB	Antenna Factor dB/m	Preamp Factor dB	Remark	A/Pos cm	T/Pos deg	Pol/Phase
1	47.46	36.61	40.00	-3.39	54.19	0.80	9.42	27.80	Peak	400	0	VERTICAL
2	79.47	36.38	40.00	-3.62	55.98	0.96	7.12	27.68	Peak	400	0	VERTICAL
3	500.45	36.19	46.00	-9.81	43.99	2.67	17.63	28.10	Peak	400	0	VERTICAL
4	524.70	35.82	46.00	-10.18	43.29	2.72	17.91	28.10	Peak	400	0	VERTICAL
5	575.14	34.44	46.00	-11.56	41.26	2.80	18.48	28.10	Peak	400	0	VERTICAL
6	725.49	34.69	46.00	-11.31	40.18	3.15	19.26	27.90	Peak	400	0	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

<For Non-Beamforming Mode>

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT20 CH 1 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4816.34	32.53	54.00	-21.47	28.52	5.85	33.36	35.20 Average	100	274	HORIZONTAL
2	4821.72	45.35	74.00	-28.65	41.29	5.87	33.39	35.20 Peak	100	274	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.99	32.41	54.00	-21.59	28.35	5.87	33.39	35.20 Average	100	50	VERTICAL
2	4828.62	45.09	74.00	-28.91	41.03	5.87	33.39	35.20 Peak	100	50	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT20 CH 6 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4867.05	45.24	74.00	-28.76	41.09	5.90	33.45	35.20	Peak	100	0	HORIZONTAL
2	4868.04	31.99	54.00	-22.01	27.82	5.92	33.45	35.20	Average	100	0	HORIZONTAL
3	7305.23	40.66	54.00	-13.34	32.47	7.13	36.48	35.42	Average	100	335	HORIZONTAL
4	7310.30	54.44	74.00	-19.56	46.23	7.13	36.51	35.43	Peak	100	335	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4872.37	45.42	74.00	-28.58	41.22	5.92	33.48	35.20	Peak	100	55	VERTICAL
2	4878.33	32.55	54.00	-21.45	28.35	5.92	33.48	35.20	Average	100	55	VERTICAL
3	7308.53	56.06	74.00	-17.94	47.85	7.13	36.51	35.43	Peak	122	209	VERTICAL
4	7309.43	42.69	54.00	-11.31	34.48	7.13	36.51	35.43	Average	122	209	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT20 CH 11 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	3282.59	47.19	74.00	-26.81	47.05	4.89	30.45	35.20	Peak	100	116	HORIZONTAL
2	3282.66	41.74	54.00	-12.26	41.60	4.89	30.45	35.20	Average	100	116	HORIZONTAL
3	4923.87	45.76	74.00	-28.24	41.41	5.97	33.58	35.20	Peak	100	185	HORIZONTAL
4	4924.09	32.32	54.00	-21.68	27.97	5.97	33.58	35.20	Average	100	185	HORIZONTAL
5	7385.60	49.67	74.00	-24.33	41.35	7.17	36.61	35.46	Peak	100	57	HORIZONTAL
6	7385.92	36.79	54.00	-17.21	28.47	7.17	36.61	35.46	Average	100	57	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	3282.59	51.92	74.00	-22.08	51.78	4.89	30.45	35.20	Peak	100	284	VERTICAL
2	3282.66	49.59	54.00	-4.41	49.45	4.89	30.45	35.20	Average	100	284	VERTICAL
3	4924.02	45.51	74.00	-28.49	41.16	5.97	33.58	35.20	Peak	100	273	VERTICAL
4	4924.23	32.56	54.00	-21.44	28.21	5.97	33.58	35.20	Average	100	273	VERTICAL
5	7385.77	49.83	74.00	-24.17	41.51	7.17	36.61	35.46	Peak	100	164	VERTICAL
6	7386.40	36.80	54.00	-17.20	28.48	7.17	36.61	35.46	Average	100	164	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT40 CH 3 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4848.17	44.65	74.00	-29.35	40.55	5.88	33.42	35.20	Peak	100	222	HORIZONTAL
2	4848.78	32.56	54.00	-21.44	28.46	5.88	33.42	35.20	Average	100	222	HORIZONTAL
3	7263.21	49.71	74.00	-24.29	41.59	7.10	36.43	35.41	Peak	100	84	HORIZONTAL
4	7274.85	36.60	54.00	-17.40	28.45	7.11	36.45	35.41	Average	100	84	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4838.55	45.71	74.00	-28.29	41.61	5.88	33.42	35.20	Peak	100	112	VERTICAL
2	4849.06	32.62	54.00	-21.38	28.52	5.88	33.42	35.20	Average	100	112	VERTICAL
3	7262.25	36.42	54.00	-17.58	28.30	7.10	36.43	35.41	Average	100	157	VERTICAL
4	7269.69	49.25	74.00	-24.75	41.12	7.11	36.43	35.41	Peak	100	157	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT40 CH 6 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4865.70	44.75	74.00	-29.25	40.60	5.90	33.45	35.20	Peak	100	273	HORIZONTAL
2	4880.41	32.01	54.00	-21.99	27.81	5.92	33.48	35.20	Average	100	273	HORIZONTAL
3	7307.80	36.74	54.00	-17.26	28.53	7.13	36.51	35.43	Average	100	109	HORIZONTAL
4	7309.14	49.86	74.00	-24.14	41.65	7.13	36.51	35.43	Peak	100	109	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4874.80	32.06	54.00	-21.94	27.86	5.92	33.48	35.20	Average	100	357	VERTICAL
2	4881.89	44.90	74.00	-29.10	40.70	5.92	33.48	35.20	Peak	100	357	VERTICAL
3	7305.74	36.58	54.00	-17.42	28.39	7.13	36.48	35.42	Average	100	320	VERTICAL
4	7311.93	49.47	74.00	-24.53	41.26	7.13	36.51	35.43	Peak	100	320	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT40 CH 9 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 22, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	3269.17	45.42	74.00	-28.58	45.29	4.88	30.45	35.20	Peak	100	299	HORIZONTAL
2	3269.27	39.77	54.00	-14.23	39.64	4.88	30.45	35.20	Average	100	299	HORIZONTAL
3	4921.71	32.56	54.00	-21.44	28.25	5.97	33.54	35.20	Average	100	109	HORIZONTAL
4	4923.58	46.14	74.00	-27.86	41.79	5.97	33.58	35.20	Peak	100	109	HORIZONTAL
5	7386.34	36.62	54.00	-17.38	28.30	7.17	36.61	35.46	Average	100	136	HORIZONTAL
6	7388.90	50.28	74.00	-23.72	41.96	7.17	36.61	35.46	Peak	100	136	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	3269.35	49.57	54.00	-4.43	49.44	4.88	30.45	35.20	Average	100	305	VERTICAL
2	3269.35	51.70	74.00	-22.30	51.57	4.88	30.45	35.20	Peak	100	305	VERTICAL
3	4921.45	32.63	54.00	-21.37	28.32	5.97	33.54	35.20	Average	100	218	VERTICAL
4	4921.55	46.21	74.00	-27.79	41.90	5.97	33.54	35.20	Peak	100	218	VERTICAL
5	7381.27	36.71	54.00	-17.29	28.39	7.16	36.61	35.45	Average	100	176	VERTICAL
6	7385.98	50.57	74.00	-23.43	42.25	7.17	36.61	35.46	Peak	100	176	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 149 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11485.40	54.66	74.00	-19.34	41.00	9.24	39.50	35.08 Peak	119	337	HORIZONTAL
2	11489.70	43.01	54.00	-10.99	29.35	9.24	39.50	35.08 Average	119	337	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11488.30	43.68	54.00	-10.32	30.02	9.24	39.50	35.08 Average	137	20	VERTICAL
2	11489.50	55.86	74.00	-18.14	42.20	9.24	39.50	35.08 Peak	137	20	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 157 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.70	54.46	74.00	-19.54	40.82	9.26	39.47	35.09	Peak	111	28	HORIZONTAL
2	11569.90	43.42	54.00	-10.58	29.78	9.26	39.47	35.09	Average	111	28	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.40	44.50	54.00	-9.50	30.86	9.26	39.47	35.09	Average	109	58	VERTICAL
2	11569.80	57.00	74.00	-17.00	43.36	9.26	39.47	35.09	Peak	109	58	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT20 CH 165 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11649.80	43.24	54.00	-10.76	29.59	9.28	39.44	35.07 Average	112	35	HORIZONTAL
2	11654.90	54.89	74.00	-19.11	41.24	9.28	39.44	35.07 Peak	112	35	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11651.00	43.99	54.00	-10.01	30.34	9.28	39.44	35.07 Average	123	29	VERTICAL
2	11651.50	55.28	74.00	-18.72	41.63	9.28	39.44	35.07 Peak	123	29	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 151 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11509.72	53.78	74.00	-20.22	40.13	9.25	39.50	35.10 Peak	100	314	HORIZONTAL
2	11510.00	42.75	54.00	-11.25	29.10	9.25	39.50	35.10 Average	100	314	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11513.30	54.49	74.00	-19.51	40.84	9.25	39.50	35.10 Peak	113	12	VERTICAL
2	11513.70	42.37	54.00	-11.63	28.72	9.25	39.50	35.10 Average	113	12	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT40 CH 159 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11590.10	42.54	54.00	-11.46	28.88	9.27	39.47	35.08	Average	119	315 HORIZONTAL
2	11591.00	54.30	74.00	-19.70	40.64	9.27	39.47	35.08	Peak	119	315 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11590.90	42.63	54.00	-11.37	28.97	9.27	39.47	35.08	Average	129	19 VERTICAL
2	11598.10	54.70	74.00	-19.30	41.04	9.27	39.47	35.08	Peak	129	19 VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS0/Nss1 VHT80 CH 155 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 24, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11549.75	54.40	74.00	-19.60	40.74	9.26	39.49	35.09	Peak	100	154	HORIZONTAL
2	11550.00	42.30	54.00	-11.70	28.64	9.26	39.49	35.09	Average	100	154	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11550.40	53.70	74.00	-20.30	40.05	9.26	39.48	35.09	Peak	110	325	VERTICAL
2	11550.42	41.97	54.00	-12.03	28.32	9.26	39.48	35.09	Average	110	325	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 1 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.90	48.42	74.00	-25.58	44.36	5.87	33.39	35.20	Peak	173	120	HORIZONTAL
2	4823.93	39.18	54.00	-14.82	35.12	5.87	33.39	35.20	Average	173	120	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4823.87	45.13	74.00	-28.87	41.07	5.87	33.39	35.20	Peak	100	250	VERTICAL
2	4824.12	32.92	54.00	-21.08	28.86	5.87	33.39	35.20	Average	100	250	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 6 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4873.91	53.42	74.00	-20.58	51.11	4.22	34.57	2.31	Peak	291	143	HORIZONTAL
2	4873.96	50.23	54.00	-3.77	47.92	4.22	34.57	2.31	Average	291	143	HORIZONTAL
3	7309.40	57.37	74.00	-16.63	49.78	5.34	34.82	7.59	Peak	329	136	HORIZONTAL
4	7310.20	50.85	54.00	-3.15	43.26	5.34	34.82	7.59	Average	329	136	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	4873.94	39.51	54.00	-14.49	37.20	4.22	34.57	2.31	Average	188	139	VERTICAL
2	4874.04	47.31	74.00	-26.69	45.00	4.22	34.57	2.31	Peak	188	139	VERTICAL
3	7310.22	48.29	54.00	-5.71	40.70	5.34	34.82	7.59	Average	164	101	VERTICAL
4	7311.74	55.52	74.00	-18.48	47.94	5.34	34.83	7.58	Peak	164	101	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 11 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.86	50.19	74.00	-23.81	45.84	5.97	33.58	35.20 Peak	126	104	HORIZONTAL
2	4923.95	44.21	54.00	-9.79	39.86	5.97	33.58	35.20 Average	126	104	HORIZONTAL
3	7385.20	47.97	54.00	-6.03	39.65	7.17	36.61	35.46 Average	140	130	HORIZONTAL
4	7385.42	53.87	74.00	-20.13	45.55	7.17	36.61	35.46 Peak	140	130	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4923.74	49.80	74.00	-24.20	45.45	5.97	33.58	35.20 Peak	106	21	VERTICAL
2	4923.91	43.46	54.00	-10.54	39.11	5.97	33.58	35.20 Average	106	21	VERTICAL
3	7385.17	41.05	54.00	-12.95	32.73	7.17	36.61	35.46 Average	164	2	VERTICAL
4	7386.45	50.53	74.00	-23.47	42.21	7.17	36.61	35.46 Peak	164	2	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 1 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4820.35	32.92	54.00	-21.08	28.86	5.87	33.39	35.20 Average	100	5	HORIZONTAL
2	4826.08	45.35	74.00	-28.65	41.29	5.87	33.39	35.20 Peak	100	5	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4823.81	45.75	74.00	-28.25	41.69	5.87	33.39	35.20 Peak	100	360	VERTICAL
2	4824.05	32.70	54.00	-21.30	28.64	5.87	33.39	35.20 Average	100	360	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 6 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.68	32.51	54.00	-21.49	28.31	5.92	33.48	35.20	Average	100	13	HORIZONTAL
2	4874.04	45.28	74.00	-28.72	41.08	5.92	33.48	35.20	Peak	100	13	HORIZONTAL
3	7310.52	40.54	54.00	-13.46	32.33	7.13	36.51	35.43	Average	100	315	HORIZONTAL
4	7311.06	54.23	74.00	-19.77	46.02	7.13	36.51	35.43	Peak	100	315	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	4873.91	45.31	74.00	-28.69	41.11	5.92	33.48	35.20	Peak	100	343	VERTICAL
2	4874.45	32.67	54.00	-21.33	28.47	5.92	33.48	35.20	Average	100	343	VERTICAL
3	7305.17	42.13	54.00	-11.87	33.94	7.13	36.48	35.42	Average	109	198	VERTICAL
4	7305.23	59.02	74.00	-14.98	50.83	7.13	36.48	35.42	Peak	109	198	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 11 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	3282.60	46.49	74.00	-27.51	46.35	4.89	30.45	35.20	Peak	100	64	HORIZONTAL
2	3282.60	41.35	54.00	-12.65	41.21	4.89	30.45	35.20	Average	100	64	HORIZONTAL
3	4914.03	45.38	74.00	-28.62	41.09	5.95	33.54	35.20	Peak	100	287	HORIZONTAL
4	4918.42	32.67	54.00	-21.33	28.38	5.95	33.54	35.20	Average	100	287	HORIZONTAL
5	7377.19	49.99	74.00	-24.01	41.67	7.16	36.61	35.45	Peak	100	32	HORIZONTAL
6	7388.89	36.81	54.00	-17.19	28.49	7.17	36.61	35.46	Average	100	32	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	3282.61	49.64	54.00	-4.36	49.50	4.89	30.45	35.20	Average	100	304	VERTICAL
2	3282.65	52.13	74.00	-21.87	51.99	4.89	30.45	35.20	Peak	100	304	VERTICAL
3	4914.99	45.43	74.00	-28.57	41.14	5.95	33.54	35.20	Peak	100	120	VERTICAL
4	4918.55	32.85	54.00	-21.15	28.54	5.97	33.54	35.20	Average	100	120	VERTICAL
5	7381.90	50.11	74.00	-23.89	41.79	7.16	36.61	35.45	Peak	100	350	VERTICAL
6	7389.91	37.00	54.00	-17.00	28.68	7.17	36.61	35.46	Average	100	350	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 149 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11487.60	54.94	74.00	-19.06	41.28	9.24	39.50	35.08	Peak	115	36 HORIZONTAL
2	11489.80	43.22	54.00	-10.78	29.56	9.24	39.50	35.08	Average	115	36 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11491.50	43.74	54.00	-10.26	30.08	9.24	39.50	35.08	Average	102	335 VERTICAL
2	11492.50	55.49	74.00	-18.51	41.83	9.24	39.50	35.08	Peak	102	335 VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 157 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11569.30	55.84	74.00	-18.16	42.20	9.26	39.47	35.09	Peak	109	34 HORIZONTAL
2	11570.00	44.08	54.00	-9.92	30.44	9.26	39.47	35.09	Average	109	34 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	11571.90	44.97	54.00	-9.03	31.32	9.26	39.47	35.08	Average	101	18 VERTICAL
2	11572.00	57.01	74.00	-16.99	43.36	9.26	39.47	35.08	Peak	101	18 VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 165 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11650.00	43.27	54.00	-10.73	29.62	9.28	39.44	35.07	Average	107	52	HORIZONTAL
2	11658.30	54.00	74.00	-20.00	40.35	9.28	39.44	35.07	Peak	107	52	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11651.30	44.21	54.00	-9.79	30.56	9.28	39.44	35.07	Average	119	30	VERTICAL
2	11656.70	55.92	74.00	-18.08	42.27	9.28	39.44	35.07	Peak	119	30	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Beamforming Mode>

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1 VHT20 CH 149 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 10, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11486.65	56.24	74.00	-17.76	46.79	5.11	39.39	35.05	Peak	101	5	HORIZONTAL
2	11487.87	43.80	54.00	-10.20	34.35	5.11	39.39	35.05	Average	101	5	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.87	41.03	54.00	-12.97	31.58	5.11	39.39	35.05	Average	100	237	VERTICAL
2	11490.79	52.03	74.00	-21.97	42.58	5.11	39.39	35.05	Peak	100	237	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1VHT20 CH 157 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 10, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11568.41	39.20	54.00	-14.80	29.69	5.13	39.44	35.06	Average	100	249	HORIZONTAL
2	11571.27	51.62	74.00	-22.38	42.10	5.14	39.44	35.06	Peak	100	249	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11571.12	53.59	74.00	-20.41	44.07	5.14	39.44	35.06	Peak	131	335	VERTICAL
2	11574.71	42.03	54.00	-11.97	32.51	5.14	39.44	35.06	Average	131	335	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1 VHT20 CH 165 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 10, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11645.05	41.99	54.00	-12.01	32.42	5.16	39.48	35.07	Average	100	217	HORIZONTAL
2	11647.08	51.58	74.00	-22.42	42.02	5.16	39.48	35.08	Peak	100	217	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	11645.05	53.08	74.00	-20.92	43.51	5.16	39.48	35.07	Peak	119	263	VERTICAL
2	11647.85	43.04	54.00	-10.96	33.48	5.16	39.48	35.08	Average	119	263	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1 VHT40 CH 151 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 10, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11506.27	50.60	74.00	-23.40	41.13	5.12	39.40	35.05	Peak	100	274	HORIZONTAL
2	11510.10	39.47	54.00	-14.53	30.00	5.12	39.40	35.05	Average	100	274	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.10	56.12	74.00	-17.88	46.65	5.12	39.40	35.05	Peak	128	328	VERTICAL
2	11510.79	43.52	54.00	-10.48	34.05	5.12	39.40	35.05	Average	128	328	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1 VHT40 CH 159 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 10, 2014		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11589.38	50.63	74.00	-23.37	41.10	5.14	39.45	35.06	Peak	100	128	HORIZONTAL
2	11591.38	39.20	54.00	-14.80	29.67	5.14	39.45	35.06	Average	100	128	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11587.96	42.13	54.00	-11.87	32.60	5.14	39.45	35.06	Average	100	178	VERTICAL
2	11590.59	52.96	74.00	-21.04	43.43	5.14	39.45	35.06	Peak	100	178	VERTICAL

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11ac MCS2/Nss1 VHT80 CH 155 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Apr. 15, 2014		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	5133.10	47.55	74.00	-26.45	42.65	6.12	33.98	35.20	Peak	116	6	HORIZONTAL
2	5133.23	36.22	54.00	-17.78	31.32	6.12	33.98	35.20	Average	116	6	HORIZONTAL
3	11549.79	41.72	54.00	-12.28	28.06	9.26	39.49	35.09	Average	100	66	HORIZONTAL
4	11550.05	53.63	74.00	-20.37	39.97	9.26	39.49	35.09	Peak	100	66	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	5133.23	42.92	54.00	-11.08	38.02	6.12	33.98	35.20	Average	122	20	VERTICAL
2	5133.46	54.41	74.00	-19.59	49.51	6.12	33.98	35.20	Peak	122	20	VERTICAL
3	11549.62	53.49	74.00	-20.51	39.83	9.26	39.49	35.09	Peak	100	168	VERTICAL
4	11550.96	41.06	54.00	-12.94	27.41	9.26	39.48	35.09	Average	100	168	VERTICAL

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Radiated Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The radiated emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Radiated Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

For non-beamforming mode:

The EUT was programmed to be in continuously transmitting mode.

For beamforming mode:

The EUT was programmed to be in beamforming transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

<For Non-Beamforming Mode>

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT20 CH 1, 6, 11 / Ant. 1 + Ant. 2 + Ant. 3
Test date	Mar. 11, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	52.54	54.00	-1.46	20.40	4.09	28.05	0.00	Average	102	188	HORIZONTAL
2	2390.00	67.94	74.00	-6.06	35.80	4.09	28.05	0.00	Peak	102	188	HORIZONTAL
3	2407.80	99.50			67.30	4.11	28.09	0.00	Average	102	188	HORIZONTAL
4	2417.80	110.75			78.51	4.11	28.13	0.00	Peak	102	188	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.80	52.87	54.00	-1.13	20.73	4.09	28.05	0.00	Average	101	204	HORIZONTAL
2	2389.80	64.85	74.00	-9.15	32.71	4.09	28.05	0.00	Peak	101	204	HORIZONTAL
3	2432.20	109.67			77.42	4.12	28.13	0.00	Average	101	204	HORIZONTAL
4	2432.20	121.92			89.67	4.12	28.13	0.00	Peak	101	204	HORIZONTAL
5	2483.50	50.65	54.00	-3.35	18.23	4.16	28.26	0.00	Average	101	204	HORIZONTAL
6	2483.70	68.33	74.00	-5.67	35.91	4.16	28.26	0.00	Peak	101	204	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2457.80	100.97	54.00			4.14	28.22	0.00	Average	100	202	HORIZONTAL
2	2469.40	111.78	74.00			4.14	28.26	0.00	Peak	100	202	HORIZONTAL
3	2483.50	52.76	54.00	-1.24	20.34	4.16	28.26	0.00	Average	100	202	HORIZONTAL
4	2483.50	68.62	74.00	-5.38	36.20	4.16	28.26	0.00	Peak	100	202	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 HT40 CH 3, 6, 9 / Ant. 1 + Ant. 2 + Ant. 3
Test date	Mar. 11, 2014		

Channel 3

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2382.40	66.74	74.00	-7.26	34.65	4.08	28.01	0.00	Peak	100	187	HORIZONTAL
2	2383.20	52.23	54.00	-1.77	20.10	4.08	28.05	0.00	Average	100	187	HORIZONTAL
3	2417.60	103.20			70.96	4.11	28.13	0.00	Peak	100	187	HORIZONTAL
4	2418.00	91.55			59.31	4.11	28.13	0.00	Average	100	187	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.20	66.86	74.00	-7.14	34.72	4.09	28.05	0.00	Peak	100	203	HORIZONTAL
2	2390.00	52.82	54.00	-1.18	20.68	4.09	28.05	0.00	Average	100	203	HORIZONTAL
3	2434.60	97.56			65.26	4.12	28.18	0.00	Average	100	203	HORIZONTAL
4	2439.80	109.60			77.29	4.13	28.18	0.00	Peak	100	203	HORIZONTAL
5	2483.50	49.70	54.00	-4.30	17.28	4.16	28.26	0.00	Average	100	203	HORIZONTAL
6	2485.10	63.55	74.00	-10.45	31.09	4.16	28.30	0.00	Peak	100	203	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 9

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2450.00	97.06			64.75	4.13	28.18	0.00	Average	175	163	VERTICAL
2	2450.00	108.49			76.18	4.13	28.18	0.00	Peak	175	163	VERTICAL
3	2485.10	67.10	74.00	-6.90	34.64	4.16	28.30	0.00	Peak	175	163	VERTICAL
4	2485.50	52.94	54.00	-1.06	20.48	4.16	28.30	0.00	Average	175	163	VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.20	63.05	74.00	-10.95	30.91	4.09	28.05	0.00	Peak	100	150	VERTICAL
2	2390.00	52.91	54.00	-1.09	20.77	4.09	28.05	0.00	Average	100	150	VERTICAL
3	2412.80	111.20			79.00	4.11	28.09	0.00	Average	100	150	VERTICAL
4	2413.00	114.92			82.72	4.11	28.09	0.00	Peak	100	150	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2381.60	52.57	54.00	-1.43	20.48	4.08	28.01	0.00	Average	102	189	HORIZONTAL
2	2390.00	64.37	74.00	-9.63	32.23	4.09	28.05	0.00	Peak	102	189	HORIZONTAL
3	2436.20	115.12			82.82	4.12	28.18	0.00	Average	102	189	HORIZONTAL
4	2436.20	119.00			86.70	4.12	28.18	0.00	Peak	102	189	HORIZONTAL
5	2483.50	48.90	54.00	-5.10	16.48	4.16	28.26	0.00	Average	102	189	HORIZONTAL
6	2484.70	59.75	74.00	-14.25	27.33	4.16	28.26	0.00	Peak	102	189	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2461.20	112.64			80.28	4.14	28.22	0.00	Average	100	188	HORIZONTAL
2	2461.20	116.50			84.14	4.14	28.22	0.00	Peak	100	188	HORIZONTAL
3	2483.50	63.30	74.00	-10.70	30.88	4.16	28.26	0.00	Peak	100	188	HORIZONTAL
4	2483.70	52.98	54.00	-1.02	20.56	4.16	28.26	0.00	Average	100	188	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24°C	Humidity	55%
Test Engineer	Serway Li	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Mar. 11, 2014		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2389.80	66.12	74.00	-7.88	33.98	4.09	28.05	0.00	Peak	101	188	HORIZONTAL
2	2390.00	52.81	54.00	-1.19	20.67	4.09	28.05	0.00	Average	101	188	HORIZONTAL
3	2409.60	100.14			67.94	4.11	28.09	0.00	Average	101	188	HORIZONTAL
4	2410.80	109.94			77.74	4.11	28.09	0.00	Peak	101	188	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2387.20	66.68	74.00	-7.32	34.54	4.09	28.05	0.00	Peak	100	203	HORIZONTAL
2	2390.00	52.85	54.00	-1.15	20.71	4.09	28.05	0.00	Average	100	203	HORIZONTAL
3	2434.40	120.99			88.69	4.12	28.18	0.00	Peak	100	203	HORIZONTAL
4	2435.60	109.65			77.35	4.12	28.18	0.00	Average	100	203	HORIZONTAL
5	2483.50	50.24	54.00	-3.76	17.82	4.16	28.26	0.00	Average	100	203	HORIZONTAL
6	2483.50	62.61	74.00	-11.39	30.19	4.16	28.26	0.00	Peak	100	203	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2460.20	101.26			68.90	4.14	28.22	0.00	Average	100	203	HORIZONTAL
2	2460.80	111.36			79.00	4.14	28.22	0.00	Peak	100	203	HORIZONTAL
3	2483.50	52.69	54.00	-1.31	20.27	4.16	28.26	0.00	Average	100	203	HORIZONTAL
4	2483.70	68.76	74.00	-5.24	36.34	4.16	28.26	0.00	Peak	100	203	HORIZONTAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

<For Non-Beamforming Mode>


For Emission not in Restricted Band

Plot on Configuration IEEE 802.11n MCS0 HT20 / Reference Level




Date: 22.MAR.2014 14:38:41

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:39:15

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:39:35

Plot on Configuration IEEE 802.11n MCS0 HT20 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:40:12

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:22:56

Plot on Configuration IEEE 802.11n MCS0 HT40 / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:24:03

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Reference Level




Date: 24.MAR.2014 16:19:07

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:20:21

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 24.MAR.2014 16:21:21

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:23:39

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 24.MAR.2014 16:24:45

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Reference Level




Date: 24.MAR.2014 16:07:06

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:12:18

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 24.MAR.2014 16:13:09

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:08:22

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 24.MAR.2014 16:09:20

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Reference Level




Date: 24.MAR.2014 15:59:47

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / CH 155 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:00:48

Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / CH 155 / 5850MHz~40000MHz (down 30dBc)




Date: 24.MAR.2014 16:01:42

Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:44:44

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:45:23

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:45:05

Plot on Configuration IEEE 802.11g / Reference Level




Date: 22.MAR.2014 14:41:16

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:41:45

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:42:03

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 22.MAR.2014 14:42:51

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 22.MAR.2014 14:42:24

Plot on Configuration IEEE 802.11a / Reference Level




Date: 24.MAR.2014 16:28:38

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 24.MAR.2014 16:30:22

Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~4000MHz (down 30dBc)



Date: 24.MAR.2014 16:31:33


Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)



Date: 24.MAR.2014 16:32:46


<For Beamforming Mode>

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / Reference Level




Date: 10.APR.2014 04:12:34

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / CH 149 / 30MHz~5725MHz (down 30dBc)




Date: 10.APR.2014 04:14:32

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 10.APR.2014 04:15:29

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 10.APR.2014 04:16:27

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT20 / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 10.APR.2014 04:16:06

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / Reference Level




Date: 10.APR.2014 04:21:56

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / CH 151 / 30MHz~5725MHz (down 30dBc)




Date: 10.APR.2014 04:24:14

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / CH 151 / 5850MHz~40000MHz (down 30dBc)




Date: 10.APR.2014 04:25:54

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / CH 159 / 30MHz~5725MHz (down 30dBc)




Date: 10.APR.2014 04:27:14

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT40 / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 10.APR.2014 04:26:48

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / Reference Level




Date: 10.APR.2014 04:32:30

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / CH 155 / 30MHz~5725MHz (down 30dBc)



Date: 10.APR.2014 04:34:21

Plot on Configuration IEEE 802.11ac MCS2/Nss1 VHT80 / CH 155 / 5850MHz~40000MHz (down 30dBc)



Date: 10.APR.2014 04:34:53

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100355	9 kHz ~ 2.75 GHz	Apr. 12, 2013	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150 kHz ~ 100 MHz	Nov. 23, 2013	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Nov. 23, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	150 kHz ~ 30 MHz	Dec. 04, 2013	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	N.C.R.	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 01, 2013	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Dec. 17, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Dec. 16, 2013	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26GHz ~ 40GHz	Oct. 23, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R.	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R.	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2013	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz~40GHz	Nov. 29, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2013	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 18, 2013	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1= AMN/LISN VSWR 2=	-0.080	dB	U-shaped	0.060
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.173	dB	K=1	0.086
Cable loss	± 0.174	dB	K=2	0.087
Antenna gain	± 0.169	dB	K=2	0.084
Site imperfection	± 0.433	dB	Triangular	0.214
Pre-amplifier gain	± 0.366	dB	K=2	0.183
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.191	dB	K=1	0.095
Cable loss	±0.169	dB	K=2	0.084
Antenna gain	±0.191	dB	K=2	0.096
Site imperfection	±0.582	dB	Triangular	0.291
Pre-amplifier gain	±0.304	dB	K=2	0.152
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.186	dB	K=1	0.093
Cable loss	±0.167	dB	K=2	0.083
Antenna gain	±0.190	dB	K=2	0.095
Site imperfection	±0.488	dB	Triangular	0.244
Pre-amplifier gain	±0.269	dB	K=2	0.134
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	±0.038	dB	K=2	0.019
Attenuator	±0.047	dB	K=2	0.024
Power Meter specification	±0.300	dB	Triangular	0.150
Power Sensor specification	±0.300	dB	Rectangular	0.150
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				1.726