



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

| | |
|------------------------|--|
| Applicant's company | Linksys LLC |
| Applicant Address | 131 Theory Drive, Irvine, CA 92617, USA |
| FCC ID | Q87-RE6500 |
| Manufacturer's company | U-MEDIA Communications, Inc. |
| Manufacturer Address | 9F, No. 1, Jin-Shan 7th St., Hsinchu 300, Taiwan |

| | |
|-------------------|--|
| Product Name | Linksys AC1200 MAX Wi-Fi Range Extender |
| Brand Name | Linksys |
| Model No. | RE6500 |
| Test Rule Part(s) | 47 CFR FCC Part 15 Subpart E § 15.407 |
| Test Freq. Range | 5150 ~ 5250MHz |
| Received Date | Feb. 18, 2014 |
| Final Test Date | Jul. 08, 2014 |
| Submission Type | Class II Change |
| Operating Mode | Master and Client (without radar detection function) |

Statement

Test result included is for the IEEE 802.11n and IEEE 802.11 a/ac of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart E, KDB789033 D02 v01, KDB662911 D01 v02r01, KDB644545 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

| | |
|---|----------------|
| 1. CERTIFICATE OF COMPLIANCE | 1 |
| 2. SUMMARY OF THE TEST RESULT | 2 |
| 3. GENERAL INFORMATION | 3 |
| 3.1. Product Details..... | 3 |
| 3.2. Accessories..... | 5 |
| 3.3. Table for Filed Antenna..... | 6 |
| 3.4. Table for Carrier Frequencies | 7 |
| 3.5. Table for Test Modes..... | 7 |
| 3.6. Table for Testing Locations..... | 8 |
| 3.7. Table for Class II Change | 8 |
| 3.8. Table for Supporting Units | 9 |
| 3.9. Table for Parameters of Test Software Setting | 10 |
| 3.10. EUT Operation during Test | 11 |
| 3.11. Duty Cycle..... | 12 |
| 3.12. Test Configurations | 14 |
| 4. TEST RESULT | 16 |
| 4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement..... | 16 |
| 4.2. Maximum Conducted Output Power Measurement..... | 24 |
| 4.3. Power Spectral Density Measurement | 27 |
| 4.4. Radiated Emissions Measurement | 37 |
| 4.5. Band Edge Emissions Measurement | 53 |
| 4.6. Frequency Stability Measurement | 58 |
| 4.7. Antenna Requirements | 60 |
| 5. LIST OF MEASURING EQUIPMENTS | 61 |
| 6. MEASUREMENT UNCERTAINTY..... | 63 |
| APPENDIX A. TEST PHOTOS | A1 ~ A4 |
| APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE | B1 ~ B4 |
| APPENDIX C. RADIATED EMISSION CO-LOCATION REPORT | C1 ~ C3 |




History of This Test Report

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|---------------|---------|-------------------------|---------------|
| FR421849-01AB | Rev. 01 | Initial issue of report | Jul. 15, 2014 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

1. CERTIFICATE OF COMPLIANCE

Product Name : Linksys AC1200 MAX Wi-Fi Range Extender
Brand Name : Linksys
Model No. : RE6500
Applicant : Linksys LLC
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 18, 2014 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

| Applied Standard: 47 CFR FCC Part 15 Subpart E | | | | |
|--|--------------|--|----------|-------------|
| Part | Rule Section | Description of Test | Result | Under Limit |
| 4.1 | 15.407(a) | 26dB Spectrum Bandwidth and 99% Occupied Bandwidth | Complies | - |
| 4.2 | 15.407(a) | Maximum Conducted Output Power | Complies | 0.31 dB |
| 4.3 | 15.407(a) | Power Spectral Density | Complies | 0.01 dB |
| 4.4 | 15.407(b) | Radiated Emissions | Complies | 3.09 dB |
| 4.5 | 15.407(b) | Band Edge Emissions | Complies | 1.00 dB |
| 4.6 | 15.407(g) | Frequency Stability | Complies | - |
| 4.7 | 15.203 | Antenna Requirements | Complies | - |

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n/ac

| Items | Description |
|--------------------------------|--|
| Product Type | WLAN (2TX, 2RX) |
| Radio Type | Intentional Transceiver |
| Power Type | From power adapter |
| Modulation | see the below table for IEEE 802.11n/ac |
| Data Modulation | For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) |
| Data Rate (Mbps) | see the below table for IEEE 802.11n/ac |
| Frequency Range | 5150 ~ 5250MHz |
| Channel Number | 4 for 20MHz bandwidth ; 2 for 40MHz bandwidth 1 for 80MHz bandwidth |
| Channel Band Width (99%) | 802.11ac MCS0/Nss1 (VHT20): 33.60 MHz ; 802.11ac MCS0/Nss1 (VHT40): 59.20 MHz ; 802.11ac MCS0/Nss1 (VHT80): 74.88 MHz |
| Maximum Conducted Output Power | For Master function: 802.11ac MCS0/Nss1 (VHT20): 24.06 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.50 dBm ; 802.11ac MCS0/Nss1 (VHT80): 17.98 dBm For Client without radar detection function: 802.11ac MCS0/Nss1 (VHT20): 23.69 dBm ; 802.11ac MCS0/Nss1 (VHT40): 23.50 dBm ; 802.11ac MCS0/Nss1 (VHT80): 17.98 dBm |
| Carrier Frequencies | Please refer to section 3.4 |
| Antenna | Please refer to section 3.3 |

IEEE 802.11a

| Items | Description |
|--------------------------------|--|
| Product Type | WLAN (2TX, 2RX) |
| Radio Type | Intentional Transceiver |
| Power Type | From power adapter |
| Modulation | OFDM for IEEE 802.11a |
| Data Modulation | OFDM (BPSK / QPSK / 16QAM / 64QAM) |
| Data Rate (Mbps) | OFDM (6/9/12/18/24/36/48/54) |
| Frequency Range | 5150 ~ 5250MHz |
| Channel Number | 4 |
| Channel Band Width (99%) | 31.52 MHz |
| Maximum Conducted Output Power | For Master function: 24.07 dBm For Client without radar detection function: 23.28 dBm |
| Carrier Frequencies | Please refer to section 3.4 |
| Antenna | Please refer to section 3.3 |

| Items | Description | |
|----------------------|---|---|
| Communication Mode | <input checked="" type="checkbox"/> IP Based (Load Based) | <input type="checkbox"/> Frame Based |
| Beamforming Function | <input type="checkbox"/> With beamforming | <input checked="" type="checkbox"/> Without beamforming |

Antenna and Band width

| Antenna | Two (TX) | | |
|---------------|----------|--------|--------|
| | 20 MHz | 40 MHz | 80 MHz |
| IEEE 802.11a | V | X | X |
| IEEE 802.11n | V | V | X |
| IEEE 802.11ac | V | V | V |

IEEE 11n/ac Spec.

| Protocol | Number of Transmit Chains (NTX) | Data Rate / MCS |
|------------------|---------------------------------|-----------------|
| 802.11n (HT20) | 2 | MCS 0-15 |
| 802.11n (HT40) | 2 | MCS 0-15 |
| 802.11ac (VHT20) | 2 | MCS 0-9/Nss1-2 |
| 802.11ac (VHT40) | 2 | MCS 0-9/Nss1-2 |
| 802.11ac (VHT80) | 2 | MCS 0-9/Nss1-2 |

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).
Then EUT support HT20 and HT40.

Note 2: IEEE Std. 802.11ac modulation consists of VHT20, VHT40, VHT80 and VHT160 (VHT: Very High Throughput). Then EUT support VHT20, VHT40 and VHT80.

Note 3: Modulation modes consist of below configuration:
HT20/HT40: IEEE 802.11n, VHT20/VHT40/VHT80: IEEE 802.11ac

3.2. Accessories

| Power | Brand | Model | Rating |
|-----------------------------------|-------|------------------|---|
| Adapter 1 (Fixed plug) | Ktec | KSAS0121200100VU | INPUT: 100-240Vac, 50/60Hz, 0.4A OUTPUT: 12Vdc, 1.0A |
| Adapter 2 (Removable plug) | Ktec | KSAS0121200100D5 | INPUT: 100-240Vac, 50/60Hz, 0.4A OUTPUT: 12Vdc, 1.0A |
| Others | | | |
| Plug*1 (Only for Adapter 2's use) | | | |
| RJ-45 cable*1: Non-shielded, 1.5m | | | |

3.3. Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | | Cable Loss (dB) | | True Gain (dBi) | |
|------|--------|------------------|--------------|------------------|------------|------|-----------------|------|-----------------|------|
| | | | | | 2.4GHz | 5GHz | 2.4GHz | 5GHz | 2.4GHz | 5GHz |
| 1 | Joymax | TWX-1561RSXX-711 | Dipole | Reversed-SMA | 5.5 | 5.62 | 1.0 | 2.8 | 4.50 | 2.82 |
| 2 | Joymax | TWX-1561RSXX-711 | Dipole | Reversed-SMA | 5.5 | 5.62 | 2.8 | 1.0 | 2.70 | 4.62 |
| 3 | Cortec | AN2450-9220BRS | Dipole | SMA Male Reverse | 5.03 | 5.01 | 1.0 | 2.8 | 4.03 | 2.21 |
| 4 | Cortec | AN2450-9220BRS | Dipole | SMA Male Reverse | 5.03 | 5.01 | 2.8 | 1.0 | 2.23 | 4.01 |

Note:

Ant. 1~4 are the same type antennas. Only the higher gain antennas "Ant. 1~2" were tested and recorded in the report.

For 2.4GHz function:


For IEEE 802.11b/g/n mode (2TX/2RX)

Chain 1 and Chain 2 could transmit/receive simultaneously.

For 5GHz function:

For IEEE 802.11a/n/ac mode (2TX/2RX):

Chain 1 and Chain 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are three bandwidth systems.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

For 80MHz bandwidth systems, use Channel 42.

| Frequency Band | Channel No. | Frequency | Channel No. | Frequency |
|-------------------------|-------------|-----------|-------------|-----------|
| 5150~5250 MHz Band 1 | 36 | 5180 MHz | 44 | 5220 MHz |
| | 38 | 5190 MHz | 46 | 5230 MHz |
| | 40 | 5200 MHz | 48 | 5240 MHz |
| | 42 | 5210 MHz | - | - |

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items | Mode | | Data Rate | Channel | Chain |
|--|---------------|--------|-----------|----------|-------|
| AC Power Conducted Emission | Normal Link | | - | - | - |
| Max. Conducted Output Power | 11ac VHT20 | Band 1 | MCS0/Nss1 | 36/40/48 | 1+2 |
| | 11ac VHT40 | Band 1 | MCS0/Nss1 | 38/46 | 1+2 |
| | 11ac VHT80 | Band 1 | MCS0/Nss1 | 42 | 1+2 |
| | 11a/BPSK | Band 1 | 6Mbps | 36/40/48 | 1+2 |
| Power Spectral Density | 11ac VHT20 | Band 1 | MCS0/Nss1 | 36/40/48 | 1+2 |
| | 11ac VHT40 | Band 1 | MCS0/Nss1 | 38/46 | 1+2 |
| | 11ac VHT80 | Band 1 | MCS0/Nss1 | 42 | 1+2 |
| | 11a/BPSK | Band 1 | 6Mbps | 36/40/48 | 1+2 |
| 26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement | 11ac VHT20 | Band 1 | MCS0/Nss1 | 36/40/48 | 1+2 |
| | 11ac VHT40 | Band 1 | MCS0/Nss1 | 38/46 | 1+2 |
| | 11ac VHT80 | Band 1 | MCS0/Nss1 | 42 | 1+2 |
| | 11a/BPSK | Band 1 | 6Mbps | 36/40/48 | 1+2 |
| Radiated Emission Below 1GHz | Normal Link | | - | - | - |
| Radiated Emission Above 1GHz | 11ac VHT20 | Band 1 | MCS0/Nss1 | 36/40/48 | 1+2 |
| | 11ac VHT40 | Band 1 | MCS0/Nss1 | 38/46 | 1+2 |
| | 11ac VHT80 | Band 1 | MCS0/Nss1 | 42 | 1+2 |
| | 11a/BPSK | Band 1 | 6Mbps | 36/40/48 | 1+2 |
| Band Edge Emission | 11ac VHT20 | Band 1 | MCS0/Nss1 | 36/40/48 | 1+2 |
| | 11ac VHT40 | Band 1 | MCS0/Nss1 | 38/46 | 1+2 |
| | 11ac VHT80 | Band 1 | MCS0/Nss1 | 42 | 1+2 |
| | 11a/BPSK | Band 1 | 6Mbps | 36/40/48 | 1+2 |
| Frequency Stability | Un-modulation | | - | 40 | 1+2 |

The following test modes were performed for all tests:

For Radiated Emissions below 1GHz test:

Mode 1. EUT laying + Adapter 1

Mode 2. EUT standing + Adapter 1

Mode 1 has been evaluated to be the worst case among Mode 1~2, thus measurement for Mode 3 will follow this same test mode.

Mode 3. EUT laying + Adapter 2

Mode 1 is the worst case, so it was selected to record in this test report.

For Radiated Emissions above 1GHz test:

The EUT for Radiated emission test was performed at laying and standing position and the worst case was found from laying. So the measurement will follow this same test configuration.

Mode 1. EUT laying

For Co-location MPE and Radiated Emission Co-location Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to Appendix B) and Radiated Emission Co-location (please refer to Appendix C) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

| Test Site Location | | | | | |
|--------------------|--|----------|--------------|-------------|--------------|
| Address: | No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C. | | | | |
| TEL: | 886-3-656-9065 | | | | |
| FAX: | 886-3-656-9085 | | | | |
| Test Site No. | Site Category | Location | FCC Reg. No. | IC File No. | VCCI Reg. No |
| 03CH01-CB | SAC | Hsin Chu | 262045 | IC 4086D | - |
| TH01-CB | OVEN Room | Hsin Chu | - | - | - |

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: 421849

Below is the table for the change of the product with respect to the original one.

| Modifications | Performance Checking |
|--------------------------------|--|
| Adding 4 higher gain antennas. | 1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement 2. Maximum Conducted Output Power Measurement 3. Power Spectral Density Measurement 4. Radiated Emissions Measurement 5. Band Edge Emissions Measurement 6. Frequency Stability Measurement 7. Maximum Permissible Exposure 8. Radiated Emission Co-location |

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB

For Radiated Emissions below 1GHz test:

| Support Unit | Brand | Model | FCC ID |
|--------------|---------|------------|------------------|
| Notebook | DELL | M1340 | E2K4965AGNM |
| Notebook | DELL | E6430 | DoC |
| Notebook | DELL | D420 | E2KWM3945ABG |
| AP Router | Planex | GW-AP54SGX | KA220030603014-1 |
| Earphone | E-BOOKI | E-EPC040 | N/A |

For Radiated Emissions above 1GHz test:

| Support Unit | Brand | Model | FCC ID |
|--------------|-------|-------|-------------|
| Notebook | DELL | M1330 | E2K4965AGNM |

For Test Site No: TH01-CB

| Support Unit | Brand | Model | FCC ID |
|--------------|-------|-------|--------|
| Notebook | DELL | E6430 | DoC |

3.9. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For Master function:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

| Test Software Version | MT7662 QA V0.0.2.3 | | |
|-----------------------|--------------------|----------|----------|
| Frequency | 5180 MHz | 5200 MHz | 5240 MHz |
| MCS0/Nss1 VHT20 | 2D/2A | 3E/3B | 3E/3C |

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

| Test Software Version | MT7662 QA V0.0.2.3 | |
|-----------------------|--------------------|----------|
| Frequency | 5190 MHz | 5230 MHz |
| MCS0/Nss1 VHT40 | 1F/20 | 32/30 |

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

| Test Software Version | MT7662 QA V0.0.2.3 |
|-----------------------|--------------------|
| Frequency | 5210 MHz |
| MCS0/Nss1 VHT80 | 1E/1B |

Power Parameters of IEEE 802.11a

| Test Software Version | MT7662 QA V0.0.2.3 | | |
|-----------------------|--------------------|----------|----------|
| Frequency | 5180 MHz | 5200 MHz | 5240 MHz |
| 802.11a | 2E/29 | 3D/39 | 3E/3C |

For Client without radar detection function:

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT20

| Test Software Version | MT7662 QA V0.0.2.3 | | |
|-----------------------|--------------------|----------|----------|
| Frequency | 5180 MHz | 5200 MHz | 5240 MHz |
| MCS0/Nss1 VHT20 | 2D/2A | 31/32 | 31/32 |

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT40

| Test Software Version | MT7662 QA V0.0.2.3 | |
|-----------------------|--------------------|----------|
| Frequency | 5190 MHz | 5230 MHz |
| MCS0/Nss1 VHT40 | 1F/20 | 32/30 |

Power Parameters of IEEE 802.11ac MCS0/Nss1 VHT80

| Test Software Version | MT7662 QA V0.0.2.3 |
|-----------------------|--------------------|
| Frequency | 5210 MHz |
| MCS0/Nss1 VHT80 | 1E/1B |

Power Parameters of IEEE 802.11a


| Test Software Version | MT7662 QA V0.0.2.3 | | |
|-----------------------|--------------------|----------|----------|
| Frequency | 5180 MHz | 5200 MHz | 5240 MHz |
| 802.11a | 2E/29 | 2F/30 | 2E/2F |

3.10. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.11. Duty Cycle

IEEE 802.11ac MCS0/Nss1 VHT20




Date: 3.JUL.2014 13:12:31

IEEE 802.11ac MCS0/Nss1 VHT40




Date: 3.JUL.2014 13:13:28

IEEE 802.11ac MCS0/Nss1 VHT80



Date: 3.JUL.2014 13:14:10

IEEE 802.11a




Date: 3.JUL.2014 13:12:10

3.12. Test Configurations


3.12.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz ~ 1GHz



| Item | Connection | Shielded | Length |
|------|---------------|----------|--------|
| 1 | Power cable | No | 1.5m |
| 2 | RJ-45 cable | No | 1.5m |
| 3 | Audio cable | No | 1.1m |
| 4 | RJ-45 cable*3 | No | 0.4m |
| 5 | RJ-45 cable | No | 10m |

Test Configuration: above 1GHz



| Item | Connection | Shielded | Length |
|------|-------------|----------|--------|
| 1 | Power cable | No | 1.5m |
| 2 | RJ-45 cable | No | 10m |

4. TEST RESULT

4.1. 26dB Bandwidth and 99% Occupied Bandwidth Measurement

4.1.1. Limit

No restriction limits.

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| 26dB Bandwidth | |
|------------------------|--|
| Spectrum Parameters | Setting |
| Attenuation | Auto |
| Span Frequency | > 26dB Bandwidth |
| RBW | Approximately 1% of the emission bandwidth |
| VBW | VBW > RBW |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | Auto |
| 99% Occupied Bandwidth | |
| Spectrum Parameters | Setting |
| Span | 1.5 times to 5.0 times the OBW |
| RBW | 1 % to 5 % of the OBW |
| VBW | $\geq 3 \times$ RBW |
| Detector | Peak |
| Trace | Max Hold |

4.1.3. Test Procedures

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

1. The transmitter was radiated to the spectrum analyzer in peak hold mode.
2. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

4.1.4. Test Setup Layout

For Radiated 26dB Bandwidth and 99% Occupied Bandwidth Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.1.7. Test Result of 26dB Bandwidth and 99% Occupied Bandwidth

| | | | |
|---------------|-------------|----------------|---------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Benson Peng | Configurations | IEEE 802.11ac |

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

| Channel | Frequency | 26dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------|----------------------|------------------------------|
| 36 | 5180 MHz | 38.08 | 22.88 |
| 40 | 5200 MHz | 48.32 | 33.44 |
| 48 | 5240 MHz | 48.64 | 33.60 |

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

| Channel | Frequency | 26dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------|----------------------|------------------------------|
| 38 | 5190 MHz | 43.84 | 36.16 |
| 46 | 5230 MHz | 89.60 | 59.20 |

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2


| Channel | Frequency | 26dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------|----------------------|------------------------------|
| 42 | 5210 MHz | 81.28 | 74.88 |

| | | | |
|----------------------|-------------|-----------------------|--------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Benson Peng | Configurations | IEEE 802.11a |

Configuration IEEE 802.11a / Chain 1 + Chain 2


| Channel | Frequency | 26dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) |
|----------------|------------------|-----------------------------|-------------------------------------|
| 36 | 5180 MHz | 34.56 | 20.48 |
| 40 | 5200 MHz | 43.52 | 31.52 |
| 48 | 5240 MHz | 43.68 | 30.88 |

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5180 MHz




Date: 3.JUL.2014 12:28:04

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5200 MHz




Date: 3.JUL.2014 12:16:04

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5240 MHz




Date: 3.JUL.2014 12:15:16

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5190 MHz




Date: 3.JUL.2014 12:19:16

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5230 MHz




Date: 3.JUL.2014 12:20:03

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz




Date: 3.JUL.2014 12:21:22

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5180 MHz




Date: 3.JUL.2014 12:11:59

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5200 MHz



Date: 3.JUL.2014 12:13:03

26dB Bandwidth and 99% Occupied Bandwidth Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5240 MHz



Date: 3.JUL.2014 12:14:29

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm) for master limit and 250 mW (24dBm) for client limit provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

| Power Meter Parameter | Setting |
|-----------------------|---------|
| Detector | AVERAGE |

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (E) Maximum conducted output power =>3. Measurement using a Power Meter (PM) =>b) Method PM-G (Measurement using a gated RF average power meter).
3. Multiple antenna systems was performed in accordance with KDB662911 D01 v02r01 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

| | | | |
|---------------|---------------|----------------|-----------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Benson Peng | Configurations | IEEE 802.11ac/a |
| Test Date | Jul. 03, 2014 | | |

For Master function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 36 | 5180 MHz | 19.54 | 18.81 | 22.20 | 30.00 | Complies |
| 40 | 5200 MHz | 21.23 | 20.82 | 24.04 | 30.00 | Complies |
| 48 | 5240 MHz | 21.17 | 20.93 | 24.06 | 30.00 | Complies |

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 38 | 5190 MHz | 15.62 | 15.43 | 18.54 | 30.00 | Complies |
| 46 | 5230 MHz | 20.82 | 20.14 | 23.50 | 30.00 | Complies |

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 42 | 5210 MHz | 15.36 | 14.53 | 17.98 | 30.00 | Complies |

Configuration IEEE 802.11a

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 36 | 5180 MHz | 19.41 | 19.02 | 22.23 | 30.00 | Complies |
| 40 | 5200 MHz | 21.14 | 20.97 | 24.07 | 30.00 | Complies |
| 48 | 5240 MHz | 21.05 | 20.96 | 24.02 | 30.00 | Complies |

| | | | |
|---------------|---------------|----------------|-----------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Jim Huang | Configurations | IEEE 802.11ac/a |
| Test Date | Jul. 08, 2014 | | |

For Client without radar detection function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 36 | 5180 MHz | 19.54 | 18.81 | 22.20 | 24.00 | Complies |
| 40 | 5200 MHz | 20.57 | 20.62 | 23.61 | 24.00 | Complies |
| 48 | 5240 MHz | 20.51 | 20.85 | 23.69 | 24.00 | Complies |

Configuration IEEE 802.11ac MCS0/Nss1 VHT40

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 38 | 5190 MHz | 15.62 | 15.43 | 18.54 | 24.00 | Complies |
| 46 | 5230 MHz | 20.82 | 20.14 | 23.50 | 24.00 | Complies |

Configuration IEEE 802.11ac MCS0/Nss1 VHT80

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 42 | 5210 MHz | 15.36 | 14.53 | 17.98 | 24.00 | Complies |

Configuration IEEE 802.11a

| Channel | Frequency | Conducted Power (dBm) | | | Max. Limit (dBm) | Result |
|---------|-----------|-----------------------|---------|-------|------------------|----------|
| | | Chain 1 | Chain 2 | Total | | |
| 36 | 5180 MHz | 19.41 | 19.02 | 22.23 | 24.00 | Complies |
| 40 | 5200 MHz | 20.18 | 20.22 | 23.21 | 24.00 | Complies |
| 48 | 5240 MHz | 20.10 | 20.43 | 23.28 | 24.00 | Complies |

4.3. Power Spectral Density Measurement

4.3.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.2.1.

| Frequency Range | Power Spectral Density limit (dBm/MHz) |
|-----------------|--|
| 5.15~5.25 GHz | 17 for master limit |
| | 11 for client limit |

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|--------------------|--|
| Attenuation | Auto |
| Span Frequency | Encompass the entire emissions bandwidth (EBW) of the signal |
| RBW | 1000 kHz |
| VBW | 3000 kHz |
| Detector | RMS |
| Trace | AVERAGE |
| Sweep Time | Auto |
| Trace Average | 100 times |

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected RF switch to the spectrum analyzer.
2. Test was performed in accordance with KDB789033 D02 v01 for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - section (F) Maximum Power Spectral Density (PSD).
3. Multiple antenna systems was performed in accordance KDB662911 D01 v02r01 in-Band Power Spectral Density (PSD) Measurements (a) Measure and sum the spectra across the outputs.
4. When measuring first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3 and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

| | | | |
|---------------|---------------|----------------|-----------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Benson Peng | Configurations | IEEE 802.11ac/a |
| Test Date | Jul. 03, 2014 | | |

For Master function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 36 | 5180 MHz | 8.70 | 16.18 | Complies |
| 40 | 5200 MHz | 10.51 | 16.18 | Complies |
| 48 | 5240 MHz | 10.59 | 16.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 38 | 5190 MHz | 2.02 | 16.18 | Complies |
| 46 | 5230 MHz | 7.26 | 16.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 42 | 5210 MHz | -1.54 | 16.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

Configuration IEEE 802.11a / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 36 | 5180 MHz | 8.79 | 16.18 | Complies |
| 40 | 5200 MHz | 10.67 | 16.18 | Complies |
| 48 | 5240 MHz | 10.76 | 16.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $17 - (6.82 - 6) = 16.18\text{dBm/MHz}$

| | | | |
|---------------|---------------|----------------|-----------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Jim Huang | Configurations | IEEE 802.11ac/a |
| Test Date | Jul. 08, 2014 | | |

For Client without radar detection function:

Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 36 | 5180 MHz | 8.70 | 10.18 | Complies |
| 40 | 5200 MHz | 10.10 | 10.18 | Complies |
| 48 | 5240 MHz | 10.14 | 10.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $11 - (6.82 - 6) = 10.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 38 | 5190 MHz | 2.02 | 10.18 | Complies |
| 46 | 5230 MHz | 7.26 | 10.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $11 - (6.82 - 6) = 10.18\text{dBm/MHz}$

Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2

| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 42 | 5210 MHz | -1.54 | 10.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $11 - (6.82 - 6) = 10.18\text{dBm/MHz}$

Configuration IEEE 802.11a / Chain 1 + Chain 2


| Channel | Frequency | Total Power Density (dBm/MHz) | Max. Limit (dBm/MHz) | Result |
|---------|-----------|-------------------------------|----------------------|----------|
| 36 | 5180 MHz | 8.79 | 10.18 | Complies |
| 40 | 5200 MHz | 10.17 | 10.18 | Complies |
| 48 | 5240 MHz | 10.13 | 10.18 | Complies |

Note: $DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right] = 6.82\text{dBi} > 6\text{dBi}$, so B1 limit = $11 - (6.82 - 6) = 10.18\text{dBm/MHz}$


Note: All the test values were listed in the report.

For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz




Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5240 MHz




For Client without radar detection function:


Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT20 / Chain 1 + Chain 2 / 5240 MHz




Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT40 / Chain 1 + Chain 2 / 5230 MHz



Power Density Plot on Configuration IEEE 802.11ac MCS0/Nss1 VHT80 / Chain 1 + Chain 2 / 5210 MHz



Power Density Plot on Configuration IEEE 802.11a / Chain 1 + Chain 2 / 5200 MHz



4.4. Radiated Emissions Measurement

4.4.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 40 GHz |
| RBW / VBW (Emission in restricted band) | 1MHz / 3MHz for Peak, 1MHz / 10Hz for Average |
| RBW / VBW (Emission in non-restricted band) | 1MHz / 3MHz for peak |


| Receiver Parameter | Setting |
|------------------------|-----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RBW 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RBW 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RBW 120kHz for QP |

4.4.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.4.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Results of Radiated Emissions (9kHz~30MHz)

| | | | |
|----------------------|---------------|-----------------------|-------------|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | Normal Link |
| Test Date | Jun. 10, 2014 | Test Mode | Mode 1 |

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Limit Line (dBuV) | Remark |
|-------------|--------------|-----------------|-------------------|----------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.4.8. Results of Radiated Emissions (30MHz~1GHz)


| | | | |
|---------------|------------|----------------|-------------|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | Normal Link |
| Test Mode | Mode 1 | | |

Horizontal



| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|--------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|-----------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 67.83 | 31.77 | 40.00 | -8.23 | 57.52 | 0.98 | 5.08 | 31.81 | 300 | 104 | HORIZONTAL Peak |
| 2 | 90.14 | 32.71 | 43.50 | -10.79 | 54.43 | 1.13 | 8.74 | 31.59 | 400 | 95 | HORIZONTAL Peak |
| 3 | 135.73 | 32.01 | 43.50 | -11.49 | 50.97 | 1.38 | 11.20 | 31.54 | 300 | 259 | HORIZONTAL Peak |
| 4 | 270.56 | 32.77 | 46.00 | -13.23 | 49.96 | 1.99 | 12.37 | 31.55 | 100 | 38 | HORIZONTAL Peak |
| 5 | 413.15 | 30.82 | 46.00 | -15.18 | 43.27 | 2.53 | 16.37 | 31.35 | 100 | 200 | HORIZONTAL Peak |
| 6 | 500.45 | 32.60 | 46.00 | -13.40 | 44.27 | 2.82 | 16.92 | 31.41 | 100 | 88 | HORIZONTAL Peak |

Vertical



| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|--------|--------|--------|--------|-------|--------------|--------|-------|-------|--------------|--------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 36.79 | 35.84 | 40.00 | -4.16 | 52.81 | 0.71 | 14.20 | 31.88 | 100 | 82 VERTICAL | QP |
| 2 | 58.13 | 33.57 | 40.00 | -6.43 | 59.16 | 0.88 | 5.31 | 31.78 | 200 | 260 VERTICAL | QP |
| 3 | 89.17 | 35.45 | 43.50 | -8.05 | 57.39 | 1.12 | 8.54 | 31.60 | 125 | 186 VERTICAL | Peak |
| 4 | 165.80 | 32.03 | 43.50 | -11.47 | 52.63 | 1.56 | 9.38 | 31.54 | 100 | 143 VERTICAL | Peak |
| 5 | 478.14 | 28.20 | 46.00 | -17.80 | 39.90 | 2.72 | 16.79 | 31.21 | 200 | 339 VERTICAL | Peak |
| 6 | 500.45 | 33.27 | 46.00 | -12.73 | 44.94 | 2.82 | 16.92 | 31.41 | 125 | 0 VERTICAL | Peak |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.4.9. Results for Radiated Emissions (1GHz~40GHz)

| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT20 CH 36 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15544.78 | 58.91 | 74.00 | -15.09 | 44.28 | 10.37 | 38.78 | 34.52 | 168 | 360 | HORIZONTAL | Peak |
| 2 | 15545.86 | 45.00 | 54.00 | -9.00 | 30.37 | 10.37 | 38.78 | 34.52 | 168 | 354 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15538.62 | 48.35 | 54.00 | -5.65 | 33.71 | 10.37 | 38.78 | 34.51 | 130 | 210 | VERTICAL | Average |
| 2 | 15541.40 | 60.71 | 74.00 | -13.29 | 46.08 | 10.37 | 38.78 | 34.52 | 130 | 210 | VERTICAL | Peak |



| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT20 CH 40 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15596.32 | 48.26 | 54.00 | -5.74 | 33.72 | 10.36 | 38.77 | 34.59 | 151 | 351 | HORIZONTAL Average |
| 2 | 15604.24 | 60.81 | 74.00 | -13.19 | 46.30 | 10.36 | 38.75 | 34.60 | 151 | 351 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15596.96 | 62.64 | 74.00 | -11.36 | 48.10 | 10.36 | 38.77 | 34.59 | 121 | 285 | VERTICAL Peak |
| 2 | 15600.90 | 50.54 | 54.00 | -3.46 | 36.02 | 10.36 | 38.75 | 34.59 | 121 | 285 | VERTICAL Average |



| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT20 CH 48 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15718.58 | 47.51 | 54.00 | -6.49 | 33.17 | 10.36 | 38.72 | 34.74 | 155 | 348 | HORIZONTAL Average |
| 2 | 15727.68 | 59.59 | 74.00 | -14.41 | 45.26 | 10.36 | 38.72 | 34.75 | 155 | 348 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15714.52 | 57.59 | 74.00 | -16.41 | 43.24 | 10.36 | 38.72 | 34.73 | 135 | 278 | VERTICAL Peak |
| 2 | 15715.84 | 50.07 | 54.00 | -3.93 | 35.72 | 10.36 | 38.72 | 34.73 | 135 | 278 | VERTICAL Average |



| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT40 CH 38 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15571.68 | 45.04 | 54.00 | -8.96 | 30.45 | 10.37 | 38.77 | 34.55 | 100 | 78 | HORIZONTAL Average |
| 2 | 15574.00 | 56.43 | 74.00 | -17.57 | 41.85 | 10.37 | 38.77 | 34.56 | 100 | 78 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15569.64 | 59.21 | 74.00 | -14.79 | 44.62 | 10.37 | 38.77 | 34.55 | 124 | 336 | VERTICAL Peak |
| 2 | 15573.84 | 47.38 | 54.00 | -6.62 | 32.80 | 10.37 | 38.77 | 34.56 | 124 | 336 | VERTICAL Average |



| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT40 CH 46 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15685.68 | 45.63 | 54.00 | -8.37 | 31.24 | 10.36 | 38.73 | 34.70 | 100 | 348 | HORIZONTAL Average |
| 2 | 15693.20 | 57.36 | 74.00 | -16.64 | 42.99 | 10.36 | 38.72 | 34.71 | 100 | 348 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|--------|--------|-------|--------------|--------|-------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15692.64 | 48.47 | 54.00 | -5.53 | 34.10 | 10.36 | 38.72 | 34.71 | 120 | 209 | VERTICAL Average |
| 2 | 15699.76 | 59.34 | 74.00 | -14.66 | 44.97 | 10.36 | 38.72 | 34.71 | 120 | 209 | VERTICAL Peak |



| | | | |
|----------------------|---------------|-----------------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|---------------|-------|-------|-----------|--------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15637.20 | 44.92 | 54.00 | -9.08 | 30.45 | 10.36 | 38.75 | 34.64 | 100 | 269 | HORIZONTAL Average |
| 2 | 15642.76 | 57.13 | 74.00 | -16.87 | 42.66 | 10.36 | 38.75 | 34.64 | 100 | 269 | HORIZONTAL Peak |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|---------------|-------|-------|-----------|------------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 15636.40 | 56.67 | 74.00 | -17.33 | 42.20 | 10.36 | 38.75 | 34.64 | 100 | 117 | VERTICAL Peak |
| 2 | 15642.96 | 45.09 | 54.00 | -8.91 | 30.62 | 10.36 | 38.75 | 34.64 | 100 | 117 | VERTICAL Average |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



| | | | |
|----------------------|---------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11a CH 36 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15537.04 | 46.17 | 54.00 | -7.83 | 31.53 | 10.37 | 38.78 | 34.51 | 100 | 16 | HORIZONTAL | Average |
| 2 | 15541.02 | 56.11 | 74.00 | -17.89 | 41.48 | 10.37 | 38.78 | 34.52 | 100 | 16 | HORIZONTAL | Peak |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15537.28 | 50.89 | 54.00 | -3.11 | 36.25 | 10.37 | 38.78 | 34.51 | 129 | 279 | VERTICAL | Average |
| 2 | 15542.16 | 65.32 | 74.00 | -8.68 | 50.69 | 10.37 | 38.78 | 34.52 | 132 | 286 | VERTICAL | Peak |

| | | | |
|----------------------|---------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11a CH 40 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15599.32 | 57.45 | 74.00 | -16.55 | 42.91 | 10.36 | 38.77 | 34.59 | 100 | 33 | HORIZONTAL | Peak |
| 2 | 15600.76 | 48.63 | 54.00 | -5.37 | 34.11 | 10.36 | 38.75 | 34.59 | 100 | 33 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15595.10 | 61.15 | 74.00 | -12.85 | 46.60 | 10.36 | 38.77 | 34.58 | 120 | 284 | VERTICAL | Peak |
| 2 | 15599.62 | 50.72 | 54.00 | -3.28 | 36.18 | 10.36 | 38.77 | 34.59 | 120 | 284 | VERTICAL | Average |



| | | | |
|----------------------|---------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11a CH 48 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Horizontal

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|------------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15714.68 | 60.40 | 74.00 | -13.60 | 46.05 | 10.36 | 38.72 | 34.73 | 150 | 360 | HORIZONTAL | Peak |
| 2 | 15719.68 | 48.05 | 54.00 | -5.95 | 33.71 | 10.36 | 38.72 | 34.74 | 150 | 360 | HORIZONTAL | Average |

Vertical

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | A/Pos | T/Pos | Pol/Phase | Remark |
|---|----------|--------|------------|------------|------------|-------------------|----------------|---------------|-------|-------|-----------|---------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | | |
| 1 | 15719.58 | 50.91 | 54.00 | -3.09 | 36.57 | 10.36 | 38.72 | 34.74 | 116 | 122 | VERTICAL | Average |
| 2 | 15724.36 | 65.14 | 74.00 | -8.86 | 50.81 | 10.36 | 38.72 | 34.75 | 116 | 122 | VERTICAL | Peak |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5. Band Edge Emissions Measurement

4.5.1. Limit

For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(kHz) | 300 |
| 0.490~1.705 | 24000/F(kHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Span Frequency | 100 MHz |
| RBW / VBW (Emission in restricted band) | 1 MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |
| RBW / VBW (Emission in non-restricted band) | 1 MHz / 3MHz for Peak |

4.5.3. Test Procedures

- The test procedure is the same as section 4.4.3, only the frequency range investigated is limited to 100MHz around bandedges.

4.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.4.4.

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Band Edge and Fundamental Emissions

| | | | |
|---------------|---------------|----------------|---|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT20 CH 36, 40, 48 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Channel 36

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | Remark | A/Pos | T/Pos | PoI/Phase |
|---|---------|--------|------------|------------|------------|-------------------|----------------|---------------|---------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | | cm | deg | |
| 1 | 5146.60 | 71.83 | 74.00 | -2.17 | 66.89 | 6.13 | 34.01 | 35.20 | Peak | 112 | 71 | VERTICAL |
| 2 | 5150.00 | 52.94 | 54.00 | -1.06 | 48.00 | 6.13 | 34.01 | 35.20 | Average | 112 | 71 | VERTICAL |
| 3 | 5180.40 | 111.56 | | | 106.53 | 6.15 | 34.08 | 35.20 | Peak | 112 | 71 | VERTICAL |
| 4 | 5180.60 | 101.57 | | | 96.54 | 6.15 | 34.08 | 35.20 | Average | 112 | 71 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | Remark | A/Pos | T/Pos | PoI/Phase |
|---|---------|--------|------------|------------|------------|-------------------|----------------|---------------|---------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | | cm | deg | |
| 1 | 5150.00 | 48.14 | 54.00 | -5.86 | 43.20 | 6.13 | 34.01 | 35.20 | Average | 100 | 146 | VERTICAL |
| 2 | 5150.00 | 68.90 | 74.00 | -5.10 | 63.96 | 6.13 | 34.01 | 35.20 | Peak | 100 | 146 | VERTICAL |
| 3 | 5200.60 | 104.38 | | | 99.31 | 6.16 | 34.11 | 35.20 | Average | 100 | 146 | VERTICAL |
| 4 | 5201.20 | 115.06 | | | 109.99 | 6.16 | 34.11 | 35.20 | Peak | 100 | 146 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

| | Freq | Level | Limit Line | Over Limit | Read Level | CableAntenna Loss | Antenna Factor | Preamp Factor | Remark | A/Pos | T/Pos | PoI/Phase |
|---|---------|--------|------------|------------|------------|-------------------|----------------|---------------|---------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | | cm | deg | |
| 1 | 5130.80 | 57.13 | 74.00 | -16.87 | 52.23 | 6.12 | 33.98 | 35.20 | Peak | 115 | 199 | VERTICAL |
| 2 | 5150.00 | 43.78 | 54.00 | -10.22 | 38.84 | 6.13 | 34.01 | 35.20 | Average | 115 | 199 | VERTICAL |
| 3 | 5240.60 | 105.63 | | | 100.47 | 6.18 | 34.18 | 35.20 | Average | 115 | 199 | VERTICAL |
| 4 | 5242.40 | 115.90 | | | 110.72 | 6.20 | 34.18 | 35.20 | Peak | 115 | 199 | VERTICAL |
| 5 | 5350.00 | 44.57 | 54.00 | -9.43 | 39.09 | 6.26 | 34.42 | 35.20 | Average | 115 | 199 | VERTICAL |
| 6 | 5353.00 | 57.07 | 74.00 | -16.93 | 51.59 | 6.26 | 34.42 | 35.20 | Peak | 115 | 199 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5240 MHz.

| | | | |
|----------------------|-------------------------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT40 CH 38, 46 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 ~ Jun. 26, 2014 | | |

Channel 38

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|-------|--------|--------------|--------|---------------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 5150.00 | 52.72 | 54.00 | -1.28 | 47.78 | 6.13 | 34.01 | 35.20 Average | 102 | 7 | VERTICAL |
| 2 | 5150.00 | 69.07 | 74.00 | -4.93 | 64.13 | 6.13 | 34.01 | 35.20 Peak | 102 | 7 | VERTICAL |
| 3 | 5188.00 | 96.01 | | | 90.98 | 6.15 | 34.08 | 35.20 Average | 102 | 7 | VERTICAL |
| 4 | 5188.00 | 105.90 | | | 100.87 | 6.15 | 34.08 | 35.20 Peak | 102 | 7 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|-------|--------|--------------|--------|---------------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 5150.00 | 52.77 | 54.00 | -1.23 | 47.83 | 6.13 | 34.01 | 35.20 Average | 100 | 157 | VERTICAL |
| 2 | 5150.00 | 68.77 | 74.00 | -5.23 | 63.83 | 6.13 | 34.01 | 35.20 Peak | 100 | 157 | VERTICAL |
| 3 | 5228.80 | 111.82 | | | 106.66 | 6.18 | 34.18 | 35.20 Peak | 100 | 157 | VERTICAL |
| 4 | 5231.80 | 101.46 | | | 96.30 | 6.18 | 34.18 | 35.20 Average | 100 | 157 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5230 MHz.



| | | | |
|----------------------|---------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11ac MCS0/Nss1 VHT80 CH 42 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Channel 42

| | Freq | Level | Limit | Over | Read | Cable | Antenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|-------|-------|-------|---------|--------|---------|-------|-------|-----------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | Loss | Factor | Factor | | cm | deg | |
| 1 | 5147.60 | 66.63 | 74.00 | -7.37 | 61.69 | 6.13 | 34.01 | 35.20 | Peak | 101 | 144 | VERTICAL |
| 2 | 5150.00 | 52.89 | 54.00 | -1.11 | 47.95 | 6.13 | 34.01 | 35.20 | Average | 101 | 144 | VERTICAL |
| 3 | 5202.00 | 100.74 | | | 95.67 | 6.16 | 34.11 | 35.20 | Peak | 101 | 144 | VERTICAL |
| 4 | 5212.00 | 91.01 | | | 85.89 | 6.17 | 34.15 | 35.20 | Average | 101 | 144 | VERTICAL |

Item 3, 4 are the fundamental frequency at 5210 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

| | | | |
|----------------------|---------------|-----------------------|--|
| Temperature | 24°C | Humidity | 55% |
| Test Engineer | James Chou | Configurations | IEEE 802.11a CH 36, 40, 48 / Chain 1 + Chain 2 |
| Test Date | Jun. 25, 2014 | | |

Channel 36

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|-------|--------|--------------|--------|--------|---------|-------|-------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 5149.60 | 70.22 | 74.00 | -3.78 | 65.28 | 6.13 | 34.01 | 35.20 | Peak | 112 | 71 VERTICAL |
| 2 | 5150.00 | 53.00 | 54.00 | -1.00 | 48.06 | 6.13 | 34.01 | 35.20 | Average | 112 | 71 VERTICAL |
| 3 | 5180.80 | 102.07 | | | 97.04 | 6.15 | 34.08 | 35.20 | Average | 112 | 71 VERTICAL |
| 4 | 5182.40 | 111.78 | | | 106.75 | 6.15 | 34.08 | 35.20 | Peak | 112 | 71 VERTICAL |

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|-------|--------|--------------|--------|--------|---------|-------|-------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 5148.40 | 65.55 | 74.00 | -8.45 | 60.61 | 6.13 | 34.01 | 35.20 | Peak | 100 | 72 VERTICAL |
| 2 | 5150.00 | 48.88 | 54.00 | -5.12 | 43.94 | 6.13 | 34.01 | 35.20 | Average | 100 | 72 VERTICAL |
| 3 | 5198.40 | 114.09 | | | 109.02 | 6.16 | 34.11 | 35.20 | Peak | 100 | 72 VERTICAL |
| 4 | 5199.20 | 104.47 | | | 99.40 | 6.16 | 34.11 | 35.20 | Average | 100 | 72 VERTICAL |

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

| | Freq | Level | Limit | Over | Read | CableAntenna | Preamp | Remark | A/Pos | T/Pos | Pol/Phase |
|---|---------|--------|--------|--------|--------|--------------|--------|--------|---------|-------|--------------|
| | MHz | dBuV/m | dBuV/m | dB | dBuV | dB | dB/m | dB | cm | deg | |
| 1 | 5124.80 | 56.69 | 74.00 | -17.31 | 51.83 | 6.12 | 33.94 | 35.20 | Peak | 130 | 198 VERTICAL |
| 2 | 5150.00 | 44.08 | 54.00 | -9.92 | 39.14 | 6.13 | 34.01 | 35.20 | Average | 130 | 198 VERTICAL |
| 3 | 5238.80 | 115.62 | | | 110.46 | 6.18 | 34.18 | 35.20 | Peak | 130 | 198 VERTICAL |
| 4 | 5239.40 | 105.88 | | | 100.72 | 6.18 | 34.18 | 35.20 | Average | 130 | 198 VERTICAL |
| 5 | 5350.00 | 44.35 | 54.00 | -9.65 | 38.87 | 6.26 | 34.42 | 35.20 | Average | 130 | 198 VERTICAL |
| 6 | 5365.60 | 58.66 | 74.00 | -15.34 | 53.13 | 6.27 | 34.46 | 35.20 | Peak | 130 | 198 VERTICAL |

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.6. Frequency Stability Measurement

4.6.1. Limit

In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

4.6.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|--------------------|--|
| Attenuation | Auto |
| Span Frequency | Entire absence of modulation emissions bandwidth |
| RBW | 10 kHz |
| VBW | 10 kHz |
| Sweep Time | Auto |

4.6.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is $0^\circ\text{C} \sim 40^\circ\text{C}$.

4.6.4. Test Setup Layout



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.6.7. Test Result of Frequency Stability

| | | | |
|----------------------|-------------|------------------|---------------|
| Temperature | 24°C | Humidity | 61% |
| Test Engineer | Benson Peng | Test Date | Jul. 03, 2014 |

Voltage vs. Frequency Stability

| Voltage | Measurement Frequency (MHz) |
|----------------------|-----------------------------|
| (V) | 5200 MHz |
| 126.50 | 5200.0542 |
| 110.00 | 5200.0534 |
| 93.50 | 5200.0532 |
| Max. Deviation (MHz) | 0.054200 |
| Max. Deviation (ppm) | 10.42 |

Temperature vs. Frequency Stability

| Temperature | Measurement Frequency (MHz) |
|----------------------|-----------------------------|
| (°C) | 5200 MHz |
| 0 | 5200.0512 |
| 10 | 5200.0522 |
| 20 | 5200.0534 |
| 30 | 5200.0602 |
| 40 | 5200.0618 |
| Max. Deviation (MHz) | 0.061800 |
| Max. Deviation (ppm) | 11.88 |

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark |
|----------------------------|--------------|---------------|----------------|------------------|------------------|-----------------------|
| BILOG ANTENNA | Schaffner | CBL6112B | 2928 | 30MHz ~ 2GHz | Dec. 27, 2013 | Radiation (03CH01-CB) |
| Loop Antenna | Teseq | HLA 6120 | 24155 | 9 kHz - 30 MHz | Nov. 05, 2012* | Radiation (03CH01-CB) |
| Horn Antenna | EMCO | 3115 | 00075790 | 750MHz~18GHz | Nov. 01, 2013 | Radiation (03CH01-CB) |
| Horn Antenna | SCHWARZBEAK | BBHA 9170 | BBHA9170252 | 15GHz ~ 40GHz | Dec. 17, 2013 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8447D | 2944A10991 | 0.1MHz ~ 1.3GHz | Nov. 12, 2013 | Radiation (03CH01-CB) |
| Pre-Amplifier | Agilent | 8449B | 3008A02310 | 1GHz ~ 26.5GHz | Dec. 16, 2013 | Radiation (03CH01-CB) |
| Pre-Amplifier | WM | TF-130N-R1 | 923365 | 26GHz ~ 40GHz | Oct. 23, 2013 | Radiation (03CH01-CB) |
| Spectrum analyzer | R&S | FSP40 | 100019 | 9kHz~40GHz | Dec. 02, 2013 | Radiation (03CH01-CB) |
| EMI Test Receiver | Agilent | N9038A | MY52260123 | 9kHz ~ 8GHz | Dec. 12, 2013 | Radiation (03CH01-CB) |
| Turn Table | INN CO | CO 2000 | N/A | 0 ~ 360 degree | N.C.R. | Radiation (03CH01-CB) |
| Antenna Mast | INN CO | CO2000 | N/A | 1 m - 4 m | N.C.R. | Radiation (03CH01-CB) |
| RF Cable-low | Woken | Low Cable-1 | N/A | 30 MHz - 1 GHz | Nov. 17, 2013 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-3 | N/A | 1 GHz - 40 GHz | Nov. 17, 2013 | Radiation (03CH01-CB) |
| RF Cable-high | Woken | High Cable-4 | N/A | 1 GHz - 40 GHz | Nov. 17, 2013 | Radiation (03CH01-CB) |
| Signal analyzer | R&S | FSV40 | 100979 | 9kHz~40GHz | Nov. 29, 2013 | Conducted (TH01-CB) |
| Temp. and Humidity Chamber | Ten Billion | TTH-D3SP | TBN-931011 | -30~100 degree | Jun. 03, 2014 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 2 Way | 0120A02056002D | 2GHz ~ 18GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 3 Way | MDC2366 | 2GHz ~ 18GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Power Divider | Woken | 4 Way | 0120A04056002D | 2GHz ~ 18GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-7 | - | 1 GHz – 26.5 GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-8 | - | 1 GHz – 26.5 GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-9 | - | 1 GHz – 26.5 GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-10 | - | 1 GHz – 26.5 GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| RF Cable-high | Woken | High Cable-11 | - | 1 GHz – 26.5 GHz | Nov. 17, 2013 | Conducted (TH01-CB) |
| Power Sensor | Anritsu | MA2411B | 0917223 | 300MHz~40GHz | Sep. 18, 2013 | Conducted (TH01-CB) |



| | | | | | | |
|-------------|---------|---------|---------|--------------|---------------|------------------------|
| Power Meter | Anritsu | ML2495A | 1035008 | 300MHz~40GHz | Sep. 18, 2013 | Conducted (TH01-CB) |
|-------------|---------|---------|---------|--------------|---------------|------------------------|

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

NCR means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

| Test Items | Uncertainty | Remark |
|--------------------------------------|-------------|--------------------------|
| Conducted Emission (150kHz ~ 30MHz) | 2.4 dB | Confidence levels of 95% |
| Radiated Emission (30MHz ~ 1,000MHz) | 3.6 dB | Confidence levels of 95% |
| Radiated Emission (1GHz ~ 18GHz) | 3.7 dB | Confidence levels of 95% |
| Radiated Emission (18GHz ~ 40GHz) | 3.5 dB | Confidence levels of 95% |
| Conducted Emission | 1.7 dB | Confidence levels of 95% |