



## 5.6 FREQUENCY STABILITY

### 5.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/- 0.02% of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

### 5.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ANRITSU SPECTRUM ANALYZER	MS2667C	M10281	August 12, 2004
WIT STANDARD TEMPERATURE AND HUMIDITY CHAMBER	TH-4S-C	W901030	August 12, 2004

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 5.6.3 TEST PROCEDURE

1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
2. Turn the EUT on and couple its output to a spectrum analyzer.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 5.6.4 DEVIATION FROM TEST STANDARD

No deviation

#### 5.6.5 TEST SETUP



#### 5.6.6 EUT OPERATING CONDITION

Same as Item 4.1.6



5.6.7 TEST RESULTS

		Operating frequency: 5320MHz				Limit : ± 0.02%	
Temp. (°C)	Power supply (VDC)	2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	126.5	5319.9903	-0.0001823	5319.9903	-0.0001823	5319.9903	-0.0001823
	110.0	5319.9903	-0.0001823	5319.9903	-0.0001823	5319.9903	-0.0001823
	93.5	5319.9903	-0.0001823	5319.9903	-0.0001823	5319.9903	-0.0001823
40	126.5	5319.9686	-0.0005902	5319.9686	-0.0005902	5319.9686	-0.0005902
	110.0	5319.9686	-0.0005902	5319.9686	-0.0005902	5319.9686	-0.0005902
	93.5	5319.9686	-0.0005902	5319.9686	-0.0005902	5319.9686	-0.0005902
30	126.5	5319.9626	-0.0007030	5319.9626	-0.0007030	5319.9626	-0.0007030
	110.0	5319.9626	-0.0007030	5319.9626	-0.0007030	5319.9626	-0.0007030
	93.5	5319.9626	-0.0007030	5319.9626	-0.0007030	5319.9626	-0.0007030
20	126.5	5319.9599	-0.0007538	5319.9599	-0.0007538	5319.9599	-0.0007538
	110.0	5319.9599	-0.0007538	5319.9599	-0.0007538	5319.9599	-0.0007538
	93.5	5319.9599	-0.0007538	5319.9599	-0.0007538	5319.9599	-0.0007538
10	126.5	5319.9606	-0.0007406	5319.9606	-0.0007406	5319.9606	-0.0007406
	110.0	5319.9606	-0.0007406	5319.9606	-0.0007406	5319.9606	-0.0007406
	93.5	5319.9606	-0.0007406	5319.9606	-0.0007406	5319.9606	-0.0007406
0	126.5	5319.9643	-0.0006711	5319.9643	-0.0006711	5319.9643	-0.0006711
	110.0	5319.9643	-0.0006711	5319.9643	-0.0006711	5319.9643	-0.0006711
	93.5	5319.9643	-0.0006711	5319.9643	-0.0006711	5319.9643	-0.0006711
-10	126.5	5319.9703	-0.0005583	5319.9703	-0.0005583	5319.9703	-0.0005583
	110.0	5319.9703	-0.0005583	5319.9703	-0.0005583	5319.9703	-0.0005583
	93.5	5319.9703	-0.0005583	5319.9703	-0.0005583	5319.9703	-0.0005583
-20	126.5	5319.9776	-0.0004211	5319.9776	-0.0004211	5319.9776	-0.0004211
	110.0	5319.9776	-0.0004211	5319.9776	-0.0004211	5319.9776	-0.0004211
	93.5	5319.9776	-0.0004211	5319.9776	-0.0004211	5319.9776	-0.0004211
-30	126.5	5319.9916	-0.0001579	5319.9916	-0.0001579	5319.9916	-0.0001579
	110.0	5319.9916	-0.0001579	5319.9916	-0.0001579	5319.9916	-0.0001579
	93.5	5319.9916	-0.0001579	5319.9916	-0.0001579	5319.9916	-0.0001579



**5.7 BAND EDGES MEASUREMENT**

**5.7.1 TEST INSTRUMENTS**

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004
SPECTRUM ANALYZER	8564EC	4208A00660	Nov. 20, 2003

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

**5.7.2 TEST PROCEDURE**

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 1MHz and 300Hz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

**5.7.3 EUT OPERATING CONDITION**

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

**5.7.4 TEST RESULTS**


For signals in the restricted bands above and below the 5.15 to 5.35GHz allocated band a measurement was made of the amplitude of the spurious emissions with respect to the intentional signals. The relative amplitude, in dBc, was applied to the average and peak filed strength of the intentional signal made on the OATS to calculate the field strength of the unintentional signals.

The spectrum plots (Peak RBW=VBW=1MHz; Average RBW=1MHz, VBW=300Hz) are attached on the following 8 pages.



Normal Mode: Channel 1 (5180 MHz)


The band edge emission plot on the following diagram shows 51.75dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 (normal mode) is 98.2dBuV/m, so the maximum field strength in restrict band is  $98.2 - 51.75 = 46.45$  dBuV/m which is under 54dBuV/m limit.





Normal Mode: Channel 8 (5320 MHz)


The band edge emission plot on the following diagram shows 52.05dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 8 (normal mode) is 97.2dBuV/m, so the maximum field strength in restrict band is  $97.2 - 52.05 = 45.15$  dBuV/m which is under 54dBuV/m limit.





Turbo Mode: Channel 1 (5210 MHz)


The band edge emission plot on the following diagram shows 48.83dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 1 (turbo mode) is 100.3dBuV/m, so the maximum field strength in restrict band is  $100.3 - 48.83 = 51.47$  dBuV/m which is under 54dBuV/m limit.





Turbo Mode: Channel 3 (5290 MHz)

The band edge emission plot on the following diagram shows 49.42dBc (Average) between carrier maximum power and local maximum emission in restrict band. The emission of carrier strength list in the test result of channel 3 (turto mode) is 91.3dBuV/m, so the maximum field strength in restrict band is  $91.3 - 49.42 = 41.88$  dBuV/m which is under 54dBuV/m limit.







## **5.8 ANTENNA REQUIREMENT**

### **5.8.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407(a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **5.8.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna used in this product is Dipole antenna with UFL connector. The maximum Gain of the antenna is 3dBi.

## 6. PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 7. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP, UL
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.