



FCC TEST REPORT

REPORT NO.: RF921226R04

MODEL NO.: WRT54AG

RECEIVED: Dec. 19, 2003

TESTED: Dec. 22, 2003 ~ Jan. 9, 2004

APPLICANT: Cisco-Linksys, LLC

ADDRESS: 17401 Armstrong Ave., Irvine, CA 92614

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 119 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Table of Contents

1. CERTIFICATION.....	6
2. SUMMARY OF TEST RESULTS	7
3. GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	10
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.4 DESCRIPTION OF SUPPORT UNITS.....	12
3.5 CONFIGURATION OF SYSTEM UNDER TEST	12
4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND).....	13
4.1 CONDUCTED EMISSION MEASUREMENT.....	13
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
4.1.2 TEST INSTRUMENTS	13
4.1.3 TEST PROCEDURES	13
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP	14
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT.....	22
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	22
4.2.2 TEST INSTRUMENTS	23
4.2.3 TEST PROCEDURES	24
4.2.4 DEVIATION FROM TEST STANDARD	24
4.2.5 TEST SETUP	25
4.2.6 EUT OPERATING CONDITIONS	25
4.2.7 TEST RESULTS	26
4.2.8 TEST RESULTS	28
4.3 6dB BANDWIDTH MEASUREMENT	34
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	34
4.3.2 TEST INSTRUMENTS	34
4.3.3 TEST PROCEDURE	35
4.3.4 DEVIATION FROM TEST STANDARD	35
4.3.5 TEST SETUP	35
4.3.6 EUT OPERATING CONDITIONS	35
4.3.7 TEST RESULTS	36



4.4	MAXIMUM PEAK OUTPUT POWER.....	44
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT.....	44
4.4.2	TEST INSTRUMENTS.....	44
4.4.3	TEST PROCEDURES	45
4.4.4	DEVIATION FROM TEST STANDARD	45
4.4.5	TEST SETUP	45
4.4.6	EUT OPERATING CONDITIONS	45
4.4.7	TEST RESULTS	46
4.5	POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	47
4.5.2	TEST INSTRUMENTS	47
4.5.3	TEST PROCEDURE	48
4.5.4	DEVIATION FROM TEST STANDARD	48
4.5.5	TEST SETUP	48
4.5.6	EUT OPERATING CONDITION	48
4.5.7	TEST RESULTS	49
4.6	BAND EDGES MEASUREMENT.....	57
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	57
4.6.2	TEST INSTRUMENTS	57
4.6.3	TEST PROCEDURE	57
4.6.4	DEVIATION FROM TEST STANDARD	57
4.6.5	EUT OPERATING CONDITION	57
4.6.6	TEST RESULTS	58
4.7	ANTENNA REQUIREMENT	68
4.7.1	STANDARD APPLICABLE.....	68
4.7.2	ANTENNA CONNECTED CONSTRUCTION	68
5.	TEST TYPES AND RESULTS (FOR 5GHz BAND).....	69
5.1	CONDUCTED EMISSION MEASUREMENT.....	69
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	69
5.1.2	TEST INSTRUMENTS	69
5.1.3	TEST PROCEDURES	70
5.1.4	DEVIATION FROM TEST STANDARD	70
5.1.5	TEST SETUP	71
5.1.6	EUT OPERATING CONDITIONS	71
5.1.7	TEST RESULTS	72
5.2	RADIATED EMISSION MEASUREMENT.....	74
5.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	74



5.2.2	LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS..	75
5.2.3	TEST INSTRUMENTS.....	76
5.2.4	TEST PROCEDURES	77
5.2.5	DEVIATION FROM TEST STANDARD.....	77
5.2.6	TEST SETUP.....	78
5.2.7	EUT OPERATING CONDITIONS	78
5.2.8	TEST RESULTS	79
5.2.9	TEST RESULTS	81
5.3	PEAK TRANSMIT POWER MEASUREMENT.....	85
5.3.1	LIMITS OF PEAK TRANSMIT POWER MEASUREMENT	85
5.3.2	TEST INSTRUMENTS	85
5.3.3	TEST PROCEDURE	86
5.3.4	DEVIATION FROM TEST STANDARD	86
5.3.5	TEST SETUP	86
5.3.6	EUT OPERATING CONDITIONS	86
5.3.7	TEST RESULTS	87
5.4	PEAK POWER EXCURSION MEASUREMENT.....	96
5.4.1	LIMITS OF PEAK POWER EXCURSION MEASUREMENT	96
5.4.2	TEST INSTRUMENTS	96
5.4.3	TEST PROCEDURE	97
5.4.4	DEVIATION FROM TEST STANDARD	97
5.4.5	TEST SETUP	97
5.4.6	EUT OPERATING CONDITIONS	97
5.4.7	TEST RESULTS	98
5.5	PEAK POWER SPECTRAL DENSITY MEASUREMENT.....	103
5.5.1	LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT	103
5.5.2	TEST INSTRUMENTS	103
5.5.3	TEST PROCEDURES	103
5.5.4	DEVIATION FROM TEST STANDARD	103
5.5.5	TEST SETUP	104
5.5.6	EUT OPERATING CONDITIONS	104
5.5.7	TEST RESULTS	105
5.6	FREQUENCY STABILITY.....	110
5.6.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT.....	110
5.6.2	TEST INSTRUMENTS	110
5.6.3	TEST PROCEDURE	110
5.6.4	DEVIATION FROM TEST STANDARD	110



5.6.5 TEST SETUP	111
5.6.6 EUT OPERATING CONDITION	111
5.6.7 TEST RESULTS	112
5.7 BAND EDGES MEASUREMENT.....	113
5.7.1 TEST INSTRUMENTS	113
5.7.2 TEST PROCEDURE	113
5.7.3 EUT OPERATING CONDITION	113
5.7.4 TEST RESULTS	113
5.8 ANTENNA REQUIREMENT	116
5.8.1 STANDARD APPLICABLE.....	116
5.8.2 ANTENNA CONNECTED CONSTRUCTION	116
6. PHOTOGRAPHS OF THE TEST CONFIGURATION	117
7. INFORMATION ON THE TESTING LABORATORIES.....	119



1. CERTIFICATION

PRODUCT : Wireless A/G Broadband Router
BRAND NAME : Linksys
MODEL NO. : WRT54AG
TEST ITEM : ENGINEERING SAMPLE
APPLICANT : Cisco-Linksys, LLC
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
Subpart E (Section 15.407),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Dec. 22, 2003 ~ Jan. 9, 2004. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

PREPARED BY: Rita Yi, **DATE:** Jan. 13, 2004
Rita Yi

APPROVED BY: Ellis Wu, **DATE:** Jan. 13, 2004
Ellis Wu, Manager



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.21dB at 0.420MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -1.11dB at 2483.50MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(e)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

NOTE: The information of measurement uncertainty is available upon the customer's request.

APPLIED STANDARD: FCC Part 15, Subpart E

Standard Section	Test Type	Result	REMARK
15.407(b)(5)	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.29dB at 0.416MHz
15.407(b/1/2/3)(b)(5)	Electric Field Strength Spurious Emissions, 30MHz ~ 40000MHz	PASS	Meet the requirement of limit Minimum passing margin is -2.37dB at 280.76MHz
15.407(a/1/2/3)	Peak Transmit Power	PASS	Meet the requirement of limit
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit
15.407(a/1/2/3)	Peak Power Spectral Density	PASS	Meet the requirement of limit
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit

NOTE: The information of measurement uncertainty is available upon the customer's request.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless A/G Broadband Router
MODEL NO.	WRT54AG
POWER SUPPLY	5Vdc from power adapter
MODULATION TYPE	BPSK, QPSK, CCK, 16QAM, 64QAM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	54/48/36/24/18/12/11/9/6/5.5/2/1Mbps
FREQUENCY RANGE	802.11b and 802.11g: 2412~2462MHz 802.11a: 5.15~5.35GHz
NUMBER OF CHANNEL	802.11b and 802.11g: 11 802.11a: 8
CHANNEL SPACING	802.11b and 802.11g: 5MHz 802.11a: 20MHz
OUTPUT POWER	802.11b and 802.11g: 13.6dBm 802.11a: 13.54dBm
ANTENNA TYPE	Dipole antenna
DATA CABLE	Unshielded Twisted Pair, UTP, Cable
I/O PORTS	RJ45
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was powered by the following adapter:

BRAND :	Linksys
MODEL :	MS15-050250-A1D
INPUT :	100-240Vac, 50/60Hz, 0.5A
OUTPUT :	5Vdc / 2.5A

2. The EUT operates in both the 5GHz and 2.4GHz Bands and compatibility with 802.11a and 802.11g technology.
3. IEEE 802.11a, 802.11b, and draft 802.11g compliant.
4. For more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 DESCRIPTION OF TEST MODES

For 802.11b and 802.11g: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1GHz, channels 1, 6, and 11 were pre-tested in chamber. Channel 11, the worst case, was chosen for final test.
2. Above 1GHz, channels 1, 6, and 11 were tested individually.
3. Transfer rates at 6Mbps with OFDM technique, worst cases, was chosen for final test.

For 802.11a: Eight channels are provided to this EUT for Normal mode.

Channel	Frequency	Channel	Frequency
1	5180 MHz	5	5260 MHz
2	5200 MHz	6	5280 MHz
3	5220 MHz	7	5300 MHz
4	5240 MHz	8	5320 MHz

NOTE:

1. The EUT was tested in normal mode (channel bandwidth of approximately 30MHz).
2. "Normal Mode" allows data rates of up to 54Mbps. The device was, therefore, tested in Normal mode at the data rate that produced the highest output power for normal mode at 6Mbps.
3. Channel 1, 4, 5, and 8 are the closest frequencies to the band edge, were chosen for final test of Normal Mode.



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless A/G Broadband Router. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247),
Subpart E (15.407)**

ANSI C63.4-1992

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	C600	N/A	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC Approved
3	MODEM	ACEEX	1414	980020503	IFAXDM1414
4	NOTEBOOK	Compaq	N800C	470048-515	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.
4	N/A

NOTE: All power cords of the above support units are non-shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST





4. TEST TYPES AND RESULTS (FOR 2.4GHz BAND)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Jan. 20, 2004
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Dec. 09, 2004
*ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 19, 2004
*ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 19, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	May 01, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010770	Mar. 24, 2004
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Apr. 06, 2004

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. **: These equipment are used for conducted telecom port test only (if tested).
3. The test was performed in ADT Shielded Room No. 10.
4. The VCCI Site Registration No. is C-1312.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



4.1.6 EUT OPERATING CONDITIONS

- a. Placed the EUT on the testing table.
- b. The computer system sent data to EUT by command "PING" via RJ45 cable.
- c. The computer system displayed "H" patterns on its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to the printer, and the printer prints them on paper.
- f. Prepared another computer system to act as a communication partner and placed it outside of testing area.
- g. The communication partner ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency via RJ45 cable and wireless.
- h. The communication partner sent data to EUT by command "PING".
- i. Repeat steps b~i.


4.1.7 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	1	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.138	0.10	44.28	55.75	44.38	55.85	-	-	-	-
2	0.274	0.10	43.60	-	43.70	-	61.01	51.01	-17.31	-
3	0.420	0.10	41.14	-	41.24	-	57.46	47.46	-16.21	-
4	2.080	0.20	34.49	-	34.69	-	56.00	46.00	-21.31	-
5	4.914	0.35	31.66	-	32.01	-	56.00	46.00	-23.99	-
6	18.023	0.86	30.26	-	31.12	-	60.00	50.00	-28.88	-

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	1	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.10	38.12	-	38.22	-	66.00	56.00	-27.78	-
2	0.274	0.10	42.48	-	42.58	-	61.01	51.01	-18.43	-
3	0.420	0.10	39.03	-	39.13	-	57.46	47.46	-18.32	-
4	0.969	0.19	34.34	-	34.53	-	56.00	46.00	-21.47	-
5	2.090	0.20	36.54	-	36.74	-	56.00	46.00	-19.26	-
6	10.473	0.52	33.66	-	34.18	-	60.00	50.00	-25.82	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	6	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.150	0.10	38.20	-	38.30	-	66.00	56.00	-27.70	-
2	0.276	0.10	43.47	-	43.57	-	60.93	50.93	-17.36	-
3	0.417	0.10	40.93	-	41.03	-	57.51	47.51	-16.48	-
4	2.063	0.20	34.14	-	34.34	-	56.00	46.00	-21.66	-
5	5.055	0.35	31.32	-	31.67	-	60.00	50.00	-28.33	-
6	12.809	0.71	31.70	-	32.41	-	60.00	50.00	-27.59	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	6	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.150	0.10	36.11	-	36.21	-	66.00	56.00	-29.79	-
2	0.270	0.10	42.09	-	42.19	-	61.12	51.12	-18.93	-
3	0.420	0.10	36.96	-	37.06	-	57.46	47.46	-20.39	-
4	0.955	0.19	36.75	-	36.94	-	56.00	46.00	-19.06	-
5	2.195	0.21	35.54	-	35.75	-	56.00	46.00	-20.25	-
6	10.531	0.52	33.62	-	34.14	-	60.00	50.00	-25.86	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.267	0.10	38.96	-	39.06	-	61.20	51.20	-22.14	-
2	0.416	0.10	41.18	-	41.28	-	57.54	47.54	-16.25	-
3	0.537	0.12	32.47	-	32.59	-	56.00	46.00	-23.41	-
4	0.689	0.15	33.76	-	33.91	-	56.00	46.00	-22.09	-
5	2.066	0.20	34.11	-	34.31	-	56.00	46.00	-21.69	-
6	10.160	0.61	31.52	-	32.13	-	60.00	50.00	-27.87	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	6dB BANDWIDTH	9kHz
MODULATION	OFDM	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	20deg.C, 60%RH, 991hPa	INPUT POWER (SYSTEM)	120Vac, 60Hz
TESTED BY	Jamison Chan		

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.273	0.10	42.60	-	42.70	-	61.04	51.04	-18.34	-
2	0.416	0.10	38.11	-	38.21	-	57.54	47.54	-19.32	-
3	0.951	0.19	36.53	-	36.72	-	56.00	46.00	-19.28	-
4	2.063	0.20	36.38	-	36.58	-	56.00	46.00	-19.42	-
5	7.375	0.41	32.03	-	32.44	-	60.00	50.00	-27.56	-
6	14.570	0.68	31.74	-	32.42	-	60.00	50.00	-27.58	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_BV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8593E	3911A07465	July 07, 2004
* HP Preamplifier	8447D	2432A03504	June 10, 2004
* HP Preamplifier	8449B	3008A01201	Dec. 11, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Jun. 26, 2004
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Feb. 13, 2004
*Schwarzbeck Antenna	VULB9168	137	Apr. 03, 2004
SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	June 30, 2004
*ADT. Turn Table	TT100	0306	NA
*ADT. Tower	AT100	0306	NA
*Software	ADT_Radiated_V 5.14	NA	NA
*TIMES RF cable	LL142	CABLE-CH6-01	Apr. 30, 2004

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*” = These equipment are used for the final measurement.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The test was performed in ADT Chamber No. 6.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



4.2.7 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	FREQUENCY RANGE	Below 1000MHz
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	218.51	41.32 QP	46.00	-4.68	1.25 H	33	29.21	12.11
2	280.76	43.63 QP	46.00	-2.37	1.00 H	331	28.98	14.65
3	300.20	38.79 QP	46.00	-7.21	1.00 H	88	23.70	15.10
4	342.97	34.69 QP	46.00	-11.31	1.00 H	205	18.45	16.23
5	374.07	34.89 QP	46.00	-11.11	1.00 H	235	17.85	17.04
6	500.42	37.03 QP	46.00	-8.97	1.50 H	307	17.01	20.02
7	562.63	30.91 QP	46.00	-15.09	1.50 H	355	9.42	21.49
8	624.83	39.32 QP	46.00	-6.68	1.00 H	37	16.40	22.92
9	687.03	34.75 QP	46.00	-11.25	1.00 H	340	10.96	23.79
10	720.08	38.77 QP	46.00	-7.23	1.00 H	1	14.24	24.53
11	749.24	36.51 QP	46.00	-9.49	1.00 H	181	11.18	25.33
12	817.27	36.50 QP	46.00	-9.50	1.00 H	148	10.70	25.80
13	912.53	38.21 QP	46.00	-7.79	1.00 H	229	10.93	27.28

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	FREQUENCY RANGE	Below 1000MHz
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	218.51	43.57 QP	46.00	-2.43	1.00 V	54	31.46	12.11
2	280.76	37.64 QP	46.00	-8.36	1.50 V	10	22.99	14.65
3	342.97	31.76 QP	46.00	-14.24	1.50 V	262	15.53	16.23
4	342.97	31.76 QP	46.00	-14.24	1.50 V	262	15.53	16.23
5	374.07	37.94 QP	46.00	-8.06	1.50 V	250	20.89	17.04
6	399.34	33.53 QP	46.00	-12.47	1.00 V	7	15.83	17.69
7	500.42	38.02 QP	46.00	-7.98	1.00 V	79	18.00	20.02
8	624.83	40.28 QP	46.00	-5.72	1.00 V	298	17.36	22.92
9	720.08	38.56 QP	46.00	-7.44	1.00 V	355	14.03	24.53
10	749.24	41.91 QP	46.00	-4.09	1.00 V	355	16.59	25.33
11	817.27	36.40 QP	46.00	-9.60	1.50 V	82	10.60	25.80
12	875.59	36.03 QP	46.00	-9.97	1.50 V	166	9.38	26.65
13	912.53	37.63 QP	46.00	-8.37	1.00 V	88	10.34	27.28

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



4.2.8 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	47.96 PK	74.00	-26.04	1.00 H	309	18.31	29.65
1	2390.00	41.30 AV	54.00	-12.70	1.00 H	309	11.60	29.65
2	*2412.00	104.48 PK			1.00 H	309	74.76	29.72
2	*2412.00	97.81 AV			1.00 H	309	68.09	29.72
3	4824.00	43.85 PK	74.00	-30.15	1.05 H	126	8.40	35.45
4	9648.00	55.88 PK	84.48	-28.60	1.56 H	139	11.41	44.46
4	9648.00	44.18 AV	77.81	-33.63	1.56 H	139	-0.29	44.46

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.67 PK	74.00	-18.33	1.00 V	124	26.02	29.65
1	2390.00	48.50 AV	54.00	-5.50	1.00 V	124	18.85	29.65
2	*2412.00	112.19 PK			1.00 V	124	82.47	29.72
2	*2412.00	105.02 AV			1.00 V	124	75.30	29.72
3	4824.00	45.00 PK	74.00	-29.00	1.05 V	177	9.55	35.45
4	9648.00	56.93 PK	92.19	-35.26	1.13 V	106	12.46	44.46
4	9648.00	51.33 AV	85.02	-33.69	1.13 V	106	6.86	44.46

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	103.23 PK			1.70 H	201	73.44	29.79
1	*2437.00	95.67 AV			1.70 H	201	65.88	29.79
2	4874.00	44.17 PK	74.00	-29.83	1.20 H	213	8.38	35.79
3	9748.00	54.12 PK	83.23	-29.11	1.16 H	177	9.92	44.20
3	9748.00	43.28 AV	75.67	-32.39	1.16 H	177	-0.92	44.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	113.46 PK			1.00 V	116	83.67	29.79
1	*2437.00	106.21 AV			1.00 V	116	76.42	29.79
2	4874.00	45.25 PK	74.00	-28.75	1.04 V	158	9.46	35.79
3	9748.00	56.84 PK	93.46	-36.62	1.08 V	103	12.64	44.20
3	9748.00	51.38 AV	86.21	-34.83	1.08 V	103	7.18	44.20

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “*”: Fundamental frequency.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.16 PK			1.00 H	303	73.31	29.85
1	*2462.00	96.11 AV			1.00 H	303	66.26	29.85
2	2483.50	47.54 PK	74.00	-26.46	1.00 H	303	17.63	29.91
3	4924.00	43.87 PK	74.00	-30.13	1.05 H	183	7.78	36.09
4	9848.00	54.25 PK	83.16	-28.91	1.98 H	36	10.15	44.10
4	9848.00	45.06 AV	76.11	-31.05	1.98 H	36	0.96	44.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.17 PK			1.00 V	195	82.32	29.85
1	*2462.00	105.11 AV			1.00 V	195	75.26	29.85
2	2483.50	56.55 PK	74.00	-17.45	1.00 V	195	26.64	29.91
2	2483.50	49.49 AV	54.00	-4.51	1.00 V	195	19.58	29.91
3	4924.00	46.00 PK	74.00	-28.00	1.05 V	187	9.91	36.09
4	9848.00	57.91 PK	92.17	-34.26	1.56 V	102	13.80	44.10
4	9848.00	51.54 AV	85.11	-33.57	1.56 V	102	7.43	44.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “*”: Fundamental frequency.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	50.88 PK	74.00	-23.12	1.70 H	345	21.23	29.65
1	2390.00	42.68 AV	54.00	-11.32	1.70 H	345	13.03	29.65
2	*2412.00	100.55 PK			1.70 H	345	70.83	29.72
2	*2412.00	92.35 AV			1.70 H	345	62.63	29.72
3	4824.00	44.14 PK	74.00	-29.86	1.00 H	235	8.69	35.45
4	9648.00	54.97 PK	80.55	-25.58	1.07 H	182	10.50	44.46
4	9648.00	44.82 AV	72.35	-27.53	1.07 H	182	0.35	44.46

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.14 PK	74.00	-15.86	1.78 V	60	28.49	29.65
1	2390.00	50.25 AV	54.00	-3.75	1.78 V	60	20.60	29.65
2	*2412.00	107.81 PK			1.78 V	60	78.09	29.72
2	*2412.00	99.92 AV			1.78 V	60	70.20	29.72
3	4824.00	45.29 PK	74.00	-28.71	1.10 V	144	9.84	35.45
4	9648.00	58.11 PK	87.81	-29.70	1.13 V	108	13.64	44.46
4	9648.00	50.19 AV	79.92	-29.73	1.13 V	108	5.72	44.46

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	98.87 PK			1.00 H	304	69.08	29.79
1	*2437.00	90.84 AV			1.00 H	304	61.05	29.79
2	4874.00	44.70 PK	74.00	-29.30	1.02 H	268	8.91	35.79
3	9748.00	54.01 PK	78.87	-24.86	1.14 H	183	9.82	44.20
3	9748.00	43.67 AV	70.84	-27.71	1.14 H	183	-0.52	44.20

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2437.00	*108.87 PK			1.00 V	110	79.08	29.79
1	2437.00	*100.86 AV			1.00 V	110	71.07	29.79
2	4874.00	45.70 PK	74.00	-28.30	1.24 V	120	9.91	35.79
3	9748.00	57.12 PK	88.87	-31.75	1.56 V	106	12.93	44.20
3	9748.00	50.32 AV	80.86	-30.54	1.56 V	106	6.13	44.20

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
CHANNEL	11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	20deg.C, 70%RH, 991hPa	DETECTOR FUNCTION	Peak(PK) Average (AV)
TESTED BY	Steven Lu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	99.23 PK			1.70 H	14	69.38	29.85
1	*2462.00	91.17 AV			1.70 H	14	61.32	29.85
2	2483.50	52.18 PK	74.00	-21.82	1.70 H	14	22.27	29.91
2	2483.50	44.12 AV	54.00	-9.88	1.70 H	14	14.21	29.91
3	4924.00	44.11 PK	74.00	-29.89	1.04 H	188	8.02	36.09
4	9848.00	54.90 PK	79.23	-24.33	2.08 H	4	10.79	44.10
4	9848.00	44.94 AV	71.17	-26.23	2.08 H	4	0.83	44.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.58 PK			1.00 V	111	77.73	29.85
1	*2462.00	99.94 AV			1.00 V	111	70.09	29.85
2	2483.50	60.53 PK	74.00	-13.47	1.00 V	111	30.62	29.91
2	2483.50	52.89 AV	54.00	-1.11	1.00 V	111	22.98	29.91
3	4924.00	44.19 PK	74.00	-29.81	1.00 V	108	8.10	36.09
4	9848.00	57.14 PK	87.58	-30.44	1.00 V	111	13.03	44.10
4	9848.00	50.84 AV	79.94	-29.10	1.00 V	111	6.73	44.10

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency.



4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


FCC ID: Q87-WRT54AG




4.3.7 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MPDULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.56	0.5	PASS
6	2437	11.52	0.5	PASS
11	2462	11.52	0.5	PASS

**CH1**


CH6



FCC ID: Q87-WRT54AG



CH11




FCC ID: Q87-WRT54AG



EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MODULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.36	0.5	PASS
6	2437	16.32	0.5	PASS
11	2462	16.36	0.5	PASS

CH1






CH6



CH11





4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator . The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

FCC ID: Q87-WRT54AG



4.4.7 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MPDULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	13.5	30	PASS
6	2437	13.5	30	PASS
11	2462	13.6	30	PASS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MPDULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	13.4	30	PASS
6	2437	13.6	30	PASS
11	2462	13.5	30	PASS



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.



4.5.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6





4.5.7 TEST RESULTS

EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MPDULATION	CCK	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan


CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-5.30	8	PASS
6	2437	-5.28	8	PASS
11	2462	-5.15	8	PASS

CH1



**CH6**

CH11



FCC ID: Q87-WRT54AG




EUT	Wireless A/G Broadband Router	MODEL	WRT54AG
MPDULATION	OFDM	INPUT POWER (SYSTEM)	120Vac, 60Hz
ENVIRONMENTAL CONDITIONS	27deg.C, 60%RH, 991hPa	TESTED BY	Jamison Chan

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.70	8	PASS
6	2437	-13.45	8	PASS
11	2462	-13.27	8	PASS




CH1






CH6





CH11





4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug.12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100kHz bandwidth from band edge for CCK technique and set RBW=1MHz and VBW=10Hz of spectrum analyzer to 100kHz with suitable frequency span including 100kHz bandwidth from band edge for OFDM technique. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



4.6.6 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

FOR MODULATION CCK

NOTE 1: The band edge emission plot of CCK technique on the following page shows 54.09dB delta between carrier maximum power and local maximum emission in restrict band (2.3868GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 105.02dB_{UV}/m, so the maximum field strength in restrict band is $105.02 - 54.09 = 50.93$ dB_{UV}/m, which is under 54dB_{UV}/m limit.

NOTE 2: The band edge emission plot of CCK on the following 2nd page shows 54.81dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 105.11dB_{UV}/m, so the maximum field strength in restrict band is $105.11 - 54.81 = 50.30$ dB_{UV}/m, which is under 54dB_{UV}/m limit.

