




Turbo Mode (CH3)









5.8 ANTENNA REQUIREMENT

5.8.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407(a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.8.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is dipole antenna with UFL antenna connector. The maximum Gain of the antenna is 4dBi.

FOR FREQUENCY 5.725~5.850GHz**5.9 6dB BANDWIDTH MEASUREMENT****5.9.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT**

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

5.9.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.9.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

5.9.4 DEVIATION FROM TEST STANDARD

No deviation.

5.9.5 TEST SETUP



5.9.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.9.7 TEST RESULTS

EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Normal	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24 deg. C, 67% RH, 991 hPa	TESTED BY	Leo Hung


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
9	5745	16.55	0.5	PASS
11	5785	16.57	0.5	PASS
13	5825	16.51	0.5	PASS

Delta 1 [T1]
 -0.15 dB
 16.55310621 MHz
 Ref Lvl 10.5 dBm
 RBW 100 kHz
 VBW 100 kHz
 SWT 5 ms
 RF Att 20 dB
 Unit dBm


0.5 dB Offset
 D1 -2.22 dBm
 D2 -8.22 dBm
 F1 TH -89.5 dBm
 F2
 1MA

Center 5.745 GHz
 2 MHz
 Span 20 MHz

CH11



CH13





EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Turbo	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24 deg. C, 67% RH, 991 hPa	TESTED BY	Leo Hung

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
4	5760	32.71	0.5	PASS
5	5800	32.63	0.5	PASS

Delta 1 [T1] 100 kHz RBW 100 kHz RF Att 20 dB

Ref Lvl 10.5 dBm 1.97 dB VBW 100 kHz Unit dBm

10.5 dB Offset

0 -10 -20 -30 -40 -50 -60 -70 -80 -89.5


0 10 20 30 40 50 60 70 80 90 100

F1 F2

1MA

Center 5.76 GHz Span 40 MHz

CH5





5.10 MAXIMUM PEAK OUTPUT POWER

5.10.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

5.10.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 31, 2004
TEKTRONIX OSCILLOSCOPE	TDS 1012	C019167	Feb. 01, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..

5.10.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator . The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

5.10.4 DEVIATION FROM TEST STANDARD

No deviation.

5.10.5 TEST SETUP



5.10.6 EUT OPERATING CONDITIONS

Same as Item 5.9.6.

5.10.7 TEST RESULTS

EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Normal	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24 deg. C, 67% RH, 991 hPa	TESTED BY	Leo Hung

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
9	5745	40.738	16.10	30	PASS
11	5785	41.687	16.20	30	PASS
13	5825	39.811	16.00	30	PASS

EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Turbo	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24 deg. C, 67% RH, 991 hPa	TESTED BY	Leo Hung

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
4	5760	40.738	16.10	30	PASS
5	5800	41.687	16.20	30	PASS

5.11 POWER SPECTRAL DENSITY MEASUREMENT

5.11.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.11.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTES:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.11.3 TEST PROCEDURE


The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time = span/3 kHz. The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span/3 kHz for a full response of the mixer in the spectrum analyzer.

5.11.4 DEVIATION FROM TEST STANDARD

No deviation.

5.11.5 TEST SETUP



5.11.6 EUT OPERATING CONDITION


Same as Item 5.9.6.

5.11.7 TEST RESULTS


EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Normal	INPUT POWER (SYSTEM)	120 Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24 deg. C, 67% RH, 991 hPa	TESTED BY	Leo Hung

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
9	5745	-11.30	8	PASS
11	5785	-11.69	8	PASS
13	5825	-11.34	8	PASS


CH9



CH11



CH13





EUT	Wireless A+G Broadband Router	MODEL	WRT55AG ver. 2
MODE	Turbo	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	24deg. C, 65%RH, 991 hPa	TESTED BY	Steven Lu

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
4	5760	-11.35	8	PASS
5	5800	-11.46	8	PASS