



FCC TEST REPORT

REPORT NO.: RF921128R03

MODEL NO.: WUSB54GP

RECEIVED: Sep. 8, 2003

TESTED: Sep. 8 ~ Dec. 16, 2003

REPORT HOLDER: Cisco-Linksys, LLC

ADDRESS: 17401 Armstrong Ave., Irvine, CA 92614

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: 47 14th Lin, Chiapau Tsun, Linko, Taipei,
Taiwan, R.O.C.

This test report consists of 73 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



Lab Code: 200102-0

Table of Contents

1	CERTIFICATION	4
2	SUMMARY OF TEST RESULTS	5
3	GENERAL INFORMATION	6
3.1	GENERAL DESCRIPTION OF EUT	6
3.2	DESCRIPTION OF TEST MODES	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.4	DESCRIPTION OF SUPPORT UNITS	8
3.5	CONFIGURATION OF SYSTEM UNDER TEST	9
4	TEST TYPES AND RESULTS	10
4.1	CONDUCTED EMISSION MEASUREMENT	10
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	10
4.1.2	TEST INSTRUMENTS	10
4.1.3	TEST PROCEDURES	11
4.1.4	DEVIATION FROM TEST STANDARD	11
4.1.5	TEST SETUP	12
4.1.6	EUT OPERATING CONDITIONS	12
4.1.7	TEST RESULTS	13
4.2	RADIATED EMISSION MEASUREMENT	25
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	25
4.2.2	TEST INSTRUMENTS	26
4.2.3	TEST PROCEDURES	27
4.2.4	DEVIATION FROM TEST STANDARD	27
4.2.5	TEST SETUP	28
4.2.6	EUT OPERATING CONDITIONS	28
4.2.7	TEST RESULTS	29
4.2.8	TEST RESULTS (For CCK)	31
4.2.9	TEST RESULTS (For OFDM)	34
4.3	6dB BANDWIDTH MEASUREMENT	37
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	37
4.3.2	TEST INSTRUMENTS	37
4.3.3	TEST PROCEDURE	38
4.3.4	DEVIATION FROM TEST STANDARD	38
4.3.5	TEST SETUP	38
4.3.6	EUT OPERATING CONDITIONS	38
4.3.7	TEST RESULTS (For CCK)	39



4.3.8	TEST RESULTS (For OFDM)	43
4.4	MAXIMUM PEAK OUTPUT POWER	47
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	47
4.4.2	TEST INSTRUMENTS	47
4.4.3	TEST PROCEDURES	48
4.4.4	DEVIATION FROM TEST STANDARD	48
4.4.5	TEST SETUP	48
4.4.6	EUT OPERATING CONDITIONS	48
4.4.4	TEST RESULTS (For CCK)	49
4.4.5	TEST RESULTS (For OFDM)	50
4.5	POWER SPECTRAL DENSITY MEASUREMENT	51
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	51
4.5.2	TEST INSTRUMENTS	51
4.5.3	TEST PROCEDURE	52
4.5.4	DEVIATION FROM TEST STANDARD	52
4.5.5	TEST SETUP	52
4.5.6	EUT OPERATING CONDITIONS	52
4.5.7	TEST RESULTS (For CCK)	53
4.5.8	TEST RESULTS (For OFDM)	57
4.6	BAND EDGES MEASUREMENT	61
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	61
4.6.2	TEST INSTRUMENTS	61
4.6.3	TEST PROCEDURE	61
4.6.4	DEVIATION FROM TEST STANDARD	61
4.6.5	EUT OPERATING CONDITION	62
4.6.6	TEST RESULTS (For CCK)	62
4.6.7	TEST RESULTS (For OFDM)	65
4.7	ANTENNA REQUIREMENT	68
4.7.1	STANDARD APPLICABLE	68
4.7.2	ANTENNA CONNECTED CONSTRUCTION	68
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	69
6	INFORMATION ON THE TESTING LABORATORIES	73



1 CERTIFICATION

PRODUCT : Wireless-G USB 2.0 Pen-type Network Adapter
BRAND NAME : Linksys
MODEL NO. : WUSB54GP
TEST IDEM : Engineering Sample
REPORT HOLDER : Cisco-Linksys, LLC
STANDARDS : FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Sep. 8 ~ Dec. 16, 2003. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

PREPARED BY:  , **DATE:** Dec. 18, 2003
Stephanie Hung

APPROVED BY:  , **DATE:** Dec. 18, 2003
Ellis Wu / Manager

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.36dB at 0.18MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -3.90dB at 480.12MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit

Note: The information of measurement uncertainty is available upon the customer's request.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Wireless-G USB 2.0 Pen-type Network Adapter
MODEL NO.	WUSB54GP
POWER SUPPLY	5Vdc from host equipment
MODULATION TYPE	DBPSK,DQPSK,CCK,16QAM,64QAM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b:1/2/5.5/11Mbps 802.11g:6/12/18/24/36/48/54Mbps
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	11
OUTPUT POWER	16.30dBm
ANTENNA TYPE	Dipole Antenna
ANTENNA GAIN	2dBi
DATA CABLE	USB 1.8m shielded cable
I/O PORTS	USB
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
2. The EUT complies with IEEE 802.11g draft standards, and backwards compatible with IEEE 802.11b products.
3. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

NOTE:

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.
3. Transfer rate of 11Mbps with CCK technique and 6Mbps with OFDM technique, the worst case, were chosen for final test.
4. For Conducted Emission test and Radiated Emission test (below 1GHz). There are two test modes for this EUT. The test mode 1 is powered by host equipment and the test mode 2 is powered by charging cradle.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Wireless-G USB 2.0 Pen-type Network Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)
ANSI C63.4 : 1992

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK COMPUTER	DELL	PP05L	24729091408	FCC DoC Approved
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC Approved
3	MODEM	ACEEX	1414	980020516	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.


NOTE: All power cords of the above support units are non shielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST

Mode 1:



Mode 2:



4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS 30	838251/021	Jan. 20, 2004
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH3-Z5	100218	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100219	Dec. 09, 2004
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	100220	Dec. 09, 2004
*ROHDE & SCHWARZ 4-wire ISN	ENY41	837032/016	Nov. 19, 2004
*ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/016	Nov. 19, 2004
Software	Cond-V2M3	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C10.01	May 01, 2004
SUHNTER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010770	Mar. 24, 2004
SUHNTER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010773	Apr. 06, 2004

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. “*”: These equipment are used for conducted telecom port test only (if tested).
 3. The test was performed in ADT Shielded Room No. 10.
 4. The VCCI Site Registration No. is C-1312.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Plug the EUT into the notebook system placed on a testing table.
- b. The notebook system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to printer, and the printer prints them on paper.
- e. Repeat c~d.


4.1.7 TEST RESULTS

Test Mode 1:

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.205	0.06	44.39	-	44.45	-	63.42	53.42	-18.97	-
2	0.220	0.06	45.72	-	45.78	-	62.81	52.81	-17.03	-
3	0.275	0.06	9.97	-	10.03	-	60.97	50.97	-50.94	-
4	0.380	0.06	4.53	-	4.59	-	58.27	48.27	-53.68	-
5	2.039	0.18	27.67	-	27.85	-	56.00	46.00	-28.15	-
6	10.598	0.43	29.07	-	29.50	-	60.00	50.00	-30.50	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.209	0.05	44.31	-	44.36	-	63.26	53.26	-18.90	-
2	0.306	0.05	29.79	-	29.84	-	60.07	50.07	-30.23	-
3	1.559	0.17	26.95	-	27.12	-	56.00	46.00	-28.88	-
4	2.004	0.18	27.68	-	27.86	-	56.00	46.00	-28.14	-
5	2.406	0.19	25.95	-	26.14	-	56.00	46.00	-29.86	-
6	10.750	0.40	28.39	-	28.79	-	60.00	50.00	-31.21	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.201	0.06	44.43	-	44.49	-	63.58	53.58	-19.09	-
2	0.314	0.06	32.94	-	33.00	-	59.86	49.86	-26.86	-
3	0.412	0.06	28.19	-	28.25	-	57.61	47.61	-29.36	-
4	2.129	0.18	27.67	-	27.85	-	56.00	46.00	-28.15	-
5	7.121	0.32	23.42	-	23.74	-	60.00	50.00	-36.26	-
6	9.902	0.41	29.00	-	29.41	-	60.00	50.00	-30.59	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.201	0.05	44.10	-	44.15	-	63.58	53.58	-19.43	-
2	0.302	0.05	30.19	-	30.24	-	60.18	50.18	-29.94	-
3	0.513	0.07	22.82	-	22.89	-	56.00	46.00	-33.11	-
4	1.918	0.18	26.56	-	26.74	-	56.00	46.00	-29.26	-
5	5.465	0.25	22.37	-	22.62	-	60.00	50.00	-37.38	-
6	10.418	0.40	28.62	-	29.02	-	60.00	50.00	-30.98	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.209	0.06	45.59	-	45.65	-	63.26	53.26	-17.61	-
2	0.322	0.06	33.44	-	33.50	-	59.66	49.66	-26.16	-
3	0.412	0.06	28.02	-	28.08	-	57.61	47.61	-29.53	-
4	0.533	0.08	27.08	-	27.16	-	56.00	46.00	-28.84	-
5	2.141	0.18	27.45	-	27.63	-	56.00	46.00	-28.37	-
6	9.020	0.38	29.41	-	29.79	-	60.00	50.00	-30.21	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.205	0.05	44.69	-	44.74	-	63.42	53.42	-18.68	-
2	0.298	0.05	26.73	-	26.78	-	60.29	50.29	-33.51	-
3	0.416	0.05	26.37	-	26.42	-	57.54	47.54	-31.11	-
4	0.537	0.07	25.72	-	25.79	-	56.00	46.00	-30.21	-
5	1.719	0.17	27.64	-	27.81	-	56.00	46.00	-28.19	-
6	10.574	0.40	28.56	-	28.96	-	60.00	50.00	-31.04	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.




Test Mode 2:

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.06	43.48	-	43.54	-	64.61	54.61	-21.07	-
2	0.200	0.06	44.56	-	44.62	-	63.58	53.58	-18.96	-
3	0.232	0.06	42.26	-	42.32	-	62.38	52.38	-20.06	-
4	0.271	0.06	33.63	-	33.69	-	61.08	51.08	-27.39	-
5	2.093	0.18	26.09	-	26.27	-	56.00	46.00	-29.73	-
6	10.261	0.42	29.21	-	29.63	-	60.00	50.00	-30.37	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.05	46.39	-	46.44	-	64.79	54.79	-18.35	-
2	0.228	0.05	43.40	-	43.45	-	62.52	52.52	-19.07	-
3	0.255	0.05	18.32	-	18.37	-	61.58	51.58	-43.21	-
4	1.957	0.18	28.01	-	28.19	-	56.00	46.00	-27.81	-
5	10.734	0.40	28.45	-	28.85	-	60.00	50.00	-31.15	-
6	17.418	0.50	22.51	-	23.01	-	60.00	50.00	-36.99	-


REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.06	28.25	-	28.31	-	65.58	55.58	-37.27	-
2	0.177	0.06	47.43	-	47.49	-	64.61	54.61	-17.12	-
3	0.259	0.06	33.79	-	33.85	-	61.45	51.45	-27.60	-
4	1.910	0.18	27.75	-	27.93	-	56.00	46.00	-28.07	-
5	9.121	0.38	29.42	-	29.80	-	60.00	50.00	-30.20	-
6	10.504	0.43	29.01	-	29.44	-	60.00	50.00	-30.56	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.05	46.45	-	46.50	-	64.79	54.79	-18.29	-
2	0.213	0.05	46.05	-	46.10	-	63.11	53.11	-17.01	-
3	0.267	0.05	32.33	-	32.38	-	61.20	51.20	-28.82	-
4	1.473	0.17	26.15	-	26.32	-	56.00	46.00	-29.68	-
5	8.426	0.34	27.12	-	27.46	-	60.00	50.00	-32.54	-
6	10.473	0.40	28.52	-	28.92	-	60.00	50.00	-31.08	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Line (L)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.181	0.06	48.01	-	48.07	-	64.43	54.43	-16.36	-
2	0.212	0.06	45.95	-	46.01	-	63.11	53.11	-17.10	-
3	0.271	0.06	34.18	-	34.24	-	61.08	51.08	-26.84	-
4	1.750	0.17	27.46	-	27.63	-	56.00	46.00	-28.37	-
5	2.277	0.19	26.19	-	26.38	-	56.00	46.00	-29.62	-
6	9.195	0.39	29.46	-	29.85	-	60.00	50.00	-30.15	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	PHASE	Neutral (N)
ENVIRONMENTAL CONDITIONS	18deg. C, 60%RH, 991 hPa	TESTED BY: Jamison Chan	

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.05	47.49	-	47.54	-	64.61	54.61	-17.07	-
2	0.197	0.05	46.57	-	46.62	-	63.74	53.74	-17.12	-
3	0.263	0.05	33.75	-	33.80	-	61.33	51.33	-27.53	-
4	1.734	0.17	27.60	-	27.77	-	56.00	46.00	-28.23	-
5	3.660	0.20	22.75	-	22.95	-	56.00	46.00	-33.05	-
6	10.531	0.40	28.58	-	28.98	-	60.00	50.00	-31.02	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	Jun. 10, 2004
* HP Preamplifier	8447D	2944A08485	May 01, 2004
* HP Spectrum Analyzer	8593E	3926A04191	
* HP Preamplifier	8449B	3008A01292	Aug. 13, 2004
ROHDE & SCHWARZ TEST RECEIVER	ESI7	838496/016	Feb. 23, 2004
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Feb. 13, 2004
SCHAFFNER Tunable Dipole Antenna	VHBA 9123	459	Jun. 26, 2004
SCHWARZBECK Tunable Dipole Antenna	UHA 9105	977	
* CHASE BILOG Antenna	CBL6112A	2221	July 26, 2004
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jun. 30, 2004
* EMCO Turn Table	1060	1115	NA
* CHANCE Tower	CM-AT40	CM-A010	NA
* Software	ADT_Radiated_V5.14	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 05, 2004
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jan. 05, 2004

NOTE: 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

2. "*" = These equipment are used for the final measurement.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The test was performed in ADT Open Site No. 5.
5. The VCCI Site Registration No. is R-1039.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

4.2.7 TEST RESULTS

Test Mode 1:

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Hardaway Lee	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	65.34	23.30 QP	40.00	-16.70	1.03 H	160	15.70	7.60
2	148.30	26.00 QP	43.50	-17.50	1.43 H	321	14.60	11.50
3	160.03	28.80 QP	43.50	-14.70	1.38 H	159	18.10	10.70
4	221.13	28.50 QP	46.00	-17.50	1.67 H	70	16.50	12.00
5	270.07	31.20 QP	46.00	-14.80	1.25 H	313	16.00	15.20
6	280.00	34.60 QP	46.00	-11.40	1.78 H	119	19.30	15.30
7	375.01	29.40 QP	46.00	-16.60	1.13 H	245	12.10	17.30
8	400.01	32.80 QP	46.00	-13.20	1.69 H	112	14.50	18.20
9	534.50	35.60 QP	46.00	-10.40	1.66 H	2	15.00	20.60
10	560.00	36.40 QP	46.00	-9.60	1.00 H	337	15.20	21.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.74	30.70 QP	40.00	-9.30	1.00 V	71	22.40	8.30
2	85.94	28.30 QP	40.00	-11.70	1.16 V	139	19.30	9.00
3	113.24	27.90 QP	43.50	-15.60	1.24 V	2	15.30	12.60
4	132.00	33.40 QP	43.50	-10.10	1.39 V	95	20.90	12.50
5	160.00	35.40 QP	43.50	-8.10	1.42 V	350	24.70	10.70
6	176.02	36.10 QP	43.50	-7.40	1.26 V	217	25.60	10.50
7	198.01	28.10 QP	43.50	-15.40	1.81 V	39	17.30	10.70
8	240.15	29.20 QP	46.00	-16.80	1.11 V	2	16.20	13.00
9	250.13	29.50 QP	46.00	-16.50	1.52 V	316	15.90	13.60
10	280.01	35.50 QP	46.00	-10.50	1.14 V	198	20.10	15.30
11	354.30	32.60 QP	46.00	-13.40	1.55 V	328	16.00	16.60
12	377.00	31.50 QP	46.00	-14.50	1.99 V	256	14.10	17.40
13	532.99	38.50 QP	46.00	-7.50	1.52 V	49	17.90	20.60
14	584.45	33.70 QP	46.00	-12.30	1.08 V	315	11.90	21.80
15	637.80	33.00 QP	46.00	-13.00	1.75 V	84	10.60	22.40

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

Test Mode 2:

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	FREQUENCY RANGE	Below 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	133.10	27.90 QP	43.50	-15.60	2.15 H	240	15.60	12.40
2	167.55	28.20 QP	43.50	-15.20	2.19 H	203	17.60	10.60
3	193.05	27.30 QP	43.50	-16.20	2.06 H	26	16.60	10.70
4	221.43	31.90 QP	46.00	-14.10	1.00 H	89	19.90	12.00
5	225.30	29.70 QP	46.00	-16.30	1.00 H	133	17.50	12.20
6	240.15	33.40 QP	46.00	-12.60	1.19 H	94	20.40	13.00
7	270.43	32.60 QP	46.00	-13.40	1.19 H	41	17.40	15.20
8	280.23	37.70 QP	46.00	-8.30	1.00 H	75	22.40	15.30
9	345.00	37.40 QP	46.00	-8.60	1.00 H	249	21.00	16.30
10	401.00	36.60 QP	46.00	-9.40	1.00 H	311	18.40	18.30
11	480.12	41.40 QP	46.00	-4.60	1.00 H	261	21.70	19.60
12	799.70	31.30 QP	46.00	-14.70	1.52 H	359	7.60	23.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	132.58	28.60 QP	43.50	-14.90	1.00 V	101	16.20	12.40
2	160.03	25.90 QP	43.50	-17.60	1.00 V	260	15.30	10.70
3	221.38	26.40 QP	46.00	-19.60	1.00 V	317	14.40	12.00
4	225.13	30.60 QP	46.00	-15.40	1.00 V	208	18.50	12.20
5	239.98	32.30 QP	46.00	-13.70	1.00 V	189	19.30	13.00
6	280.23	33.00 QP	46.00	-13.00	1.00 V	112	17.70	15.30
7	401.00	32.90 QP	46.00	-13.10	1.74 V	319	14.60	18.30
8	480.12	42.10 QP	46.00	-3.90	1.16 V	340	22.50	19.60
9	533.00	38.10 QP	46.00	-7.90	1.33 V	298	17.50	20.60
10	800.50	33.70 QP	46.00	-12.30	1.28 V	174	10.00	23.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

4.2.8 TEST RESULTS (For CCK)

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	45.30 PK	74.00	-28.70	1.36 H	24	15.70	29.60
2	*2412.00	105.70 PK			1.36 H	24	76.00	29.70
2	*2412.00	99.00 AV			1.36 H	24	69.30	29.70
3	4824.00	50.10 PK	74.00	-23.90	1.39 H	24	14.80	35.30
4	9648.00	54.70 PK	74.00	-19.30	1.08 H	271	11.20	43.60
4	9648.00	41.80 AV	54.00	-12.20	1.08 H	271	-1.80	43.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	49.70 PK	74.00	-24.30	1.23 V	358	20.10	29.60
2	*2412.00	110.10 PK			1.23 V	358	80.50	29.70
2	*2412.00	103.00 AV			1.23 V	358	73.30	29.70
3	4824.00	50.60 PK	74.00	-23.40	1.24 V	238	15.30	35.30
4	9648.00	54.70 PK	74.00	-19.30	1.17 V	325	11.10	43.60
4	9648.00	42.10 AV	54.00	-11.90	1.17 V	325	-1.40	43.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. Margin value = Emission level – Limit value.
 4. “ * ” : Fundamental frequency
 5. The other emission levels were very low against the limit.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	104.30 PK			1.41 H	263	74.60	29.70
1	*2437.00	94.60 AV			1.41 H	263	64.90	29.70
2	4874.00	53.20 PK	74.00	-20.80	1.02 H	263	17.80	35.50
2	4874.00	47.40 AV	54.00	-6.60	1.02 H	263	11.90	35.50
3	9748.00	47.80 PK	74.00	-26.20	1.06 H	216	4.10	43.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	110.20 PK			1.23 V	127	80.50	29.70
1	*2437.00	103.40 AV			1.23 V	127	73.70	29.70
2	4874.00	50.50 PK	74.00	-23.50	1.16 V	168	15.00	35.50
3	9748.00	54.00 PK	74.00	-20.00	1.08 V	216	10.30	43.70
3	9748.00	40.80 AV	54.00	-13.20	1.08 V	216	-2.90	43.70

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. Margin value = Emission level – Limit value.
 4. “ * ” : Fundamental frequency
 5. The other emission levels were very low against the limit.

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.80 PK			1.35 H	320	76.00	29.80
1	*2462.00	98.10 AV			1.35 H	320	68.20	29.80
2	2483.50	48.40 PK	74.00	-25.60	1.35 H	320	18.50	29.90
3	4924.00	50.40 PK	74.00	-23.60	1.21 H	265	14.70	35.70
4	9848.00	54.70 PK	74.00	-19.30	1.07 H	325	11.00	43.80
4	9848.00	42.60 AV	54.00	-11.40	1.07 H	325	-1.10	43.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	110.60 PK			1.24 V	346	80.80	29.80
1	*2462.00	102.70 AV			1.24 V	346	72.90	29.80
2	2483.50	53.20 PK	74.00	-20.80	1.24 V	346	23.30	29.90
2	2483.50	45.30 AV	54.00	-8.70	1.24 V	346	15.40	29.90
3	4924.00	53.20 PK	74.00	-20.80	1.00 V	13	17.60	35.70
3	4924.00	49.00 AV	54.00	-5.00	1.00 V	13	13.40	35.70
4	9848.00	53.90 PK	74.00	-20.10	1.06 V	214	10.10	43.80
4	9848.00	41.80 AV	54.00	-12.20	1.06 V	214	-1.90	43.80

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level – Limit value.
4. “ * ” : Fundamental frequency
5. The other emission levels were very low against the limit.

4.2.9 TEST RESULTS (For OFDM)

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 1	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2391.00	44.90 PK	74.00	-29.10	1.00 H	110	15.30	29.60
2	*2412.00	99.40 PK			1.00 H	110	69.70	29.70
2	*2412.00	91.30 AV			1.00 H	110	61.60	29.70
3	4824.00	49.30 PK	74.00	-24.70	1.37 H	35	14.00	35.30
4	9648.00	54.20 PK	74.00	-19.80	1.02 H	126	10.60	43.60
4	9648.00	42.10 AV	54.00	-11.90	1.02 H	126	-1.40	43.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	50.60 PK	74.00	-23.40	1.00 V	163	21.00	29.60
2	*2412.00	105.10 PK			1.00 V	163	75.40	29.70
2	*2412.00	96.70 AV			1.00 V	163	67.00	29.70
3	4824.00	49.10 PK	74.00	-24.90	1.33 V	127	13.80	35.30
4	9648.00	54.10 PK	74.00	-19.90	1.31 V	235	10.60	43.60
4	9648.00	41.50 AV	54.00	-12.50	1.31 V	235	-2.00	43.60

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. Margin value = Emission level – Limit value.
 4. “ * ” : Fundamental frequency
 5. The other emission levels were very low against the limit.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 6	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	110.20 PK			1.24 H	166	80.50	29.70
1	*2437.00	103.40 AV			1.24 H	166	73.70	29.70
2	4874.00	50.50 PK	74.00	-23.50	1.36 H	166	15.00	35.50
3	9748.00	54.00 PK	74.00	-20.00	1.23 H	213	10.30	43.70
3	9748.00	40.80 AV	54.00	-13.20	1.23 H	213	-2.90	43.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	105.60 PK			1.00 V	165	75.80	29.70
1	*2437.00	98.30 AV			1.00 V	165	68.60	29.70
2	4874.00	51.00 PK	74.00	-23.00	1.17 V	84	15.50	35.50
3	9748.00	53.80 PK	74.00	-20.20	1.28 V	35	10.10	43.70
3	9748.00	41.10 AV	54.00	-12.90	1.28 V	35	-2.60	43.70

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. Margin value = Emission level – Limit value.
4. “ * ” : Fundamental frequency
5. The other emission levels were very low against the limit.



EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
MODE	Channel 11	FREQUENCY RANGE	Above 1000 MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	30 deg. C, 60 % RH, 991 hPa	TESTED BY: Jun Wu	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.20 PK			1.23 H	263	68.40	29.80
1	*2462.00	90.60 AV			1.23 H	263	60.80	29.80
2	2483.50	50.30 PK	74.00	-23.70	1.23 H	263	20.40	29.90
3	4924.00	49.90 PK	74.00	-24.10	1.58 H	129	14.20	35.70
4	9848.00	54.40 PK	74.00	-19.60	1.09 H	263	10.60	43.80
4	9848.00	40.90 AV	54.00	-13.10	1.09 H	263	-2.80	43.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	105.20 PK			1.00 V	101	75.30	29.80
1	*2462.00	96.50 AV			1.00 V	101	66.70	29.80
2	2483.50	57.30 PK	74.00	-16.70	1.00 V	101	27.40	29.90
2	2483.50	48.60 AV	54.00	-5.40	1.00 V	101	18.70	29.90
3	4924.00	53.90 PK	74.00	-20.10	1.00 V	101	18.20	35.70
3	4924.00	48.60 AV	54.00	-5.40	1.00 V	101	12.90	35.70
4	9848.00	54.30 PK	74.00	-19.70	1.19 V	196	10.50	43.80
4	9848.00	41.40 AV	54.00	-12.60	1.19 V	196	-2.30	43.80

REMARKS:

- 1.Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
- 2.Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
- 3.Margin value = Emission level – Limit value.
- 4.“ * “ : Fundamental frequency
- 5.The other emission levels were very low against the limit.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.3.7 TEST RESULTS (For CCK)


EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	11.54	0.5	PASS
6	2437	11.54	0.5	PASS
11	2462	11.50	0.5	PASS


CH1



CH6



CH11




4.3.8 TEST RESULTS (For OFDM)


EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.47	0.5	PASS
6	2437	16.47	0.5	PASS
11	2462	16.47	0.5	PASS


CH1



CH6



CH11



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004
R&S SIGNAL GENERATOR	SMP04	100011	May 28, 2004
TEKTRONIX OSCILLOSCOPE	TDS 220	B048470	Mar. 05, 2004
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

- a. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
- b. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
- c. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.

4.4.4 TEST RESULTS (For CCK)

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	16.1	30	PASS
6	2437	16.3	30	PASS
11	2462	16.2	30	PASS



4.4.5 TEST RESULTS (For OFDM)

EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	15.1	30	PASS
6	2437	15.2	30	PASS
11	2462	15.1	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITIONS


Same as 4.3.6.

4.5.7 TEST RESULTS (For CCK)


EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-8.81	8	PASS
6	2437	-8.74	8	PASS
11	2462	-8.89	8	PASS


CH1



CH6



CH11






4.5.8 TEST RESULTS (For OFDM)


EUT	Wireless-G USB 2.0 Pen-type Network Adapter	MODEL	WUSB54GP
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 57%RH, 991 hPa
TESTED BY: Ansen Lei			

CHANNEL NUMBER	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3 KHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-17.55	8	PASS
6	2437	-17.32	8	PASS
11	2462	-17.31	8	PASS


CH1



CH6



CH11



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2004

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation



4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6.

4.6.6 TEST RESULTS (For CCK)


The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE:

The band edge emission plot on the following first pages shows 56.29dB delta between carrier maximum power and local maximum emission in restrict band (2.3896GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.8 is 103.00dBuV/m, so the maximum field strength in restrict band is $103.00 - 56.29 = 46.71$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following second pages shows 58.64dB delta between carrier maximum power and local maximum emission in restrict band (2.4892GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.8 is 102.70dBuV/m, so the maximum field strength in restrict band is $102.70 - 58.64 = 44.06$ dBuV/m which is under 54 dBuV/m limit.








4.6.7 TEST RESULTS (For OFDM)


The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

NOTE:

The band edge emission plot on the following first pages shows 49.19dB delta between carrier maximum power and local maximum emission in restrict band (2.3899GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.9 is 96.70dBuV/m, so the maximum field strength in restrict band is $96.70 - 49.19 = 47.51$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following second pages shows 48.61dB delta between carrier maximum power and local maximum emission in restrict band (2.4837GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.9 is 96.50dBuV/m, so the maximum field strength in restrict band is $96.50 - 48.61 = 47.89$ dBuV/m which is under 54 dBuV/m limit.







4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The maximum Gain antenna used in this product is Dipole antenna without antenna connector. And the maximum Gain of the antenna is 2dBi.

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST (Mode 1)



CONDUCTED EMISSION TEST (Mode 2)



RADIATED EMISSION TEST (Mode 1)



RADIATED EMISSION TEST (Mode 2)





6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	MoC
Norway	NEMKO
R.O.C.	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC Lab:

Tel: 886-35-935343

Fax: 886-35-935342

Lin Kou Safety Lab:

Tel: 886-2-26093195

Fax: 886-2-26093184

Lin Kou RF&Telecom Lab

Tel: 886-3-3270910

Fax: 886-3-3270892

Email: service@mail.adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.