



SAR TEST REPORT

REPORT NO.: SA961122H02

MODEL NO.: WUSB600N

RECEIVED: Nov. 22, 2007

TESTED: Dec. 04 ~ Dec. 07, 2007

ISSUED: Dec. 11, 2007

APPLICANT: Cisco-Linksys LLC

ADDRESS: 121 Theory Drive Irvine, CA 92617 (USA)

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan
Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 60 pages in total except Appendix. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF, A2LA or any government agencies. The test results in the report only apply to the tested sample.





TABLE OF CONTENTS

1.	CERTIFICATION.....	3
2.	GENERAL INFORMATION	4
2.1	GENERAL DESCRIPTION OF EUT	4
2.2	GENERAL DESCRIPTION OF APPLIED STANDARDS	6
2.3	GENERAL INFORMATION OF THE SAR SYSTEM	7
2.4	GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION	10
3.	DESCRIPTION OF SUPPORT UNITS	14
4.	DESCRIPTION OF TEST MODES AND CONFIGURATIONS.....	15
4.1.	DESCRIPTION OF ANTENNA LOCATION.....	15
4.2.	DESCRIPTION OF ASSESSMENT POSITION	16
4.3.	DESCRIPTION OF TEST MODE.....	17
4.4.	SUMMARY OF TEST RESULTS	19
5.	TEST RESULTS.....	23
5.1	TEST PROCEDURES	23
5.2	MEASURED SAR RESULTS.....	25
5.3	SAR LIMITS	36
5.4	RECIPES FOR TISSUE SIMULATING LIQUIDS	37
5.5	TEST EQUIPMENT FOR TISSUE PROPERTY	46
6.	SYSTEM VALIDATION.....	47
6.1	TEST EQUIPMENT	47
6.2	TEST PROCEDURE	48
6.3	VALIDATION RESULTS.....	50
6.4	SYSTEM VALIDATION UNCERTAINTIES	51
7.	MEASUREMENT SAR PROCEDURE UNCERTAINTIES	52
7.1.	PROBE CALIBRATION UNCERTAINTY	52
7.2.	ISOTROPY UNCERTAINTY.....	53
7.3.	BOUNDARY EFFECT UNCERTAINTY	53
7.4.	PROBE LINEARITY UNCERTAINTY.....	54
7.5.	READOUT ELECTRONICS UNCERTAINTY.....	54
7.6.	RESPONSE TIME UNCERTAINTY	54
7.7.	INTEGRATION TIME UNCERTAINTY	55
7.8.	PROBE POSITIONER MECHANICAL TOLERANCE	56
7.9.	PROBE POSITIONING	56
7.10.	PHANTOM UNCERTAINTY	57
7.11.	DASY4 UNCERTAINTY BUDGET (FOR 2.4GHz).....	58
7.12.	DASY4 UNCERTAINTY BUDGET (FOR 5 ~ 6GHz)	59
8.	INFORMATION ON THE TESTING LABORATORIES.....	60
	APPENDIX A: TEST CONFIGURATIONS AND TEST DATA	
	APPENDIX B: ADT SAR MEASUREMENT SYSTEM	
	APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION	
	APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION	



1. CERTIFICATION

PRODUCT: Dual-Band Wireless-N USB Network Adapter
MODEL: WUSB600N
BRAND: Linksys
APPLICANT: Cisco-Linksys LLC
TESTED : Dec. 04 ~ Dec. 07, 2007
TEST SAMPLE: R&D SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1093)**
FCC OET Bulletin 65, Supplement C (01-01)
RSS-102
IEEE 1528-2003

The above equipment (model: WUSB600N) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rennie Wang , **DATE:** Dec. 11, 2007
Rennie Wang / Senior Specialist

TECHNICAL ACCEPTANCE : Stanely Hsu , **DATE:** Dec. 11, 2007
Responsible for RF Stanely Hsu / Senior Engineer

APPROVED BY : Gary Chang , **DATE:** Dec. 11, 2007
Gary Chang / Assistant Manager



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Dual-Band Wireless-N USB Network Adapter	
MODEL NO.	WUSB600N	
FCC ID	Q87-WUSB600N	
POWER SUPPLY	5Vdc from host equipment	
CLASSIFICATION	Portable device, production unit	
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS, 64QAM, 16QAM, QPSK, BPSK for OFDM	
RADIO TECHNOLOGY	DSSS, OFDM	
TRANSFER RATE	802.11b: 11 / 5.5 / 2 / 1Mbps 802.11g: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps 802.11a: 54 / 48 / 36 / 24 / 18 / 12 / 9 / 6Mbps Draft 802.11n (20MHz): 130 / 117 / 104 / 78 / 65 / 58.5 / 52 / 39 / 26 / 19.5 / 13 / 6.5Mbps Draft 802.11n (40MHz): 270 / 243 / 216 / 162 / 135 / 121.5 / 108 / 81 / 54 / 40.5 / 27 / 13.5Mbps s	
FREQUENCY RANGE	2.4GHz:	2400 ~ 2483.5MHz
	5.0GHz:	5150 ~ 5350MHz, 5470 ~ 5725MHz, 5725 ~ 5850MHz
NUMBER OF CHANNEL	2.4GHz:	11 for 802.11b, 802.11g, draft 802.11n (20MHz) 7 for draft 802.11n (40MHz)
	5.0GHz:	5150 ~ 5350MHz, 5470 ~ 5725MHz: 19 for 802.11a, draft 802.11n (20MHz) ; 9 for draft 802.11n (40MHz) 5725 ~ 5850MHz: 5 for 802.11a, draft 802.11n (20MHz) ; 2 for draft 802.11n (40MHz)
CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER FOR 2.4GHz	802.11b:	802.11g:
	25.704mW / Ch1: 2412MHz 31.623mW / Ch6: 2437MHz 34.674mW / Ch11: 2462MHz	93.325mW / Ch1: 2412MHz 97.724mW / Ch6: 2437MHz 91.201mW / Ch11: 2462MHz
	DRAFT 802.11n (20MHz):	DRAFT 802.11n (40MHz):
	80.549mW / Ch1: 2412MHz 92.483mW / Ch6: 2437MHz 133.677mW / Ch11: 2462MHz	52.007mW / Ch1: 2422MHz 100.264mW / Ch4: 2437MHz 132.138mW / Ch7: 2452MHz

CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER FOR 5GHz	802.11a:	
	24.660mW / Ch36: 5180MHz	14.223mW / Ch120: 5600MHz
	30.549mW / Ch48: 5240MHz	13.243mW / Ch124: 5620MHz
	32.810mW / Ch52: 5260MHz	19.275mW / Ch136: 5680MHz
	32.961mW / Ch64: 5320MHz	21.727mW / Ch140: 5700MHz
	20.512mW / Ch100: 5500MHz	43.652mW / Ch149: 5745MHz
	20.091mW / Ch104: 5520MHz	47.863mW / Ch157: 5785MHz
	15.382mW / Ch116: 5580MHz	46.774mW / Ch165: 5825MHz
	DRAFT 802.11n (20MHz):	
	23.015mW / Ch36: 5180MHz	20.983mW / Ch120: 5600MHz
25.677mW / Ch48: 5240MHz	19.953mW / Ch124: 5620MHz	
32.395mW / Ch52: 5260MHz	20.417mW / Ch136: 5680MHz	
22.173mW / Ch64: 5320MHz	32.489mW / Ch140: 5700MHz	
18.932mW / Ch100: 5500MHz	81.563mW / Ch149: 5745MHz	
16.596mW / Ch104: 5520MHz	68.771mW / Ch157: 5785MHz	
17.783mW / Ch116: 5580MHz	65.338mW / Ch165: 5825MHz	
DRAFT 802.11n (40MHz):		
27.543mW / Ch38: 5190MHz	18.879mW / Ch118: 5590MHz	
30.926mW / Ch46: 5230MHz	36.377mW / Ch134: 5670MHz	
26.058mW / Ch54: 5270MHz	85.882mW / Ch151: 5755MHz	
21.783mW / Ch62: 5310MHz	81.822mW / Ch159: 5795MHz	
18.729mW / Ch102: 5510MHz		
AVERAGE SAR (1g)	0.808W/kg for 2.4GHz 1.400W/kg for 5.0GHz	
ANTENNA TYPE	Refer to NOTE 1	
DATA CABLE	1.8m shielded cable without core for Cradle	
I/O PORTS	USB	
ACCESSORY DEVICES	Cradle	

NOTE:

- There are two antennas provided to this EUT, please refer to the following table:

No.	Antenna Type	For 2.4GHz Gain (dBi)	For 5GHz Gain (dBi)	Antenna Connector
1	PCB Print	2.0	4.0	NA
2	PCB Print	2.0	4.0	NA

- The EUT incorporates a MIMO function with 802.11a, 802.11b, 802.11g, draft 802.11n. Physically, the card provides two completed transmit and two completed receivers.
- The EUT is 2 * 2 spatial MIMO (2Tx & 2Rx) without beam forming function. The antenna configurations are two transmitter antennas and two receiver antennas, as there are 2 PCB Print antennas. Spatial multiplexing modes for simultaneous transmission using 2 antennas, and for simultaneous receiver using 2 antennas.



4. When the EUT operating in draft 802.11n, the software operation, which is defined by manufacturer, MCS (Modulation and Coding Schemes) from 0 to 15.
5. The EUT complies with draft 802.11n standards and backwards compatible with 802. 11a, 802.11b, 802.11g products.
6. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to the specifications of the manufacturer, this product must comply with the requirements of the following standards:

FCC Part 2 (2.1093)

FCC OET Bulletin 65, Supplement C (01- 01)

RSS-102

IEEE 1528-2003

All test items have been performed and recorded as per the above standards.



2.3 GENERAL INFORMATION OF THE SAR SYSTEM

DASY4 (software 4.7 Build 53) consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4 software defined. The DASY4 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

ET3DV6 ISOTROPIC E-FIELD PROBE (FREQUENCY BAND < 3GHz)

CONSTRUCTION	Symmetrical design with triangular core. Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., glycoether).
FREQUENCY	10 MHz to 3 GHz; Linearity: ± 0.2 dB (30 MHz to 3 GHz)
DYNAMIC RANGE	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
OPTICAL SURFACE DETECTION	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
DIMENSIONS	Overall length: 330 mm (Tip Length: 16 mm) Tip diameter: 6.8 mm (Body diameter: 12 mm) Distance from probe tip to dipole centers: 2.7 mm
APPLICATION	General dosimetric measurements up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (ET3DV6)



EX3DV3 ISOTROPIC E-FIELD PROBE (FREQUENCY BAND 5 ~ 6GHz)

DIMENSIONS	Overall length: 330 mm (Tip Length: 20 mm) Tip diameter: 2.5 mm (Body diameter: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
APPLICATION	General dosimetric measurements range 5 ~ 6 GHz. Fast automatic scanning in arbitrary phantoms (EX3DV3)

NOTE

1. The Probe parameters have been calibrated by the SPEAG. Please reference "APPENDIX D" for the Calibration Certification Report.
2. For frequencies above 800 MHz, calibration in a rectangular wave-guide is used, because wave-guide size is manageable.
3. For frequencies below 800 MHz, temperature transfer calibration is used because the wave-guide size becomes relatively large.

TWIN SAM V4.0

CONSTRUCTION	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.
SHELL THICKNESS	2 ± 0.2mm
FILLING VOLUME	Approx. 25liters
DIMENSIONS	Height: 810mm; Length: 1000mm; Width: 500mm

SYSTEM VALIDATION KITS:

CONSTRUCTION	Symmetrical dipole with 1/4 balun enables measurement of feedpoint impedance with NWA matched for use near flat phantoms filled with brain simulating solutions. Includes distance holder and tripod adaptor
CALIBRATION	Calibrated SAR value for specified position and input power at the flat phantom in brain simulating solutions
FREQUENCY	2450 , 5200, 5500, 5800 MHz



RETURN LOSS	> 20dB at specified validation position
POWER CAPABILITY	> 100W (f < 1GHz); > 40W (f > 1GHz)
OPTIONS	Dipoles for other frequencies or solutions and other calibration conditions upon request

DEVICE HOLDER FOR SAM TWIN PHANTOM

CONSTRUCTION The device holder for the mobile phone device is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles. The holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered. The device holder for the portable device makes up of the polyethylene foam. The dielectric parameters of material close to the dielectric parameters of the air.

DATA ACQUISITION ELECTRONICS

CONSTRUCTION The data acquisition electronics (DAE3) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplex, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe is mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 box is 200M Ω ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

2.4 GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION

The DASYS4 post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the micro-volt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm _i , a _{i0} , a _{i1} , a _{i2}
	- Conversion factor	ConvF _i
	- Diode compression point	dcp _i
Device parameters:	- Frequency	F
	- Crest factor	Cf
Media parameters:	- Conductivity	σ
	- Density	ρ

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

V _i	=compensated signal of channel i	(i = x, y, z)
U _i	=input signal of channel I	(i = x, y, z)
Cf	=crest factor of exciting field	(DASY parameter)
dcp _i	=diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

- V_i = compensated signal of channel I (i = x, y, z)
- Norm_i = sensor sensitivity of channel i $\mu\text{V}/(\text{V/m})^2$ for E-field Probes (i = x, y, z)
- ConvF = sensitivity enhancement in solution
- a_{ij} = sensor sensitivity factors for H-field probes
- f = carrier frequency [GHz]
- E_i = electric field strength of channel i in V/m
- H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{S}{r \cdot 1'000}$$

- SAR = local specific absorption rate in mW/g
- E_{tot} = total field strength in V/m
- σ = conductivity in [mho/m] or [Siemens/m]
- ρ = equivalent tissue density in g/cm³



Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid. The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. The generation of a high-resolution mesh within the measured volume
4. The interpolation of all measured values from the measurement grid to the high-resolution grid
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5mm.



The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7 x 7 x 7 scans. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30 x 30 x 30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid (42875 points). In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is moved around until the highest averaged SAR is found. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.



3. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	HP	nx6215	s/n:CND5390CMP	FCC DoC Approved
2	NOTEBOOK	DELL	D820	21498926752	FCC DoC Approved
3	NOTEBOOK	Compaq	N800C	470048-515	FCC DoC Approved
4	NOTEBOOK	Dell	PP01L	TW-09C748-12800-16M-5064	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	NA
4	NA

NOTE: All power cords of the above support units are non shielded (1.8m).

4. DESCRIPTION OF TEST MODES AND CONFIGURATIONS

4.1. DESCRIPTION OF ANTENNA LOCATION



4.2. DESCRIPTION OF ASSESSMENT POSITION

The following test configurations have been applied in this test report:

	
<p>A: NOTEBOOK MODEL: nx6125</p> <p>The bottom of the EUT face to the phantom with 4mm-separation distance.</p>	<p>B: NOTEBOOK MODEL: D820</p> <p>The bottom of the EUT face to the phantom with 6mm-separation distance.</p>
	
<p>C: NOTEBOOK MODEL: N800C</p> <p>The bottom of the EUT face to the phantom with 7mm-separation distance.</p>	<p>D: NOTEBOOK MODEL: PP01L</p> <p>The edge of the EUT face to the phantom with 5mm-separation distance.</p>

NOTE: The bottom of the notebook contacts to the bottom of the flat phantom with 0mm-separation distance.

4.3. DESCRIPTION OF TEST MODE

ITEM	TEST MODE	MODULATION	ASSESSMENT POSITION	TESTED CHANNEL
FOR 2.4GHz				
1	802.11b	DBPSK	A	L, M, H
2	802.11g	BPSK	A	L, M, H
3	Draft 802.11n (20MHz)	BPSK	A	L, M, H
4	Draft 802.11n (40MHz)	BPSK	A	L, M, H
5	802.11b	DBPSK	B	H
6	802.11g	BPSK	B	M
7	Draft 802.11n (20MHz)	BPSK	B	H
8	Draft 802.11n (40MHz)	BPSK	B	H
9	802.11b	DBPSK	C	H
10	802.11g	BPSK	C	M
11	Draft 802.11n (20MHz)	BPSK	C	H
12	Draft 802.11n (40MHz)	BPSK	C	H
13	802.11b	DBPSK	D	L, M, H
14	802.11g	BPSK	D	L, M, H
15	Draft 802.11n (20MHz)	BPSK	D	L, M, H
16	Draft 802.11n (40MHz)	BPSK	D	L, M, H

ITEM	TEST MODE	MODULATION	ASSESSMENT POSITION	TESTED CHANNEL
FOR 5GHz				
17	802.11a	BPSK	A	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
18	Draft 802.11n (20MHz)	BPSK	A	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
19	Draft 802.11n (40MHz)	BPSK	A	38, 46, 54, 62, 102, 118, 134, 151, 159
20	802.11a	BPSK	B	36, 100, 157
21	Draft 802.11n (20MHz)	BPSK	B	48, 100, 157
22	Draft 802.11n (40MHz)	BPSK	B	38, 102, 151
23	802.11a	BPSK	C	36, 100, 157
24	Draft 802.11n (20MHz)	BPSK	C	48, 100, 157
25	Draft 802.11n (40MHz)	BPSK	C	38, 102, 151
26	802.11a	BPSK	D	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
27	Draft 802.11n (20MHz)	BPSK	D	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
28	Draft 802.11n (40MHz)	BPSK	D	38, 46, 54, 62, 102, 118, 134, 151, 159

4.4. SUMMARY OF TEST RESULTS

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	1	2	3	4
MEASURED VALUE OF 1g SAR (W/kg)				
CHANNEL	ASSESSMENT POSITION (A)			
LOW	0.271	0.656	0.470	0.323
MIDDLE	0.328	0.701	0.493	0.611
HIGH	0.380	0.676	0.808	0.755

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	5	6	7	8
MEASURED VALUE OF 1g SAR (W/kg)				
CHANNEL	ASSESSMENT POSITION (B)			
LOW	-	-	-	-
MIDDLE	-	0.428	-	-
HIGH	0.243	-	0.459	0.392

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	9	10	11	12
MEASURED VALUE OF 1g SAR (W/kg)				
CHANNEL	ASSESSMENT POSITION (C)			
LOW	-	-	-	-
MIDDLE	-	0.205	-	-
HIGH	0.121	-	0.236	0.188

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	13	14	15	16
MEASURED VALUE OF 1g SAR (W/kg)				
CHANNEL	ASSESSMENT POSITION (D)			
LOW	0.074	0.162	0.111	0.053
MIDDLE	0.086	0.173	0.108	0.096
HIGH	0.097	0.162	0.158	0.124

NOTE: The worst value has been marked by boldface.

COMMUNICATION MODE	802.11a	Draft 802.11n (20MHz)
TEST MODE	17	18
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (A)	
36	1.400	0.726
48	1.170	0.834
52	1.110	0.744
64	1.130	0.485
100	0.550	0.615
104	0.526	0.493
116	0.417	0.522
120	0.357	0.497
124	0.344	0.415
136	0.372	0.483
140	0.400	0.404
149	0.311	0.497
157	0.337	0.633
165	0.268	0.385

COMMUNICATION MODE	Draft 802.11n (40MHz)	
TEST MODE	19	
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (A)	
38	0.853	
46	0.443	
54	0.742	
62	0.593	
102	0.571	
118	0.279	
134	0.251	
151	0.196	
159	0.171	

NOTE: The worst value has been marked by boldface.

COMMUNICATION MODE	802.11a	
TEST MODE	20	23
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (B)	ASSESSMENT POSITION (C)
36	0.913	0.682
100	0.173	0.134
157	0.111	0.078

COMMUNICATION MODE	Draft 802.11n (20MHz)	
TEST MODE	21	24
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (B)	ASSESSMENT POSITION (C)
48	0.300	0.219
100	0.163	0.126
157	0.157	0.115

COMMUNICATION MODE	Draft 802.11n (40MHz)	
TEST MODE	22	25
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (B)	ASSESSMENT POSITION (C)
38	0.273	0.200
102	0.158	0.121
151	0.130	0.087

COMMUNICATION MODE	802.11a	Draft 802.11n (20MHz)
TEST MODE	26	27
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (D)	
36	0.448	0.140
48	0.350	0.193
52	0.343	0.137
64	0.465	0.173
100	0.250	0.260
104	0.257	0.266
116	0.243	0.252
120	0.239	0.237
124	0.237	0.197
136	0.280	0.184
140	0.315	0.163
149	0.251	0.195
157	0.256	0.393
165	0.218	0.266

COMMUNICATION MODE	Draft 802.11n (40MHz)	
TEST MODE	28	
MEASURED VALUE OF 1g SAR (W/kg)		
CHANNEL	ASSESSMENT POSITION (D)	
38	0.151	
46	0.140	
54	0.159	
62	0.179	
102	0.259	
118	0.247	
134	0.256	
151	0.248	
159	0.227	

5. TEST RESULTS

5.1 TEST PROCEDURES

The EUT plugged into the notebook. Use the software to control the EUT channel and transmission power. Then record the conducted power before the testing. Place the EUT to the specific test location. After the testing, must writing down the conducted power of the EUT into the report. The SAR value was calculated via the 3D spline interpolation algorithm that has been implemented in the software of DASY4 SAR measurement system manufactured and calibrated by SPEAG. According to the IEEE 1528 standards, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Verification of the power reference measurement
- Area scan
- Zoom scan
- Power reference measurement

The area scan was performed for the highest spatial SAR location. The zoom scan with 30mm x 30mm x 30mm volume was performed for SAR value averaged over 1g and 10g spatial volumes.



In the zoom scan, the distance between the measurement point at the probe sensor location (geometric center behind the probe tip) and the phantom surface is 4.0mm and maintained at a constant distance of ± 1.0 mm during a zoom scan to determine peak SAR locations. The distance is 4mm between the first measurement point and the bottom surface of the phantom. The secondary measurement point to the bottom surface of the phantom is with 9mm separation distance. The cube size is 7 x 7 x 7 points consist of 343 points and the grid space is 5mm.

The measurement time is 0.5s at each point of the zoom scan. The probe boundary effect compensation shall be applied during the SAR test. Because of the tip of the probe to the Phantom surface separated distances are longer than half a tip probe diameter.

In the area scan, the separation distance is 4mm between the each measurement point and the phantom surface. The scan size shall be included the transmission portion of the EUT. The measurement time is the same as the zoom scan. At last the reference power drift shall be less than $\pm 5\%$.

5.2 MEASURED SAR RESULTS

ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.2°C Humidity : 56%RH					
TESTED BY		Sam Onn			DATE		Dec. 04, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
1	2412 (Low)	802.11b	25.704	25.483	-0.86	1	0.271
6	2437 (Mid.)	802.11b	31.623	31.332	-0.92	1	0.328
11	2462 (High)	802.11b	34.674	34.331	-0.99	1	0.380
1	2412 (Low)	802.11g	93.325	92.368	-1.03	2	0.656
6	2437 (Mid.)	802.11g	97.724	96.629	-1.12	2	0.701
11	2462 (High)	802.11g	91.201	90.079	-1.23	2	0.676
1	2412 (Low)	DRAFT 802.11n (20MHz)	80.549	79.542	-1.25	3	0.470
6	2437 (Mid.)	DRAFT 802.11n (20MHz)	92.483	91.270	-1.31	3	0.493
11	2462 (High)	DRAFT 802.11n (20MHz)	133.677	131.820	-1.39	3	0.808
1	2422 (Low)	DRAFT 802.11n (40MHz)	52.007	51.274	-1.41	4	0.323
4	2437 (Mid.)	DRAFT 802.11n (40MHz)	100.264	98.770	-1.49	4	0.611
7	2452 (High)	DRAFT 802.11n (40MHz)	132.138	130.130	-1.52	4	0.755

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.2°C Humidity : 56%RH					
TESTED BY		Sam Onn			DATE		Dec. 04, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
11	2462 (High)	802.11b	34.674	34.272	-1.16	5	0.243
6	2437 (Mid.)	802.11g	97.724	96.473	-1.28	6	0.428
11	2462 (High)	DRAFT 802.11n (20MHz)	133.677	131.887	-1.34	7	0.459
7	2452 (High)	DRAFT 802.11n (40MHz)	132.138	130.249	-1.43	8	0.392
11	2462 (High)	802.11b	34.674	34.237	-1.26	9	0.121
6	2437 (Mid.)	802.11g	97.724	96.444	-1.31	10	0.205
11	2462 (High)	DRAFT 802.11n (20MHz)	133.677	131.847	-1.37	11	0.236
7	2452 (High)	DRAFT 802.11n (40MHz)	132.138	130.210	-1.46	12	0.188

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.2°C Humidity : 56%RH						
TESTED BY		Sam Onn			DATE		Dec. 04, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
1	2412 (Low)	802.11b	25.704	25.432	-1.06	13	0.074	
6	2437 (Mid.)	802.11b	31.623	31.262	-1.14	13	0.086	
11	2462 (High)	802.11b	34.674	34.254	-1.21	13	0.097	
1	2412 (Low)	802.11g	93.325	92.149	-1.26	14	0.162	
6	2437 (Mid.)	802.11g	97.724	96.405	-1.35	14	0.173	
11	2462 (High)	802.11g	91.201	89.924	-1.40	14	0.162	
1	2412 (Low)	DRAFT 802.11n (20MHz)	80.549	79.945	-0.75	15	0.111	
6	2437 (Mid.)	DRAFT 802.11n (20MHz)	92.483	91.714	-0.83	15	0.108	
11	2462 (High)	DRAFT 802.11n (20MHz)	133.677	132.462	-0.91	15	0.158	
1	2422 (Low)	DRAFT 802.11n (40MHz)	52.007	51.456	-1.06	16	0.053	
4	2437 (Mid.)	DRAFT 802.11n (40MHz)	100.264	99.141	-1.12	16	0.096	
7	2452 (High)	DRAFT 802.11n (40MHz)	132.138	130.514	-1.23	16	0.124	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.4°C, Liquid Temperature : 22.2°C Humidity : 53%RH					
TESTED BY		Sam Onn			DATE		Dec. 05, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
36	5180.000	802.11a	24.660	24.522	-0.56	17	1.400
48	5240.000	802.11a	30.549	30.357	-0.63	17	1.170
52	5260.000	802.11a	32.810	32.574	-0.72	17	1.110
64	5320.000	802.11a	32.961	32.687	-0.83	17	1.130
100	5500.000	802.11a	20.512	20.323	-0.92	17	0.550
104	5520.000	802.11a	20.091	19.878	-1.06	17	0.526
116	5580.000	802.11a	15.382	15.208	-1.13	17	0.417
120	5600.000	802.11a	14.223	14.031	-1.35	17	0.357
124	5620.000	802.11a	13.243	13.056	-1.41	17	0.344
136	5680.000	802.11a	19.275	18.988	-1.49	17	0.372
140	5700.000	802.11a	21.727	21.481	-1.13	17	0.400
149	5745.000	802.11a	43.652	43.102	-1.26	17	0.311
157	5785.000	802.11a	47.863	47.217	-1.35	17	0.337
165	5825.000	802.11a	46.774	46.114	-1.41	17	0.268

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.4°C, Liquid Temperature : 22.2°C Humidity : 53%RH						
TESTED BY		Sam Onn			DATE		Dec. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
36	5180.000	DRAFT 802.11n (20MHz)	23.015	22.870	-0.63	18	0.726	
48	5240.000	DRAFT 802.11n (20MHz)	25.677	25.496	-0.71	18	0.834	
52	5260.000	DRAFT 802.11n (20MHz)	32.395	32.123	-0.84	18	0.744	
64	5320.000	DRAFT 802.11n (20MHz)	22.173	21.969	-0.92	18	0.485	
100	5500.000	DRAFT 802.11n (20MHz)	18.932	18.739	-1.02	18	0.615	
104	5520.000	DRAFT 802.11n (20MHz)	16.596	16.415	-1.09	18	0.493	
116	5580.000	DRAFT 802.11n (20MHz)	17.783	17.582	-1.13	18	0.522	
120	5600.000	DRAFT 802.11n (20MHz)	20.983	20.731	-1.20	18	0.497	
124	5620.000	DRAFT 802.11n (20MHz)	19.953	19.696	-1.29	18	0.415	
136	5680.000	DRAFT 802.11n (20MHz)	20.417	20.139	-1.36	18	0.483	
140	5700.000	DRAFT 802.11n (20MHz)	32.489	32.028	-1.42	18	0.404	
149	5745.000	DRAFT 802.11n (20MHz)	81.563	80.306	-1.54	18	0.497	
157	5785.000	DRAFT 802.11n (20MHz)	68.771	67.656	-1.62	18	0.633	
165	5825.000	DRAFT 802.11n (20MHz)	65.338	64.220	-1.71	18	0.385	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION			Air Temperature : 23.4°C, Liquid Temperature : 22.2°C Humidity : 53%RH				
TESTED BY			Sam Onn		DATE		Dec. 05, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
38	5190.000	DRAFT 802.11n (40MHz)	27.543	27.331	-0.77	19	0.853
46	5230.000	DRAFT 802.11n (40MHz)	30.926	30.665	-0.85	19	0.443
54	5270.000	DRAFT 802.11n (40MHz)	26.058	25.816	-0.93	19	0.742
62	5310.000	DRAFT 802.11n (40MHz)	21.783	21.548	-1.08	19	0.593
102	5510.000	DRAFT 802.11n (40MHz)	18.729	18.512	-1.16	19	0.571
118	5590.000	DRAFT 802.11n (40MHz)	18.879	18.647	-1.23	19	0.279
134	5670.000	DRAFT 802.11n (40MHz)	36.377	35.878	-1.37	19	0.251
151	5755.000	DRAFT 802.11n (40MHz)	85.882	84.654	-1.43	19	0.196
159	5795.000	DRAFT 802.11n (40MHz)	81.822	80.578	-1.52	19	0.171

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 22.9°C, Liquid Temperature : 21.9°C Humidity : 61%RH						
TESTED BY		Sam Onn			DATE		Dec. 06, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
36	5180.000	802.11a	24.660	24.322	-1.37	20	0.913	
100	5500.000	802.11a	20.512	20.213	-1.46	20	0.173	
157	5785.000	802.11a	47.863	47.135	-1.52	20	0.111	
48	5240.000	DRAFT 802.11n (20MHz)	25.677	25.442	-0.92	21	0.300	
100	5500.000	DRAFT 802.11n (20MHz)	18.932	18.745	-0.99	21	0.163	
157	5785.000	DRAFT 802.11n (20MHz)	68.771	68.065	-1.03	21	0.157	
38	5190.000	DRAFT 802.11n (40MHz)	27.543	27.199	-1.25	22	0.273	
102	5510.000	DRAFT 802.11n (40MHz)	18.729	18.484	-1.31	22	0.158	
151	5755.000	DRAFT 802.11n (40MHz)	85.882	84.688	-1.39	22	0.130	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 22.9°C, Liquid Temperature : 21.9°C Humidity : 61%RH						
TESTED BY		Sam Onn			DATE		Dec. 06, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
36	5180.000	802.11a	24.660	24.485	-0.71	23	0.682	
100	5500.000	802.11a	20.512	20.340	-0.84	23	0.134	
157	5785.000	802.11a	47.863	47.423	-0.92	23	0.078	
48	5240.000	DRAFT 802.11n (20MHz)	25.677	25.534	-0.56	24	0.219	
100	5500.000	DRAFT 802.11n (20MHz)	18.932	18.813	-0.63	24	0.126	
157	5785.000	DRAFT 802.11n (20MHz)	68.771	68.275	-0.72	24	0.115	
38	5190.000	DRAFT 802.11n (40MHz)	27.543	27.251	-1.06	25	0.200	
102	5510.000	DRAFT 802.11n (40MHz)	18.729	18.515	-1.14	25	0.121	
151	5755.000	DRAFT 802.11n (40MHz)	85.882	84.813	-1.21	25	0.087	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.1°C Humidity : 58%RH					
TESTED BY		Sam Onn			DATE		Dec. 07, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
36	5180.000	802.11a	24.660	24.408	-1.02	26	0.448
48	5240.000	802.11a	30.549	30.216	-1.09	26	0.350
52	5260.000	802.11a	32.810	32.439	-1.13	26	0.343
64	5320.000	802.11a	32.961	32.565	-1.20	26	0.465
100	5500.000	802.11a	20.512	20.247	-1.29	26	0.250
104	5520.000	802.11a	20.091	19.818	-1.36	26	0.257
116	5580.000	802.11a	15.382	15.164	-1.42	26	0.243
120	5600.000	802.11a	14.223	14.004	-1.54	26	0.239
124	5620.000	802.11a	13.243	13.028	-1.62	26	0.237
136	5680.000	802.11a	19.275	18.945	-1.71	26	0.280
140	5700.000	802.11a	21.727	21.334	-1.81	26	0.315
149	5745.000	802.11a	43.652	42.528	-2.52	26	0.251
157	5785.000	802.11a	47.863	46.882	-2.05	26	0.256
165	5825.000	802.11a	46.774	45.778	-2.13	26	0.218

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.1°C Humidity : 58%RH						
TESTED BY		Sam Onn			DATE		Dec. 07, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
36	5180.000	DRAFT 802.11n (20MHz)	23.015	22.720	-1.28	27	0.140	
48	5240.000	DRAFT 802.11n (20MHz)	25.677	25.334	-1.34	27	0.193	
52	5260.000	DRAFT 802.11n (20MHz)	32.395	31.932	-1.43	27	0.137	
64	5320.000	DRAFT 802.11n (20MHz)	22.173	21.836	-1.52	27	0.173	
100	5500.000	DRAFT 802.11n (20MHz)	18.932	18.616	-1.67	27	0.260	
104	5520.000	DRAFT 802.11n (20MHz)	16.596	16.294	-1.82	27	0.266	
116	5580.000	DRAFT 802.11n (20MHz)	17.783	17.443	-1.91	27	0.252	
120	5600.000	DRAFT 802.11n (20MHz)	20.983	20.559	-2.02	27	0.237	
124	5620.000	DRAFT 802.11n (20MHz)	19.953	19.522	-2.16	27	0.197	
136	5680.000	DRAFT 802.11n (20MHz)	20.417	19.966	-2.21	27	0.184	
140	5700.000	DRAFT 802.11n (20MHz)	32.489	31.745	-2.29	27	0.163	
149	5745.000	DRAFT 802.11n (20MHz)	81.563	79.629	-2.37	27	0.195	
157	5785.000	DRAFT 802.11n (20MHz)	68.771	67.099	-2.43	27	0.393	
165	5825.000	DRAFT 802.11n (20MHz)	65.338	63.664	-2.56	27	0.266	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.1°C, Liquid Temperature : 22.1°C Humidity : 58%RH						
TESTED BY		Sam Onn			DATE		Dec. 07, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
38	5190.000	DRAFT 802.11n (40MHz)	27.543	27.364	-0.65	28	0.151	
46	5230.000	DRAFT 802.11n (40MHz)	30.926	30.700	-0.73	28	0.140	
54	5270.000	DRAFT 802.11n (40MHz)	26.058	25.842	-0.83	28	0.159	
62	5310.000	DRAFT 802.11n (40MHz)	21.783	21.576	-0.95	28	0.179	
102	5510.000	DRAFT 802.11n (40MHz)	18.729	18.534	-1.04	28	0.259	
118	5590.000	DRAFT 802.11n (40MHz)	18.879	18.666	-1.13	28	0.247	
134	5670.000	DRAFT 802.11n (40MHz)	36.377	35.932	-1.22	28	0.256	
151	5755.000	DRAFT 802.11n (40MHz)	85.882	84.723	-1.35	28	0.248	
159	5795.000	DRAFT 802.11n (40MHz)	81.822	80.627	-1.46	28	0.227	

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.

5.3 SAR LIMITS

HUMAN EXPOSURE	SAR (W/kg)	
	(GENERAL POPULATION / UNCONTROLLED EXPOSURE ENVIRONMENT)	(OCCUPATIONAL / CONTROLLED EXPOSURE ENVIRONMENT)
Spatial Average (whole body)	0.08	0.4
Spatial Peak (averaged over 1 g)	1.6	8.0
Spatial Peak (hands / wrists / feet / ankles averaged over 10 g)	4.0	20.0

NOTE:

1. This limits accord to 47 CFR 2.1093 – Safety Limit.
2. The EUT property been complied with the partial body exposure limit under the general population environment.

5.4 RECIPES FOR TISSUE SIMULATING LIQUIDS

For the measurement of the field distribution inside the SAM phantom, the phantom must be filled with 25 liters of tissue simulation liquid.

The following ingredients are used :

- **WATER-** Deionized water (pure H₂O), resistivity $\approx 16 \text{ M}$ - as basis for the liquid
- **SUGAR-** Refined sugar in crystals, as available in food shops - to reduce relative permittivity
- **SALT-** Pure NaCl - to increase conductivity
- **CELLULOSE-** Hydroxyethyl-cellulose, medium viscosity (75-125mPa.s, 2% in water, 20_C),
CAS # 54290 - to increase viscosity and to keep sugar in solution
- **PRESERVATIVE-** Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS # 55965-84-9 - to prevent the spread of bacteria and molds
- **DGMBE-** Diethylenglycol-monobuthyl ether (DGMBE), Fluka Chemie GmbH, CAS # 112-34-5 - to reduce relative permittivity

THE RECIPES FOR 2450MHz SIMULATING LIQUID TABLE

INGREDIENT	HEAD SIMULATING LIQUID 2450MHz (HSL-2450)	MUSCLE SIMULATING LIQUID 2450MHz (MSL-2450)
Water	45%	69.83%
DGMBE	55%	30.17%
Salt	NA	NA
Dielectric Parameters at 22°C	f= 2450MHz $\epsilon = 39.2 \pm 5\%$ $\sigma = 1.80 \pm 5\% \text{ S/m}$	f= 2450MHz $\epsilon = 52.7 \pm 5\%$ $\sigma = 1.95 \pm 5\% \text{ S/m}$



THE INFORMATION FOR 5GHz SIMULATING LIQUID

The 5GHz liquids were purchased from SPEAG.

Body liquid model: HSL 5800, P/N: SL AAH 5800 AA

Head liquid model: M 5800, P/N: SL AAM 580 AD

5GHz liquids contain the following ingredients:

Water 64 - 78%

Mineral Oil 11 - 18%

Emulsifiers 9 - 15%

Additives and Salt 2 - 3%

Testing the liquids using the Agilent Network Analyzer E8358A and Agilent Dielectric Probe Kit 85070D. The testing procedure is following as

1. Turn Network Analyzer on and allow at least 30min. warm up.
2. Mount dielectric probe kit so that interconnecting cable to Network Analyzer will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ($\pm 1^\circ$).
4. Set water temperature in Agilent-Software (Calibration Setup).
5. Perform calibration.
6. Validate calibration with dielectric material of known properties (e.g. polished ceramic slab with >8mm thickness $\epsilon' = 10.0$, $\epsilon'' = 0.0$). If measured parameters do not fit within tolerance, repeat calibration (± 0.2 for ϵ' : ± 0.1 for ϵ'').
7. Conductivity can be calculated from ϵ'' by $\sigma = \omega \epsilon_0 \epsilon'' = \epsilon'' f [\text{GHz}] / 18$.
8. Measure liquid shortly after calibration. Repeat calibration every hour.
9. Stir the liquid to be measured. Take a sample (~ 50ml) with a syringe from the center of the liquid container.
10. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
11. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
12. Perform measurements.
13. Adjust medium parameters in DASY4 for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Brain 900MHz) and press 'Option'-button.
14. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 900MHz).



FOR 2.4GHz BAND SIMULATING LIQUID

LIQUID TYPE		HSL-2450		MSL-2450	
SIMULATING LIQUID TEMP.		NA		22.2	
TEST DATE		NA		Dec. 04, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
2412.0	Permittivity (ϵ)	NA	NA	52.80	54.80
2422.0		NA	NA	52.70	54.70
2437.0		NA	NA	52.70	54.60
2450.0		NA	NA	52.70	54.30
2452.0		NA	NA	52.70	54.30
2462.0		NA	NA	52.70	54.20
2412.0	Conductivity (σ) S/m	NA	NA	1.91	1.94
2422.0		NA	NA	1.92	1.95
2437.0		NA	NA	1.94	1.97
2450.0		NA	NA	1.95	1.99
2452.0		NA	NA	1.95	1.99
2462.0		NA	NA	1.96	2.00
Dielectric Parameters Required at 22°C		f= 2450MHz $\epsilon= 39.2 \pm 5\%$ $\sigma= 1.80 \pm 5\% \text{ S/m}$		f= 2450MHz $\epsilon= 52.7 \pm 5\%$ $\sigma= 1.95 \pm 5\% \text{ S/m}$	



FOR 5.0GHz BAND SIMULATING LIQUID

LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.2	
TEST DATE		NA		Dec. 05, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permittivity (ε)	NA	NA	49.00	50.10
5190		NA	NA	49.00	50.10
5200		NA	NA	49.00	50.10
5230		NA	NA	49.00	50.00
5240		NA	NA	49.00	50.00
5260		NA	NA	48.90	50.00
5270		NA	NA	48.90	49.90
5310		NA	NA	48.90	49.80
5320		NA	NA	48.90	49.80
5500		NA	NA	48.60	49.50
5510		NA	NA	48.60	49.50
5520		NA	NA	48.60	49.50
5580		NA	NA	48.50	49.30
5590		NA	NA	48.50	49.30
5600		NA	NA	48.50	49.30
5620		NA	NA	48.40	49.20
5670		NA	NA	48.40	49.10
5680		NA	NA	48.40	49.10
5700		NA	NA	48.30	49.10
5745		NA	NA	48.30	49.00
5755		NA	NA	48.30	49.00
5785		NA	NA	48.20	48.90
5795		NA	NA	48.20	48.90
5800		NA	NA	48.20	48.90
5825		NA	NA	48.20	48.80
Dielectric Parameters Required at 21°C					



LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.2	
TEST DATE		NA		Dec. 05, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Conductivity (σ) S/m	NA	NA	5.28	5.19
5190		NA	NA	5.29	5.20
5200		NA	NA	5.30	5.22
5230		NA	NA	5.33	5.26
5240		NA	NA	5.35	5.27
5260		NA	NA	5.37	5.31
5270		NA	NA	5.38	5.32
5310		NA	NA	5.43	5.38
5320		NA	NA	5.44	5.39
5500		NA	NA	5.65	5.66
5510		NA	NA	5.66	5.67
5520		NA	NA	5.67	5.68
5580		NA	NA	5.74	5.77
5590		NA	NA	5.75	5.78
5600		NA	NA	5.77	5.80
5620		NA	NA	5.79	5.83
5670		NA	NA	5.85	5.90
5680		NA	NA	5.86	5.92
5700		NA	NA	5.88	5.96
5745		NA	NA	5.94	6.02
5755		NA	NA	5.95	6.04
5785		NA	NA	5.98	6.08
5795	NA	NA	5.99	6.10	
5800	NA	NA	6.00	6.11	
5825	NA	NA	6.03	6.15	
Dielectric Parameters Required at 21°C					



LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		21.9	
TEST DATE		NA		Dec. 06, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permittivity (ϵ)	NA	NA	49.00	50.50
5190		NA	NA	49.00	50.40
5200		NA	NA	49.00	50.40
5230		NA	NA	49.00	50.30
5240		NA	NA	49.00	50.30
5260		NA	NA	48.90	50.30
5270		NA	NA	48.90	50.30
5310		NA	NA	48.90	50.20
5320		NA	NA	48.90	50.20
5500		NA	NA	48.60	49.80
5510		NA	NA	48.60	49.80
5520		NA	NA	48.60	49.80
5580		NA	NA	48.50	49.70
5590		NA	NA	48.50	49.60
5600		NA	NA	48.50	49.60
5620		NA	NA	48.40	49.60
5670		NA	NA	48.40	49.50
5680		NA	NA	48.40	49.40
5700		NA	NA	48.30	49.40
5745		NA	NA	48.30	49.30
5755		NA	NA	48.30	49.60
5785		NA	NA	48.20	49.30
5795	NA	NA	48.20	49.20	
5800	NA	NA	48.20	49.20	
5825	NA	NA	48.20	49.20	
Dielectric Parameters Required at 21°C					



LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		21.9	
TEST DATE		NA		Dec. 06, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Conductivity (σ) S/m	NA	NA	5.28	5.17
5190		NA	NA	5.29	5.18
5200		NA	NA	5.30	5.20
5230		NA	NA	5.33	5.24
5240		NA	NA	5.35	5.26
5260		NA	NA	5.37	5.29
5270		NA	NA	5.38	5.30
5310		NA	NA	5.43	5.36
5320		NA	NA	5.44	5.38
5500		NA	NA	5.65	5.64
5510		NA	NA	5.66	5.65
5520		NA	NA	5.67	5.66
5580		NA	NA	5.74	5.75
5590		NA	NA	5.75	5.76
5600		NA	NA	5.77	5.78
5620		NA	NA	5.79	5.81
5670		NA	NA	5.85	5.88
5680		NA	NA	5.86	5.90
5700		NA	NA	5.88	5.94
5745		NA	NA	5.94	6.00
5755		NA	NA	5.95	6.02
5785		NA	NA	5.98	6.06
5795	NA	NA	5.99	6.08	
5800	NA	NA	6.00	6.09	
5825	NA	NA	6.03	6.13	
Dielectric Parameters Required at 21°C					



LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.1	
TEST DATE		NA		Dec. 07, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permittivity (ϵ)	NA	NA	49.00	50.80
5190		NA	NA	49.00	50.70
5200		NA	NA	49.00	50.70
5230		NA	NA	49.00	50.60
5240		NA	NA	49.00	50.60
5260		NA	NA	48.90	50.60
5270		NA	NA	48.90	50.60
5310		NA	NA	48.90	50.50
5320		NA	NA	48.90	50.50
5500		NA	NA	48.60	50.20
5510		NA	NA	48.60	50.10
5520		NA	NA	48.60	50.10
5580		NA	NA	48.50	50.00
5590		NA	NA	48.50	49.90
5600		NA	NA	48.50	49.90
5620		NA	NA	48.40	49.90
5670		NA	NA	48.40	49.80
5680		NA	NA	48.40	49.80
5700		NA	NA	48.30	49.70
5745		NA	NA	48.30	49.60
5755		NA	NA	48.30	49.60
5785		NA	NA	48.20	49.60
5795		NA	NA	48.20	49.50
5800		NA	NA	48.20	49.50
5825	NA	NA	48.20	49.50	
Dielectric Parameters Required at 21°C					



LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.1	
TEST DATE		NA		Dec. 07, 2007	
TESTED BY		NA		Sam Onn	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Conductivity (σ) S/m	NA	NA	5.28	5.18
5190		NA	NA	5.29	5.19
5200		NA	NA	5.30	5.21
5230		NA	NA	5.33	5.25
5240		NA	NA	5.35	5.27
5260		NA	NA	5.37	5.30
5270		NA	NA	5.38	5.31
5310		NA	NA	5.43	5.36
5320		NA	NA	5.44	5.38
5500		NA	NA	5.65	5.64
5510		NA	NA	5.66	5.65
5520		NA	NA	5.67	5.67
5580		NA	NA	5.74	5.76
5590		NA	NA	5.75	5.77
5600		NA	NA	5.77	5.79
5620		NA	NA	5.79	5.82
5670		NA	NA	5.85	5.90
5680		NA	NA	5.86	5.91
5700		NA	NA	5.88	5.94
5745		NA	NA	5.94	6.01
5755	NA	NA	5.95	6.02	
5785	NA	NA	5.98	6.07	
5795	NA	NA	5.99	6.08	
5800	NA	NA	6.00	6.10	
5825	NA	NA	6.03	6.13	
Dielectric Parameters Required at 21°C					



5.5 TEST EQUIPMENT FOR TISSUE PROPERTY

ITEM	NAME	BAND	TYPE	SERIES NO.	CALIBRATED UNTIL
1	Network Analyzer	Agilent	E8358A	US41480538	Nov. 11, 2008
2	Dielectric Probe	Agilent	85070D	US01440176	NA

NOTE:

1. Before starting, all test equipment shall be warmed up for 30min.
2. The tolerance ($k=1$) specified by Agilent for general dielectric measurements, deriving from inaccuracies in the calibration data, analyzer drift, and random errors, are usually $\pm 2.5\%$ and $\pm 5\%$ for measured permittivity and conductivity, respectively. However, the tolerances for the conductivity is smaller for material with large loss tangents, i.e., less than $\pm 2.5\%$ ($k=1$). It can be substantially smaller if more accurate methods are applied.

6. SYSTEM VALIDATION

The system validation was performed in the flat phantom with equipment listed in the following table. Since the SAR value is calculated from the measured electric field, dielectric constant and conductivity of the body tissue, and the SAR is proportional to the square of the electric field. So, the SAR value will be also proportional to the RF power input to the system validation dipole under the same test environment. In our system validation test, 250mW RF input power was used.

6.1 TEST EQUIPMENT

ITEM	NAME	BAND	TYPE	SERIES NO.	CALIBRATED UNTIL
1	SAM Phantom	S & P	QD000 P40 CA	PT-1150	NA
2	Signal Generator	Anritsu	68247B	984703	May 18, 2008
3	E-Field Probe	Speaq	EX3DV3	3506	Mar. 19, 2008
4	DAE	Speaq	DAE	579	Mar. 22, 2008
5	Robot Positioner	Staubli Unimation	NA	NA	NA
6	Validation Dipole	Speaq	D2450V2	737	Apr. 23, 2008
7	Validation Dipole	Speaq	D5GHzV2	1018	Apr. 18, 2008
8	Power Meter	Agilent	E4416A	GB41291763	May 27, 2008
9	Peak and Average Power Sensor	Agilent	E9327A	US40441181	May 27, 2008

NOTE: Before starting the measurement, all test equipment shall be warmed up for 30min.



6.2 TEST PROCEDURE

Before the system performance check, we need only to tell the system which components (probe, medium, and device) are used for the system performance check; the system will take care of all parameters. The dipole must be placed beneath the flat section of the SAM Twin Phantom with the correct distance holder in place. The distance holder should touch the phantom surface with a light pressure at the reference marking (little cross) and be oriented parallel to the long side of the phantom. Accurate positioning is not necessary, since the system will search for the peak SAR location, except that the dipole arms should be parallel to the surface. The device holder for mobile phones can be left in place but should be rotated away from the dipole.

The "Power Reference Measurement" and "Power Drift Measurement" jobs are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above ± 0.1 dB), the system performance check should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY system below ± 0.02 dB.

The "Surface Check" job tests the optical surface detection system of the DASY system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1 mm). In that case it is better to abort the system performance check and stir the liquid. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within $\pm 30^\circ$.) However, varying breaking indices of different liquid compositions might also influence the distance. If the indicated difference varies from the actual setting, the probe parameter "optical surface



The "Area Scan" job measures the SAR above the dipole on a plane parallel to the surface. It is used to locate the approximate location of the peak SAR. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field, the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.

The "Zoom Scan" job measures the field in a volume around the peak SAR value assessed in the previous "Area Scan" job (for more information see the application note on SAR evaluation).

About the validation dipole positioning uncertainty, the constant and low loss dielectric spacer is used to establish the correct distance between the top surface of the dipole and the bottom surface of the phantom, the error component introduced by the uncertainty of the distance between the liquid (i.e., phantom shell) and the validation dipole in the DASY4 system is less than ± 0.1 mm.

$$SAR_{tolerance} [\%] = 100 \times \left(\frac{(a + d)^2}{a^2} - 1 \right)$$

As the closest distance is 10mm, the resulting tolerance $SAR_{tolerance} [\%]$ is <2%.



6.3 VALIDATION RESULTS

SYSTEM VALIDATION TEST IN THE MUSCLE SIMULATING LIQUID					
TEST FREQUENCY (MHz)	REQUIRED SAR (mW/g)	MEASURED SAR (mW/g)	DEVIATION (%)	SEPARATION DISTANCE	TEST DATE
MSL2450	12.90 (1g)	12.90	0	10mm	Dec. 04, 2007
MSL5200	19.50 (1g)	18.60	-4.62	10mm	Dec. 05, 2007
MSL5200	19.50 (1g)	18.30	-6.15	10mm	Dec. 06, 2007
MSL5200	19.50 (1g)	18.70	-4.10	10mm	Dec. 07, 2007
MSL5500	19.60 (1g)	18.80	-4.08	10mm	Dec. 05, 2007
MSL5500	19.60 (1g)	18.80	-4.08	10mm	Dec. 06, 2007
MSL5500	19.60 (1g)	19.10	-2.55	10mm	Dec. 07, 2007
MSL5800	17.60 (1g)	17.10	-2.84	10mm	Dec. 05, 2007
MSL5800	17.60 (1g)	17.20	-2.27	10mm	Dec. 06, 2007
MSL5800	17.60 (1g)	17.40	-1.14	10mm	Dec. 07, 2007
TESTED BY	Sam Onn				

NOTE: Please see Appendix for the photo of system validation test.

6.4 SYSTEM VALIDATION UNCERTAINTIES

In the table below, the system validation uncertainty with respect to the analytically assessed SAR value of a dipole source as given in the IEEE 1528 standard is given. This uncertainty is smaller than the expected uncertainty for mobile phone measurements due to the simplified setup and the symmetric field distribution.

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C _i)		Standard Uncertainty (±%)		(v _i)
				(1g)	(10g)	(1g)	(10g)	
Measurement System								
Probe Calibration	4.8	Normal	1	1	1	4.8	4.8	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
Hemispherical Isotropy	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
Boundary effect	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
RF Ambient Conditions	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe positioning	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Algorithms for Max. SAR Evaluation	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Dipole								
Dipole Axis to Liquid Distance	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Input power and SAR drift measurement	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
Phantom and Tissue Parameters								
Phantom Uncertainty	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity (target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	2.5	Normal	1	0.64	0.43	1.6	1.1	∞
Liquid Permittivity (target)	5.0	Rectangular	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	2.5	Normal	1	0.6	0.49	1.5	1.2	∞
Combined Standard Uncertainty						8.4	8.1	∞
Coverage Factor for 95%						k _p =2		
Expanded Uncertainty (K=2)						16.8	16.2	

NOTE: About the system validation uncertainty assessment, please reference the section 7.

7. MEASUREMENT SAR PROCEDURE UNCERTAINTIES

The assessment of spatial peak SAR of the hand handheld devices is according to IEEE 1528. All testing situation shall be met below these requirements.

- The system is used by an experienced engineer who follows the manual and the guidelines taught during the training provided by SPEAG.
- The probe has been calibrated within the requested period and the stated uncertainty for the relevant frequency bands does not exceed 4.8% (k=1).
- The validation dipole has been calibrated within the requested period and the system performance check has been successful.
- The DAE unit has been calibrated within the within the requested period.
- The minimum distance between the probe sensor and inner phantom shell is selected to be between 4 and 5mm.
- The operational mode of the DUT is CW, CDMA, FDMA or TDMA (GSM, DCS, PCS, IS136 and PDC) and the measurement/integration time per point is >500 ms.
- The dielectric parameters of the liquid have been assessed using Agilent 85070D dielectric probe kit or a more accurate method.
- The dielectric parameters are within 5% of the target values.
- The DUT has been positioned as described in section 3.

7.1. PROBE CALIBRATION UNCERTAINTY

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN 50361, IEC 62209, etc.) under ISO17025. The uncertainties are stated on the calibration certificate. For the most relevant frequency bands, these values do not exceed 4.8% (k=1). If evaluations of other bands are performed for which the uncertainty exceeds these values, the uncertainty tables given in the summary have to be revised accordingly.

7.2. ISOTROPY UNCERTAINTY

The axial isotropy tolerance accounts for probe rotation around its axis while the hemispherical isotropy error includes all probe orientations and field polarizations. These parameters are assessed by SPEAG during initial calibration. In 2001, SPEAG further tightened its quality controls and warrants that the maximal deviation from axial isotropy is $\pm 0.20\text{dB}$, while the maximum deviation of hemispherical isotropy is $\pm 0.40\text{dB}$, corresponding to $\pm 4.7\%$ and $\pm 9.6\%$, respectively. A weighting factor of c_p equal to 0.5 can be applied, since the axis of the probe deviates less than 30 degrees from the normal surface orientation.

7.3. BOUNDARY EFFECT UNCERTAINTY

The effect can be estimated according to the following error approximation formula

$$SAR_{tolerance}[\%] = SAR_{be}[\%] \times \frac{(d_{be} + d_{step})^2}{2d_{step}} e^{-\frac{d_{be}}{d/2}}$$

$$d_{be} + d_{step} < 10\text{mm}$$

The parameter d_{be} is the distance in mm between the surface and the closest measurement point used in the averaging process; d_{step} is the separation distance in mm between the first and second measurement points; δ is the minimum penetration depth in mm within the head tissue equivalent liquids (i.e., $\delta = 13.95\text{mm}$ at 3GHz); SAR_{be} is the deviation between the measured SAR value at the distance d_{be} from the boundary and the wave-guide analytical value SAR_{ref} . DASY4 applies a boundary effect compensation algorithm according to IEEE 1528, which is possible since the axis of the probe never deviates more than 30 degrees from the normal surface orientation. $SAR_{be}[\%]$ is assessed during the calibration process and SPEAG warrants that the uncertainty at distances larger than 4mm is always less than 1%. In summary, the worst case boundary effect SAR tolerance[%] for scanning distances larger than 4mm is $< \pm 0.8\%$.

7.4. PROBE LINEARITY UNCERTAINTY

Field probe linearity uncertainty includes errors from the assessment and compensation of the diode compression effects for CW and pulsed signals with known duty cycles. This error is assessed using the procedure described in IEEE 1528. For SPEAG field probes, the measured difference between CW and pulsed signals, with pulse frequencies between 10Hz and 1kHz and duty cycles between 1 and 100, is $< \pm 0.20\text{dB}$ ($< \pm 4.7\%$).

7.5. READOUT ELECTRONICS UNCERTAINTY

All uncertainties related to the probe readout electronics (DAE unit), including the gain and linearity of the instrumentation amplifier, its loading effect on the probe, and accuracy of the signal conversion algorithm, have been assessed accordingly to IEEE 1528. The combination (root-sum-square RSS method) of these components results in an overall maximum error of $\pm 1.0\%$.

7.6. RESPONSE TIME UNCERTAINTY

The time response of the field probes is assessed by exposing the probe to a well-controlled electric field producing SAR larger than 2.0W/kg at the tissue medium surface. The signal response time is evaluated as the time required by the system to reach 90% of the expected final value after an on/of switch of the power source. Analytically, it can be expressed as:

$$SAR_{tolerance} [\%] = 100 \times \left(\frac{T_m}{T_m + te^{-T_m/t} - t} - 1 \right)$$

where T_m is 500 ms, i.e., the time between measurement samples, and τ the time constant. The response time τ of SPEAG's probes is $< 5\text{ms}$. In the current implementation, DASY4 waits longer than 100 ms after having reached the grid point before starting a measurement, i.e., the response time uncertainty is negligible.

7.7. INTEGRATION TIME UNCERTAINTY

If the device under test does not emit a CW signal, the integration time applied to measure the electric field at a specific point may introduce additional uncertainties due to the discretization and can be assessed as follows

$$SAR_{tolerance} [\%] = 100 \times \sum_{all\ sub-frames} \frac{t_{frame}}{t_{integration}} \frac{slot_{idle}}{slot_{total}}$$

The tolerances for the different systems are given in Table 7.1, whereby the worst-case $SAR_{tolerance}$ is 2.6%.

System	$SAR_{tolerance}$ %
CW	0
CDMA*	0
WCDMA*	0
FDMA	0
IS-136	2.6
PDC	2.6
GSM/DCS/PCS	1.7
DECT	1.9
Worst-Case	2.6

TABLE 7.1

7.8. PROBE POSITIONER MECHANICAL TOLERANCE

The mechanical tolerance of the field probe positioner can introduce probe positioning uncertainties. The resulting SAR uncertainty is assessed by comparing the SAR obtained according to the specifications of the probe positioner with respect to the actual position defined by the geometric center of the probe sensors. The tolerance is determined as:

$$SAR_{tolerance} [\%] = 100 \times \frac{d_{ph}}{d/2}$$

The specified repeatability of the RX robot family used in DASY4 systems is $\pm 25\mu\text{m}$. The absolute accuracy for short distance movements is better than $\pm 0.1\text{mm}$, i.e., the $SAR_{tolerance} [\%]$ is better than 1.5% (rectangular).

7.9. PROBE POSITIONING

The probe positioning procedures affect the tolerance of the separation distance between the probe tip and the phantom surface as:

$$SAR_{tolerance} [\%] = 100 \times \frac{d_{ph}}{d/2}$$

where d_{ph} is the maximum deviation of the distance between the probe tip and the phantom surface. The optical surface detection has a precision of better than 0.2mm, resulting in an $SAR_{tolerance} [\%]$ of <2.9% (rectangular distribution). Since the mechanical detection provides better accuracy, 2.9% is a worst-case figure for DASY4 system.

7.10. PHANTOM UNCERTAINTY

The SAR measurement uncertainty due to SPEAG phantom shell production tolerances has been evaluated using

$$SAR_{tolerance}[\%] \cong 100 \times \frac{2d}{a}, \quad d \ll a$$

For a maximum deviation d of the inner and outer shell of the phantom from that specified in the CAD file of $\pm 0.2\text{mm}$, and a 10mm spacing a between source and tissue liquid, the calculated phantom uncertainty is $\pm 4.0\%$.

7.11. DASY4 UNCERTAINTY BUDGET (FOR 2.4GHz)

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C _i)		Standard Uncertainty (±%)		(v _i)
				(1g)	(10g)	(1g)	(10g)	
Measurement Equipment								
Probe Calibration	4.8	Normal	1	1	1	4.8	4.8	∞
Axial Isotropy	4.7	Rectangular	√3	1	1	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	1	1	3.9	3.9	∞
Boundary effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0.8	Normal	1	1	1	0.8	0.8	∞
Integration Time	2.6	Normal	1	1	1	2.6	2.6	∞
Noise	0.0	Normal	1	0	0	0	0	∞
Mechanical Constraints								
Scanning System	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Phantom Shell	4.0	Rectangular	√3	1	1	2.3	2.3	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	875
Physical Parameters								
Liquid Conductivity (target)	5.0	Rectangular	√3	0.7	0.5	2	1.4	∞
Liquid Conductivity (measurement)	4.3	Rectangular	√3	0.7	0.5	1.7	1.2	∞
Liquid Permittivity (target)	5.0	Rectangular	√3	0.6	0.5	1.7	1.4	∞
Liquid Permittivity (measurement)	4.3	Rectangular	√3	0.6	0.5	1.5	1.2	∞
Power Drift	5	Rectangular	√3	1	1	2.9	2.9	∞
RF Ambient Conditions	3.0	Rectangular	√3	1	1	1.7	1.7	∞
Post-Processing								
Extrapolation and Integration	1	Rectangular	√3	1	1	0.6	0.6	∞
Combined Standard Uncertainty						9.9	9.7	
Coverage Factor for 95%						kp=2		
Expanded Uncertainty (K=2)						19.9	19.3	

TABLE 7.2

The table 7.2: Worst-Case uncertainty budget for DASY4 assessed according to IEEE 1528. The budget is valid for the frequency range 300MHz ~ 3GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerable smaller.

7.12.DASY4 UNCERTAINTY BUDGET (FOR 5 ~ 6GHz)

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C _i)		Standard Uncertainty (±%)		(v _i)
				(1g)	(10g)	(1g)	(10g)	
Measurement System								
Probe Calibration	6.8	Normal	1	1	1	6.8	6.8	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Boundary effect	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0.8	Rectangular	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration Time	2.6	Rectangular	$\sqrt{3}$	1	1	1.5	1.5	∞
RF Ambient Conditions	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner	0.8	Rectangular	$\sqrt{3}$	1	1	0.5	0.5	∞
Probe positioning	5.7	Normal	1	1	1	5.7	5.7	∞
Algorithms for Max. SAR Evaluation	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Test EUT Related								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	∞
Phantom and Tissue Parameters								
Phantom Uncertainty	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity (target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	2.5	Normal	1	0.64	0.43	1.6	1.1	∞
Liquid Permittivity (target)	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	2.5	Normal	1	0.60	0.49	1.5	1.2	∞
Combined Standard Uncertainty						12.8	12.7	330
Expanded STD Uncertainty						25.7	25.3	

TABLE 7.3

The table 7.3: Worst-Case uncertainty budget for DASY4 valid for the frequency range 5 ~ 6 GHz. Probe calibration error reflects uncertainty of the narrow-bandwidth EX3DV3 probe conversion factor (±50 MHz).



8. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
GERMANY	TUV Rheinland
JAPAN	VCCI
NORWAY	NEMKO
CANADA	INDUSTRY CANADA , CSA
R.O.C.	TAF, BSMI, NCC
NETHERLANDS	Telefication
SINGAPORE	GOST-ASIA (MOU)
RUSSIA	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.