

## FCC Test Report

**Report No.:** RF140220D03D

**FCC ID:** Q87-LAPAC1200

**Test Model:** LAPAC1200

**Received Date:** May 4, 2016

**Test Date:** May 4 ~ 11, 2016

**Issued Date:** May 19, 2016

**Applicant:** Linksys LLC

**Address:** 121 Theory Drive Irvine California 92617 United States

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>Report Issue History Record .....</b>                         | <b>4</b>  |
| <b>Release Control Record .....</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity .....</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results .....</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty .....                                | 6         |
| 2.2 Modification Record .....                                    | 6         |
| <b>3 General Information .....</b>                               | <b>7</b>  |
| 3.1 General Description of EUT .....                             | 7         |
| 3.2 Description of Test Modes .....                              | 9         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail .....    | 10        |
| 3.3 Duty Cycle of Test Signal .....                              | 12        |
| 3.4 Description of Support Units .....                           | 13        |
| 3.4.1 Configuration of System under Test .....                   | 13        |
| 3.5 General Description of Applied Standard .....                | 14        |
| <b>4 Test Types and Results .....</b>                            | <b>15</b> |
| 4.1 Radiated Emission and Bandedge Measurement .....             | 15        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement ..... | 15        |
| 4.1.2 Test Instruments .....                                     | 16        |
| 4.1.3 Test Procedure .....                                       | 17        |
| 4.1.4 Deviation from Test Standard .....                         | 17        |
| 4.1.5 Test Setup .....                                           | 18        |
| 4.1.6 EUT Operating Condition .....                              | 18        |
| 4.1.7 Test Results .....                                         | 19        |
| 4.2 Conducted Emission Measurement .....                         | 38        |
| 4.2.1 Limits of Conducted Emission Measurement .....             | 38        |
| 4.2.2 Test Instruments .....                                     | 38        |
| 4.2.3 Test Procedures .....                                      | 39        |
| 4.2.4 Deviation from Test Standard .....                         | 39        |
| 4.2.5 Test Setup .....                                           | 39        |
| 4.2.6 EUT Operating Conditions .....                             | 39        |
| 4.2.7 Test Results .....                                         | 40        |
| 4.3 Transmit Power Measurement .....                             | 42        |
| 4.3.1 Limits of Transmit Power Measurement .....                 | 42        |
| 4.3.2 Test Setup .....                                           | 42        |
| 4.3.3 Test Instruments .....                                     | 42        |
| 4.3.4 Test Procedure .....                                       | 43        |
| 4.3.5 Deviation from Test Standard .....                         | 43        |
| 4.3.6 EUT Operating Condition .....                              | 43        |
| 4.3.7 Test Result .....                                          | 44        |
| 4.4 Peak Power Spectral Density Measurement .....                | 50        |
| 4.4.1 Limits of Peak Power Spectral Density Measurement .....    | 50        |
| 4.4.2 Test Setup .....                                           | 50        |
| 4.4.3 Test Instruments .....                                     | 50        |
| 4.4.4 Test Procedure .....                                       | 50        |
| 4.4.5 Deviation from Test Standard .....                         | 51        |
| 4.4.6 EUT Operating Condition .....                              | 51        |
| 4.4.7 Test Results .....                                         | 52        |
| 4.5 Frequency Stability Measurement .....                        | 56        |
| 4.5.1 Limits of Frequency Stability Measurement .....            | 56        |
| 4.5.2 Test Setup .....                                           | 56        |

|                                                                                           |           |
|-------------------------------------------------------------------------------------------|-----------|
| 4.5.3 Test Instruments .....                                                              | 56        |
| 4.5.4 Test Procedure .....                                                                | 56        |
| 4.5.5 Deviation from Test Standard .....                                                  | 56        |
| 4.5.6 EUT Operating Condition .....                                                       | 56        |
| 4.5.7 Test Results .....                                                                  | 57        |
| 4.6 6dB Bandwidth Measurement .....                                                       | 58        |
| 4.6.1 Limits of 6dB Bandwidth Measurement .....                                           | 58        |
| 4.6.2 Test Setup .....                                                                    | 58        |
| 4.6.3 Test Instruments .....                                                              | 58        |
| 4.6.4 Test Procedure .....                                                                | 58        |
| 4.6.5 Deviation from Test Standard .....                                                  | 58        |
| 4.6.6 EUT Operating Condition .....                                                       | 58        |
| 4.6.7 Test Results .....                                                                  | 59        |
| <b>5 Pictures of Test Arrangements .....</b>                                              | <b>61</b> |
| <b>Annex A- Radiated Out of Band Emisison (OOBE) Measurement (For U-NII-3 band) .....</b> | <b>62</b> |
| <b>Appendix – Information on the Testing Laboratories .....</b>                           | <b>65</b> |

### Report Issue History Record

| Issue No.    | Description                                                                                  | Date Issued   |
|--------------|----------------------------------------------------------------------------------------------|---------------|
| RF140220D03  | Original                                                                                     | Apr. 15, 2014 |
| RF140220D03C | Upgraded the standard to section 15.407 under new rule for U-NII-1 and U-NII-3 band.         | May 4, 2016   |
| RF140220D03D | Upgraded the standard to section 15.407 under new rule (16-24) for U-NII-1 and U-NII-3 band. | May 19, 2016  |

### Release Control Record

| Issue No.    | Description      | Date Issued  |
|--------------|------------------|--------------|
| RF140220D03D | Original release | May 19, 2016 |

## 1 Certificate of Conformity

**Product:** AC1200 Dual Band Access Point

**Brand:** Linksys

**Test Model:** LAPAC1200

**Sample Status:** Engineering Sample

**Applicant:** Linksys LLC

**Test Date:** May 4 ~ 11, 2016

**Standard:** 47 CFR FCC Part 15, Subpart E (Section 15.407)  
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**

*Annie Chang*

**, Date:**

May 19, 2016

Annie Chang / Senior Specialist

**Approved by :**

*Rex Lai*

**, Date:**

May 19, 2016

Rex Lai / Assistant Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart E (SECTION 15.407) |                                             |        |                                                                                  |
|------------------------------------------------|---------------------------------------------|--------|----------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                   | Result | Remarks                                                                          |
| 15.407(b)(6)                                   | AC Power Conducted Emissions                | Pass   | Meet the requirement of limit. Minimum passing margin is -20.85dB at -20.85 MHz. |
| 15.407(b)(1/2/3/4(i/ii)/6)                     | Radiated Emissions & Band Edge Measurement* | Pass   | Meet the requirement of limit. Minimum passing margin is -0.2dB at 5150.00 MHz.  |
| 15.407(a)(1/2/3)                               | Max Average Transmit Power                  | Pass   | Meet the requirement of limit.                                                   |
| 15.407(a)(1/2/3)                               | Peak Power Spectral Density                 | Pass   | Meet the requirement of limit.                                                   |
| 15.407(e)                                      | 6dB bandwidth                               | Pass   | Meet the requirement of limit. (U-NII-3 Band only)                               |
| 15.407(g)                                      | Frequency Stability                         | Pass   | Meet the requirement of limit.                                                   |
| 15.203                                         | Antenna Requirement                         | Pass   | Antenna connector is I-PEX not a standard connector.                             |

**NOTE:** This report is prepared for FCC Class II change. (Upgraded the standard to section 15.407 under new rule (16-24) for U-NII-1 and U-NII-3 band)

\*For U-NII-3 band compliance with rule part 15.407(b)(i), the OOB test plots were recorded in Annex A.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency       | Expended Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|-----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz  | 2.78 dB                              |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 1000MHz | 4.00 dB                              |
| Radiated Emissions above 1 GHz     | 1GHz ~ 40GHz    | 3.36 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | AC1200 Dual Band Access Point                                                                                                                                                                                            |
| Brand                 | Linksys                                                                                                                                                                                                                  |
| Test Model            | LAPAC1200                                                                                                                                                                                                                |
| Driver Version        | v1.1.00.005                                                                                                                                                                                                              |
| Status of EUT         | Engineering Sample                                                                                                                                                                                                       |
| Power Supply Rating   | 12Vdc from AC Adapter or 48Vdc from PoE                                                                                                                                                                                  |
| Modulation Type       | 64QAM, 16QAM, QPSK, BPSK<br>256QAM for OFDM in 11ac mode only                                                                                                                                                            |
| Modulation Technology | OFDM                                                                                                                                                                                                                     |
| Transfer Rate         | 802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps<br>802.11n: up to 300Mbps<br>802.11ac: up to 866.7Mbps                                                                                                         |
| Operating Frequency   | 5180 ~ 5240MHz<br>5745 ~ 5825MHz                                                                                                                                                                                         |
| Number of Channel     | <b>5180 ~ 5240MHz</b><br>4 for 802.11a, 802.11n (20MHz)<br>2 for 802.11n (40MHz)<br>1 for 802.11ac (80MHz)<br><b>5745 ~ 5825MHz</b><br>5 for 802.11a, 802.11n (20MHz)<br>2 for 802.11n (40MHz)<br>1 for 802.11ac (80MHz) |
| Output Power          | <b>5180 ~ 5240MHz:</b> 375.850 mW<br><b>5745 ~ 5825MHz:</b> 544.780mW                                                                                                                                                    |
| Antenna Type          | PIFA antenna with 2dBi gain                                                                                                                                                                                              |
| Antenna Connector     | N/A                                                                                                                                                                                                                      |
| Accessory Device      | Adapter                                                                                                                                                                                                                  |
| Data Cable Supplied   | N/A                                                                                                                                                                                                                      |

Note:

- This report is a supplementary report of RF140220D03 and RF140220D03-1. The differences between them are as below information:  
  - ✧ Upgraded the standard to section 15.407 under new rule (16-24) for U-NII-1 and U-NII-3 band
- According to above conditions, all test items of U-NII-1 and U-NII-3 band needs to be performed. And all data was verified to meet the requirements.
- This report is prepared for FCC class II permissive change.

4. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

| Modulation Mode  | TX FUNCTION |
|------------------|-------------|
| 802.11a          | 2TX         |
| 802.11n (20MHz)  | 2TX         |
| 802.11n (40MHz)  | 2TX         |
| 802.11ac (20MHz) | 2TX         |
| 802.11ac (40MHz) | 2TX         |
| 802.11ac (80MHz) | 2TX         |

\* The modulation and bandwidth are similar for 802.11n mode for HT20 / HT40 and 802.11ac mode for HT20 / HT40, therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

5. The EUT was power supplied from the following power adapters or PoE:

| Item      | Brand                                                                             | Model No.               | Plug Type       | Rating                                                                       |
|-----------|-----------------------------------------------------------------------------------|-------------------------|-----------------|------------------------------------------------------------------------------|
| Adapter 1 | LEI                                                                               | IU18-2120150-WP         | US, EU, UK Plug | AC I/P: 100-240V, 50/60Hz 0.6A<br>DC O/P: 12V 1.5A<br>Non-shielded DC (1.5m) |
| Adapter 2 | LEI                                                                               | MU18-R120150-A1         | US Plug         | AC I/P: 100-240V, 50/60Hz 0.6A<br>DC O/P: 12V 1.5A<br>Non-shielded DC (1.5m) |
|           | LEI                                                                               | MU18-R120150-C5         | EU Plug         |                                                                              |
|           | LEI                                                                               | MU18-R120150-B2         | UK Plug         |                                                                              |
|           | LEI                                                                               | MU18-R120150-A3         | AU Plug         |                                                                              |
|           | Four adapters are identical with each other except for their plug type difference |                         |                 |                                                                              |
| Adapter 3 | DVE                                                                               | DSA-20CA-12 120150      | US, EU, UK Plug | AC I/P: 100-240V, 50/60Hz 0.8A<br>DC O/P: 12V 1.5A<br>Non-shielded DC (1.5m) |
| Adapter 4 | DVE                                                                               | DSA-18PFG-12 FUS 12015  | US Plug         | AC I/P:100-240V, 50/60Hz 0.6A<br>DC O/P:12V 1.5A<br>Non-shielded DC (1.5m)   |
|           | DVE                                                                               | DSA-18PFG-12 FEU 120150 | EU Plug         |                                                                              |
|           | DVE                                                                               | DSA-18PFG-12 FUK 120120 | UK Plug         |                                                                              |
|           | DVE                                                                               | DSA-18PFG-12 FAU 120150 | AU Plug         |                                                                              |
|           | Four adapters are identical with each other except for their plug type difference |                         |                 |                                                                              |
| PoE       | -                                                                                 |                         |                 | 48Vdc                                                                        |

Select the previous worse case (**Adapter 2**) for final test, therefore, only its test data was recorded in this report.

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

#### FOR 5180 ~ 5240MHz

4 channels are provided for 802.11a, 802.11n (20MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 36      | 5180 MHz  | 44      | 5220 MHz  |
| 40      | 5200 MHz  | 48      | 5240 MHz  |

2 channels are provided for 802.11n (40MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 38      | 5190 MHz  | 46      | 5230 MHz  |

1 channel is provided for 802.11ac (80MHz):

| Channel | Frequency |
|---------|-----------|
| 42      | 5210MHz   |

#### FOR 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (20MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 149     | 5745MHz   | 161     | 5805MHz   |
| 153     | 5765MHz   | 165     | 5825MHz   |
| 157     | 5785MHz   |         |           |

2 channels are provided for 802.11n (40MHz):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 151     | 5755MHz   | 159     | 5795MHz   |

1 channel is provided for 802.11ac (80MHz):

| Channel | Frequency |
|---------|-----------|
| 155     | 5775MHz   |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT<br>CONFIGURE<br>MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|--------------------------|---------------|-------|-----|------|-------------|
|                          | RE $\geq$ 1G  | RE<1G | PLC | APCM |             |
| -                        | √             | √     | √   | √    | -           |

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz

**RE<1G**: Radiated Emission below 1GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**NOTE**: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

#### **Radiated Emission Test (Above 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE             | FREQ. BAND<br>(MHz) | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA<br>RATE<br>(Mbps) |
|--------------------------|------------------|---------------------|----------------------|-------------------|--------------------------|--------------------|------------------------|
| -                        | 802.11a          | 5180-5240           | 36 to 48             | 36, 40, 48        | OFDM                     | BPSK               | 6.0                    |
| -                        | 802.11n (20MHz)  |                     | 36 to 48             | 36, 40, 48        | OFDM                     | BPSK               | 6.5                    |
| -                        | 802.11n (40MHz)  |                     | 38 to 46             | 38, 46            | OFDM                     | BPSK               | 13.0                   |
| -                        | 802.11ac (80MHz) |                     | 42                   | 42                | OFDM                     | BPSK               | 29.3                   |
| -                        | 802.11a          | 5745-5825           | 149 to 165           | 149, 157, 165     | OFDM                     | BPSK               | 6.0                    |
| -                        | 802.11n (20MHz)  |                     | 149 to 165           | 149, 157, 165     | OFDM                     | BPSK               | 6.5                    |
| -                        | 802.11n (40MHz)  |                     | 151 to 159           | 151, 159          | OFDM                     | BPSK               | 13.0                   |
| -                        | 802.11ac (80MHz) |                     | 155                  | 155               | OFDM                     | BPSK               | 29.3                   |

#### **Radiated Emission Test (Below 1GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE    | FREQ. BAND<br>(MHz) | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA<br>RATE<br>(Mbps) |
|--------------------------|---------|---------------------|----------------------|-------------------|--------------------------|--------------------|------------------------|
| -                        | 802.11a | 5180-5240           | 36 to 48             | 36                | OFDM                     | BPSK               | 6.0                    |

#### **Power Line Conducted Emission Test:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT<br>CONFIGURE<br>MODE | MODE    | FREQ. BAND<br>(MHz) | AVAILABLE<br>CHANNEL | TESTED<br>CHANNEL | MODULATION<br>TECHNOLOGY | MODULATION<br>TYPE | DATA<br>RATE<br>(Mbps) |
|--------------------------|---------|---------------------|----------------------|-------------------|--------------------------|--------------------|------------------------|
| -                        | 802.11a | 5180-5240           | 36 to 48             | 36                | OFDM                     | BPSK               | 6.0                    |

### **Antenna Port Conducted Measurement:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE             | FREQ. BAND (MHz) | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|------------------|------------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11a          | 5180-5240        | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (20MHz)  |                  | 36 to 48          | 36, 40, 48     | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11n (40MHz)  |                  | 38 to 46          | 38, 46         | OFDM                  | BPSK            | 13.0             |
|                    | 802.11ac (80MHz) |                  | 42                | 42             | OFDM                  | BPSK            | 29.3             |
| -                  | 802.11a          | 5745-5825        | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (20MHz)  |                  | 149 to 165        | 149, 157, 165  | OFDM                  | BPSK            | 6.5              |
| -                  | 802.11n (40MHz)  |                  | 151 to 159        | 151, 159       | OFDM                  | BPSK            | 13.0             |
|                    | 802.11ac (80MHz) |                  | 155               | 155            | OFDM                  | BPSK            | 29.3             |

### **Test Condition:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER  | TESTED BY |
|---------------|--------------------------|--------------|-----------|
| RE $\geq$ 1G  | 16deg. C, 76%RH          | 120Vac, 60Hz | Dalen Dai |
| RE<1G         | 20deg. C, 66%RH          | 120Vac, 60Hz | Aaron You |
| PLC           | 23deg. C, 75%RH          | 120Vac, 60Hz | Aaron You |
| APCM          | 25deg. C, 60%RH          | 120Vac, 60Hz | Saxon Lee |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor is required

**802.11a:** Duty cycle =  $2.014/2.087 = 0.965$ , Duty factor =  $10 * \log(1/0.965) = 0.15$

**802.11n (20MHz):** Duty cycle =  $1.855/1.942 = 0.955$ , Duty factor =  $10 * \log(1/0.955) = 0.20$

**802.11n (40MHz):** Duty cycle =  $0.92/1 = 0.920$ , Duty factor =  $10 * \log(1/0.920) = 0.36$

**802.11ac (80MHz):** Duty cycle =  $0.413/0.543 = 0.761$ , Duty factor =  $10 * \log(1/0.761) = 1.19$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| ID | Product     | Brand | Model No. | Serial No. | FCC ID           | Remarks         |
|----|-------------|-------|-----------|------------|------------------|-----------------|
| A. | Notebook PC | DELL  | PP27L     | 8SNZ12S    | FCC DoC Approved | Provided by Lab |


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as communication partners to transfer data.

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks            |
|----|--------------|------|------------|--------------------|--------------|--------------------|
| 1. | DC cable     | 1    | 1.5        | N                  | 0            | Supplied by client |
| 2. | LAN cable    | 1    | 10         | N                  | 0            | Provided by Lab    |

Note: The core(s) is(are) originally attached to the cable(s).

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standard

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**  
**KDB 789033 D02 General UNII Test Procedure New Rules v01r02**  
**KDB 662911 D01 Multiple Transmitter Output v02r01**  
**ANSI C63.10-2013**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### Limits Of Unwanted Emission Out Of The Restricted Bands

| Applicable To                                                                                                                                                                                                                                                                                                                                                                   | Limit                                                                                                                               |                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| 789033 D02 General UNII Test Procedure New Rules v01r02                                                                                                                                                                                                                                                                                                                         | FIELD STRENGTH at 3m                                                                                                                |                                                                                                                                         |
|                                                                                                                                                                                                                                                                                                                                                                                 | PK:74 (dBuV/m)                                                                                                                      | AV:54 (dBuV/m)                                                                                                                          |
| Applicable To                                                                                                                                                                                                                                                                                                                                                                   | EIRP Limit                                                                                                                          | Equivalent Field Strength at 3m                                                                                                         |
| 15.407(b)(1)                                                                                                                                                                                                                                                                                                                                                                    | PK:-27 (dBm/MHz)                                                                                                                    | PK:68.2(dBuV/m)                                                                                                                         |
| 15.407(b)(2)                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                     |                                                                                                                                         |
| 15.407(b)(3)                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                     |                                                                                                                                         |
| 15.407(b)(4)(i)                                                                                                                                                                                                                                                                                                                                                                 | PK:-27 (dBm/MHz) <sup>*1</sup><br>PK:10 (dBm/MHz) <sup>*2</sup><br>PK:15.6 (dBm/MHz) <sup>*3</sup><br>PK:27 (dBm/MHz) <sup>*4</sup> | PK: 68.2(dBuV/m) <sup>*1</sup><br>PK:105.2 (dBuV/m) <sup>*2</sup><br>PK: 110.8(dBuV/m) <sup>*3</sup><br>PK:122.2 (dBuV/m) <sup>*4</sup> |
| 15.407(b)(4)(ii)                                                                                                                                                                                                                                                                                                                                                                | FIELD STRENGTH at 3m / § 15.247(d),                                                                                                 |                                                                                                                                         |
|                                                                                                                                                                                                                                                                                                                                                                                 | PK:74 (dBuV/m)                                                                                                                      | AV:54 (dBuV/m)                                                                                                                          |
| <sup>*1</sup> beyond 75 MHz or more above of the band edge.<br><sup>*2</sup> below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.<br><sup>*3</sup> below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.<br><sup>*4</sup> from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. |                                                                                                                                     |                                                                                                                                         |

**NOTE:** The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$

#### 4.1.2 Test Instruments

| DESCRIPTION & MANUFACTURER                | MODEL NO.            | SERIAL NO.     | CALIBRATED DATE | CALIBRATED UNTIL |
|-------------------------------------------|----------------------|----------------|-----------------|------------------|
| HP Preamplifier                           | 8447D                | 2432A03504     | Feb. 26, 2016   | Feb. 25, 2017    |
| HP Preamplifier                           | 8449B                | 3008A01201     | Feb. 26, 2016   | Feb. 25, 2017    |
| MITEQ Preamplifier                        | AMF-6F-260400-33-8P  | 892164         | Mar. 01, 2016   | Feb. 28, 2017    |
| Agilent TEST RECEIVER                     | N9038A               | MY51210129     | Feb. 02, 2016   | Feb. 01, 2017    |
| Schwarzbeck Antenna                       | VULB 9168            | 139            | Jan. 04, 2016   | Jan. 03, 2017    |
| Schwarzbeck Antenna                       | VHBA 9123            | 480            | May 29, 2015    | May 28, 2017     |
| Schwarzbeck Horn Antenna                  | BBHA-9170            | 212            | Jan. 08, 2016   | Jan. 07, 2017    |
| Schwarzbeck Horn Antenna                  | BBHA 9120-D1         | D130           | Jan. 21, 2016   | Jan. 20, 2017    |
| ADT. Turn Table                           | TT100                | 0306           | NA              | NA               |
| ADT. Tower                                | AT100                | 0306           | NA              | NA               |
| Software                                  | Radiated_V7.6.15.9.4 | NA             | NA              | NA               |
| SUHNER RF cable<br>With 4dB PAD           | SF104                | CABLE-CH6      | Aug. 15, 2015   | Aug. 14, 2016    |
| SUHNER RF cable<br>With 3dB PAD           | SF102                | Cable-CH8-3.6m | Aug. 15, 2015   | Aug. 14, 2016    |
| KEYSIGHT<br>Spectrum Analyzer             | N9030A               | MY54490260     | Jul. 14, 2015   | Jul. 13, 2016    |
| EMCO Horn Antenna                         | 3115                 | 00028257       | Jan. 19, 2016   | Jan. 18, 2017    |
| Highpass filter<br>Wainwright Instruments | WHK 3.1/18G-10SS     | SN 8           | NA              | NA               |
| ROHDE & SCHWARZ<br>Spectrum Analyzer      | FSV40                | 101042         | Sep. 23, 2015   | Sep. 22, 2016    |
| Anritsu<br>Power Sensor                   | MA2411B              | 0738404        | Apr. 28, 2016   | Apr. 27, 2017    |
| Anritsu<br>Power Meter                    | ML2495A              | 0842014        | Apr. 28, 2016   | Apr. 27, 2017    |
| Temperature & Humidity<br>Chamber         | MHU-225AU            | 920409         | May 25, 2015    | May 24, 2016     |

- NOTE:** 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in Chamber No. 6.
4. The Industry Canada Reference No. IC 7450E-6.
5. The FCC Site Registration No. is 447212.

#### 4.1.3 Test Procedure

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup

##### <Frequency Range below 1GHz>



##### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Condition

The Notebook connected with EUT via a LAN cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

#### ABOVE 1GHz DATA

##### 802.11a

|                        |               |                          |              |
|------------------------|---------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 36 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 73.1 PK                 | 74.0           | -0.9        | 1.14 H             | 13                   | 64.56            | 8.53                     |
| 2                                                   | 5150.00     | 53.7 AV                 | 54.0           | -0.3        | 1.14 H             | 13                   | 45.17            | 8.53                     |
| 3                                                   | *5180.00    | 115.0 PK                |                |             | 1.14 H             | 13                   | 106.28           | 8.71                     |
| 4                                                   | *5180.00    | 104.7 AV                |                |             | 1.14 H             | 13                   | 95.95            | 8.71                     |
| 5                                                   | #10360.00   | 60.2 PK                 | 74.0           | -13.8       | 1.65 H             | 117                  | 39.88            | 20.33                    |
| 6                                                   | #10360.00   | 47.5 AV                 | 54.0           | -6.5        | 1.65 H             | 117                  | 27.14            | 20.33                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 5150.00     | 72.3 PK                 | 74.0           | -1.7        | 1.08 V             | 318                  | 63.78            | 8.53                     |
| 2                                                   | 5150.00     | 53.3 AV                 | 54.0           | -0.7        | 1.08 V             | 318                  | 44.79            | 8.53                     |
| 3                                                   | *5180.00    | 114.1 PK                |                |             | 1.08 V             | 318                  | 105.35           | 8.71                     |
| 4                                                   | *5180.00    | 104.1 AV                |                |             | 1.08 V             | 318                  | 95.34            | 8.71                     |
| 5                                                   | #10360.00   | 61.2 PK                 | 74.0           | -12.9       | 1.41 V             | 229                  | 40.82            | 20.33                    |
| 6                                                   | #10360.00   | 48.7 AV                 | 54.0           | -5.3        | 1.41 V             | 229                  | 28.35            | 20.33                    |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 66.1 PK                       | 74.0              | -7.9           | 1.32 H                   | 1                          | 59.24                  | 6.85                           |
| 2                                                   | 5150.00        | 49.5 AV                       | 54.0              | -4.5           | 1.32 H                   | 1                          | 42.67                  | 6.85                           |
| 3                                                   | *5200.00       | 108.0 PK                      |                   |                | 1.32 H                   | 1                          | 100.94                 | 7.01                           |
| 4                                                   | *5200.00       | 97.6 AV                       |                   |                | 1.32 H                   | 1                          | 90.56                  | 7.01                           |
| 5                                                   | #10400.00      | 57.7 PK                       | 74.0              | -16.4          | 2.80 H                   | 20                         | 40.21                  | 17.44                          |
| 6                                                   | #10400.00      | 43.7 AV                       | 54.0              | -10.3          | 2.80 H                   | 20                         | 26.24                  | 17.44                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 71.5 PK                       | 74.0              | -2.5           | 1.58 V                   | 360                        | 64.61                  | 6.85                           |
| 2                                                   | 5150.00        | 53.8 AV                       | 54.0              | -0.2           | 1.58 V                   | 360                        | 46.91                  | 6.85                           |
| 3                                                   | *5200.00       | 110.6 PK                      |                   |                | 1.58 V                   | 360                        | 103.54                 | 7.01                           |
| 4                                                   | *5200.00       | 100.6 AV                      |                   |                | 1.58 V                   | 360                        | 93.57                  | 7.01                           |
| 5                                                   | #10400.00      | 56.8 PK                       | 74.0              | -17.2          | 1.64 V                   | 178                        | 39.35                  | 17.44                          |
| 6                                                   | #10400.00      | 43.1 AV                       | 54.0              | -10.9          | 1.64 V                   | 178                        | 25.64                  | 17.44                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 113.7 PK                      |                   |                | 1.67 H                   | 229                        | 106.52                 | 7.16                           |
| 2                                                   | *5240.00       | 102.8 AV                      |                   |                | 1.67 H                   | 229                        | 95.63                  | 7.16                           |
| 3                                                   | 5350.00        | 59.8 PK                       | 74.0              | -14.2          | 1.67 H                   | 229                        | 52.19                  | 7.64                           |
| 4                                                   | 5350.00        | 49.6 AV                       | 54.0              | -4.5           | 1.67 H                   | 229                        | 41.91                  | 7.64                           |
| 5                                                   | #10480.00      | 57.5 PK                       | 74.0              | -16.5          | 1.87 H                   | 115                        | 39.64                  | 17.87                          |
| 6                                                   | #10480.00      | 43.5 AV                       | 54.0              | -10.5          | 1.87 H                   | 115                        | 25.61                  | 17.87                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 113.3 PK                      |                   |                | 1.39 V                   | 49                         | 106.13                 | 7.16                           |
| 2                                                   | *5240.00       | 102.4 AV                      |                   |                | 1.39 V                   | 49                         | 95.19                  | 7.16                           |
| 3                                                   | 5350.00        | 58.9 PK                       | 74.0              | -15.1          | 1.39 V                   | 49                         | 51.23                  | 7.64                           |
| 4                                                   | 5350.00        | 45.4 AV                       | 54.0              | -8.6           | 1.39 V                   | 49                         | 37.76                  | 7.64                           |
| 5                                                   | #10480.00      | 58.4 PK                       | 74.0              | -15.6          | 1.97 V                   | 231                        | 40.52                  | 17.87                          |
| 6                                                   | #10480.00      | 44.6 AV                       | 54.0              | -9.4           | 1.97 V                   | 231                        | 26.71                  | 17.87                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 149 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 62.9 PK                       | 68.2              | -5.3           | 1.09 H                   | 4                          | 52.36                  | 10.50                          |
| 2                                                   | *5745.00       | 113.4 PK                      |                   |                | 1.09 H                   | 4                          | 103.00                 | 10.35                          |
| 3                                                   | *5745.00       | 102.7 AV                      |                   |                | 1.09 H                   | 4                          | 92.39                  | 10.35                          |
| 4                                                   | 11490.00       | 63.9 PK                       | 74.0              | -10.1          | 1.43 H                   | 337                        | 41.62                  | 22.26                          |
| 5                                                   | 11490.00       | 50.1 AV                       | 54.0              | -3.9           | 1.43 H                   | 337                        | 27.88                  | 22.26                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 63.9 PK                       | 68.2              | -4.3           | 1.12 V                   | 250                        | 53.39                  | 10.50                          |
| 2                                                   | *5745.00       | 115.1 PK                      |                   |                | 1.12 V                   | 250                        | 104.76                 | 10.35                          |
| 3                                                   | *5745.00       | 104.2 AV                      |                   |                | 1.12 V                   | 250                        | 93.85                  | 10.35                          |
| 4                                                   | 11490.00       | 65.4 PK                       | 74.0              | -8.6           | 3.47 V                   | 227                        | 43.13                  | 22.26                          |
| 5                                                   | 11490.00       | 51.7 AV                       | 54.0              | -2.3           | 3.47 V                   | 227                        | 29.40                  | 22.26                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5785.00       | 113.7 PK                      |                   |                | 1.05 H                   | 5                          | 103.40                 | 10.26                          |
| 2                                                   | *5785.00       | 103.0 AV                      |                   |                | 1.05 H                   | 5                          | 92.69                  | 10.26                          |
| 3                                                   | 11570.00       | 63.6 PK                       | 74.0              | -10.4          | 1.38 H                   | 320                        | 41.28                  | 22.35                          |
| 4                                                   | 11570.00       | 50.0 AV                       | 54.0              | -4.0           | 1.38 H                   | 320                        | 27.69                  | 22.35                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | *5785.00       | 114.4 PK                      |                   |                | 1.06 V                   | 254                        | 104.11                 | 10.26                          |
| 2                                                 | *5785.00       | 103.8 AV                      |                   |                | 1.06 V                   | 254                        | 93.57                  | 10.26                          |
| 3                                                 | 11570.00       | 66.5 PK                       | 74.0              | -7.5           | 3.81 V                   | 220                        | 44.16                  | 22.35                          |
| 4                                                 | 11570.00       | 52.4 AV                       | 54.0              | -1.6           | 3.81 V                   | 220                        | 30.03                  | 22.35                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5825.00       | 113.5 PK                      |                   |                | 1.20 H                   | 5                          | 103.24                 | 10.27                          |
| 2                                                   | *5825.00       | 102.3 AV                      |                   |                | 1.20 H                   | 5                          | 92.04                  | 10.27                          |
| 3                                                   | #5925.01       | 66.4 PK                       | 68.2              | -1.8           | 1.20 H                   | 5                          | 55.93                  | 10.50                          |
| 4                                                   | 11650.00       | 63.9 PK                       | 74.0              | -10.1          | 1.37 H                   | 332                        | 41.82                  | 22.06                          |
| 5                                                   | 11650.00       | 49.9 AV                       | 54.0              | -4.1           | 1.37 H                   | 332                        | 27.80                  | 22.06                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | *5825.00       | 113.7 PK                      |                   |                | 1.20 V                   | 269                        | 103.44                 | 10.27                          |
| 2                                                 | *5825.00       | 103.1 AV                      |                   |                | 1.20 V                   | 269                        | 92.78                  | 10.27                          |
| 3                                                 | #5925.01       | 67.2 PK                       | 68.2              | -1.1           | 1.20 V                   | 269                        | 56.65                  | 10.50                          |
| 4                                                 | 11650.00       | 65.7 PK                       | 74.0              | -8.3           | 3.84 V                   | 221                        | 43.63                  | 22.06                          |
| 5                                                 | 11650.00       | 51.8 AV                       | 54.0              | -2.2           | 3.84 V                   | 221                        | 29.72                  | 22.06                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

### 802.11n (20MHz)

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 36 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 72.8 PK                       | 74.0              | -1.2           | 1.12 H                   | 7                          | 64.27                  | 8.53                           |
| 2                                                   | 5150.00        | 53.7 AV                       | 54.0              | -0.3           | 1.12 H                   | 7                          | 45.14                  | 8.53                           |
| 3                                                   | *5180.00       | 114.7 PK                      |                   |                | 1.12 H                   | 7                          | 105.95                 | 8.71                           |
| 4                                                   | *5180.00       | 103.5 AV                      |                   |                | 1.12 H                   | 7                          | 94.77                  | 8.71                           |
| 5                                                   | #10360.00      | 60.0 PK                       | 74.0              | -14.0          | 1.51 H                   | 94                         | 39.71                  | 20.33                          |
| 6                                                   | #10360.00      | 47.6 AV                       | 54.0              | -6.4           | 1.51 H                   | 94                         | 27.28                  | 20.33                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 71.9 PK                       | 74.0              | -2.1           | 1.03 V                   | 324                        | 63.41                  | 8.53                           |
| 2                                                   | 5150.00        | 53.3 AV                       | 54.0              | -0.8           | 1.03 V                   | 324                        | 44.72                  | 8.53                           |
| 3                                                   | *5180.00       | 114.1 PK                      |                   |                | 1.03 V                   | 324                        | 105.36                 | 8.71                           |
| 4                                                   | *5180.00       | 102.8 AV                      |                   |                | 1.03 V                   | 324                        | 94.06                  | 8.71                           |
| 5                                                   | #10360.00      | 61.0 PK                       | 74.0              | -13.0          | 1.33 V                   | 234                        | 40.66                  | 20.33                          |
| 6                                                   | #10360.00      | 48.6 AV                       | 54.0              | -5.4           | 1.33 V                   | 234                        | 28.23                  | 20.33                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 40 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 62.2 PK                       | 74.0              | -11.8          | 1.34 H                   | 2                          | 55.34                  | 6.85                           |
| 2                                                   | 5150.00        | 48.5 AV                       | 54.0              | -5.5           | 1.34 H                   | 2                          | 41.62                  | 6.85                           |
| 3                                                   | *5200.00       | 103.4 PK                      |                   |                | 1.34 H                   | 2                          | 96.43                  | 7.01                           |
| 4                                                   | *5200.00       | 94.0 AV                       |                   |                | 1.34 H                   | 2                          | 87.00                  | 7.01                           |
| 5                                                   | #10400.00      | 58.1 PK                       | 74.0              | -16.0          | 2.09 H                   | 147                        | 40.61                  | 17.44                          |
| 6                                                   | #10400.00      | 42.6 AV                       | 54.0              | -11.4          | 2.09 H                   | 147                        | 25.16                  | 17.44                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 68.6 PK                       | 74.0              | -5.4           | 1.01 V                   | 360                        | 61.77                  | 6.85                           |
| 2                                                   | 5150.00        | 53.5 AV                       | 54.0              | -0.5           | 1.01 V                   | 360                        | 46.64                  | 6.85                           |
| 3                                                   | *5200.00       | 110.4 PK                      |                   |                | 1.01 V                   | 360                        | 103.37                 | 7.01                           |
| 4                                                   | *5200.00       | 101.8 AV                      |                   |                | 1.01 V                   | 360                        | 94.77                  | 7.01                           |
| 5                                                   | #10400.00      | 58.1 PK                       | 74.0              | -16.0          | 1.94 V                   | 56                         | 40.61                  | 17.44                          |
| 6                                                   | #10400.00      | 44.3 AV                       | 54.0              | -9.7           | 1.94 V                   | 56                         | 26.89                  | 17.44                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 48 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 111.8 PK                      |                   |                | 1.18 H                   | 167                        | 104.68                 | 7.16                           |
| 2                                                   | *5240.00       | 100.5 AV                      |                   |                | 1.18 H                   | 167                        | 93.29                  | 7.16                           |
| 3                                                   | 5350.00        | 56.3 PK                       | 74.0              | -17.7          | 1.18 H                   | 167                        | 48.63                  | 7.64                           |
| 4                                                   | 5350.00        | 47.3 AV                       | 54.0              | -6.7           | 1.18 H                   | 167                        | 39.65                  | 7.64                           |
| 5                                                   | #10480.00      | 57.3 PK                       | 74.0              | -16.7          | 1.58 H                   | 216                        | 39.39                  | 17.87                          |
| 6                                                   | #10480.00      | 42.1 AV                       | 54.0              | -11.9          | 1.58 H                   | 216                        | 24.19                  | 17.87                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5240.00       | 114.2 PK                      |                   |                | 1.00 V                   | 7                          | 107.07                 | 7.16                           |
| 2                                                   | *5240.00       | 103.8 AV                      |                   |                | 1.00 V                   | 7                          | 96.59                  | 7.16                           |
| 3                                                   | 5350.00        | 59.0 PK                       | 74.0              | -15.0          | 1.00 V                   | 7                          | 51.32                  | 7.64                           |
| 4                                                   | 5350.00        | 45.6 AV                       | 54.0              | -8.4           | 1.00 V                   | 7                          | 37.93                  | 7.64                           |
| 5                                                   | #10480.00      | 58.4 PK                       | 74.0              | -15.6          | 1.35 V                   | 167                        | 40.51                  | 17.87                          |
| 6                                                   | #10480.00      | 44.0 AV                       | 54.0              | -10.0          | 1.35 V                   | 167                        | 26.15                  | 17.87                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |                |                              |              |
|------------------------|----------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 149 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz   |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 66.4 PK                       | 68.2              | -1.8           | 1.01 H                   | 4                          | 55.92                  | 10.50                          |
| 2                                                   | *5745.00       | 113.9 PK                      |                   |                | 1.01 H                   | 4                          | 103.54                 | 10.35                          |
| 3                                                   | *5745.00       | 102.6 AV                      |                   |                | 1.01 H                   | 4                          | 92.21                  | 10.35                          |
| 4                                                   | 11490.00       | 62.6 PK                       | 74.0              | -11.4          | 1.52 H                   | 308                        | 40.38                  | 22.26                          |
| 5                                                   | 11490.00       | 49.1 AV                       | 54.0              | -4.9           | 1.52 H                   | 308                        | 26.85                  | 22.26                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | #5649.99       | 67.1 PK                       | 68.2              | -1.1           | 1.13 V                   | 252                        | 56.63                  | 10.50                          |
| 2                                                 | *5745.00       | 115.6 PK                      |                   |                | 1.13 V                   | 252                        | 105.21                 | 10.35                          |
| 3                                                 | *5745.00       | 104.4 AV                      |                   |                | 1.13 V                   | 252                        | 94.01                  | 10.35                          |
| 4                                                 | 11490.00       | 64.7 PK                       | 74.0              | -9.3           | 3.46 V                   | 227                        | 42.47                  | 22.26                          |
| 5                                                 | 11490.00       | 50.7 AV                       | 54.0              | -3.4           | 3.46 V                   | 227                        | 28.39                  | 22.26                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 157 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5785.00       | 113.6 PK                      |                   |                | 1.22 H                   | 3                          | 103.29                 | 10.26                          |
| 2                                                   | *5785.00       | 102.5 AV                      |                   |                | 1.22 H                   | 3                          | 92.20                  | 10.26                          |
| 3                                                   | 11570.00       | 62.9 PK                       | 74.0              | -11.1          | 1.44 H                   | 330                        | 40.51                  | 22.35                          |
| 4                                                   | 11570.00       | 49.1 AV                       | 54.0              | -4.9           | 1.44 H                   | 330                        | 26.73                  | 22.35                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | *5785.00       | 115.0 PK                      |                   |                | 1.12 V                   | 252                        | 104.69                 | 10.26                          |
| 2                                                 | *5785.00       | 103.8 AV                      |                   |                | 1.12 V                   | 252                        | 93.51                  | 10.26                          |
| 3                                                 | 11570.00       | 64.9 PK                       | 74.0              | -9.1           | 3.58 V                   | 226                        | 42.55                  | 22.35                          |
| 4                                                 | 11570.00       | 51.7 AV                       | 54.0              | -2.3           | 3.58 V                   | 226                        | 29.31                  | 22.35                          |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 165 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5825.00       | 112.2 PK                      |                   |                | 1.43 H                   | 7                          | 101.89                 | 10.27                          |
| 2                                                   | *5825.00       | 101.5 AV                      |                   |                | 1.43 H                   | 7                          | 91.24                  | 10.27                          |
| 3                                                   | #5925.01       | 65.9 PK                       | 68.2              | -2.3           | 1.43 H                   | 7                          | 55.37                  | 10.50                          |
| 4                                                   | 11650.00       | 62.9 PK                       | 74.0              | -11.1          | 1.37 H                   | 325                        | 40.82                  | 22.06                          |
| 5                                                   | 11650.00       | 49.0 AV                       | 54.0              | -5.0           | 1.37 H                   | 325                        | 26.90                  | 22.06                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5825.00       | 113.9 PK                      |                   |                | 1.14 V                   | 268                        | 103.62                 | 10.27                          |
| 2                                                   | *5825.00       | 102.8 AV                      |                   |                | 1.14 V                   | 268                        | 92.50                  | 10.27                          |
| 3                                                   | #5925.01       | 66.5 PK                       | 68.2              | -1.7           | 1.14 V                   | 268                        | 56.01                  | 10.50                          |
| 4                                                   | 11650.00       | 64.5 PK                       | 74.0              | -9.5           | 3.81 V                   | 225                        | 42.43                  | 22.06                          |
| 5                                                   | 11650.00       | 51.1 AV                       | 54.0              | -3.0           | 3.81 V                   | 225                        | 28.99                  | 22.06                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

### 802.11n (40MHz)

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 38 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 71.1 PK                       | 74.0              | -2.9           | 1.25 H                   | 8                          | 62.54                  | 8.53                           |
| 2                                                   | 5150.00        | 53.6 AV                       | 54.0              | -0.4           | 1.25 H                   | 8                          | 45.06                  | 8.53                           |
| 3                                                   | *5190.00       | 110.6 PK                      |                   |                | 1.25 H                   | 8                          | 101.84                 | 8.77                           |
| 4                                                   | *5190.00       | 97.4 AV                       |                   |                | 1.25 H                   | 8                          | 88.62                  | 8.77                           |
| 5                                                   | #10380.00      | 60.0 PK                       | 74.0              | -14.0          | 1.55 H                   | 108                        | 39.60                  | 20.40                          |
| 6                                                   | #10380.00      | 47.9 AV                       | 54.0              | -6.1           | 1.55 H                   | 108                        | 27.51                  | 20.40                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 70.6 PK                       | 74.0              | -3.4           | 1.21 V                   | 323                        | 62.11                  | 8.53                           |
| 2                                                   | 5150.00        | 53.3 AV                       | 54.0              | -0.8           | 1.21 V                   | 323                        | 44.72                  | 8.53                           |
| 3                                                   | *5190.00       | 110.1 PK                      |                   |                | 1.21 V                   | 323                        | 101.37                 | 8.77                           |
| 4                                                   | *5190.00       | 96.9 AV                       |                   |                | 1.21 V                   | 323                        | 88.13                  | 8.77                           |
| 5                                                   | #10380.00      | 60.9 PK                       | 74.0              | -13.1          | 1.28 V                   | 227                        | 40.53                  | 20.40                          |
| 6                                                   | #10380.00      | 48.6 AV                       | 54.0              | -5.4           | 1.28 V                   | 227                        | 28.16                  | 20.40                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 46 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 65.2 PK                       | 74.0              | -8.8           | 1.42 H                   | 36                         | 58.34                  | 6.85                           |
| 2                                                   | 5150.00        | 48.5 AV                       | 54.0              | -5.5           | 1.42 H                   | 36                         | 41.69                  | 6.85                           |
| 3                                                   | *5230.00       | 100.4 PK                      |                   |                | 1.42 H                   | 36                         | 93.24                  | 7.13                           |
| 4                                                   | *5230.00       | 91.7 AV                       |                   |                | 1.42 H                   | 36                         | 84.61                  | 7.13                           |
| 5                                                   | 5350.00        | 57.3 PK                       | 74.0              | -16.7          | 1.42 H                   | 36                         | 49.64                  | 7.64                           |
| 6                                                   | 5350.00        | 40.9 AV                       | 54.0              | -13.1          | 1.42 H                   | 36                         | 33.28                  | 7.64                           |
| 7                                                   | #10460.00      | 57.1 PK                       | 74.0              | -16.9          | 1.18 H                   | 64                         | 39.30                  | 17.77                          |
| 8                                                   | #10460.00      | 42.9 AV                       | 54.0              | -11.1          | 1.18 H                   | 64                         | 25.14                  | 17.77                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 5150.00        | 69.5 PK                       | 74.0              | -4.5           | 1.17 V                   | 3                          | 62.63                  | 6.85                           |
| 2                                                 | 5150.00        | 53.6 AV                       | 54.0              | -0.4           | 1.17 V                   | 3                          | 46.73                  | 6.85                           |
| 3                                                 | *5230.00       | 109.7 PK                      |                   |                | 1.17 V                   | 3                          | 102.61                 | 7.13                           |
| 4                                                 | *5230.00       | 99.9 AV                       |                   |                | 1.17 V                   | 3                          | 92.80                  | 7.13                           |
| 5                                                 | 5350.00        | 61.3 PK                       | 74.0              | -12.7          | 1.17 V                   | 3                          | 53.64                  | 7.64                           |
| 6                                                 | 5350.00        | 46.0 AV                       | 54.0              | -8.0           | 1.17 V                   | 3                          | 38.40                  | 7.64                           |
| 7                                                 | #10460.00      | 58.5 PK                       | 74.0              | -15.5          | 1.94 V                   | 13                         | 40.74                  | 17.77                          |
| 8                                                 | #10460.00      | 44.6 AV                       | 54.0              | -9.4           | 1.94 V                   | 13                         | 26.80                  | 17.77                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 151 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 65.1 PK                       | 68.2              | -3.1           | 1.15 H                   | 4                          | 54.61                  | 10.50                          |
| 2                                                   | *5755.00       | 108.0 PK                      |                   |                | 1.15 H                   | 4                          | 97.67                  | 10.34                          |
| 3                                                   | *5755.00       | 97.8 AV                       |                   |                | 1.15 H                   | 4                          | 87.46                  | 10.34                          |
| 4                                                   | 11510.00       | 61.0 PK                       | 74.0              | -13.0          | 1.50 H                   | 330                        | 38.69                  | 22.29                          |
| 5                                                   | 11510.00       | 48.7 AV                       | 54.0              | -5.3           | 1.50 H                   | 330                        | 26.43                  | 22.29                          |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | #5649.99       | 67.9 PK                       | 68.2              | -0.3           | 1.20 V                   | 254                        | 57.38                  | 10.50                          |
| 2                                                 | *5755.00       | 110.1 PK                      |                   |                | 1.20 V                   | 254                        | 99.72                  | 10.34                          |
| 3                                                 | *5755.00       | 99.9 AV                       |                   |                | 1.20 V                   | 254                        | 89.52                  | 10.34                          |
| 4                                                 | 11510.00       | 63.1 PK                       | 74.0              | -10.9          | 3.16 V                   | 230                        | 40.78                  | 22.29                          |
| 5                                                 | 11510.00       | 49.7 AV                       | 54.0              | -4.4           | 3.16 V                   | 230                        | 27.36                  | 22.29                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 159 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5795.00       | 108.3 PK                      |                   |                | 1.09 H                   | 7                          | 98.02                  | 10.24                          |
| 2                                                   | *5795.00       | 98.5 AV                       |                   |                | 1.09 H                   | 7                          | 88.29                  | 10.24                          |
| 3                                                   | #5925.01       | 65.8 PK                       | 68.2              | -2.4           | 1.09 H                   | 7                          | 55.26                  | 10.50                          |
| 4                                                   | 11590.00       | 61.1 PK                       | 74.0              | -12.9          | 1.43 H                   | 305                        | 38.71                  | 22.37                          |
| 5                                                   | 11590.00       | 48.8 AV                       | 54.0              | -5.2           | 1.43 H                   | 305                        | 26.39                  | 22.37                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *5795.00       | 110.1 PK                      |                   |                | 1.05 V                   | 255                        | 99.88                  | 10.24                          |
| 2                                                   | *5795.00       | 99.1 AV                       |                   |                | 1.05 V                   | 255                        | 88.87                  | 10.24                          |
| 3                                                   | #5925.01       | 67.7 PK                       | 68.2              | -0.5           | 1.05 V                   | 255                        | 57.22                  | 10.50                          |
| 4                                                   | 11590.00       | 63.1 PK                       | 74.0              | -11.0          | 3.23 V                   | 227                        | 40.68                  | 22.37                          |
| 5                                                   | 11590.00       | 49.9 AV                       | 54.0              | -4.1           | 3.23 V                   | 227                        | 27.50                  | 22.37                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

### 802.11ac (80MHz)

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 42 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 40GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 71.6 PK                       | 74.0              | -2.5           | 1.13 H                   | 9                          | 63.02                  | 8.53                           |
| 2                                                   | 5150.00        | 53.7 AV                       | 54.0              | -0.3           | 1.13 H                   | 9                          | 45.13                  | 8.53                           |
| 3                                                   | *5210.00       | 111.8 PK                      |                   |                | 1.13 H                   | 9                          | 102.93                 | 8.86                           |
| 4                                                   | *5210.00       | 95.9 AV                       |                   |                | 1.13 H                   | 9                          | 87.04                  | 8.86                           |
| 5                                                   | 5350.00        | 58.4 PK                       | 74.0              | -15.6          | 1.13 H                   | 9                          | 48.94                  | 9.43                           |
| 6                                                   | 5350.00        | 46.5 AV                       | 54.0              | -7.5           | 1.13 H                   | 9                          | 37.11                  | 9.43                           |
| 7                                                   | #10420.00      | 60.2 PK                       | 74.0              | -13.8          | 1.66 H                   | 120                        | 39.65                  | 20.58                          |
| 8                                                   | #10420.00      | 47.9 AV                       | 54.0              | -6.1           | 1.66 H                   | 120                        | 27.34                  | 20.58                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 5150.00        | 70.8 PK                       | 74.0              | -3.2           | 1.20 V                   | 325                        | 62.25                  | 8.53                           |
| 2                                                   | 5150.00        | 53.5 AV                       | 54.0              | -0.5           | 1.20 V                   | 325                        | 44.93                  | 8.53                           |
| 3                                                   | *5210.00       | 111.4 PK                      |                   |                | 1.20 V                   | 325                        | 102.55                 | 8.86                           |
| 4                                                   | *5210.00       | 95.6 AV                       |                   |                | 1.20 V                   | 325                        | 86.72                  | 8.86                           |
| 5                                                   | 5350.00        | 58.2 PK                       | 74.0              | -15.8          | 1.20 V                   | 325                        | 48.76                  | 9.43                           |
| 6                                                   | 5350.00        | 46.2 AV                       | 54.0              | -7.8           | 1.20 V                   | 325                        | 36.81                  | 9.43                           |
| 7                                                   | #10420.00      | 61.2 PK                       | 74.0              | -12.8          | 1.31 V                   | 219                        | 40.58                  | 20.58                          |
| 8                                                   | #10420.00      | 48.9 AV                       | 54.0              | -5.2           | 1.31 V                   | 219                        | 28.27                  | 20.58                          |

#### REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.
- " # ": The radiated frequency is out of the restricted band.

|                 |                |                      |              |
|-----------------|----------------|----------------------|--------------|
| CHANNEL         | TX Channel 155 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 40GHz   |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 67.0 PK                       | 68.2              | -1.2           | 1.46 H                   | 6                          | 56.47                  | 10.50                          |
| 2                                                   | *5775.00       | 104.8 PK                      |                   |                | 1.46 H                   | 6                          | 94.52                  | 10.29                          |
| 3                                                   | *5775.00       | 93.2 AV                       |                   |                | 1.46 H                   | 6                          | 82.92                  | 10.29                          |
| 4                                                   | #5925.01       | 63.1 PK                       | 68.2              | -5.1           | 1.46 H                   | 6                          | 52.59                  | 10.50                          |
| 5                                                   | 11550.00       | 60.6 PK                       | 74.0              | -13.4          | 1.45 H                   | 317                        | 38.26                  | 22.33                          |
| 6                                                   | 11550.00       | 48.1 AV                       | 54.0              | -5.9           | 1.45 H                   | 317                        | 25.80                  | 22.33                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | #5649.99       | 65.2 PK                       | 68.2              | -3.0           | 1.50 V                   | 250                        | 54.72                  | 10.50                          |
| 2                                                   | *5775.00       | 105.0 PK                      |                   |                | 1.50 V                   | 250                        | 94.68                  | 10.29                          |
| 3                                                   | *5775.00       | 93.7 AV                       |                   |                | 1.50 V                   | 250                        | 83.42                  | 10.29                          |
| 4                                                   | #5925.01       | 67.9 PK                       | 68.2              | -0.3           | 1.50 V                   | 250                        | 57.38                  | 10.50                          |
| 5                                                   | 11550.00       | 62.2 PK                       | 74.0              | -11.8          | 3.00 V                   | 239                        | 39.88                  | 22.33                          |
| 6                                                   | 11550.00       | 49.1 AV                       | 54.0              | -4.9           | 3.00 V                   | 239                        | 26.78                  | 22.33                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

## BELOW 1GHz WORST-CASE DATA

802.11a

|                 |               |                      |                 |
|-----------------|---------------|----------------------|-----------------|
| CHANNEL         | TX Channel 36 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz  |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 32.47          | 32.6 QP                       | 40.0              | -7.4           | 4.00 H                   | 73                         | 43.89                  | -11.31                         |
| 2                                                   | 150.04         | 22.9 QP                       | 43.5              | -20.7          | 4.00 H                   | 57                         | 32.40                  | -9.55                          |
| 3                                                   | 275.02         | 28.1 QP                       | 46.0              | -17.9          | 3.58 H                   | 112                        | 36.28                  | -8.18                          |
| 4                                                   | 425.03         | 30.9 QP                       | 46.0              | -15.1          | 2.26 H                   | 192                        | 35.94                  | -5.06                          |
| 5                                                   | 690.04         | 29.9 QP                       | 46.0              | -16.1          | 1.37 H                   | 188                        | 30.14                  | -0.21                          |
| 6                                                   | 895.53         | 37.8 QP                       | 46.0              | -8.2           | 1.00 H                   | 155                        | 34.75                  | 3.04                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 32.18          | 33.7 QP                       | 40.0              | -6.3           | 1.53 V                   | 258                        | 45.07                  | -11.39                         |
| 2                                                   | 157.12         | 22.4 QP                       | 43.5              | -21.1          | 1.00 V                   | 308                        | 31.70                  | -9.29                          |
| 3                                                   | 460.05         | 30.0 QP                       | 46.0              | -16.0          | 1.82 V                   | 128                        | 34.68                  | -4.65                          |
| 4                                                   | 690.04         | 33.9 QP                       | 46.0              | -12.2          | 2.03 V                   | 230                        | 34.06                  | -0.21                          |
| 5                                                   | 822.93         | 32.0 QP                       | 46.0              | -14.0          | 2.41 V                   | 354                        | 29.87                  | 2.17                           |
| 6                                                   | 920.02         | 33.7 QP                       | 46.0              | -12.3          | 2.33 V                   | 199                        | 29.52                  | 4.17                           |

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer                                       | Model No.   | Serial No.   | Cal. Date     | Cal. Due      |
|------------------------------------------------------------------|-------------|--------------|---------------|---------------|
| ROHDE & SCHWARZ<br>TEST RECEIVER                                 | ESCS 30     | 100290       | Dec. 24, 2015 | Dec. 23, 2016 |
| ROHDE & SCHWARZ<br>Artificial Mains Network<br>(for EUT)         | ESH2-Z5     | 100104       | Dec. 07, 2015 | Dec. 06, 2016 |
| LISN With Adapter (for EUT)                                      | AD10        | C09Ada-001   | Dec. 07, 2015 | Dec. 06, 2016 |
| ROHDE & SCHWARZ<br>Artificial Mains Network<br>(for peripherals) | ESH3-Z5     | 847265/023   | Oct. 21, 2015 | Oct. 20, 2016 |
| SCHWARZBECK<br>Artificial Mains Network (For<br>EUT)             | NNLK8129    | 8129229      | May 04, 2016  | May 03, 2017  |
| Software                                                         | Cond_V7.3.7 | NA           | NA            | NA            |
| RF cable (JYEBAO)<br>With 10dB PAD                               | 5D-FB       | Cable-C09.01 | Feb. 23, 2016 | Feb. 22, 2017 |
| SUHNER Terminator<br>(For ROHDE & SCHWARZ<br>LISN)               | 65BNC-5001  | E1-010789    | May 19, 2015  | May 18, 2016  |
| ROHDE & SCHWARZ<br>Artificial Mains Network (For<br>TV EUT)      | ESH3-Z5     | 100220       | Nov. 13, 2015 | Nov. 12, 2016 |
| LISN With Adapter<br>(for TV EUT)                                | 100220      | N/A          | Nov. 13, 2015 | Nov. 12, 2016 |

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in Shielded Room No. 9.

3. The VCCI Site Registration No. C-1312.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.

#### 4.2.7 Test Results


##### 802.11a: CH 36

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
|-------|----------|-------------------|-----------------------------------|
|-------|----------|-------------------|-----------------------------------|

| No | Frequency<br>(MHz) | Correction<br>Factor<br>(dB) | Reading Value<br>(dBuV) |       | Emission Level<br>(dBuV) |       | Limit<br>(dBuV) |       | Margin<br>(dB) |        |
|----|--------------------|------------------------------|-------------------------|-------|--------------------------|-------|-----------------|-------|----------------|--------|
|    |                    |                              | Q.P.                    | AV.   | Q.P.                     | AV.   | Q.P.            | AV.   | Q.P.           | AV.    |
| 1  | 0.16562            | 10.24                        | 27.67                   | 6.09  | 37.91                    | 16.33 | 65.18           | 55.18 | -27.27         | -38.85 |
| 2  | 0.28281            | 10.27                        | 17.81                   | 1.58  | 28.08                    | 11.85 | 60.73           | 50.73 | -32.65         | -38.88 |
| 3  | 0.73984            | 10.34                        | 14.04                   | 8.27  | 24.38                    | 18.61 | 56.00           | 46.00 | -31.62         | -27.39 |
| 4  | 1.73828            | 10.48                        | 13.10                   | 10.14 | 23.58                    | 20.62 | 56.00           | 46.00 | -32.42         | -25.38 |
| 5  | 4.33594            | 10.66                        | 8.56                    | 4.38  | 19.22                    | 15.04 | 56.00           | 46.00 | -36.78         | -30.96 |
| 6  | 19.68359           | 11.43                        | 11.26                   | 6.08  | 22.69                    | 17.51 | 60.00           | 50.00 | -37.31         | -32.49 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|----|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
|    |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1  | 0.18516         | 10.21                  | 30.03                | 18.48 | 40.24                 | 28.69 | 64.25        | 54.25 | -24.01      | -25.56 |
| 2  | 0.34531         | 10.24                  | 25.33                | 17.35 | 35.57                 | 27.59 | 59.07        | 49.07 | -23.51      | -21.49 |
| 3  | 0.54453         | 10.27                  | 20.69                | 14.88 | 30.96                 | 25.15 | 56.00        | 46.00 | -25.04      | -20.85 |
| 4  | 1.72266         | 10.47                  | 15.56                | 12.17 | 26.03                 | 22.64 | 56.00        | 46.00 | -29.97      | -23.36 |
| 5  | 2.63672         | 10.56                  | 12.32                | 8.26  | 22.88                 | 18.82 | 56.00        | 46.00 | -33.12      | -27.18 |
| 6  | 17.71094        | 11.11                  | 11.20                | 7.02  | 22.31                 | 18.13 | 60.00        | 50.00 | -37.69      | -31.87 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



### 4.3 Transmit Power Measurement

#### 4.3.1 Limits of Transmit Power Measurement

| Operation Band | EUT Category |                                   | Limit                                                                                                                       |
|----------------|--------------|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| U-NII-1        |              | Outdoor Access Point              | 1 Watt (30 dBm)<br>(Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon) |
|                |              | Fixed point-to-point Access Point | 1 Watt (30 dBm)                                                                                                             |
|                | √            | Indoor Access Point               | 1 Watt (30 dBm)                                                                                                             |
|                |              | Mobile and Portable client device | 250mW (24 dBm)                                                                                                              |
| U-NII-2A       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                          |
| U-NII-2C       | ---          |                                   | 250mW (24 dBm) or 11 dBm+10 log B*                                                                                          |
| U-NII-3        | √            |                                   | 1 Watt (30 dBm)                                                                                                             |

\*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \leq 4$ ;


Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any  $N_{ANT}$ ;

Array Gain = 5 log( $N_{ANT}/N_{SS}$ ) dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \geq 5$ .


For power measurements on all other devices: Array Gain = 10 log( $N_{ANT}/N_{SS}$ ) dB.

#### 4.3.2 Test Setup

##### FOR POWER OUTPUT MEASUREMENT



##### FOR 26dB & OCCUPIED BANDWIDTH



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

##### For Average Power Measurement

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

##### For 26dB Bandwidth

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

##### For Occupied Bandwidth

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to SAMPLE. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### POWER OUTPUT:

##### 802.11a

| CHAN. | FREQ.<br>(MHz) | MAXIMUM CONDUCTED<br>POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | POWER<br>LIMIT (dBm) | PASS / FAIL |
|-------|----------------|----------------------------------|---------|------------------------|-------------------------|----------------------|-------------|
|       |                | CHAIN 0                          | CHAIN 1 |                        |                         |                      |             |
| 36    | 5180           | 21.59                            | 22.02   | 303.433                | 24.82                   | 30                   | PASS        |
| 40    | 5200           | 22.94                            | 22.53   | <b>375.850</b>         | 25.75                   | 30                   | PASS        |
| 48    | 5240           | 22.08                            | 22.17   | 326.252                | 25.14                   | 30                   | PASS        |
| 149   | 5745           | 24.10                            | 24.59   | <b>544.780</b>         | 27.36                   | 30                   | PASS        |
| 157   | 5785           | 23.78                            | 24.19   | 501.203                | 27.00                   | 30                   | PASS        |
| 165   | 5825           | 22.84                            | 23.32   | 407.092                | 26.10                   | 30                   | PASS        |

##### 802.11n (20MHz)

| CHAN. | FREQ.<br>(MHz) | MAXIMUM CONDUCTED<br>POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | POWER<br>LIMIT (dBm) | PASS / FAIL |
|-------|----------------|----------------------------------|---------|------------------------|-------------------------|----------------------|-------------|
|       |                | CHAIN 0                          | CHAIN 1 |                        |                         |                      |             |
| 36    | 5180           | 21.48                            | 21.91   | 295.844                | 24.71                   | 30                   | PASS        |
| 40    | 5200           | 22.66                            | 22.31   | 354.718                | 25.50                   | 30                   | PASS        |
| 48    | 5240           | 22.15                            | 22.27   | 332.714                | 25.22                   | 30                   | PASS        |
| 149   | 5745           | 23.98                            | 24.52   | 533.174                | 27.27                   | 30                   | PASS        |
| 157   | 5785           | 23.70                            | 24.19   | 496.845                | 26.96                   | 30                   | PASS        |
| 165   | 5825           | 23.18                            | 23.49   | 431.327                | 26.35                   | 30                   | PASS        |

##### 802.11n (40MHz)

| CHAN. | FREQ.<br>(MHz) | MAXIMUM CONDUCTED<br>POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | POWER<br>LIMIT (dBm) | PASS / FAIL |
|-------|----------------|----------------------------------|---------|------------------------|-------------------------|----------------------|-------------|
|       |                | CHAIN 0                          | CHAIN 1 |                        |                         |                      |             |
| 38    | 5190           | 18.69                            | 18.82   | 150.169                | 21.77                   | 30                   | PASS        |
| 46    | 5230           | 21.94                            | 22.22   | 323.040                | 25.09                   | 30                   | PASS        |
| 151   | 5755           | 22.19                            | 22.67   | 350.504                | 25.45                   | 30                   | PASS        |
| 159   | 5795           | 21.65                            | 22.14   | 309.900                | 24.91                   | 30                   | PASS        |

### 802.11ac (80MHz)

| CHAN. | FREQ.<br>(MHz) | MAXIMUM CONDUCTED<br>POWER (dBm) |         | TOTAL<br>POWER<br>(mW) | TOTAL<br>POWER<br>(dBm) | POWER<br>LIMIT (dBm) | PASS / FAIL |
|-------|----------------|----------------------------------|---------|------------------------|-------------------------|----------------------|-------------|
|       |                | CHAIN 0                          | CHAIN 1 |                        |                         |                      |             |
| 42    | 5210           | 16.61                            | 17.06   | 96.630                 | 19.85                   | 30                   | PASS        |
| 155   | 5775           | 20.73                            | 21.11   | 247.426                | 23.93                   | 30                   | PASS        |

## 26dB BANDWIDTH:

### 802.11a

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 26dBc BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|-----------------------|---------|-------------|
|         |                               | CHAIN 0               | CHAIN 1 |             |
| 36      | 5180                          | 25.52                 | 25.74   | PASS        |
| 40      | 5200                          | 43.92                 | 43.12   | PASS        |
| 48      | 5240                          | 27.53                 | 27.66   | PASS        |

### 802.11n (20MHz)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 26dBc BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|-----------------------|---------|-------------|
|         |                               | CHAIN 0               | CHAIN 1 |             |
| 36      | 5180                          | 27.81                 | 26.59   | PASS        |
| 40      | 5200                          | 43.83                 | 43.64   | PASS        |
| 48      | 5240                          | 29.40                 | 28.53   | PASS        |

### 802.11n (40MHz)


| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 26dBc BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|-----------------------|---------|-------------|
|         |                               | CHAIN 0               | CHAIN 1 |             |
| 38      | 5190                          | 45.32                 | 46.04   | PASS        |
| 46      | 5230                          | 65.70                 | 65.29   | PASS        |

### 802.11ac (80MHz)


| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | 26dBc BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|-----------------------|---------|-------------|
|         |                               | CHAIN 0               | CHAIN 1 |             |
| 42      | 5210                          | 113.00                | 110.94  | PASS        |

## SPECTRUM PLOT OF WORST VALUE


802.11a




802.11n (20MHz)



802.11n (40MHz)



802.11ac (80MHz)



## OCCUPIED BANDWIDTH:

### 802.11a

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | OCCUPIED BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|--------------------------|---------|-------------|
|         |                               | CHAIN 0                  | CHAIN 1 |             |
| 36      | 5180                          | 16.92                    | 16.92   | PASS        |
| 40      | 5200                          | 22.92                    | 23.52   | PASS        |
| 48      | 5240                          | 17.16                    | 17.04   | PASS        |
| 149     | 5745                          | 32.43                    | 32.10   | PASS        |
| 157     | 5785                          | 32.30                    | 32.60   | PASS        |
| 165     | 5825                          | 28.60                    | 28.80   | PASS        |

### 802.11n (20MHz)

| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | OCCUPIED BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|--------------------------|---------|-------------|
|         |                               | CHAIN 0                  | CHAIN 1 |             |
| 36      | 5180                          | 18.12                    | 18.12   | PASS        |
| 40      | 5200                          | 21.24                    | 21.48   | PASS        |
| 48      | 5240                          | 18.24                    | 18.24   | PASS        |
| 149     | 5745                          | 34.26                    | 33.80   | PASS        |
| 157     | 5785                          | 34.20                    | 34.50   | PASS        |
| 165     | 5825                          | 30.00                    | 29.30   | PASS        |

### 802.11n (40MHz)


| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | OCCUPIED BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|--------------------------|---------|-------------|
|         |                               | CHAIN 0                  | CHAIN 1 |             |
| 38      | 5190                          | 36.80                    | 36.80   | PASS        |
| 46      | 5230                          | 37.40                    | 37.20   | PASS        |
| 151     | 5755                          | 38.26                    | 38.67   | PASS        |
| 159     | 5795                          | 38.67                    | 38.50   | PASS        |

### 802.11ac (80MHz)


| CHANNEL | CHANNEL<br>FREQUENCY<br>(MHz) | OCCUPIED BANDWIDTH (MHz) |         | PASS / FAIL |
|---------|-------------------------------|--------------------------|---------|-------------|
|         |                               | CHAIN 0                  | CHAIN 1 |             |
| 42      | 5210                          | 76.08                    | 76.32   | PASS        |
| 155     | 5775                          | 75.88                    | 76.16   | PASS        |

## SPECTRUM PLOT OF WORST VALUE


**802.11a**




**802.11n (20MHz)**



**802.11n (40MHz)**



**802.11ac (80MHz)**




#### 4.4 Peak Power Spectral Density Measurement

##### 4.4.1 Limits of Peak Power Spectral Density Measurement

| Operation Band | EUT Category |                                   | LIMIT         |
|----------------|--------------|-----------------------------------|---------------|
| U-NII-1        |              | Outdoor Access Point              | 17dBm/ MHz    |
|                |              | Fixed point-to-point Access Point |               |
|                | √            | Indoor Access Point               |               |
|                |              | Mobile and Portable client device | 11dBm/ MHz    |
| U-NII-2A       | ---          |                                   | 11dBm/ MHz    |
| U-NII-2C       | ---          |                                   | 11dBm/ MHz    |
| U-NII-3        | √            |                                   | 30dBm/ 500kHz |

##### 4.4.2 Test Setup



##### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

##### 4.4.4 Test Procedure

###### For U-NII-1 band:

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS
- 3) Sweep time = auto, trigger set to "free run".
- 4) Trace average at least 100 traces in power averaging mode.
- 5) Record the max value and add 10 log (1/duty cycle)

###### For U-NII-3 band:

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 500 kHz, Set VBW ≥ 3 RBW, Detector = RMS
- 3) Sweep time = auto, trigger set to "free run".
- 4) Trace average at least 100 traces in power averaging mode.
- 5) Record the max value and add 10 log (1/duty cycle)

#### 4.4.5 Deviation from Test Standard

No deviation.

#### 4.4.6 EUT Operating Condition

Same as Item 4.3.6.

#### 4.4.7 Test Results

##### For U-NII-1 Band 802.11a

| Chan. | Freq.<br>(MHz) | PSD (dBm) |         | Total PSD<br>W/O Duty<br>Factor<br>(dBm) | Duty Factor | Total PSD<br>With Duty<br>Factor<br>(dBm) | MAX. Limit<br>(dBm) | Pass / Fail |
|-------|----------------|-----------|---------|------------------------------------------|-------------|-------------------------------------------|---------------------|-------------|
|       |                | Chain 0   | Chain 1 |                                          |             |                                           |                     |             |
| 36    | 5180           | 7.52      | 7.52    | 10.54                                    | 0.15        | 10.69                                     | 17.00               | Pass        |
| 40    | 5200           | 9.37      | 9.34    | 12.37                                    | 0.15        | 12.52                                     | 17.00               | Pass        |
| 48    | 5240           | 7.86      | 7.79    | 11.14                                    | 0.15        | 10.99                                     | 17.00               | Pass        |

##### NOTE:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11n (20MHz)

| Chan. | Freq.<br>(MHz) | PSD (dBm) |         | Total PSD<br>W/O Duty<br>Factor<br>(dBm) | Duty Factor | Total PSD<br>With Duty<br>Factor<br>(dBm) | MAX. Limit<br>(dBm) | Pass / Fail |
|-------|----------------|-----------|---------|------------------------------------------|-------------|-------------------------------------------|---------------------|-------------|
|       |                | Chain 0   | Chain 1 |                                          |             |                                           |                     |             |
| 36    | 5180           | 7.18      | 7.19    | 10.20                                    | 0.20        | 10.40                                     | 17.00               | Pass        |
| 40    | 5200           | 8.76      | 8.84    | 11.81                                    | 0.20        | 12.01                                     | 17.00               | Pass        |
| 48    | 5240           | 7.46      | 7.43    | 10.86                                    | 0.20        | 10.66                                     | 17.00               | Pass        |

##### NOTE:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11n (40MHz)

| Chan. | Freq.<br>(MHz) | PSD (dBm) |         | Total PSD<br>W/O Duty<br>Factor<br>(dBm) | Duty Factor | Total PSD<br>With Duty<br>Factor<br>(dBm) | MAX. Limit<br>(dBm) | Pass / Fail |
|-------|----------------|-----------|---------|------------------------------------------|-------------|-------------------------------------------|---------------------|-------------|
|       |                | Chain 0   | Chain 1 |                                          |             |                                           |                     |             |
| 38    | 5190           | 1.03      | 0.96    | 4.01                                     | 0.36        | 4.37                                      | 17.00               | Pass        |
| 46    | 5230           | 4.69      | 4.68    | 7.70                                     | 0.36        | 8.06                                      | 17.00               | Pass        |

##### NOTE:

1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

## 802.11ac (80MHz)


| Chan. | Freq. (MHz) | PSD (dBm) |         | Total PSD W/O Duty Factor (dBm) | Duty Factor | Total PSD With Duty Factor (dBm) | MAX. Limit (dBm) | Pass / Fail |
|-------|-------------|-----------|---------|---------------------------------|-------------|----------------------------------|------------------|-------------|
|       |             | Chain 0   | Chain 1 |                                 |             |                                  |                  |             |
| 42    | 5210        | 1.16      | 1.02    | 4.10                            | 1.19        | 5.29                             | 17.00            | Pass        |

### NOTE:


- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
- Refer to section 3.3 for duty cycle spectrum plot.

### SPECTRUM PLOT OF WORST VALUE


#### 802.11a: Chian 0 (CH40)




#### 802.11n (20MHz): Chian 1 (CH40)



#### 802.11n (40MHz): Chian 0 (CH46)



#### 802.11ac (80MHz): Chian 0 (CH42)



## For U-NII-3 Band

### 802.11a

| TX chain | Channel | Freq. (MHz) | PSD (dBm/500kHz) | 10 log (N=2) dB | DUTY FACTOR | Total PSD (dBm/500kHz) | Limit (dBm/500kHz) | PASS /FAIL |
|----------|---------|-------------|------------------|-----------------|-------------|------------------------|--------------------|------------|
| 0        | 149     | 5745        | 19.05            | 3.01            | 0.15        | 22.21                  | 30.00              | PASS       |
|          | 157     | 5785        | 18.68            | 3.01            | 0.15        | 21.84                  | 30.00              | PASS       |
|          | 165     | 5825        | 17.90            | 3.01            | 0.15        | 21.06                  | 30.00              | PASS       |
| 1        | 149     | 5745        | 18.49            | 3.01            | 0.15        | 21.65                  | 30.00              | PASS       |
|          | 157     | 5785        | 18.50            | 3.01            | 0.15        | 21.66                  | 30.00              | PASS       |
|          | 165     | 5825        | 18.09            | 3.01            | 0.15        | 21.25                  | 30.00              | PASS       |

#### NOTE:

1. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (20MHz)

| TX chain | Channel | Freq. (MHz) | PSD (dBm/500kHz) | 10 log (N=2) dB | DUTY FACTOR | Total PSD (dBm/500kHz) | Limit (dBm/500kHz) | PASS /FAIL |
|----------|---------|-------------|------------------|-----------------|-------------|------------------------|--------------------|------------|
| 0        | 149     | 5745        | 17.58            | 3.01            | 0.20        | 20.79                  | 30.00              | PASS       |
|          | 157     | 5785        | 17.28            | 3.01            | 0.20        | 20.49                  | 30.00              | PASS       |
|          | 165     | 5825        | 16.41            | 3.01            | 0.20        | 19.62                  | 30.00              | PASS       |
| 1        | 149     | 5745        | 17.42            | 3.01            | 0.20        | 20.63                  | 30.00              | PASS       |
|          | 157     | 5785        | 17.32            | 3.01            | 0.20        | 20.53                  | 30.00              | PASS       |
|          | 165     | 5825        | 16.53            | 3.01            | 0.20        | 19.74                  | 30.00              | PASS       |

#### NOTE:

1. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
2. Refer to section 3.3 for duty cycle spectrum plot.

### 802.11n (40MHz)

| TX chain | Channel | Freq. (MHz) | PSD (dBm/500kHz) | 10 log (N=2) dB | DUTY FACTOR | Total PSD (dBm/500kHz) | Limit (dBm/500kHz) | PASS /FAIL |
|----------|---------|-------------|------------------|-----------------|-------------|------------------------|--------------------|------------|
| 0        | 151     | 5755        | 12.96            | 3.01            | 0.36        | 16.33                  | 30.00              | PASS       |
|          | 159     | 5795        | 12.53            | 3.01            | 0.36        | 15.90                  | 30.00              | PASS       |
| 1        | 151     | 5755        | 12.37            | 3.01            | 0.36        | 15.74                  | 30.00              | PASS       |
|          | 159     | 5795        | 12.26            | 3.01            | 0.36        | 15.63                  | 30.00              | PASS       |

#### NOTE:


1. Directional gain =  $2\text{dBi} + 10\log(2) = 5.01\text{dBi} < 6\text{dBi}$ , so the power spectral density limit is not reduced.
2. Refer to section 3.3 for duty cycle spectrum plot.

## 802.11ac (80MHz)

| TX chain | Channel | Freq. (MHz) | PSD (dBm/500kHz) | 10 log (N=2) dB | DUTY FACTOR | Total PSD (dBm/500kHz) | Limit (dBm/500kHz) | PASS /FAIL |
|----------|---------|-------------|------------------|-----------------|-------------|------------------------|--------------------|------------|
| 0        | 155     | 5775        | 9.21             | 3.01            | 0.36        | 13.41                  | 30.00              | PASS       |
| 1        | 155     | 5775        | 9.25             | 3.01            | 0.36        | 13.45                  | 30.00              | PASS       |

### NOTE:

1. Directional gain = 2dBi + 10log(2) = 5.01dBi < 6dBi, so the power spectral density limit is not reduced.
2. Refer to section 3.3 for duty cycle spectrum plot.




## 4.5 Frequency Stability Measurement

### 4.5.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

#### 4.5.7 Test Results

| FREQUENCY STABILITY VERSUS TEMP. |                          |                                |                             |                                |                             |                                |                             |                                |                             |
|----------------------------------|--------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|
| OPERATING FREQUENCY: 5180MHz     |                          |                                |                             |                                |                             |                                |                             |                                |                             |
| TEMP.<br>(°C)                    | POWER<br>SUPPLY<br>(Vac) | 0 MINUTE                       |                             | 2 MINUTE                       |                             | 5 MINUTE                       |                             | 10 MINUTE                      |                             |
|                                  |                          | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) |
| 50                               | 120                      | 5180.042936                    | 8.2887219                   | 5180.043193                    | 8.3384170                   | 5180.043238                    | 8.3470553                   | 5180.042905                    | 8.2828185                   |
| 40                               | 120                      | 5180.043134                    | 8.3271168                   | 5180.043368                    | 8.3722008                   | 5180.043063                    | 8.3133054                   | 5180.043157                    | 8.3314672                   |
| 30                               | 120                      | 5180.043234                    | 8.3463110                   | 5180.043218                    | 8.3432432                   | 5180.043110                    | 8.3223801                   | 5180.043508                    | 8.3992278                   |
| 20                               | 120                      | 5180.042444                    | 8.1937622                   | 5180.042721                    | 8.2472973                   | 5180.042660                    | 8.2355221                   | 5180.042476                    | 8.2000000                   |
| 10                               | 120                      | 5180.04317                     | 8.3340178                   | 5180.043129                    | 8.3260618                   | 5180.043399                    | 8.3781746                   | 5180.043111                    | 8.3225869                   |
| 0                                | 120                      | 5180.043201                    | 8.3398860                   | 5180.04315                     | 8.3301158                   | 5180.043270                    | 8.3533145                   | 5180.043412                    | 8.3806950                   |
| -10                              | 120                      | 5180.042603                    | 8.2245210                   | 5180.04242                     | 8.1891892                   | 5180.042333                    | 8.1724718                   | 5180.042431                    | 8.1913127                   |
| -20                              | 120                      | 5180.043512                    | 8.4000000                   | 5180.043491                    | 8.3959459                   | 5180.042914                    | 8.2845560                   | 5180.043088                    | 8.3181467                   |


| FREQUENCY STABILITY VERSUS VOLTAGE |                          |                                |                             |                                |                             |                                |                             |                                |                             |
|------------------------------------|--------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|--------------------------------|-----------------------------|
| OPERATING FREQUENCY: 5180MHz       |                          |                                |                             |                                |                             |                                |                             |                                |                             |
| TEMP.<br>(°C)                      | POWER<br>SUPPLY<br>(Vac) | 0 MINUTE                       |                             | 2 MINUTE                       |                             | 5 MINUTE                       |                             | 10 MINUTE                      |                             |
|                                    |                          | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) | Measured<br>Frequency(<br>MHz) | Frequency<br>Drift<br>(ppm) |
| 20                                 | 138                      | 5180.043209                    | 8.3415505                   | 5180.043355                    | 8.3696911                   | 5180.043386                    | 8.3756835                   | 5180.043366                    | 8.3718147                   |
|                                    | 120                      | 5180.042444                    | 8.1937622                   | 5180.042721                    | 8.2472973                   | 5180.042660                    | 8.2355221                   | 5180.042476                    | 8.2000000                   |
|                                    | 102                      | 5180.043101                    | 8.3207079                   | 5180.04301                     | 8.3030888                   | 5180.042918                    | 8.2853193                   | 5180.042766                    | 8.2559846                   |

## 4.6 6dB Bandwidth Measurement

### 4.6.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.6.7 Test Results

##### 802.11a

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 149     | 5745            | 16.34               | 16.37   | 0.5                 | Pass        |
| 157     | 5785            | 16.41               | 16.40   | 0.5                 | Pass        |
| 165     | 5825            | 16.40               | 16.39   | 0.5                 | Pass        |

##### 802.11n (20MHz)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 149     | 5745            | 16.67               | 17.56   | 0.5                 | Pass        |
| 157     | 5785            | 16.97               | 17.58   | 0.5                 | Pass        |
| 165     | 5825            | 17.62               | 17.61   | 0.5                 | Pass        |

##### 802.11n (40MHz)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 151     | 5755            | 36.10               | 35.80   | 0.5                 | Pass        |
| 159     | 5795            | 36.13               | 36.38   | 0.5                 | Pass        |

##### 802.11ac (80MHz)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 155     | 5775            | 76.15               | 76.26   | 0.5                 | Pass        |

## SPECTRUM PLOT OF WORST VALUE


### 802.11a




### 802.11n (20MHz)



### 802.11n (40MHz)



### 802.11ac (80MHz)




## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Annex A- Radiated Out of Band Emisison (OOBE) Measurement (For U-NII-3 band)

### 802.11a





## 802.11n (20MHz)

### Test Plots



#### Horizontal

#### Vertical



#### Channel 149




#### Channel 157




#### Channel 165



## 802.11n (40MHz)



## 802.11ac (80MHz)



## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---