

Pages : : 33
Annexes : : 5
Total no. of sheets : : 53

Nemko Comlab AS

Office address: Gåsevikveien 8, Kjeller
Postal address: P.O.Box 96, N-2027 Kjeller
Telephone: +47 64 84 57 00
Facsimile: +47 64 84 57 05
E-mail: post@comlab.no
http://www.comlab.no
Enterprise no: NO 984 592 418 MVA

Test report : 04 / 662 / 3

Item tested : Simrad AI 80 AIS

Equipment type : AIS Transponder

Client : Kongsberg Seatex AS

Tested according to :

IEC 61993-2
(2001-12)

Date of issue : 2004. 08. 26

Authorised by : _____



Kjell G. Haga
Managing Director



Geir Antonsen
Technical Supervisor

The results detailed in this test report are valid only for the particular sample(s) tested and with configuration(s) as implemented during testing.

This test report can only be reproduced or published in full.
Reproduction or publishing of parts of this test report requires the prior written approval of Nemko Comlab AS.

CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Client Information	4
1.3	Manufacturer	4
2	TEST INFORMATION	5
2.1	Test Item	5
2.2	Standards and Regulations	5
2.3	Test Environment	5
2.3.1	Normal Test Conditions	5
2.3.2	Extreme Test Conditions	6
2.4	Test Period	6
2.5	Test Engineer	6
2.6	Additional Information	6
2.6.1	Test Methods	6
2.6.2	Selection Criteria	6
3	TEST REPORT SUMMARY	7
3.1	Abbreviations	7
3.2	Test Summary	7
4	TEST RESULTS	8
4.1	Transmitter Measurements	8
4.1.1	Frequency Error	8
4.1.2	Carrier Power	9
4.1.3	Carrier Power	10
4.1.4	Modulation Spectrum 25kHz channel mode	11
4.1.5	Modulation Spectrum 12.5kHz channel mode	11
4.1.6	Transmitter Attack Time	12
4.1.7	Transmitter Release Time	13
4.2	DSC Transmissions	14
4.2.1	Frequency error of the DSC Signal	14
4.2.2	Modulation Rate	14
4.3	TDMA Receivers	15
4.3.1	Sensitivity – 25kHz Operation	15
4.3.2	Sensitivity – 12.5kHz Operation	16
4.3.3	Error Behaviour at High Input Levels	17
4.3.4	Co-Channel Rejection - 25kHz Operation	18
4.3.5	Co-Channel Rejection - 12.5kHz Operation	19
4.3.6	Adjacent Channel Selectivity – 25kHz Operation	20
4.3.7	Adjacent Channel Selectivity – 12.5kHz Operation	21
4.3.8	Spurious Response Rejection	22
4.3.9	Intermodulation Response Rejection and Blocking	23
4.3.10	Transmit to Receive Switching Time	24
4.4	DSC Receiver	25
4.4.1	Maximum Sensitivity	25
4.4.2	Error Behaviour at High Input Levels	26
4.4.3	Co-Channel Rejection	27
4.4.4	Adjacent Channel Selectivity	28
4.4.5	Spurious Response Rejection	29
4.4.6	Intermodulation Response Rejection	29
4.4.7	Blocking or Desensitisation	30
	IEC 61993-2, Cl.15.5.1	31

4.5	Conducted Spurious Emissions Conveyed to the Antenna	31
4.5.1	Spurious Emissions from the Receiver	31
4.5.2	Spurious Emissions from the Transmitter	32
5	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	33
Annex 1 - 4	- Plots	17 pages
Annex 5	- Photos	3 pages

1 GENERAL INFORMATION

1.1 Test Laboratory

Name : Nemko Comlab AS
Address : Gåsevikveien 8, P.O.Box 96
N-2027 Kjeller, Norway
Telephone : +47 64 84 57 00
Fax : +47 64 84 57 05
E-mail : Post@comlab.no
Managing Director : Kjell G. Haga

Comlab is granted accreditation by Norwegian Accreditation under the registration number T031

1.2 Client Information

Name : Kongsberg Seatex AS
Address : Pirsenteret
N-7462 Trondheim

Telephone : + 47 73 45 55 00
Fax : + 47 73 51 50 20

Contact:

Name : Sigfred Avdal
E-mail : sigfred.avdal@kongsberg.com

1.3 Manufacturer

Name : Kongsberg Seatex A/S
Address : Pirsenteret
N-7642 Trondheim

Telephone : +47 73 54 55 00
Fax : +47 73 51 50 20

2 TEST INFORMATION

2.1 Test Item

Name : Simrad AI 80 AIS mobile unit

Model/version : AI 80 v.1.0

Serial number :

Software identity and version : main unit sw 1.00.xx

Remarks / Description of test item

The TDMA receiver measurements are performed with a number of 1000 packets.

For the DSC measurements a number of 100 packets was used.

The client supplied special test software installed in a PC. This software was absolute essential in order to carry out the measurements.

A special test unit was also supplied. This utility equipment was primarily used as a generator for the " wanted signal".

The reference for transmitter "on/off " function is a 5 V TTL control level, named TXON (TX-board).

The EUT was powered by a 24 VDC power supply.

2.2 Standards and Regulations

IEC 61993-2 (First edition (2001-12)) and IEC 60945 (Fourth edition (2002-08))

2.3 Test Environment

Environmental testing are performed according to IEC 60945 chapter 8,1 table 3

2.3.1 Normal Test Conditions

The values are the limits registered during the test period

Normal test voltage 24.0 V

Temperature: 19.9 – 22.9 °C

Relative humidity: 27 –64.9 %

2.3.2 Extreme Test Conditions

The EUT was placed in the chamber at normal room temperature 21.07.2004 13.00 and the first measurement in high temperature (+55 °C) was preformed from 22.07.2004 09.00 and low temperature from 23.07.2004 09.00

See annex 1.

Temperature

T_{min} : -15 °C

T_{max} : +55 °C

Voltage

V_{min} : 21.6 V

V_{max} : 31.2 V

2.4 Test Period

Test item received date : 14.06.04

Test period : from 14.06.04 to 23.07.04

2.5 Test Engineer

Knut Risting Hanssen and Egil J Bredholt

2.6 Additional Information

2.6.1 Test Methods

2.6.2 Selection Criteria

Selected tests have been performed on client's request

3 TEST REPORT SUMMARY

3.1 Abbreviations

- P** Passed, the equipment fulfils the requirement
F Failed, the equipment does not fulfil the requirement
NA Not applicable, the requirement is not applicable for this type of the equipment
NT Not tested, the test is not performed even though the requirement is relevant

3.2 Test Summary

Transmitter parameters

Frequency error	(P)
Carrier power H (conducted)	(P)
Carrier power L (conducted)	(P)
Modulation Spectrum 25 kHz mode	(P)
Modulation Spectrum 12.5 kHz mode	(P)
Transmitter Attack Time	(P)
Transmitter Release Time	(P)

DSC Transmissions

Frequency error of the DSC Signal	(P)
Modulation Rate	(P)

TDMA Receivers

Sensitivity – 25 kHz Operation	(P)
Sensitivity – 12.5 kHz Operation	(P)
Error Behaviour at High Input Levels	(P)
Co-Channel Rejection – 25 kHz Operation	(P)
Co-Channel Rejection – 12.5 kHz Operation	(P)
Adjacent Channel Selectivity – 25 kHz Operation	(P)
Adjacent Channel Selectivity – 12.5 kHz Operation	(P)
Spurious Response Rejection	(P)
Intermodulation Response Rejection and Blocking	(P)
Transmit to Receive Switching Time	(P)

DSC Receiver

Maximum Sensitivity	(P)
Error Behaviour at High Input Levels	(P)
Co-Channel Rejection	(P)
Adjacent Channel Selectivity	(P)
Spurious Response Rejection	(P)
Intermodulation Response Rejection	(P)
Blocking or Desensitisation	(P)

Conducted Spurious Emissions Conveyed to the Antenna

Spurious Emissions from the Receiver	(P)
Spurious Emissions from the Transmitter	(P)

4 TEST RESULTS

4.1 Transmitter Measurements

IEC 61993-2, Cl.15.1.1

4.1.1 Frequency Error

Power level at which the measurement has been performed: 2W

Test Conditions		Frequency Error kHz			
		156.025 MHz	157.4125 MHz	160.6375 MHz	162.025MHz
T _{nom}	V _{nom} (24.0 V)	-0.021	-0.021	-0.021	-0.023
T _{min} (-15 °C)	V _{min} (21.6 V)	-0.16	-0.14	-0.16	-0.16
	V _{max} (31.2 V)	-0.16	-0.15	-0.15	-0.17
T _{max} (+55 °C)	V _{min} (21.6 V)	-0.27	-0.27	-0.27	-0.28
	V _{max} (31.2 V)	-0.26	-0.27	-0.28	-0.27
Maximum frequency error (kHz)		-0.27	-0.27	-0.28	-0.28
Measurement uncertainty		≤ ± 50 Hz			

Limits:

Normal Test Conditions	Extreme Test Conditions
± 0,5 kHz	± 1 kHz

Test Equipment Used: 302, 1013, 1201, 1435 and 1442

4.1.2 Carrier Power

Rated output power level (maximum): 2W, (33 dBm)

Test Conditions		Transmitter Power dBm		
		156.025 MHz	159.025 MHz	162.025 MHz
T _{nom}	V _{nom} (24.0 V)	33.0	33.0	33.0
T _{min} (-15 °C)	V _{min} (21.6 V)	32.1	31.9	31.9
	V _{max} (31.2 V)	32.1	31.9	31.9
T _{max} (+55 °C)	V _{min} (21.6 V)	34.2	34.2	33.5
	V _{max} (31.2 V)	34.2	34.2	33.5
Variation in output power under normal test conditions (dB)		0.0	0.0	0.0
Variation in output power under extreme test conditions (dB)		+1.2 -0.9	+1.2 -1.1	+0.5 -1.1
Measurement uncertainty		≤ ± 0.7 dB		

Limits:

Under normal test conditions	± 1.5 dB
Under extreme test conditions	+ 2.0 dB - 3.0 dB

Test Equipment Used: 075, 302, 1079, 1123, 1201, 1338, 1435, 1442 and 1449

4.1.3 Carrier Power

Rated output power level (maximum): 12.5W, (41 dBm)

Test Conditions		Transmitter Power dBm		
		156.025 MHz	159.025 MHz	162.025 MHz
T _{nom}	V _{nom} (24.0 V)	40.7	40.8	41.2
T _{min} (-15 °C)	V _{min} (21.6 V)	40.6	40.6	40.8
	V _{max} (31.2 V)	40.6	40.6	40.8
T _{max} (+55 °C)	V _{min} (21.6 V)	40.4	40.5	40.7
	V _{max} (31.2 V)	40.4	40.5	40.7
Variation in output power under normal test conditions (dB)		-0.3	-0.2	+0.2
Variation in output power under extreme test conditions (dB)		-0.6	-0.5	-0.3
Measurement uncertainty		≤ ± 0.7 dB		

Limits:

Under normal test conditions	± 1.5 dB
Under extreme test conditions	+ 2.0 dB - 3.0 dB

Test Equipment Used: 075, 302, 1079, 1123, 1201, 1338, 1435, 1442 and 1449

IEC 61993-2, Cl.15.1.3

4.1.4 Modulation Spectrum 25kHz channel mode

Annex no. 2 page 1 and 2: TDMA, (High / Low power with test signal 2)
Annex no. 2 page 3 and 4: TDMA, (High / Low power with test signal 3)
Annex no. 2 page 5 and 6: DSC, (High / Low power with test signal 1)

Test Equipment Used: 302, 1201, 1337 and 1442

IEC 61993-2, Cl.15.1.4

4.1.5 Modulation Spectrum 12.5kHz channel mode

Annex no. 2, page 7 and 8: TDMA, (High / Low power with test signal 2)
Annex no. 2, page 9 and 10: TDMA, (High / Low power with test signal 3)

Test Equipment Used: 302, 1201, 1337 and 1442

IEC 61993-2, Cl.15.1.5

4.1.6 Transmitter Attack Time

Power level at which the measurement has been performed: 2W

Time Characteristics	159.025 MHz
Time relative to the power rise	0.713 ms
Time relative to the frequency behaviour	<0.3 ms
Maximum of these times	0.713 ms
Measurement uncertainty	≤ ± 5 %

See annex no. 3: page 1 and 3.

Limits Clause 15.1.5

The transmitter attack time shall not exceed:	1 ms
--	------

Test Equipment Used: 75, 86, 302, 1007, 1047, 1079, 1139, 1201, 1207, 1239, 1337 and 1442

Power level at which the measurement has been performed: 12.5W

Time Characteristics	159.025 MHz
Time relative to the power rise	0.809 ms
Time relative to the frequency behaviour	<0.3 ms
Maximum of these times	0.809 ms
Measurement uncertainty	≤ ± 5 %

See annex no. 4: page 1 and 3.

Limits Clause 15.1.5

The transmitter attack time shall not exceed:	1 ms
--	------

Test Equipment Used: 75, 86, 302, 1007, 1047, 1079, 1139, 1201, 1207, 1239, 1337 and 1442

IEC 61993-2, Cl.15.1.6**4.1.7 Transmitter Release Time****Power level at which the measurement has been performed: 2W**

Time Characteristics	159.025 MHz
Time relative to the power decrease	0.713 ms
Measurement uncertainty	$\leq \pm 5 \%$

See annex no. 3: page 2.

Limits Clause 15.1.6

The transmitter release time shall not exceed:	1 ms
---	------

Test Equipment Used: 75, 86, 302, 1007, 1047, 1079, 1139, 1201, 1207, 1239, 1337 and 1442**Power level at which the measurement has been performed: 12.5W**

Time Characteristics	159.025 MHz
Time relative to the power decrease	0.741 ms
Measurement uncertainty	$\leq \pm 5 \%$

See annex no. 4: page 2.

Limits Clause 15.1.6

The transmitter release time shall not exceed:	1 ms
---	------

Test Equipment Used: 75, 86, 302, 1007, 1047, 1079, 1139, 1201, 1207, 1239, 1337 and 1442

4.2 DSC Transmissions

IEC 61993-2, Cl.15.2.1

4.2.1 Frequency error of the DSC Signal

Power level at which the measurement has been performed: 2W

Test Conditions		Frequency Error Hz	
		B (2100Hz)	Y (1300Hz)
T _{nom}	V _{nom} (24.0 V)	-0.05	-0.07
T _{min} (-15 °C)	V _{min} (21.6 V)	+0.22	-0.56
	V _{max} (31.2 V)	+0.04	-0.61
T _{max} (+55 °C)	V _{min} (21.6 V)	-0.41	-0.43
	V _{max} (31.2 V)	-0.38	-0.55
Maximum frequency error (Hz)		0.41	0.61
Measurement uncertainty		≤ ± 0.5 Hz	

Limits:

Normal Test Conditions	Extreme Test Conditions
± 1.0%	± 1.0%

Test Equipment Used: 302, 1013, 1047, 1201, 1435 and 1442

IEC 61993-2, Cl.15.2.2

4.2.2 Modulation Rate

Measured Baud rate	Limit
1199.9764	1200 ± 30 ppm
Measurement uncertainty	≤ ± 10 ppm

Measured on printed circuit board with a frequency counter.

Test Equipment Used: 302 and 1013

4.3 TDMA Receivers

IEC 61993-2, Cl.15.3.1

4.3.1 Sensitivity – 25kHz Operation

Test Conditions		Receiver Sensitivity dBm (PER %)	
		156,025MHz	162,025MHz
T _{nom}	V _{nom} (24.0 V)	-110.0 (19.9)	-109.5 (15.1)
T _{min} (-15°C)	V _{min} (21.6 V)	-109.0 (14.5)	-109.5 (15.4)
	V _{max} (31.2 V)	-109.0 (17.4)	-109.5 (15.1)
T _{max} (+55 °C)	V _{min} (21.6 V)	-107.0 (18.0)	-108.0 (17.9)
	V _{max} (31.2 V)	-107.0 (19.2)	-108.0 (19.1)
Measurement uncertainty		≤ ± 1.5 dB	
Test criteria		PER =20%	

Limits Clause 15.3.1

Normal test conditions	-107 dBm
Extreme test conditions	-101 dBm

Test Equipment Used: 302, 1079, 1123, 1201, 1435 and 1442

IEC 61993-2, Cl.15.3.2

4.3.2 Sensitivity – 12.5kHz Operation

Test Conditions		Receiver Sensitivity dBm (PER %)	
		157,4125MHz	160,6375MHz
T _{nom}	V _{nom} (24.0 V)	-102.0 (15.5)	-102.0 (11.2)
T _{min} (-15 °C)	V _{min} (21.6 V)	-103.0 (13.2)	-103.0 (15.6)
	V _{max} (31.2 V)	-103.0 (15.0)	-103.0 (15.6)
T _{max} (+55 °C)	V _{min} (21.6 V)	-101.0 (18.6)	-101.0 (11.0)
	V _{max} (31.2 V)	-101.0 (16.6)	-101.0 (11.7)
Measurement uncertainty		≤ ± 1.5 dB	
Test criteria		PER =20%	

Limits Clause 15.3.2

Normal test conditions	-98 dBm
Extreme test conditions	-92 dBm

Test Equipment Used: 302, 1079, 1123, 1201, 1435 and 1442

IEC 61993-2, Cl.15.3.3

4.3.3 Error Behaviour at High Input Levels

Test Signal 2 159.025 MHz

Input to receiver	Number of Messages not Correctly Received at	
	- 7dBm	- 77dBm
	0.3 %	0.1 %
Variation in %	0.2	
Measurement uncertainty	$\leq \pm 0.5 \text{ dB}$	

The level of wanted signal: -104 dBm

Limit Clause 15.3.3

Variation between -7 dBm and -77 dBm	$\leq 1\%$
--------------------------------------	------------

Test Equipment Used: 302, 1079, 1201, 1337 and 1442

Test Signal 3 159.025 MHz

Input to receiver	Number of Messages not Correctly Received at	
	- 7dBm	- 77dBm
	0.2	0.0
Variation in %	0.2	
Measurement uncertainty	$\leq \pm 0.5 \text{ dB}$	

Limit Clause 15.3.3

Variation between -7 dBm and -77 dBm	$\leq 1\%$
--------------------------------------	------------

Test Equipment Used: 302, 1079, 1201, 1337 and 1442

IEC 61993-2, Cl.15.3.4

4.3.4 Co-Channel Rejection - 25kHz Operation

Frequency Of Unwanted Signal	Co-Channel Rejection Ratio dB (PER %)		
	156.025 MHz	159.025 MHz	162.025 MHz
f + 3000Hz	-10.0 (13.3)	-10.0 (8.1)	-10.0 (15.1)
f	-10.0 (11.2)	-10.0 (11.4)	-10.0 (13.6)
f - 3000Hz	-10.0 (19.7)	-10.0 (18.8)	-10.0 (17.9)
Measurement uncertainty	≤ ± 1.0 dB		

The level of wanted signal: -104 dBm

Limits Clause 15.3.4

Channel Separation: 25kHz	-10dB<Limit<0dB (and >0)
----------------------------------	--------------------------

Test Equipment Used: 086, 302, 1007, 1079, 1123, 1201 and 1442

IEC 61993-2, Cl.15.3.5**4.3.5 Co-Channel Rejection - 12.5kHz Operation**

Frequency Of Unwanted Signal	Co-Channel Rejection Ratio dB (PER %)	
	157.4125 MHz	160.6375 MHz
f + 1500Hz	-16.5 (18.0)	-16.5 (13.5)
f	-14.5 (16.1)	-13.0 (10.3)
f - 1500Hz	-16.5 (14.8)	-16.0 (13.7)
Measurement uncertainty	$\leq \pm 1.0$ dB	

The level of wanted signal: -95 dBm

Limits Clause 15.3.5

Channel Separation: 12.5kHz	-18dB<Limit<0dB (and >0)
-----------------------------	--------------------------

Test Equipment Used: 086, 302, 1007, 1079, 1123, 1201 and 1442

IEC 61993-2, Cl.15.3.6

4.3.6 Adjacent Channel Selectivity – 25kHz Operation

Test Conditions		Adjacent Channel Selectivity Ratio dB (PER %)			
		156.025 MHz		162.025 MHz	
		+ 25 kHz	- 25 kHz	+ 25 kHz	- 25 kHz
T _{nom}	V _{nom} (24 V)	70.0 (8.9)	70.0 (11.4)	70.0 (1.8)	70.0 (3.2)
T _{min} (-15 °C)	V _{min} (21.6 V)	69.0 (15.4)	63.0 (11.9)	70.5 (14.5)	69.5 (16.7)
	V _{max} (31.2V)	69.0 (14.7)	63.0 (9.5)	70.5 (11.6)	70.0 (16.9)
T _{max} (+55 °C)	V _{min} (21.6 V)	67.0 (17.0)	66.5 (17.2)	74.0 (7.0)	74.0 (4.1)
	V _{max} (31.2 V)	67.0 (15.0)	66.5 (15.7)	74.0 (8.0)	74.0 (14.0)
Measurement uncertainty		≤ ± 2.5 dB			

The level of wanted signal: -104 dBm (Normal test condition)

The level of wanted signal: -95 dBm (Extreme test conditions)

Limits Clause 15.3.6

Channel Separation	Normal Conditions	Extreme Conditions
25,0 kHz	70,0 dB	60,0 dB

Test Equipment Used: 086, 302, 1007, 1079, 1123, 1201, 1435 and 1442

IEC 61993-2, Cl.15.3.7

4.3.7 Adjacent Channel Selectivity – 12.5kHz Operation

Test Conditions		Adjacent Channel Selectivity Ratio dB (PER %)			
		157.4125 MHz		160.6375 MHz	
		+ 12.5 kHz	- 12.5 kHz	+ 12.5 kHz	- 12.5 kHz
T _{nom}	V _{nom} (24 V)	50.0 (2.2)	50.0 (1.2)	50.0 (1.4)	50.0 (1.6)
T _{min} (-15 °C)	V _{min} (21.6 V)	54.0 (19.9)	53.0 (12.7)	54.0 (19.4)	54.0 (19.4)
	V _{max} (31.2V)	54.0 (16.0)	53.0 (12.2)	54.0 (16.5)	54.0 (14.1)
T _{max} (+55 °C)	V _{min} (21.6 V)	51.5 (12.3)	51.5 (7.3)	53.5 (12.3)	54.5 (9.6)
	V _{max} (31.2 V)	51.5 (16.5)	51.5 (8.7)	53.5 (13.5)	54.5 (10.6)
Measurement uncertainty		≤ ± 2.5 dB			

The level of wanted signal: -95 dBm (Normal test condition)
The level of wanted signal: -86 dBm (Extreme test conditions)

Limits Clause 15.3.7

Channel Separation	Normal Conditions	Extreme Conditions
12,5 kHz	50,0 dB	50,0 dB

Test Equipment Used: 086, 302, 1007, 1079, 1123, 1201, 1435 and 1442

IEC 61993-2, Cl.15.3.8

4.3.8 Spurious Response Rejection**TDMA Receiver**

Spurious Response Rejection	
159.025 MHz	
Frequency MHz	Ratio dB
158.025	>75
Other (0.1 MHz – 2 GHz)	>80
-	
Measurement uncertainty	≤ ± 2.5 dB

Limits Clause 15.3.8

Rejection ratio limit	70,0 dB
------------------------------	---------

Test Equipment Used: 302, 1047, 1079, 1123, 1201, 1240 and 1442

IEC 61993-2, Cl.15.3.9

4.3.9 Intermodulation Response Rejection and Blocking

Test 1 and 2:

Measured value	Generator A	Generator B	Generator C	Generator D
PER %	-101 dBm	-27 dBm	-27 dBm	-15 dBm
8.9	156.025	156.525	157.025	161.750
1.3	162.025	161.525	161.025	156.300
1.4	156.025	155.525	155.025	150.300
0.6	162.025	162.525	163.025	167.750
Measurement uncertainty		≤ ± 2 dB		

Measured with standard test signal 2.

Limits Clause 15.3.9

The packet error rate, with the outputs of signal generators B, C and D switched on, shall be 20% or less.

Test Equipment Used: 289, 302, 1007, 1079, 1123, 1136, 1139, 1201, 1435 and 1442

IEC 61993-2, Cl.15.3.10**4.3.10 Transmit to Receive Switching Time**

MHz	Measurement results	Required results
156.025	-109 dBm (11.0 %)	-107dBm, PER \leq 20%
162.025	-109 dBm (14.6 %)	-107dBm, PER \leq 20%
Measurement uncertainty		$\leq \pm 1.5$ dB

Test Equipment Used: 16, 130, 208, 1201

4.4 DSC Receiver

IEC 61993-2, Cl.15.4.1

4.4.1 Maximum Sensitivity

Test Conditions		Receiver Sensitivity dBm (BER %)		
		156.525 MHz	156.525 MHz + 1.5 kHz	156.525 MHz - 1.5 kHz
T_{nom}	V_{nom} (24.0 V)	-111.5 (0.70)	-109.5 (0.75)	-108.5 (0.53)
T_{min} (-15 °C)	V_{min} (21.6 V)	-109 (0.35)	-109 (0.65)	-109 (0.10)
	V_{max} (31.2 V)	-109 (0.47)	-109 (0.91)	-109 (0.35)
T_{max} (+55 °C)	V_{min} (21.6 V)	-109 (0.43)	-108.5 (0.47)	-107.5 (0.34)
	V_{max} (31.2 V)	-110.5 (0.55)	-108.5 (0.56)	-107.5 (0.53)
Measurement uncertainty		$\leq \pm 1.5$ dB		
Test criterium		BER = 10^{-2}		

Limits Clause 15.4.1

Normal test conditions	$\leq - 107$ dBm
Extreme test conditions	$\leq - 101$ dBm

Test Equipment Used: 302, 1079, 1123, 1201, 1435 and 1442

IEC 61993-2, Cl.15.4.2**4.4.2 Error Behaviour at High Input Levels****Test Signal 1**

Measured value	$7.5 \cdot 10^{-5}$
Measurement uncertainty	$\leq \pm 0.5 \text{ dB}$

The level of wanted signal: -7 dBm

Limit Clause 15.4.2

BER	$\leq 10^{-2}$
------------	----------------

Test Equipment Used: 302, 1079, 1123, 1201 and 1442

IEC 61993-2, Cl.15.4.3**4.4.3 Co-Channel Rejection**

Frequency Of Unwanted Signal	Co-Channel Rejection Ratio dB (BER %)
f + 3000Hz	-8.0 (0.2)
f	-8.0 (0.5)
f - 3000Hz	-8.0 (0.4)
Measurement uncertainty	$\leq \pm 1.0$ dB

The level of wanted signal: -104 dBm

Limits Clause 15.4.3

Channel Separation: 25kHz	-10dB <Limit< 0dB (and >0)
BER	$\leq 10^{-2}$

Test Equipment Used: 86, 302, 1007, 1079, 1117, 1123, 1134, 1201 and 1442

IEC 61993-2, Cl.15.4.4

4.4.4 Adjacent Channel Selectivity

Test Conditions		Adjacent Channel Selectivity Ratio dB (BER %)	
		156.525 MHz	
		+ 25 kHz	- 25 kHz
T _{nom}	V _{nom} (24.0 V)	75 (0.47)	75 (0.50)
T _{min} (-15 °C)	V _{min} (21.6 V)	75 (0.62)	75 (0.93)
	V _{max} (31.2 V)	75 (0.47)	75 (0.60)
T _{max} (+55 °C)	V _{min} (21.6 V)	75 (0.81)	75 (0.34)
	V _{max} (31.2 V)	74 (0.75)	75 (0.47)
Measurement uncertainty		≤ ± 2.5 dB	
Test criterium		BER ≤ 10⁻²	

BER < 2*10⁻⁵ (No loss of packets)

The level of wanted signal: -104 dBm (Normal and extreme test conditions)

Limits Clause 15.4.4

Channel Separation	Normal Conditions	Extreme Conditions
25,0 kHz	70,0 dB	60,0 dB

Test Equipment Used: 86, 302, 1007, 1079, 1117, 1123, 1134, 1201, 1435 and 1442

IEC 61993-2, Cl.15.4.5

4.4.5 Spurious Response Rejection

DSC Receiver

Spurious Response Rejection	
156.525 MHz	
Frequency MHz	Ratio dB
0.1 MHz – 2 GHz	>75
-	-
Measurement uncertainty	≤ ± 2.5 dB

The level of wanted signal: -104 dBm

Limits Clause 15.4.5

Rejection ratio limit	70,0 dB
BER	≤ 10 ⁻²

Test Equipment Used: 302, 1047, 1079, 1123, 1201, 1240 and 1442

IEC 61993-2, Cl.15.4.6

4.4.6 Intermodulation Response Rejection

Frequency Increments Of Unwanted Signals	Intermodulation Response Rejection Ratio dB (BER %)
	156.525 MHz
-50 / -100 kHz	>75 (0.07)
+50 / +100 kHz	>75 (0.17)
Measurement uncertainty	≤ ± 2.0 dB

The level of wanted signal: -104 dBm

Limits Clause 15.4.6.

The intermodulation response rejection ratio	> 65.0dB
BER	≤ 10 ⁻²

Test Equipment Used: 2, 289, 302, 1002, 1079, 1123, 1136, 1139, 1201 and 1442

4.4.7 Blocking or Desensitisation

Frequency Of Wanted Signal	Blocking or Desensitisation Ratio dB (BER %)
	156.525 MHz
F - 1 MHz	>90 (0.04)
F - 2 MHz	>90 (0.06)
F - 5 MHz	>90 (0.05)
f - 10 MHz	>90 (0.02)
F + 1 MHz	>90 (0.02)
F + 2 MHz	>90 (0.09)
F + 5 MHz	>90 (0.16)
f + 10 MHz	>90 (0.10)
Measurement uncertainty	$\leq \pm 2.5$ dB

The level of wanted signal: -104 dBm

Limits Clause 15.4.7

The blocking ratio	≥ 84.0 dB
BER	$\leq 10^{-2}$

Test Equipment Used: 86, 302, 1007, 1079, 1117, 1123, 1134, 1201 and 1442

IEC 61993-2, Cl.15.5.1**4.5 Conducted Spurious Emissions Conveyed to the Antenna****4.5.1 Spurious Emissions from the Receiver**

Spurious Emissions		
159.025 MHz (TDMA), 156.525 MHz (DSC)		
Frequency MHz	Bandwidth kHz	Level dBm
0.15 - 2000	Max.100	<-70
Measurement uncertainty		$\leq \pm 1.1$ dB

Bandwidth (kHz) refers to the bandwidth of the measuring spectrum analyzer.
A peak detector is used.

Limits Clause 15.5.1

	Frequency Range	Limits
Conducted	150 KHz to 1 GHz	2 nW (-57,0 dBm)
	1 GHz to 2 GHz	20nW (-47,0 dBm)

Test Equipment Used: 302, 1079, 1123, 1201 and 1442

IEC 61993-2, Cl.15.5.2

4.5.2 Spurious Emissions from the Transmitter

Spurious Emissions		
159.025 MHz		
Frequency MHz	Bandwidth kHz	Level dBm
318.050	10	-41.5
Others 0.15 - 2000	-	< limit -10 dB
Measurement uncertainty		≤ ± 1.1 dB

* With 12.5 W output power. With 2 W output power, all < limit – 10 dB.
Bandwidth (kHz) refers to the bandwidth of the spectrum analyzer.
A peak detector is used.

Limits Clause 15.5.2



Conducted	Frequency Range	Limits
	150 KHz to 1 GHz	0,25 μW (-36,0 dBm)
	1 GHz to 2 GHz	1 μW (-30,0 dBm)

Test Equipment Used: 302, 1079, 1123 1169, 1170, 1201 and 1442

5 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify identification of the test equipment and ancillaries used, all item used are identified by the testhouse on each page of the test report. All numbers are referenced to the list given below.

C	No	Instrument/Ancillary	Manufacturer	Type
LR	002	Generator, AF../UHF	R&S	SMPD
LR	075	Wattmeter, RF, Wideband	HP	HP435A
LR	086	Hybrid	Anzaz	H-9
LR	289	Hybrid	Anzaz	DS-4-4
LR	302	Multimeter, Digital	Fluke	77
LR	1002	Generator, AF../UHF	R&S	SMPC
LR	1007	Attenuator	Narda	765-10
LR	1013	Counter Freq	HP	HP5385A
LR	1047	Radiocomm Analyzer	R&S	CMTA 54
LR	1079	Generator, AF../UHF	R&S	SMHU56
LR	1123	Spectrum Analyzer	Advantest	R3271
LR	1134	Attenuator	Suhner	6820.17.A
LR	1136	Attenuator	Narda	6810.17.A
LR	1139	Attenuator	Narda	6810.17.A
LR	1169	Filter Band Pass	Trilithic	5VF250/500
LR	1170	Filter Band Pass	Trilithic	5VF500/1000
LR	1201	Attenuator	Narda	768-20
LR	1207	Crystal Detector	HP	HP8470B
LR	1239	Oscilloscope	Fluke	PM3392A
LR	1240	Generator, AF../UHF	R&S	SMHU56
LR	1337	Spectrum Analyzer	R&S	FSEK 1088,3494,30
LR	1435	Climate Chamber	Vötsch	VC4060
LR	1442	Step Attenuator	Narda	Model 745-69
LR	1449	Power Sensor	HP	HP8481A






Ref Lvl
7 dBm

Marker [1]
4.09 dBm
159.0256012 MHz

RBW 1 kHz RF Att 30 dB
VBW 200 Hz
SWT 760 ms Unit dBm




Date: 30.JUN.2004 10:54:48



Ref Lvl
5 dBm


RBW 1 kHz RF Att 20 dB
VBW 200 Hz
SWT 760 ms Unit dBm



Date: 30 JUN 2004 11:03:33



Ref Lvl 7 dBm
Marker T11 4.03 dBm
159.02506012 MHz
RBW 1 kHz RF Att 30 dB
VBW 200 Hz
SWT 760 ms Unit dBm




Date: 30.JUN.2004 10:53:10



Ref Lvl
5 dBm

RBW 1 kHz RF Att 20 dB
VBW 200 Hz
SWT 760 ms Unit dBm




Date: 30.JUN.2004 11:05:51



Ref Lvl
10 dBm

RBW 500 Hz RF Att 30 dB
VBW 1 kHz
SWT 10 s Unit dBm




Date: 20.JUL.2004 12:40:15



Ref Lvl
10 dBm

RBW 500 Hz RF Att 40 dB
VBW 1 kHz
SWT 10 s Unit dBm




Date: 20.JUL.2004 12:21:23



Ref Lvl
7 dBm

RBW 1 kHz RF Att 30 dB
VBW 500 Hz
SWT 150 ms Unit dBm




Date: 30.JUN.2004 11:56:45



Ref Lvl
5 dBm

RBW 1 kHz RF Att 20 dB
VBW 500 Hz
SWT 150 ms Unit dBm




Date: 30 JUN 2004 11:48:47



Ref Lvl
7 dBm

RBW 1 kHz RF Att 30 dB
VBW 500 Hz
SWT 150 ms Unit dBm




Date: 30.JUN.2004 11:58:46



Ref Lvl
5 dBm

RBW 1 kHz RF Att 20 dB
VBW 500 Hz
SWT 150 ms Unit dBm



Date: 30.JUN.2004 11:51:42



Ref Lvl
6 dBm

Marker 111
98 dBm
713 426854 μ s

RBW 1 MHz RF Att 30 dB
VBW 1 MHz
SWT 2 ms Unit dBm




Date: 30.JUN.2004 13:36:20



Ref Lvl
10 dBm


Marker 1 [M1]
50.54 dBm
713.426854 μ s

RBW 1 MHz RF Att 30 dB
VBW 1 MHz
SWT 2 ms Unit dBm



Date: 30.JUN.2004 13:33:27

PM3392A, FLUKE incorporating PHILIPS T&M






Ref Lvl
15 dBm

1st ker f1
9.81 dBm
909 F 192 32 μ s


RBW 1 MHz RF Att 40 dB
VBW 1 MHz
SWT 2 ms Unit dBm



Date: 30.JUN.2004 13:23:58




Ref Lvl	Marker 1 [F1]	RBW	1 MHz	RF Att	40 dB
16 dBm	41.38 dBm	VBW	1 MHz	Unit	dBm
	74.482966 μ s	SWT	2 ms		



Date: 30.JUN.2004 13:28:17

PM3392A, FLUKE incorporating PHILIPS T&M






Simrad AI 80 AIS



Simrad AI 80 AIS



Simrad AI 80 AIS