



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: G-Wave Incorporated

Model: BDA-PS7W-37/37-90-C

Description: Bi-Directional amplifier (BDA), for the PS 700 MHz band

Serial Number: 15051001

FCC ID: Q8KPS7W3790C

To

FCC Part 1.1310

Date of Issue: January 4, 2016

On the behalf of the applicant:

G-Wave Incorporated
38 Leuning St.
South Hackensack, NJ 07606

Attention of:

Greg David, VP of Engineering
Ph: (201)343-6388
Email: tech-support@gwaverf.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1570018

Greg Corbin
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested

Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	December 3, 2015	Greg Corbin	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: BDA-PS7W-37/37-90-C

Description: Bi-Directional amplifier (BDA), for the PS 700 MHz band

Serial Number: 15051001

Additional Information:

The EUT is classified as a Part 90 PS **Class B** industrial signal booster

The EUT is a Bi-directional Amplifier that operates from 758 - 775 MHz (Base to Mobile) and 788 - 805 MHz (Mobile to Base).

System Power is 120 VAC @ 60 Hz.

EUT Operation during Tests

The EUT was tested under normal operating conditions with the front panel attenuators set to 0 dB for all measurements.

MPE calculations were performed at the manufacturer's rated output of +37 dBm using an antenna with 0 dBi gain.

MPE calculations were performed at the manufacturer's rated output of +37 dBm +20% using an antenna with 0 dBi gain.

MPE Evaluation

This is a portable device used in **Uncontrolled** Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	5012
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²
0.997 mw/cm ²

Power Density (S) = 0.997 mw/cm ²
Limit =(from above table) = 0.505 mw/cm ²

With the output power set to **manufacturer rated output power (+37 dBm)** using a 0 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

Minimum Safe Distance Evaluation

This is a mobile device used in **Uncontrolled** Exposure environment.

Test Data

Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain.

Test Frequency, MHz	758
Power, Conducted, mW (P)	5012
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Limit (L)	0.505 mw/cm ²

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
28.1 cm	5012	1	0.505

With the output power set to the manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain, the minimum safe distance is 28.1 cm.

Test Data

Output Power set to manufacturer's (Mfr) rated output power (+37 dBm +20%) using an antenna with 0 dBi gain

Test Frequency, MHz	758
Power, Conducted, mW (P)	5012 + 20% = 6014.4
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$	
Power Density (S) mw/cm ²	1.197 mw/cm ²

Power Density (S) = 1.197mw/cm ²
Limit =(from above table) = 0.505 mw/cm ²

With the output power set to **manufacturer rated output power (+37 dBm +20%)** using a 0 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

Minimum Safe Distance Evaluation

This is a mobile device used in **Uncontrolled** Exposure environment.

Test Data

Output Power set to manufacturer's (Mfr) rated output power (+37 dBm +20%) using an antenna with 0 dBi gain.

Test Frequency, MHz	758
Power, Conducted, mW (P)	5012 + 20% = 6014.4
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Limit (L)	0.505 mw/cm ²

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
30.8 cm	6014.4	1	0.505

With the output power set to the manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain, the minimum safe distance is 30.8 cm.

END OF TEST REPORT