



## Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

### Test Report

Prepared for: G-Way Microwave

Model: BDA-SMR/N-37/37-90-R

Description: Bi-Directional amplifier (BDA), used to amplify DL and UL frequencies in the CMRS 800 band.

Serial Number: N/A

FCC ID: Q8KSMRN3790R

To

FCC Part 1.1310

Date of Issue: November 19, 2015

On the behalf of the applicant:

G-Way Microwave  
38 Leuning St.  
South Hackensack, NJ 07606

Attention of:

Gregory Tsvika Blekher, Project Engineer  
Ph: (201) 343-6388  
E-Mail: [t\\_blekher@gwaymicrowave.com](mailto:t_blekher@gwaymicrowave.com)

Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p1560004-CMRS

**Greg Corbin**  
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 29, 2015	Greg Corbin	Original Document
2.0	November 18, 2015	Greg Corbin	Corrected product description under Additional Information, page 4. Updated ID and model name.

**ILAC / A2LA**

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**

**EUT Description**

**Model:** BDA-SMR/N-37/37-90-R

**Description:** Bi-Directional amplifier (BDA), used to amplify DL and UL frequencies in the PS 800 MHz band.

**Firmware:** N/A

**Serial Number:** N/A

**Additional Information:**

The EUT is classified as a Part 20 (CMRS 90-S) **Class B** industrial signal booster.

The EUT is a Bi-directional Amplifier that operates from 817 – 824 MHz (Mobile to Base) and 862 – 869 MHz (Base to Mobile).

**EUT Operation during Tests**

The EUT was tested under normal operating conditions with the front panel attenuators set to 0 dB for all measurements.

MPE calculations were performed at the manufacturer's rated output of +37 dBm using an antenna with 0 dBi gain.

MPE calculations were performed at the manufacturer's rated output of +37 dBm +20% using an antenna with 0 dBi gain.



### MPE Evaluation

This is a Fixed device used in an **Uncontrolled** Exposure environment.

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

### Test Data

**Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain**

Test Frequency, MHz	817
Power, Conducted, mW (P)	5012
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm <sup>2</sup>	Power mW (P)	Numeric Gain (G)	Distance (r <sup>2</sup> ) cm
0.997	5012	1	20

Power Density (S) = 0.997 mw/cm <sup>2</sup>
Limit =(from above table) = 0.545 mw/cm <sup>2</sup>

With the output power set to **manufacturer rated output power (+37 dBm)** using a 0 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

### Minimum Safe Distance Evaluation

#### Test Data

**Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain**

Test Frequency, MHz	817
Power, Mfr rated, mW (P)	5012
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Limit (L)	0.545

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
27.3	5012	1	0.537

With the output power set to the manufacturer's (Mfr) rated output power (+37 dBm) using an antenna with 0 dBi gain, the minimum safe distance is 27.3 cm.



**MPE Evaluation**

This is a Fixed device used in an **Uncontrolled** Exposure environment.

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

**Test Data**

**Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) + 20 % using an antenna with 0 dBi gain**

Test Frequency, MHz	817
Power, Mfr rated, mW (P)	5012
Power, Mfr rated + 20%, mW (P)	6014.4 mw (5012 + 20% )
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$			
Power Density (S) mw/cm <sup>2</sup>	Power mW (P)	Numeric Gain (G)	Distance (r <sup>2</sup> ) cm
1.20	6014.4	1	20

Power Density (S) = 1.20 mw/cm <sup>2</sup>
Limit =(from above table) = 0.545 mw/cm <sup>2</sup>

With the Uplink output power set to **manufacturer rated output power (+37 dBm) + 20 %** using a 0 dBi antenna, the EUT does not meet the power density requirements at 20 cm, so the minimum safe distance was calculated below.

**Minimum Safe Distance Evaluation**

**Test Data**

**Uplink Output Power set to manufacturer's (Mfr) rated output power (+37 dBm) + 20 % using an antenna with 0 dBi gain**

Test Frequency, MHz	817
Power, Mfr rated, mW (P)	5012
Power, Mfr rated + 20%, mW (P)	6014.4 mw (5012 + 20% )
Antenna Gain Isotropic	0 dBi
Antenna Gain Numeric (G)	1
Limit (L)	0.545

$R = \sqrt{(PG/4\pi L)}$			
Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
29.9	6014.4	1	0.537

With the Uplink Output Power set to the manufacturer's (Mfr) rated output power (+37 dBm) + 20 % using an antenna with 0 dBi gain, the minimum safe distance is 29.9 cm.

END OF TEST REPORT