

LABEL REQUIREMENTS RF IC & FCC

COMPANY NAME:	Model No.: 790
Kaba Ilco Inc.	IC: 4652A-CSC790
	FCC ID: Q8SCSC790

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

Made in Canada



COMPANY NAME: KABA INC. INC.
ADDRESS: 1000 N. 10TH ST.
MILWAUKEE, WI 53233
FCC ID: Q8SCSC790

This device complies with Part 15 of the FCC Rules
operation is subject to the following two
conditions: (1) This device must not cause harmful
interference and (2) This device must accept any
interference, including interference that
may cause undesired operation.
Made in China

Serial # / No de série
Y13BK3 300001

Part # / No de pièce
VER K3.3 CE

Warranty void if seal is broken
Garantie annulée si ce sceau est brisé





Kaba Ilco PK2818

Face Paper

Substance weight	44 lbs./ream (25" x 38")	ISO536
Caliper	3.0 mil.	ISO534
Tensile strength MD	28 lbf/in.	ISO1924
Tensile strength CD	17 lbf/in.	ISO1924
Roughness	0.7 microns PPS10	ISO8791-4
Opacity	87%	ISO2471
Brightness	87%	ISO2470

Adhesive

Tack minimum	14 N FTM 9
Shear minimum	1.0 h FTM 8
PE-looptack minimum	10 N modified FTM 9
Minimum labeling temperature	32°F
Service temperature range	- 4°F ... + 176°F

Liner

2.5 mil. White Kraft, 2.5 mil. White kraft liner. For roll stock applications and photocell dispensing..

Substance weight	40 lbs./ream (24" x 36")	ISO536
Caliper	2.5 mil.	ISO 5434