

FCC PART 15, CLASS B
MEASUREMENT AND TEST REPORT

For

Ningbo Baihuang Electric Appliances Co., Ltd
No.180, Yanshan Rd, Huximen, Heng He Town, Cixi, Ningbo, China 315318

FCC ID: Q92-BH9938U

Report Type: Original Report	Product Type: Remote Control Switch
Test Engineer: Allen Tian	<i>Allen - tian</i>
Report Number: RKS150513001-00A	
Report Date: 2015-5-18	
Reviewed By: EMC Manager	<i>Jesse Huang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....3
 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....3
 OBJECTIVE.....3
 RELATED SUBMITTAL(S)/GRANT(S).....3
 TEST METHODOLOGY.....3
 TEST FACILITY.....3

SYSTEM TEST CONFIGURATION (FCC §15.27)4
 JUSTIFICATION.....4
 EUT EXERCISE SOFTWARE.....4
 SPECIAL ACCESSORIES.....4
 EQUIPMENT MODIFICATIONS.....4
 SUPPORT EQUIPMENT LIST AND DETAILS.....4
 EXTERNAL I/O CABLE.....4
 BLOCK DIAGRAM OF TEST SETUP.....5

SUMMARY OF TEST RESULTS6

FCC §15.107 – AC LINE CONDUCTED EMISSIONS.....7
 APPLICABLE STANDARD.....7
 MEASUREMENT UNCERTAINTY.....7
 EUT SETUP.....7
 EMI TEST RECEIVER SETUP.....8
 TEST PROCEDURE.....8
 TEST EQUIPMENT LIST AND DETAILS.....8
 CORRECTED FACTOR & MARGIN CALCULATION.....8
 TEST RESULTS SUMMARY.....9
 TEST DATA.....9

FCC §15.109 - RADIATED EMISSIONS12
 APPLICABLE STANDARD.....12
 MEASUREMENT UNCERTAINTY.....12
 EUT SETUP.....12
 EMI TEST RECEIVER SETUP.....13
 TEST PROCEDURE.....13
 TEST EQUIPMENT LIST AND DETAILS.....13
 CORRECTION FACTOR & MARGIN CALCULATION.....14
 TEST RESULTS SUMMARY.....14
 TEST DATA.....14

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Ningbo Baihuang Electric Appliances Co., Ltd's product, model number: BH9938U (FCC ID: Q92-BH9938U) or the "EUT" in this report is a Remote Control Switch, which was measured approximately: 996 mm (L) x 55 mm (W) x 99.6 mm (H), the input power is AC 120V/60Hz. The highest operating frequency is 433 Hz.

**The product's series model number: BH9938U, BHC9938U, 9938-Receiver, C-9938-Receiver. These models have the same Circuits and components. The difference of these models are have different model name. but others differences as follows:*

- 1. BH9938U and 9938-Receiver with the mechanical switch button*
- 2. BHC9938U and C-9938-Receiver without the mechanical switch button*

**All measurement and test data in this report was gathered from production sample serial number: 0513006 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2015-5-13*

Objective

This report is prepared on behalf of Ningbo Baihuang Electric Appliances Co., Ltd in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15, Class B.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION (FCC §15.27)

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	Load	1000W	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

F I N A L

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC§15.107


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Kunshan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2009. The related limit was specified in FCC Part 15.107 Class B.

The EUT was connected to an AC 120V/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	831294/005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12005	2014-09-16	2015-09-16
Rohde & Schwarz	LISN	ESH3-Z5	12008	2014-09-16	2015-09-16
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - (\text{QuasiPeak} \ \& \ \text{Average})$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107 Class B, the worst margin reading as below:

25.71 dB at 16.138000 MHz in the **Line** conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m \pm U_{(L_m)} \leq L_{lim} \pm U_{cispr}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25°C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Allen.tian on 2015-5-15


Test Mode: on

AC 120V/60 Hz, Line



Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Limit (dB µ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.194000	---	4.24	53.86	49.62	9.000	L1	11.0
0.194000	14.83	---	63.86	49.03	9.000	L1	11.0
6.046000	---	7.93	50.00	42.07	9.000	L1	11.4
6.046000	15.52	---	60.00	44.48	9.000	L1	11.4
8.050000	---	3.64	50.00	46.36	9.000	L1	11.4
8.050000	8.68	---	60.00	51.32	9.000	L1	11.4
14.098000	---	5.00	50.00	45.00	9.000	L1	11.3
14.098000	9.28	---	60.00	50.72	9.000	L1	11.3
16.138000	---	24.29	50.00	25.71	9.000	L1	11.3
16.138000	32.44	---	60.00	27.56	9.000	L1	11.3
22.158000	---	3.35	50.00	46.65	9.000	L1	11.4

AC 120V/60 Hz, Neutral



Frequency (MHz)	QuasiPeak (dB µ V)	Average (dB µ V)	Limit (dB µ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.222000	---	2.66	52.74	50.08	9.000	N	11.0
0.222000	11.32	---	62.74	51.42	9.000	N	11.0
8.070000	---	5.59	50.00	44.41	9.000	N	11.4
8.070000	23.68	---	60.00	36.32	9.000	N	11.4
14.146000	---	14.59	50.00	35.41	9.000	N	11.4
14.146000	23.68	---	60.00	36.32	9.000	N	11.4
16.154000	---	18.74	50.00	31.26	9.000	N	11.4
16.154000	30.94	---	60.00	29.06	9.000	N	11.4
22.194000	---	3.56	50.00	46.44	9.000	N	11.4
22.194000	6.93	---	60.00	53.07	9.000	N	11.4
24.246000	---	18.20	50.00	31.80	9.000	N	11.4

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss
The corrected factor has been input into the transducer of the test software.
- 2) Margin = Limit - (QuasiPeak & Average)

FCC §15.109 - RADIATED EMISSIONS

Applicable Standard

FCC §15.109


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Kunshan) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

Frequency	Polarity	Measurement uncertainty
30 MHz~200 MHz	Horizontal	4.62 dB (k=2, 95% level of confidence)
	Vertical	4.54 dB (k=2, 95% level of confidence)
200 MHz~1 GHz	Horizontal	4.84 dB (k=2, 95% level of confidence)
	Vertical	5.91 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	Horizontal/Vertical	4.68 dB (k=2, 95% level of confidence)
Above 6 GHz	Horizontal/Vertical	4.92 dB (k=2, 95% level of confidence)

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The EUT was connected to an AC 120V/60 Hz power source.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 6 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2014-09-16	2015-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2014-09-16	2015-09-16
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2014.09.12	2015-09-12
ETS	Horn Antenna	3115	6229	2014.09.12	2015-09-12
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014.09.16	2015-09-16
Mini	Pre-amplifier	ZVA-183-S+	857001418	2014-09-16	2015-09-16
champrotek	Chamber	Chamber A	1#	2014-09-17	2015-09-17
R&S	Auto test Software	EMC32	V 09.10.0	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Correction Factor & Margin Calculation

The Correction Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Correction Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - (\text{QuasiPeak \& Average})$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, with the worst margin reading of:

19.58 dB at 5818.336674 MHz in the Horizontal polarization mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25°C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Allen Tian on 2015-5-15

Operation Mode: on

30MHz ~ 1GHz, AC 120V/60 Hz




Frequency (MHz)	QuasiPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
35.698750	7.88	40.00	32.12	120.000	100.0	V	82.0	-10.3
54.007500	2.75	40.00	37.25	120.000	100.0	V	6.0	-16.6
82.622500	8.21	40.00	31.79	120.000	100.0	H	172.0	-17.1
140.580000	9.28	43.50	34.22	120.000	100.0	V	132.0	-11.8
191.020000	20.00	43.50	23.50	120.000	199.0	H	197.0	-12.1
690.570000	15.24	46.00	30.76	120.000	199.0	H	315.0	-2.6

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 2) Margin = Limit - (QuasiPeak & Average)

1GHz ~ 6GHz, AC 120V/60 Hz

Full Spectrum



Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
2011.082164	37.91	---	73.90	35.99	1000.000	217.0	V	36.0
2011.082164	---	24.32	53.90	29.58	1000.000	217.0	V	36.0
2278.056112	---	25.54	53.90	28.36	1000.000	150.0	V	9.0
2278.056112	39.05	---	73.90	34.85	1000.000	150.0	V	9.0
5818.336674	---	34.32	53.90	19.58	1000.000	100.0	H	0.0
5818.336674	47.92	---	73.90	25.98	1000.000	100.0	H	0.0

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 2) Margin = Limit - (QuasiPeak & Average)

******* END OF REPORT *******