



TEST REPORT

Report No. : AD017372-1 Date : 2003 September 30

Applicant : AVC Technology Limited
Units 11-15, 11th Floor, Block A, Focal Ind. Ctr.,
21 Man Lok Street, Hung Hom,
Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be :
Model Name : Digital Audio Player
Model No. : DFP100
Rating : DC 4.5 V and 1 x 1.2 V Nickel Metal Hydride Battery
Testing Voltage : AC 120 V and DC 1.2 V
No. of sample(s) : Two(2) pieces ***

Date Received : 2003 September 20.

Test Period : 2003 September 20 – 2003 September 30.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002
ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 14.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart B.

Remark : Class II permissive change or modification of presently authorized equipment,
from CMA Report AD014112-1 issued on 2003 August 01.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

Page 1 of 14

FCC ID : Q93-F002

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

Table of Contents

1	General Information.....	3
1.1	General Description.....	3
1.2	Related Submittal Grants	3
1.3	Location of the test site.....	4
1.4	List of measuring equipment	5
1.5	List of support equipment	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Result.....	7
2.3	Radiated Emission Measurement Data.....	8
2.3	Radiated Emission Measurement Data.....	9
2.3	Radiated Emission Measurement Data.....	10
2.3	Radiated Emission Measurement Data.....	11
3	Description of the Line-conducted Test	12
3.1	Test Procedure	12
3.2	Test Result.....	12
3.3	Graph and Table of Conducted Emission Measurement Data	12
4	Photograph	13
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	13
4.2	Photographs of the External and Internal Configurations of the EUT	13
5	Supplementary document	13
6	Appendices	14



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

1 General Information

1.1 General Description

The equipment under test (EUT) is a standalone multi-function product, built-in 128 MB memory. The EUT has 5 different features :

1. Music Player (supports MP3 and WMA)
2. FM turner with memory function (Preset channel)
3. Voice Recording
4. USB interface for PC uploading and downloading files (through an USB connection cable)
5. With transformer for charging and operation

A brief circuit description is saved with filename : OpDes.pdf

1.2 Related Submittal Grants

This is a single application for certification of a computer peripheral product.



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
LISN	R&S	ESH3-Z5	100010	20-70405
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

1.5 List of support equipment

1. Intel CPU PIII 800EB / 256 cache / 133MHz
Model: L103A455-0041 SL4MB
2. Intel Mother Board
Model: Intel Type: D815EEA
3. IBM Hard-disk
Model: DTLA-30720, 20.5GB
4. Proview LCD Monitor
Model: 568
S/N: FYUJ240040133
5. IBM Mouse
Model: 12J3618
S/N: 23-005077
6. Acer Keyboard
Model: 6511-VA
7. Hewlett Packard LaserJet 2100TN
Model: C4172A
S/N: SGGS038577
8. PenPower Handwriting System
Model: PP403N
S/N: PT9122239
9. USB cable
(Provided by Applicant)
10. Transformer (120 V 60 Hz / 4.5 V DC)
Model : U035-045F0056
(Provided by Applicant)



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

2.2 Test Result

All modes had been test. The measurement data were indicated in next page.

All other measurement were 20 dB below the 15.109 limits. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : FM

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
87.723	H	15.8	8.0	23.8	40.0	-16.2
98.011	H	15.0	10.0	25.0	43.5	-18.5
108.217	H	13.6	12.0	25.6	43.5	-17.9
175.446	H	20.0	10.7	30.7	43.5	-12.8
196.022	H	23.7	10.5	34.2	43.5	-9.3
216.434	H	26.0	10.7	36.7	46.0	-9.3
350.892	H	14.9	15.3	30.2	46.0	-15.8
392.044	H	18.4	15.3	33.7	46.0	-12.3
432.868	H	15.7	18.6	34.3	46.0	-11.7



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : Play Music

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
219.642	H	21.4	10.7	32.1	46.0	-13.9
244.218	H	22.6	10.7	33.3	46.0	-12.7
256.506	H	22.9	13.9	36.8	46.0	-9.2
268.793	H	23.6	13.9	37.5	46.0	-8.5
270.329	H	21.8	13.9	35.7	46.0	-10.3
294.904	H	16.9	13.9	30.8	46.0	-15.2
344.056	H	15.8	15.3	31.1	46.0	-14.9
369.631	H	14.5	15.3	29.8	46.0	-16.2
393.207	H	16.9	15.3	32.2	46.0	-13.8
417.781	H	10.0	18.6	28.6	46.0	-17.4



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : PC connected

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
122.876	H	10.7	13.2	23.9	43.5	-19.6
147.402	H	14.2	12.2	26.4	43.5	-17.1
172.025	H	13.2	11.0	24.2	43.5	-19.3
196.601	H	14.7	10.5	25.2	43.5	-18.3
221.178	H	15.1	10.7	25.8	46.0	-20.2
245.753	H	13.3	10.7	24.0	46.0	-22.0
270.324	H	14.4	13.9	28.3	46.0	-17.7
294.903	H	11.9	13.9	25.8	46.0	-20.2
344.055	H	15.0	15.3	30.3	46.0	-15.7
466.931	H	11.3	18.6	29.9	46.0	-16.1



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : Record

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
172.034	H	15.3	11.0	26.3	43.5	-17.2
219.642	H	22.4	10.7	33.1	46.0	-12.9
256.505	H	21.8	13.9	35.7	46.0	-10.3
268.793	H	25.0	13.9	38.9	46.0	-7.1
274.937	H	15.4	13.9	29.3	46.0	-16.7
293.368	H	19.4	13.9	33.3	46.0	-12.7
348.664	H	13.9	15.3	29.2	46.0	-16.8
373.239	H	15.3	15.3	30.6	46.0	-15.4
391.670	H	13.9	15.3	29.2	46.0	-16.8
446.964	H	12.6	18.6	31.2	46.0	-14.8



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode had been tested. The EUT connecting with an USB cable and an earphone produced the maximum emission. The measurement data was indicated in next page.

The result showed that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the document are saved with filename TestRpt2.pdf



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem1.pdf to Schem2.jpg
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



TEST REPORT

Report No. : AD017372-1

Date : 2003 September 30

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of the set-up of Conducted Emissions	2 pages
A3.	Photos of External Configurations	1 page
A4.	Photos of Internal Configurations	1 page
A5.	ID Label/Location	1 page
A6.	Conducted Emission Test Result	4 pages
A7.	Block Diagram	1 page
A8.	Schematics Diagram	4 pages
A9.	User Manual	25 pages
A10.	Operation Description	1 page

***** End of Report *****