



## **TEST REPORT**

Report No. : AD015024-1 Date : 2003 September 09

Applicant : AVC Technology Limited  
Units 11-15, 11<sup>th</sup> Floor, Block A, Focal Ind. Ctr.,  
21 Man Lok Street, Hung Hom,  
Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be :  
Model Name : Digital Audio Player  
Model No. : MMP3642 and DFP50  
Rating : 1 x 1.5 V AA size battery  
No. of sample(s) : Two(2) pieces \*\*\*

Date Received : 2003 August 09.

Test Period : 2003 August 09 – 2003 August 30.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002  
ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 12.

Conclusion : The submitted sample was found to comply with requirement of FCC  
Part 15 Subpart B.

Remark : All two models are the same in circuitry and components and  
construction, and therefore model MMP3642 was chosen to be the  
representative of the test sample.

*For and on behalf of*  
CMA Testing and Certification Laboratories

Authorized Signature : \_\_\_\_\_

Danny Chui  
EMC Engineer - EL. Division

Page 1 of 12

FCC ID : Q93-F004

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmactl.com](mailto:info@cmactl.com) Web Site: <http://www.cmactl.com>



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **Table of Contents**

1	General Information.....	3
1.1	General Description.....	3
1.2	Related Submittal Grants .....	3
1.3	Location of the test site.....	4
1.4	List of measuring equipment .....	5
1.5	List of support equipment .....	6
2	Description of the radiated emission test .....	7
2.1	Test Procedure .....	7
2.2	Test Result.....	7
2.3	Radiated Emission Measurement Data.....	8
2.3	Radiated Emission Measurement Data.....	9
3	Description of the Line-conducted Test .....	10
3.1	Test Procedure .....	10
3.2	Test Result.....	10
3.3	Graph and Table of Conducted Emission Measurement Data .....	10
4	Photograph .....	11
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission .....	11
4.2	Photographs of the External and Internal Configurations of the EUT .....	11
5	Supplementary document .....	11
6	Appendices .....	12



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a standalone Multi-function product built-in 64 MB memory and support external memory (SD or MMC memory card). The (EUT) has 2 different features.

1. Music Player (supports MP3 and WMA)
2. USB interface for PC uploading and downloading files (Through an USB connection cable)

The circuit design listed as follows :

1. U1 is digital signal processor which act as LCD controller, audio output and is controlled by a 24.576 MHz crystal.
2. U3 and associated circuit act as internal memory for storing music files.

A brief circuit description is saved with filename : OpDes.pdf

The model DFP50 is the same as model MMP3642 in hardware aspect. The difference in model numbers serve as marketing strategy.

#### **1.2 Related Submittal Grants**

This is a single application for certification of a computer peripheral product.



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **1.3 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **1.4 List of measuring equipment**

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
LISN	R&S	ESH3-Z5	100010	20-70405
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **1.5 List of support equipment**

1. Intel CPU PIII 800EB/256 cache/133MHz  
Model: L103A455-0041 SL4MB
2. Intel Mother Board  
Model: Intel Type: D815EEA
3. IBM Hard-disk  
Model: DTLA-30720, 20.5GB
4. Proview LCD Monitor  
Model: 568  
S/N: FYUJ240040133
5. IBM Mouse  
Model: 12J3618  
S/N: 23-005077
6. Acer Keyboard  
Model: 6511-VA
7. Hewlett Packard LaserJet 2100TN  
Model: C4172A  
S/N: SGGS038577
8. PenPower Handwriting System  
Model: PP403N  
S/N: PT9122239
9. Panasonic 64MB SD Memory Card  
Model: RP-SD064B  
S/N: BP3AA014349
10. USB Cable  
(Provided by applicant)



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

#### **2.2 Test Result**

All modes had been test. The measurement data were indicated in next page.

All other measurements were 20 dB below the 15.109 limits. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **2.3 Radiated Emission Measurement Data**

**Radiated emission  
pursuant to  
the requirement of FCC Part 15 subpart B**

Mode : Play Music

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
233.443	H	25.7	10.70	36.4	46.0	-9.6
245.728	H	27.7	10.70	38.4	46.0	-7.6
270.301	H	27.3	13.90	41.2	46.0	-4.8
293.336	H	22.4	13.90	36.3	46.0	-9.7
316.377	H	23.0	15.30	38.3	46.0	-7.7
330.199	H	19.5	15.30	34.8	46.0	-11.2
367.057	H	17.5	15.30	32.8	46.0	-13.2
385.487	H	20.4	15.30	35.7	46.0	-10.3
408.522	H	17.3	18.60	35.9	46.0	-10.1
431.562	H	17.8	18.60	36.4	46.0	-9.6





## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **2.3 Radiated Emission Measurement Data**

**Radiated emission  
pursuant to  
the requirement of FCC Part 15 subpart B**

Mode : PC connected

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
195.048	H	19.9	10.50	30.4	43.5	-13.1
219.619	H	21.2	10.70	31.9	46.0	-14.1
233.443	H	22.6	10.70	33.3	46.0	-12.7
245.728	H	22.8	10.70	33.5	46.0	-12.5
270.301	H	27.8	13.90	41.7	46.0	-4.3
293.336	H	19.9	13.90	33.8	46.0	-12.2
330.199	H	17.8	15.30	33.1	46.0	-12.9
367.057	H	18.9	15.30	34.2	46.0	-11.8
453.059	H	16.8	18.60	35.4	46.0	-10.6
661.993	H	13.4	22.20	35.6	46.0	-10.4



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

The PC connected mode had been tested. The EUT connecting with an USB cable and an earphone produced the maximum emission. The measurement data was indicated in next page.

The result showed that the EUT met the FCC requirement.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

For electronic filing, the document are saved with filename TestRpt2.pdf



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExtPho1 to ExtPho2 and IntPho1 to InPho2

### **5 Supplementary document**

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

<b>Document</b>	<b>Filename</b>
ID Label/Location	LabelSmp.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



## **TEST REPORT**

Report No. : AD015024-1

Date : 2003 September 09

### **6 Appendices**

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of the set-up of Conducted Emissions	2 pages
A3.	Photos of External Configurations	1 page
A4.	Photos of Internal Configurations	1 page
A5.	Conducted Emission Test Result	2 pages
A6.	ID Label/Location	1 page
A7.	Block Diagram	1 page
A8.	Schematics Diagram	1 page
A9.	User Manual	9 pages
A10.	Operation Description	1 page

\*\*\*\*\* End of Report \*\*\*\*\*