



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AF006001-001 Date : 2005 March 30
Application No. : LF201180(1)
Applicant : AVC Technology Limited
6/F., Enterprise Square Three,
39 Wang Chiu Road,
Kowloon Bay, Hong Kong
Sample Description : One(1) item of submitted sample stated to be:
Model Name : Digital Audio Player
Model No. : DFP8400 / MMP8560
Rating : DC 5V / 1 x 1.5V AAA size batteries
No. of sample : Two (2) set(s)***
Date Received : 2005 March 19
Test Period : 2005 March 19 – 2005 March 29
Test Requested : FCC Part 15 Certification
Test Method : FCC Rules and Regulations Part 15 – July 2004
ANSI C63.4 – 2003
Test Result : See attached sheet(s) from page 2 to 14.
Conclusion : The submitted sample was found to comply with the applicable FCC Part 15
Subpart B test.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Daisy Chui
EMC Engineer - EL. Division

Page 1 of 14

FCC ID : Q93-F029

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing,
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment.....	5
1.5	List of support equipment	6
2	Description of the radiated emission test	7
2.1	Test Procedure	7
2.2	Test Result	7
2.3	Radiated Emission Measurement Data	8
2.3	Radiated Emission Measurement Data	9
2.3	Radiated Emission Measurement Data	10
3	Description of the Line-conducted Test	11
3.1	Test Procedure	11
3.2	Test Result	11
3.3	Graph and Table of Conducted Emission Measurement Data	11
4	Photograph	12
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	12
4.2	Photographs of the External and Internal Configurations of the EUT	12
5	Supplementary document.....	13
6	Appendices	14



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

1 General Information

1.1 General Description

The equipment under test (EUT) is a standalone multi-function product and is powered by one 1 x 1.5 V AAA size battery with built-in 128 MB memory. Controlled by a 24.000 MHz crystal, the digital audio player has three different features:

1. Music Player (supports MP3, WMA and WAV file formats)
2. FM Tuner
3. USB interface for uploading and downloading files and as mass storage through a USB connection cable

A brief circuit description is saved with filename : OpDes.pdf

1.2 Related Submittal Grants

This is a single application for certification of a computer peripheral product.



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

1.5 List of support equipment

1. Intel CPU P4 2.8GHz / 512k cache / 533MHz bus
Model: 9426A657
2. Intel Mother Board
Model: Intel Type: D815GVHZ
3. Seagate Hard-disk
Model: ST340014A, 40GB
4. Proview LCD Monitor
Model: 568
S/N: FYUJ240040133
5. IBM Mouse
Model: 12J3618
S/N: 23-005077
6. Acer Keyboard
Model: 6511-VA
7. Hewlett Packard LaserJet 2100TN
Model: C4172A
S/N: SGGS038577
8. PenPower Handwriting System
Model: PP403N
S/N: PT9122239
9. USB cable
(Provided by Applicant)
10. Earphone



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

2.2 Test Result

All modes had been test. The measurement data based on measurements employing the CISPR quasip-peak detector were indicated in next page.

All other measurement were 20 dB below the 15.109 limits. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : MP3 playback

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
183.009	H	20.8	9.2	30.0	43.5	-13.5
187.510	H	22.8	9.2	32.0	43.5	-11.5
192.010	H	24.9	9.2	34.1	43.5	-9.4
193.510	H	24.3	9.2	33.5	43.5	-10.0
275.848	H	18.1	13.9	32.0	46.0	-14.0
288.015	H	21.0	13.9	34.9	46.0	-11.1
300.015	H	20.2	14.9	35.1	46.0	-10.9
324.017	H	18.9	14.9	33.8	46.0	-12.2
342.021	H	23.5	14.9	38.4	46.0	-7.6
348.017	H	23.1	14.9	38.0	46.0	-8.0



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : USB (PC connected)

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
60.012	H	22.8	5.7	28.5	40.0	-11.5
120.004	H	19.6	12.4	32.0	43.5	-11.5
180.015	H	18.6	9.2	27.8	43.5	-15.7
204.009	H	19.2	9.7	28.9	43.5	-14.6
240.016	H	24.0	9.7	33.7	46.0	-12.3
288.030	H	15.1	13.9	29.0	46.0	-17.0
300.057	H	14.7	14.9	29.6	46.0	-16.4
324.081	H	19.1	14.9	34.0	46.0	-12.0
336.085	H	20.3	14.9	35.2	46.0	-10.8
360.091	H	17.0	14.9	31.9	46.0	-14.1



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Mode : FM

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
175.456	H	24.6	10.4	35.0	43.5	-8.5
195.836	H	31.3	9.2	40.5	43.5	-3.0
216.249	H	28.4	9.7	38.1	46.0	-7.9
350.914	H	16.4	14.9	31.3	46.0	-14.7
391.673	H	18.1	14.9	33.0	46.0	-13.0
432.500	H	18.9	17.7	36.6	46.0	-9.4
526.369	H	11.2	19.2	30.4	46.0	-15.6
587.509	H	10.6	19.2	29.8	46.0	-16.2
648.745	H	8.9	21.2	30.1	46.0	-15.9



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

The PC connected mode had been tested. The EUT connecting with an USB cable and earphone produced the maximum emission. The measurement data was indicated in Appendix.

The result showed that the EUT met the FCC requirement.

3.3 Graph and Table of Conducted Emission Measurement Data

For electronic filing, the document are saved with filename TestRpt2.pdf



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup5.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



TEST REPORT

Report No. : AF006001-001

Date : 2005 March 30

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of the set-up of Conducted Emissions	2	pages
A3.	Photos of External Configurations	1	page
A4.	Photos of Internal Configurations	1	page
A5.	ID Label/Location	1	page
A6.	Conducted Emission Measurement Data	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	2	pages
A9.	User Manual	41	pages
A10.	Operation Description	1	page

***** End of Report *****