



Hermon Laboratories Ltd.
Harakevet Industrial Zone, Binyamina 30500,
Israel
Tel. +972-4-6288001
Fax. +972-4-6288277
E-mail: mail@hermonlabs.com

TEST REPORT

ACCORDING TO: FCC CFR 47 PART 15 Subpart C, section 15.247 (FHSS) and
RSS-210, Issue 8, Annex 8

FOR:
Cardo Systems Inc.
Bluetooth headset
Model: scala rider G9
FCC ID:Q95ER14

This report is in conformity with ISO/IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.

Table of contents

1	Applicant information	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary	4
6	EUT description	5
6.1	General information	5
6.2	Support and test equipment	5
6.3	Operating frequencies	5
6.4	Changes made in the EUT	5
6.5	Test configuration	6
6.6	Transmitter characteristics	7
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-210 Annex 8 requirements	8
7.1	20 dB bandwidth	8
7.2	Carrier frequency separation	14
7.3	Number of hopping frequencies	17
7.4	Average time of occupancy	20
7.5	Peak output power	23
7.6	Band edge emissions at RF antenna connector	30
7.7	Field strength of spurious emissions	37
7.8	Antenna requirements	68
8	APPENDIX A Test equipment and ancillaries used for tests	69
9	APPENDIX A Measurement uncertainties	70
10	APPENDIX C Test laboratory description	71
11	APPENDIX D Specification references	71
12	APPENDIX E Test equipment correction factors	72
13	APPENDIX F Abbreviations and acronyms	78

1 Applicant information

Client name: Cardo Systems Inc.
Address: 100 High Tower Blvd, Pittsburgh, PA 15205, USA
Telephone: 001 412-788-4533
Fax: 001 412-788-0270
E-mail: moato@cardosystems.com
Contact name: Mr. Avi Moato

2 Equipment under test attributes

Product name: Bluetooth headset
Product type: Transceiver
Model(s): scala rider G9
Serial number: HS#1
Hardware version: 1.0
Software release: 1.0
Receipt date 12/25/2011

3 Manufacturer information

Manufacturer name: Cardo Systems Inc.
Address: 100 High Tower Blvd, Pittsburgh, PA 15205, USA
Telephone: 001 412-788-4533
Fax: 001 412-788-0270
E-Mail: moato@cardosystems.com
Contact name: Mr. Avi Moato




4 Test details

Project ID: 22777
Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel
Test started: 12/25/2011
Test completed: 1/15/2011
Test specification(s): FCC Part 15, subpart C, §15.247 (FHSS);
RSS-210 Issue 8:2010, Annex 8

5 Tests summary

Test	Status
Transmitter characteristics	
FCC section 15.247(a)1, (g), (h) / RSS-210 section A8.1, Frequency hopping requirements	Pass
FCC section 15.247(a)1 / RSS-210 section A8.1(a), The 20 dB bandwidth	Pass
FCC section 15.247(a)1 / RSS-210 section A8.1(b), Frequency separation	Pass
FCC section 15.247(a)1 / RSS-210 section A8.1(d), Number of hopping frequencies	Pass
FCC section 15.247(a)1 / RSS-210 section A8.1(d), Average time of occupancy	Pass
FCC section 15.247(b) / RSS-210 section A8.4(2), Peak output power	Pass
FCC section 15.247(i) / RSS-Gen, section 5.5, RF exposure	Exhibit provided in documentation for Application
FCC section 15.247(d) / RSS-210 section A8.5, Emissions at band edges	Pass
FCC section 15.247(d) / RSS-210 section A8.5, Radiated spurious emissions	Pass
FCC section 15.203 / RSS-Gen, section 7.1.2, Antenna requirements	Pass
FCC section 15.207(a) / RSS-Gen, section 7.2.4, Conducted emission	Not required
RSS-Gen, Section 4.6.1, 99% emission occupied bandwidth	Measured

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.
The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

	Name and Title	Date	Signature
Tested by:	Mr. S. Samokha, test engineer	January 15, 2012	
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	February 7, 2012	
Approved by:	Mr. M. Nikishin, EMC and Radio group manager	February 28, 2012	



6 EUT description

6.1 General information

This product is a Bluetooth headset for motorbikes technology compliant with Bluetooth™ Ver 2.1 class 1 and FM radio receiver.
It also has additional transceiver operating at 2401 MHz.

6.2 Support and test equipment

Description	Manufacturer	Model number	Serial number
BT headset	Cardo Systems, Inc.	scala rider G9	HS#2

6.3 Operating frequencies

Source	Frequency, MHz		
LO	26		
Blue Tooth	2402	2440	2480

6.4 Changes made in the EUT

No changes were implemented in the EUT.

6.5 Test configuration





6.6 Transmitter characteristics

Type of equipment						
X	Stand-alone (Equipment with or without its own control provisions)					
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)					
	Plug-in card (Equipment intended for a variety of host systems)					
Intended use		Condition of use				
	fixed	Always at a distance more than 2 m from all people				
	mobile	Always at a distance more than 20 cm from all people				
X	portable	May operate at a distance closer than 20 cm to human body				
Assigned frequency range		2400 - 2483.5 MHz				
Operating frequency range		2402 - 2480 MHz				
RF channel spacing		1 MHz				
Maximum rated output power		Peak output power		14.38 dBm		
Is transmitter output power variable?		X	No			
			Yes	continuous variable		
			Yes	stepped variable with stepsize		dB
			Yes	minimum RF power		dBm
			Yes	maximum RF power		dBm
Antenna connection						
unique coupling		standard connector		X	integral	
				X	with temporary RF connector without temporary RF connector	
Antenna/s technical characteristics						
Type	Manufacturer		Model number		Gain	
Printed	Cardo Systems, Inc.		NA		2 dBi	
Transmitter aggregate data rate/s			1 Mbps			
Modulation			GFSK			
Modulating test signal (baseband)			PRBS			
Transmitter power source						
X	Battery	Nominal rated voltage		3.7 VDC	Battery type	Lead acid
	DC	Nominal rated voltage		VDC		
	AC mains	Nominal rated voltage		VAC	Frequency	



Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
Remarks:		Verdict: PASS	
		Relative Humidity: 43 %	
		Power Supply: Battery	

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-210 Annex 8 requirements

7.1 20 dB bandwidth

7.1.1 General

This test was performed to measure 20 dB bandwidth of the transmitter hopping channel. Specification test limits are given in Table 7.1.1.

Table 7.1.1 The 20 dB bandwidth limits

Assigned frequency, MHz	Maximum bandwidth, kHz	Modulation envelope reference points*, dBc
902.0 – 928.0	500	20
2400.0 – 2483.5	NA	
5725.0 – 5850.0	1000	

* - Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

7.1.2 Test procedure


7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.

7.1.2.2 The EUT was set to transmit modulated carrier at maximum data rate.

7.1.2.3 The transmitter bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.2 and the associated plots.

7.1.2.4 The test was repeated for each data rate and each modulation format.

Figure 7.1.1 The 20 dB bandwidth test setup





Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
		Relative Humidity: 43 %	
		Power Supply: Battery	
Remarks:			

Table 7.1.2 The 20 dB bandwidth test results

ASSIGNED FREQUENCY BAND: 2400.0 – 2483.5 MHz
 DETECTOR USED: Peak
 SWEEP TIME: Auto
 VIDEO BANDWIDTH: ≥ RBW
 MODULATION ENVELOPE REFERENCE POINTS: 20.0 dBc
 MODULATING SIGNAL: PRBS
 FREQUENCY HOPPING: Disabled

Carrier frequency, MHz	Type of modulation	Data rate, Mbps	Symbol rate, Msymbols/s	20 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
2402.0	GFSK	1	1	930.0	NA	NA	Pass
2441.0				910.0			
2480.0				930.0			

Table 7.1.3 The 99% bandwidth test results

ASSIGNED FREQUENCY BAND: 2400 – 2483.5 MHz
 DETECTOR USED: Peak
 SWEEP TIME: Auto
 RESOLUTION BANDWIDTH: ≥ 1% of the 99% bandwidth
 VIDEO BANDWIDTH: ≥RBW
 MODULATING SIGNAL: PRBS
 FREQUENCY HOPPING: Disabled

Carrier frequency, MHz	Type of modulation	Data rate, Mbps	Symbol rate, Msymbols/s	99% bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
2402.0	GFSK	1	1	1040	NA	NA	NA
2441.0				1070			
2480.0				1040			

Reference numbers of test equipment used

HL 2909	HL 3810						
---------	---------	--	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification: Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 1/3/2012			
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 7.1.1 The 20 dB bandwidth test result at low frequency



Plot 7.1.2 The 20 dB bandwidth test result at mid frequency






HERMON LABORATORIES

Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
		Relative Humidity: 43 %	
Remarks:		Power Supply: Battery	
Verdict: PASS			

Plot 7.1.3 The 20 dB bandwidth test result at high frequency







HERMON LABORATORIES

Test specification: Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 1/3/2012			
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 7.1.4 The 99% bandwidth test result at low frequency



Plot 7.1.5 The 99% bandwidth test result at mid frequency






HERMON LABORATORIES

Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(a), 20 dB bandwidth	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
		Relative Humidity: 43 %	
Remarks:		Power Supply: Battery	
Verdict: PASS			

Plot 7.1.6 The 99% bandwidth test result at high frequency





Test specification:	Section 15.247(a)1/ RSS-210, Section A8.1(b), Frequency separation		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	1/3/2012		
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

7.2 Carrier frequency separation

7.2.1 General

This test was performed to measure frequency separation between the peaks of adjacent channels. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Carrier frequency separation limits

Assigned frequency range, MHz	Carrier frequency separation
902.0 – 928.0	25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater
2400.0 – 2483.5	
5725.0 – 5850.0	

7.2.2 Test procedure

- 7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized with frequency hopping function enabled and its proper operation was checked.
- 7.2.2.2 The spectrum analyzer span was set to capture the carrier frequency and both of adjacent channels, the lower and the higher. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.2.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.
- 7.2.2.4 The frequency separation between the peaks of adjacent channels was measured as provided in Table 7.2.2 and associated plots.

Figure 7.2.1 Carrier frequency separation test setup





Test specification: Section 15.247(a)1/ RSS-210, Section A8.1(b), Frequency separation	
Test procedure:	Public notice DA 00-705
Test mode:	Compliance
Date(s):	1/3/2012
Temperature: 22.3 °C	Air Pressure: 1024 hPa
Relative Humidity: 43 %	Power Supply: Battery
Remarks:	

Table 7.2.2 Carrier frequency separation test results

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: ≥ 1% of the span
 VIDEO BANDWIDTH: ≥ RBW
 FREQUENCY HOPPING: Enabled
 20 dB BANDWIDTH: 930 kHz

Carrier frequency separation, kHz	Limit, kHz	Margin*	Verdict
1000	930	-70	Pass

* - Margin = Carrier frequency separation – specification limit.

Reference numbers of test equipment used

HL 2909	HL 3810					
---------	---------	--	--	--	--	--


Full description is given in Appendix A.



HERMON LABORATORIES

Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(b), Frequency separation	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
		Relative Humidity: 43 %	
		Power Supply: Battery	
Remarks:			

Plot 7.2.1 Carrier frequency separation





Test specification:	Section 15.247(a)1/ RSS-210, Section A8.1(d), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	1/3/2012		
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

7.3 Number of hopping frequencies

7.3.1 General

This test was performed to calculate the number of hopping frequencies used by the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Minimum number of hopping frequencies

Assigned frequency range, MHz	Number of hopping frequencies
902.0 – 928.0	50 (if the 20 dB bandwidth is less than 250 kHz) 25 (if the 20 dB bandwidth is 250 kHz or greater)
2400.0 – 2483.5	15
5725.0 – 5850.0	75

7.3.2 Test procedure

7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized with frequency hopping function enabled and its proper operation was checked.

7.3.2.2 Initially the spectrum analyzer span was set equal to frequency band of operation and the resolution bandwidth was set wider than 1 % of the frequency span. If the separate hopping channels were not clearly resolved the frequency band of operation was broken to sections and the resolution bandwidth was set wider than 1 % of the frequency span of each section.

7.3.2.3 The spectrum analyzer was set in max hold mode and allowed trace to stabilize.

7.3.2.4 The number of frequency hopping channels was calculated as provided in Table 7.3.2 and associated plots.

Figure 7.3.1 Hopping frequencies test setup





Test specification:	Section 15.247(a)1/ RSS-210, Section A8.1(d), Number of hopping frequencies		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict: PASS	
Date(s):	1/3/2012		
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Table 7.3.2 Hopping frequencies test results

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: ≥ 1% of the span
 VIDEO BANDWIDTH: ≥ RBW
 FREQUENCY HOPPING: Enabled

Number of hopping frequencies	Minimum number of hopping frequencies	Margin*	Verdict
79	75	64	Pass

* - Margin = Number of hopping frequencies – Minimum number of hopping frequencies.

Reference numbers of test equipment used

HL 2909	HL 3810					
---------	---------	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:		Section 15.247(a)1/ RSS-210, Section A8.1(d), Number of hopping frequencies	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
Relative Humidity: 43 %		Power Supply: Battery	
Remarks:			
		Verdict: PASS	

Plot 7.3.1 Number of hopping frequencies, channels from 1 to 40



Plot 7.3.2 Number of hopping frequencies, channels from 40 to 79





Test specification: Section 15.247(a)1/RSS-210, Section A8.1(d), Average time of occupancy	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 1/3/2012	
Temperature: 22.3 °C	Air Pressure: 1024 hPa
Relative Humidity: 43 %	
Power Supply: Battery	
Remarks:	

7.4 Average time of occupancy

7.4.1 General

This test was performed to calculate the average time of occupancy (dwell time) on any frequency channel of the EUT. Specification test limits are given in Table 7.4.1.

Table 7.4.1 Average time of occupancy limits

Assigned frequency range, MHz	Maximum average time of occupancy, s	Investigated period, s	Number of hopping frequencies
902.0 – 928.0	0.4	20.0	≥ 50
902.0 – 928.0	0.4	10.0	< 50
2400.0 – 2483.5	0.4	0.4 × N	N (≥ 15)
5725.0 – 5850.0	0.4	30.0	≥ 75

7.4.2 Test procedure

7.4.2.1 The EUT was set up as shown in Figure 7.4.1, energized with frequency hopping function enabled and its proper operation was checked.


7.4.2.2 The spectrum analyzer span was set to zero centered on a hopping channel.

7.4.2.3 The single transmission duration and period were measured with oscilloscope.

7.4.2.4 The average time of occupancy was calculated as the single transmission time multiplied by the investigated period and divided by the single transmission period.

7.4.2.5 The test was repeated at each data rate and modulation type as provided in Table 7.4.2 and the associated plots.

Figure 7.4.1 Average time of occupancy test setup





Test specification: Section 15.247(a)1/RSS-210, Section A8.1(d), Average time of occupancy	
Test procedure:	Public notice DA 00-705
Test mode:	Compliance
Date(s):	1/3/2012
Temperature: 22.3 °C	Air Pressure: 1024 hPa
Relative Humidity: 43 %	Power Supply: Battery
Remarks:	
Verdict: PASS	

Table 7.4.2 Average time of occupancy test results

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1 MHz
 VIDEO BANDWIDTH: 3 MHz
 NUMBER OF HOPPING FREQUENCIES: 79
 INVESTIGATED PERIOD: 31.6 s
 FREQUENCY HOPPING: Enabled

Carrier frequency, MHz	Single transmission duration, ms	Single transmission period, s	Average time of occupancy*, s	Bit rate, Mbps	Symbol rate, Msymbol/s	Limit, s	Margin, s**	Verdict
Frequency hopping	0.408	0.099	0.13	1.0	1.0	0.4	-0.27	Pass

* - Average time of occupancy = (Single transmission duration × Investigated period) / Single transmission period

** - Margin = Average time of occupancy – specification limit.

Reference numbers of test equipment used

HL 2909	HL 3810						
---------	---------	--	--	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:		Section 15.247(a)1/RSS-210, Section A8.1(d), Average time of occupancy	
Test procedure:		Public notice DA 00-705	
Test mode:		Compliance	
Date(s):		1/3/2012	
Temperature: 22.3 °C		Air Pressure: 1024 hPa	
		Relative Humidity: 43 %	
		Power Supply: Battery	
Remarks:			
		Verdict: PASS	

Plot 7.4.1 Single transmission duration



Plot 7.4.2 Single transmission period





Test specification: Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power	
Test procedure:	Public notice DA 00-705
Test mode:	Compliance
Date(s):	12/25/2011
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 41 %	Power Supply: Battery
Remarks:	
Verdict: PASS	

7.5 Peak output power

7.5.1 General

This test was performed to measure the maximum peak output power at the transmitter RF antenna connector. Specification test limits are given in Table 7.5.1 **Error! Reference source not found.**

Table 7.5.1 Peak output power limits

Assigned frequency range, MHz	Peak output power*		Equivalent field strength limit @ 3m, dB(µV/m)*	Maximum antenna gain, dBi
	W	dBm		
902.0 – 928.0	0.25 (<50 hopping channels)	24.0(<50 hopping channels)	125.2 (<50 hopping channels)	6.0*
	1.0 (≥50 hopping channels)	30.0 (≥50 hopping channels)	131.2 (≥50 hopping channels)	
2400.0 – 2483.5	0.125 (<75 hopping channels)	21.0(<75 hopping channels)	122.2 (<75 hopping channels)	
	1.0 (≥75 hopping channels)	30.0 (≥75 hopping channels)	131.2 (≥75 hopping channels)	
5725.0 – 5850.0	1.0	30.0	131.2	

*- If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

- by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;
- without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band;
- by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

7.5.2 Test procedure

7.5.2.1 The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.

7.5.2.2 The EUT was adjusted to produce maximum available to end user RF output power.

7.5.2.3 The frequency span of spectrum analyzer was set approximately 5 times wider than 20 dB bandwidth of the EUT and the resolution bandwidth was set wider than 20 dB bandwidth of the EUT. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.

7.5.2.4 The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.5.2 and the associated plots.

7.5.2.5 The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G),$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:


$$\text{Peak output power in dBm} = \text{Field strength in dB}(\mu\text{V/m}) - \text{Transmitter antenna gain in dBi} - 95.2 \text{ dB}$$

7.5.2.6 The worst test results (the lowest margins) were recorded in Table 7.5.2.



Test specification:	Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/25/2011		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 41 %	Power Supply: Battery
Remarks:			

Figure 7.5.1 Setup for carrier field strength measurements





Test specification: Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power	
Test procedure:	Public notice DA 00-705
Test mode:	Compliance
Date(s):	12/25/2011
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 41 %	Power Supply: Battery
Remarks:	
Verdict: PASS	

Table 7.5.2 Peak output power test results

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
TEST DISTANCE: 3 m
TEST SITE: Semi anechoic chamber
EUT HEIGHT: 0.8 m
DETECTOR USED: Peak
TEST ANTENNA TYPE: Double ridged guide (above 1000 MHz)
MODULATION: GFSK
MODULATING SIGNAL: PRBS
BIT RATE: 1 Mbps
TRANSMITTER OUTPUT POWER SETTINGS: Maximum
DETECTOR USED: Peak
EUT 20 dB BANDWIDTH: 0.93 MHz
RESOLUTION BANDWIDTH: 1 MHz
VIDEO BANDWIDTH: 3 MHz
FREQUENCY HOPPING: Disabled

Frequency, MHz	Field strength, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
2401.913	111.58	Vertical	1.4	280	2.0	14.38	30.0	-15.62	Pass
2441.059	109.79	Vertical	1.3	162	2.0	12.59	30.0	-17.41	Pass
2479.950	110.02	Horizontal	2.0	72	2.0	12.82	30.0	-17.18	Pass

*- EUT front panel refer to 0 degrees position of turntable.

** - Peak output power was calculated from the field strength of carrier as follows: $P = (E \times d)^2 / (30 \times G)$, where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: *Peak output power in dBm = Field strength in dB(μV/m) - Transmitter antenna gain in dBi - 95.2 dB*

*** - Margin = Peak output power – specification limit.

Reference numbers of test equipment used

HL 0521	HL 1984	HL 2871	HL 3617				
---------	---------	---------	---------	--	--	--	--

Full description is given in Appendix A.




HERMON LABORATORIES

Test specification: Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/25/2011			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 41 %	Power Supply: Battery
Remarks:			


Plot 7.5.1 Peak output power at low frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.5.2 Peak output power at low frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/25/2011			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 41 %	Power Supply: Battery
Remarks:			


Plot 7.5.3 Peak output power at mid frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.5.4 Peak output power at mid frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification: Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/25/2011			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 41 %	Power Supply: Battery
Remarks:			


Plot 7.5.5 Peak output power at high frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.5.6 Peak output power at high frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Horizontal





HERMON LABORATORIES

Test specification:	Section 15.247(b)/RSS-210, Section A8.4(2), Peak output power		
Test procedure:	Public notice DA 00-705		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/25/2011		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 41 %	Power Supply: Battery
Remarks:			

Intentionally blank



Test specification: Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 43 %	
Power Supply: Battery	
Remarks:	

7.6 Band edge emissions at RF antenna connector

7.6.1 General

This test was performed to measure band edge emissions at RF antenna connector. Specification test limits are given in Table 7.6.1.

Table 7.6.1 Band edge emission limits

Assigned frequency, MHz	Attenuation below carrier*, dBc	Field strength at 3 m within restricted bands, dB(µV/m)	
		Peak	Average
902.0 – 928.0	20.0	74.0	54.0
2400.0 – 2483.5			
5725.0 – 5850.0			

* - Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

7.6.2 Test procedure

- 7.6.2.1 The EUT was set up as shown in Figure 7.6.1, energized normally modulated at the maximum data rate with its hopping function disabled and its proper operation was checked.
- 7.6.2.2 The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- 7.6.2.3 The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span: RBW=1 MHz, VBW=3 MHz in peak mode, RBW=1 MHz, VBW≥1/T_{on}.
- 7.6.2.4 The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- 7.6.2.5 The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.6.2 and the associated plots and referenced to the highest emission level measured within the authorized band.
- 7.6.2.6 The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.
- 7.6.2.7 The above procedure was repeated with the frequency hopping function enabled.

Figure 7.6.1 Band edge emission test setup





Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges			
Test procedure:		Public notice DA 00-705			
Test mode:		Compliance		Verdict: PASS	
Date(s):		1/2/2012			
Temperature: 22.1 °C		Air Pressure: 1019 hPa		Relative Humidity: 43 %	
Remarks:		Power Supply: Battery			

Table 7.6.2 Band edge emission test results

ASSIGNED FREQUENCY RANGE: 2400.0 – 2483.5 MHz
 DETECTOR USED: Peak
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 RESOLUTION BANDWIDTH: ≥ 1% of the span
 VIDEO BANDWIDTH: ≥ RBW

Frequency, MHz	Band edge emission, dBm	Emission at carrier, dBm	Attenuation below carrier, dBc	Limit, dBc	Margin, dB*	Verdict
Frequency hopping disabled						
2400.0	73.41	111.58	38.17	20.0	18.17	Pass
Frequency hopping enabled						
2400.0	71.36	111.58	40.22	20.0	20.22	Pass

*- Margin = Attenuation below carrier – specification limit.

RESTRICTED BANDS: 2310.0 – 2390 MHz
2483.5 – 2500 MHz

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength(VBW=3 MHz)			Average field strength(VBW=3 kHz)				Verdict
	Polarization	Height, m		Measured, dB(μV/m)	Limit, dB(μV/m)	Margin, dB**	Measured, dB(μV/m)	Calculated, dB(μV/m)	Limit, dB(μV/m)	Margin, dB***	
Frequency hopping disabled											
2330.030	Vert	1.4	280	58.33	74.0	-15.67	51.81	42.17	54.0	-11.83	Pass
2483.500	Vert	2.0	72	61.86	74.0	-12.14	50.16	40.52	54.0	-13.48	
Frequency hopping enabled											
2349.150	Vert	1.3	162	58.64	74.0	-15.36	56.97	47.33	54.0	-6.67	Pass
2483.500	Vert	2.0	72	61.74	74.0	-12.26	50.66	41.02	54.0	-12.98	

For average factor calculation (-9.64 dB) refer to Table 7.7.4.
 $VBW \geq 1/T_{on} = 1/0.41 \text{ ms} \geq 2440 \text{ Hz}$, 3 kHz was used.

Reference numbers of test equipment used

HL 0521	HL 1984	HL 2871	HL 3617				
---------	---------	---------	---------	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges	
Test procedure:		Public notice DA 00-705	
Test mode:	Compliance	Verdict:	PASS
Date(s):	1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 7.6.1 The highest emission level within the assigned band at low carrier frequency



Plot 7.6.2 The highest emission level within the assigned band at high carrier frequency







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Remarks:	

Plot 7.6.3 The highest band edge emission at low carrier frequency with hopping function disabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:



Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Outside restricted band 2390 – 2400 MHz



Plot 7.6.4 The highest band edge emission at low carrier frequency with hopping function disabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Within restricted band 2310 – 2390 MHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 43 %	
Power Supply: Battery	
Remarks:	

Plot 7.6.5 The highest band edge emission at high carrier frequency with hopping function disabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Within restricted band 2483.5 – 2500 MHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges			
Test procedure: Public notice DA 00-705			
Test mode: Compliance	Verdict: PASS		
Date(s): 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 7.6.6 The highest band edge emission at low carrier frequency with hopping function enabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:



Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Outside restricted band 2390 – 2400 MHz



Plot 7.6.7 The highest band edge emission at low carrier frequency with hopping function enabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Within restricted band 2310 – 2390 MHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Emissions at band edges	
Test procedure: Public notice DA 00-705	
Test mode: Compliance	Verdict: PASS
Date(s): 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 43 %	
Power Supply: Battery	
Remarks:	

Plot 7.6.8 The highest band edge emission at high carrier frequency with hopping function enabled

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz
NOTE:

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=3 kHz
Within restricted band 2483.5 – 2500 MHz





Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Compliance	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C		Air Pressure: 1019 hPa	
Remarks:		Verdict: PASS	
		Relative Humidity: 44 %	
		Power Supply: Battery	

7.7 Field strength of spurious emissions

7.7.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.7.1.

Table 7.7.1 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m within restricted bands, dB(μV/m) ^{***}			Attenuation of field strength of spurious versus carrier outside restricted bands, dBc ^{***}
	Peak	Quasi Peak	Average	
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5 ^{**}	20.0
0.090 – 0.110	NA	108.5 – 106.8 ^{**}	NA	
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8 ^{**}	
0.490 – 1.705	NA	73.8 – 63.0 ^{**}	NA	
1.705 – 30.0 [*]		69.5		
30 – 88		40.0		
88 – 216		43.5		
216 – 960		46.0		
960 - 1000		54.0		
1000 – 10 th harmonic	74.0	NA	54.0	

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 40 \log (S_1/S_2),$$

where S₁ and S₂ – standard defined and test distance respectively in meters.

** - The limit decreases linearly with the logarithm of frequency.

*** - The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.

7.7.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

7.7.2.1 The EUT was set up as shown in Figure 7.7.1, energized and the performance check was conducted.

7.7.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.

7.7.2.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.

7.7.3 Test procedure for spurious emission field strength measurements above 30 MHz

7.7.3.1 The EUT was set up as shown in Figure 7.7.2, energized and the performance check was conducted.

7.7.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.

7.7.3.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.



Test specification:	Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/29/2011 - 1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Figure 7.7.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.7.2 Setup for spurious emission field strength measurements above 30 MHz





Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.7.2 Field strength of emissions outside restricted bands

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 INVESTIGATED FREQUENCY RANGE: 0.009 - 25000 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DUTY CYCLE: 32.9 %
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 100 kHz
 VIDEO BANDWIDTH: 300 kHz
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)
 Double ridged guide (above 1000 MHz)
 Disabled

FREQUENCY HOPPING:

Frequency, MHz	Field strength of spurious, dB(µV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(µV/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict
Low carrier frequency									
200.017	42.69	Vert	1.1	0	110.8	68.11	20.0	48.11	Pass
7205.897	47.97	Hor	1.1	250	110.8	62.83	20.0	42.83	Pass
Mid carrier frequency									
200.017	31.97	Vert	1.1	0	109.0	77.03	20.0	57.03	Pass
1627.305	49.64	Vert	1.2	230	109.0	59.36	20.0	39.36	Pass
High carrier frequency									
200.017	31.97	Vert	1.1	0	106.7	74.73	20.0	54.73	Pass
1653.320	48.32	Vert	1.2	230	106.7	58.38	20.0	38.38	Pass

*- EUT front panel refers to 0 degrees position of turntable.

**- Margin = Attenuation below carrier – specification limit.



Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode:		Compliance		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012			
Temperature: 22.1 °C		Air Pressure: 1019 hPa		Relative Humidity: 44 %	
Remarks:		Power Supply: Battery			

Table 7.7.3 Field strength of spurious emissions above 1 GHz within restricted bands

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 INVESTIGATED FREQUENCY RANGE: 1000 - 25000 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DUTY CYCLE: 32.9 %
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1000 kHz
 TEST ANTENNA TYPE: Double ridged guide
 FREQUENCY HOPPING: Disabled

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength(VBW=3 MHz)			Average field strength(VBW=10 Hz)				Verdict
	Polarization	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**	Measured, dB(µV/m)	Calculated, dB(µV/m)	Limit, dB(µV/m)	Margin, dB***	
Low carrier frequency											
1601.288	Vert	1.1	180	54.88	74.0	-19.12	47.96	38.32	54.0	-15.68	Pass
4803.945	Hor	1.0	235	54.43	74.0	-19.57	51.19	41.55	54.0	-12.45	
12009.912	Hor	1.4	20	53.48	74.0	-20.52	46.54	36.90	54.0	-17.10	
Mid carrier frequency											
7322.922	Hor	1.1	250	54.14	74.0	-19.86	50.47	40.83	54.0	-13.17	Pass
12204.825	Vert	1.3	85	52.89	74.0	-21.11	43.49	33.85	54.0	-20.15	
High carrier frequency											
7439.900	Vert	1.2	250	52.36	74.0	-21.64	47.8	38.16	54.0	-15.84	Pass

*- EUT front panel refers to 0 degrees position of turntable.
 **- Margin = Measured field strength - specification limit.
 ***- Margin = Calculated field strength - specification limit,
 where Calculated field strength = Measured field strength + average factor.

Table 7.7.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms*	Duration, ms	Period, ms		
0.41	1.245	NA	NA	NA	-9.64

*- used during testing, the real transmission period is shown in section 7.4 Average time of occupancy, Plot 7.4.2.
 Average factor was calculated as follows

for pulse train shorter than 100 ms:

$$Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{Train\ duration} \times Number\ of\ bursts\ within\ pulse\ train \right)$$

for pulse train longer than 100 ms:

$$Average\ factor = 20 \times \log_{10} \left(\frac{Pulse\ duration}{Pulse\ period} \times \frac{Burst\ duration}{100\ ms} \times Number\ of\ bursts\ within\ 100\ ms \right)$$



Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Compliance	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C		Air Pressure: 1019 hPa	
Relative Humidity: 44 %		Power Supply: Battery	
Remarks:			

Table 7.7.5 Field strength of spurious emissions below 1 GHz within restricted bands

ASSIGNED FREQUENCY: 2400.0 – 2483.5 MHz
 INVESTIGATED FREQUENCY RANGE: 0.009 – 1000 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DUTY CYCLE: 32.9 %
 TRANSMITTER OUTPUT POWER SETTINGS: Maximum
 RESOLUTION BANDWIDTH: 1.0 kHz (9 kHz – 150 kHz)
 9.0 kHz (150 kHz – 30 MHz)
 120 kHz (30 MHz – 1000 MHz)
 VIDEO BANDWIDTH: > Resolution bandwidth
 TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
 Biconilog (30 MHz – 1000 MHz)
 Disabled

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
Low carrier frequency								
No emissions were found								Pass
Mid carrier frequency								
No emissions were found								Pass
High carrier frequency								
No emissions were found								Pass

*- Margin = Measured emission - specification limit.
 **- EUT front panel refer to 0 degrees position of turntable.

Table 7.7.6 Restricted bands

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	

Reference numbers of test equipment used

HL 0446	HL 0521	HL 0604	HL 0768	HL 2780	HL 2871	HL 3535	HL 3617
HL 3533	HL 3901	HL 4114	HL 4150				

Full description is given in Appendix A.





HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.1 Radiated emission measurements at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical



Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal



Plot 7.7.2 Radiated emission measurements at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	
Power Supply: Battery	
Remarks:	

Plot 7.7.3 Radiated emission measurements at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION: Vertical

Semi anechoic chamber
3 m
ANTENNA POLARIZATION: Horizontal






HERMON LABORATORIES

Test specification:	Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict: PASS	
Date(s):	12/29/2011 - 1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.4 Radiated emission measurements from 9 to 150 kHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.5 Radiated emission measurements from 9 to 150 kHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical






HERMON LABORATORIES

Test specification:	Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/29/2011 - 1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.6 Radiated emission measurements from 9 to 150 kHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.7 Radiated emission measurements from 0.15 to 30 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical






HERMON LABORATORIES

Test specification:	Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/29/2011 - 1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.8 Radiated emission measurements from 0.15 to 30 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical



Plot 7.7.9 Radiated emission measurements from 0.15 to 30 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical






HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.10 Radiated emission measurements from 30 to 1000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.7.11 Radiated emission measurements from 30 to 1000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal





HERMON LABORATORIES


Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict:	
Compliance		PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.12 Radiated emission measurements from 30 to 1000 MHz at the high carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



ACTV DET: PEAK
MEAS DET: PEAK OP AVG
MKR 942.8 MHz
33.91 dBµV/m







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.13 Radiated emission measurements from 1000 to 2400 MHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:



Semi anechoic chamber
3 m
Vertical and Horizontal



Plot 7.7.14 Radiated emission measurements at 1601 MHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:

Semi anechoic chamber
3 m
Vertical and Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.15 Radiated emission measurements from 1000 to 2400 MHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:


Semi anechoic chamber
3 m
Vertical and Horizontal



Plot 7.7.16 Radiated emission measurements at 1627 MHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:

Semi anechoic chamber
3 m
Vertical and Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	
Power Supply: Battery	
Remarks:	

Plot 7.7.17 Radiated emission measurements from 1000 to 2400 MHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:


Semi anechoic chamber
3 m
Vertical and Horizontal



Plot 7.7.18 Radiated emission measurements at 1653 MHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:

Semi anechoic chamber
3 m
Vertical and Horizontal







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
	Relative Humidity: 44 %
	Power Supply: Battery
Remarks:	

Plot 7.7.19 Radiated emission measurements from 2483.5 to 4000 MHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=10 kHz



Plot 7.7.20 Radiated emission measurements from 2483.5 to 4000 MHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=10 kHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.21 Radiated emission measurements from 2500 to 4000 MHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=10 kHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	Power Supply: Battery
Remarks:	

Plot 7.7.22 Radiated emission measurements from 4.0 to 8.0 GHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 kHz



Plot 7.7.23 Radiated emission measurements from 4.0 to 8.0 GHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 kHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	Power Supply: Battery
Remarks:	

Plot 7.7.24 Radiated emission measurements from 4.0 to 8.0 GHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



Semi anechoic chamber
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 kHz



Plot 7.7.25 Radiated emission measurements from 8.0 to 18.0GHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 kHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	Power Supply: Battery
Remarks:	

Plot 7.7.26 Radiated emission measurements from 8.0 to 18.0GHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 KHz



Plot 7.7.27 Radiated emission measurements from 8.0 to 18.0 GHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 KHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.28 Radiated emission measurements from 18.0 to 25.0 GHz at the low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

OATS
3 m
Vertical 1.2 m 250dgr
RBW=1MHz; VBW=100 KHz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.29 Radiated emission measurements from 18.0 to 25.0 GHz at the mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=100 KHz



Plot 7.7.30 Radiated emission measurements from 18.0 to 25.0 GHz at the high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=100 KHz






HERMON LABORATORIES


Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions			
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4			
Test mode: Compliance	Verdict: PASS		
Date(s): 12/29/2011 - 1/2/2012			
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.31 Radiated emission measurements at the second harmonic of low carrier frequency


TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz




OATS
3 m
Vertical 1.0 235dgr
RBW=1MHz; VBW=30 Hz



ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



Horizontal
RBW=1MHz; VBW=30 Hz






HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict:	
Compliance		PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.32 Radiated emission measurements at the second harmonic of mid carrier frequency

TEST SITE: OATS
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.33 Radiated emission measurements at the second harmonic of high carrier frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical 1.0m 90dgr



Plot 7.7.34 Radiated emission measurements at the third harmonic of low carrier frequency

TEST SITE: OATS
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES


Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	Power Supply: Battery
Remarks:	

Plot 7.7.35 Radiated emission measurements at the third harmonic of mid carrier frequency


TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz




ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



OATS
3 m
Vertical
RBW=1MHz; VBW=30 Hz



Horizontal
RBW=100 kHz; VBW=300 kHz






HERMON LABORATORIES


Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.36 Radiated emission measurements at the third harmonic of high carrier frequency


TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz




ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz



OATS
3 m
Vertical
RBW=1MHz; VBW=30 Hz



Horizontal
RBW=1MHz; VBW=30 Hz






HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict: PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.7.37 Radiated emission measurements at the fourth harmonic of low carrier frequency

TEST SITE: OATS
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.7.38 Radiated emission measurements at the fourth harmonic of mid carrier frequency

TEST SITE: OATS
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES

Test specification:		Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure:		Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode:		Verdict:	
Compliance		PASS	
Date(s):		12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.39 Radiated emission measurements at the fourth harmonic of high carrier frequency



TEST SITE: OATS
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.7.40 Radiated emission measurements at the fifth harmonic of low carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz

OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 Hz







HERMON LABORATORIES

Test specification: Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions	
Test procedure: Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4	
Test mode: Compliance	Verdict: PASS
Date(s): 12/29/2011 - 1/2/2012	
Temperature: 22.1 °C	Air Pressure: 1019 hPa
Relative Humidity: 44 %	Power Supply: Battery
Remarks:	

Plot 7.7.41 Radiated emission measurements at the fifth harmonic of mid carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:
RBW=1MHz; VBW=3 MHz


OATS
3 m
Vertical and Horizontal
RBW=1MHz; VBW=30 Hz



Plot 7.7.42 Radiated emission measurements at the fifth harmonic of high carrier frequency

TEST SITE:
TEST DISTANCE:
ANTENNA POLARIZATION:

OATS
3 m
Vertical and Horizontal







HERMON LABORATORIES

Test specification:	Section 15.247(d) / RSS-210, Section A8.5, Radiated spurious emissions		
Test procedure:	Public notice DA 00-705/ 47 CFR, Section 15.247(c) / ANSI C63.4, Section 13.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	12/29/2011 - 1/2/2012		
Temperature: 22.1 °C	Air Pressure: 1019 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.7.43 Transmission pulse duration



Plot 7.7.44 Transmission pulse period during testing





Test specification:	Section 15.203 / RSS-Gen, section 7.1.2, Antenna requirements		
Test procedure:	Visual inspection		
Test mode:	Compliance	Verdict:	PASS
Date(s):	1/3/2012		
Temperature: 22.3 °C	Air Pressure: 1024 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

7.8 Antenna requirements

The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters. The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.8.1.

Table 7.8.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	

Photograph 7.8.1 Antenna assembly



**8 APPENDIX A Test equipment and ancillaries used for tests**

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal./ Check	Due Cal./ Check
0446	Antenna, Loop, Active, 10 kHz - 30 MHz	EMCO	6502	2857	03-Jul-11	03-Jul-12
0521	EMI Receiver (Spectrum Analyzer) with RF filter section 9 kHz-6.5 GHz	Hewlett Packard	8546A	3617A 00319, 3448A002 53	29-Aug-11	29-Sep-12
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	11-Jan-11	11-Jan-13
0768	Antenna Standard Gain Horn, 18-26.5 GHz, WR-42, 25 dB gain	Quinstar Technology	QWH-4200-BA	110	03-Feb-12	03-Feb-15
1984	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz, 300 W	EMC Test Systems	3115	9911-5964	25-Nov-11	25-Nov-12
2780	EMC analyzer, 100 Hz to 26.5 GHz	Agilent Technologies	E7405A	MY451024 62	07-Jul-11	07-Jul-12
2871	Microwave Cable Assembly, 18 GHz, 6.4 m, SMA - SMA	Huber-Suhner	198-8155-00	2871	15-Jan-12	15-Jan-13
2909	Spectrum analyzer, ESA-E, 100 Hz to 26.5 GHz	Agilent Technologies	E4407B	MY414447 62	08-May-11	08-May-12
3533	Amplifier, low noise, 6 to 18 GHz	Quinstar Technology	QLJ-06184040-J0	111590010 01	25-Dec-11	25-Dec-12
3535	Amplifier, low noise, 18 to 40 GHz	Quinstar Technology	QLJ-18404537-J0	111590030 01	11-Jul-11	11-Jul-12
3617	Cable RF, 6.5 m, N type-N type, DC-6.5 GHz	Suhner Switzerland	RG 214/U	NA	19-May-11	19-May-12
3810	Near-Field Probe Set, Hand held, 6 probes	EMC Test Systems	7405	9706-3927	29-Sept-11	29-Sept-12
3901	Microwave Cable Assembly, 40.0 GHz, 3.5 m, SMA/SMA	Huber-Suhner	SUCOFLEX 102A	1225/2A	07-Feb-11	07-Feb-12
4114	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz	ETS Lindgren	3117	00123515	23-Jan-12	23-Jan-13
4150	Preamplifier, 0.1 to 18 GHz, Gain 25 dB, N-type(f) in, N-type(m) out.	Agilent Technologies	87405C	MY470105 91	14-Jun-11	14-Jun-12



9 APPENDIX B Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB 12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB 150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 3 m measuring distance Horizontal polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB
Vertical polarization	Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.



10 APPENDIX C Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47), Registration Numbers 90624 for OATS and 90623 for the anechoic chamber; by Industry Canada for electromagnetic emissions (file numbers IC 2186A-1 for OATS, IC 2186A-2 for anechoic chamber, IC 2186A-3 for full-anechoic chamber for RE measurements above 1 GHz), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, G-27 for full-anechoic chamber for RE measurements above 1 GHz, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports), has a status of a Telefication - Listed Testing Laboratory, Certificate No. L138/00. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01). The FCC Designation Number is US1003.

Address: P.O. Box 23, Binyamina 30500, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, CEO.

11 APPENDIX D Specification references

FCC 47CFR part 15: 2010	Radio Frequency Devices
Public notice DA 00- 705: 2000	Filing and measurement guidelines for frequency hopping spread spectrum systems.
ANSI C63.2: 1996	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications
ANSI C63.4: 2003	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
RSS-210 Issue 8: 2010	Low Power Licence- Exempt Radiocommunication Devices
RSS-Gen Issue 3: 2010	General Requirements and Information for the Certification of Radiocommunication Equipment



12 APPENDIX E Test equipment correction factors

Antenna factor
Active loop antenna
Model 6502, S/N 2857, HL 0446

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field intensity in dB(μ V/m).

Antenna factor
Standard gain horn antenna
Quinstar Technology
Model QWH
Ser.No.110, HL 0768

Frequency min, GHz	Frequency max, GHz	Antenna factor, dB(1/m)
18.000	26.500	32.01
26.500	40.000	35.48
40.000	60.000	39.03
60.000	90.000	42.55
90.000	140.000	46.23
140.000	220.000	50.11

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).



Antenna factor
Biconilog antenna EMCO Model 3141
Ser.No.1011, HL 0604

Frequency, MHz	Antenna Factor, dB(1/m)
26	7.8
28	7.8
30	7.8
40	7.2
60	7.1
70	8.5
80	9.4
90	9.8
100	9.7
110	9.3
120	8.8
130	8.7
140	9.2
150	9.8
160	10.2
170	10.4
180	10.4
190	10.3
200	10.6
220	11.6
240	12.4
260	12.8
280	13.7
300	14.7
320	15.2
340	15.4
360	16.1
380	16.4
400	16.6
420	16.7
440	17.0
460	17.7
480	18.1
500	18.5
520	19.1
540	19.5
560	19.8
580	20.6
600	21.3
620	21.5
640	21.2
660	21.4
680	21.9
700	22.2
720	22.2
740	22.1
760	22.3
780	22.6
800	22.7
820	22.9
840	23.1
860	23.4
880	23.8
900	24.1
920	24.1

Frequency, MHz	Antenna Factor, dB(1/m)
940	24.0
960	24.1
980	24.5
1000	24.9
1020	25.0
1040	25.2
1060	25.4
1080	25.6
1100	25.7
1120	26.0
1140	26.4
1160	27.0
1180	27.0
1200	26.7
1220	26.5
1240	26.5
1260	26.5
1280	26.6
1300	27.0
1320	27.8
1340	28.3
1360	28.2
1380	27.9
1400	27.9
1420	27.9
1440	27.8
1460	27.8
1480	28.0
1500	28.5
1520	28.9
1540	29.6
1560	29.8
1580	29.6
1600	29.5
1620	29.3
1640	29.2
1660	29.4
1680	29.6
1700	29.8
1720	30.3
1740	30.8
1760	31.1
1780	31.0
1800	30.9
1820	30.7
1840	30.6
1860	30.6
1880	30.6
1900	30.6
1920	30.7
1940	30.9
1960	31.2
1980	31.6
2000	32.0

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μV) to convert it into field intensity in dB(μV/m).



Antenna factor
Double-ridged waveguide horn antenna
ETS Lindgren, Model 3117, serial number: 00123515, HL 4114

Frequency, MHz	Antenna factor, dB/m		
	Measured	Manufacturer	Deviation
1000	28.0	28.4	-0.4
1500	28.0	27.4	0.6
2000	31.2	30.9	0.3
2500	32.5	33.4	-0.9
3000	32.9	32.6	0.3
3500	32.7	32.8	-0.1
4000	33.1	33.4	-0.3
4500	33.8	33.9	-0.1
5000	33.8	34.1	-0.3
5500	34.4	34.5	-0.1
6000	35.0	35.2	-0.2
6500	35.4	35.5	-0.1
7000	35.7	35.7	0.0
7500	35.9	35.7	0.2
8000	35.8	35.8	0.0
8500	35.9	35.8	0.1
9000	36.3	36.2	0.1
9500	36.6	36.6	0.0
10000	37.1	37.1	0.0
10500	37.6	37.5	0.1
11000	37.9	37.7	0.2
11500	38.5	38.1	0.4
12000	39.2	38.7	0.5
12500	39.0	38.9	0.1
13000	39.1	39.1	0.0
13500	38.9	38.8	0.1
14000	39.0	38.8	0.2
14500	39.6	39.9	-0.3
15000	39.9	39.7	0.2
15500	39.9	40.1	-0.2
16000	40.7	40.8	-0.1
16500	41.3	41.8	-0.5
17000	42.5	42.1	0.4
17500	41.3	41.2	0.1
18000	41.4	40.9	0.5

Antenna factor is to be added to receiver meter reading in dB(μ V) to convert to field strength in dB(μ V/meter)



Cable loss
Cable coaxial, Huber-Suhner, 18 GHz, 6.4 m, SMA - SMA, model 198-8155-00,
HL 2871

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.12	5750	2.34	12000	3.55
30	0.14	6000	2.39	12250	3.61
100	0.27	6250	2.46	12500	3.67
250	0.45	6500	2.52	12750	3.74
500	0.63	6750	2.58	13000	3.79
750	0.76	7000	2.64	13250	3.82
1000	0.89	7250	2.68	13500	3.83
1250	1.01	7500	2.73	13750	3.83
1500	1.12	7750	2.78	14000	3.88
1750	1.23	8000	2.83	14250	3.93
2000	1.32	8250	2.88	14500	3.96
2250	1.41	8500	2.94	14750	4.01
2500	1.49	8750	2.97	15000	4.00
2750	1.58	9000	3.02	15250	4.01
3000	1.66	9250	3.07	15500	4.00
3250	1.73	9500	3.13	15750	4.13
3500	1.80	9750	3.18	16000	4.22
3750	1.87	10000	3.21	16250	4.29
4000	1.93	10250	3.26	16500	4.29
4250	2.01	10500	3.30	16750	4.32
4500	2.06	10750	3.36	17000	4.37
4750	2.12	11000	3.39	17250	4.45
5000	2.17	11250	3.44	17500	4.49
5250	2.24	11500	3.48	17750	4.53
5500	2.29	11750	3.52	18000	4.55



Cable loss
Cable coaxial, RG-214/U, N type-N type, 6.5 m
Suhner Switzerland, HL 3617

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.13	2200	2.97	4500	5.10
50	0.33	2300	3.06	4600	5.20
100	0.48	2400	3.16	4700	5.34
200	0.71	2500	3.23	4800	5.36
300	0.89	2600	3.34	4900	5.48
400	1.04	2700	3.42	5000	5.52
500	1.19	2800	3.52	5100	5.61
600	1.32	2900	3.61	5200	5.72
700	1.44	3000	3.69	5300	5.81
800	1.56	3100	3.80	5400	5.93
900	1.68	3200	3.86	5500	6.08
1000	1.80	3300	3.98	5600	6.12
1100	1.90	3400	4.07	5700	6.25
1200	2.00	3500	4.14	5800	6.31
1300	2.11	3600	4.27	5900	6.41
1400	2.21	3700	4.36	6000	6.51
1500	2.30	3800	4.47	6100	6.62
1600	2.40	3900	4.62	6200	6.73
1700	2.49	4000	4.63	6300	6.86
1800	2.61	4100	4.76	6400	6.94
1900	2.69	4200	4.83	6500	7.06
2000	2.79	4300	4.89		
2100	2.88	4400	5.04		



Cable loss
Microwave Cable Assembly, Huber-Suhner, 40 GHz, 3.5 m, SMA-SMA, S/N 1225/2A
HL 3901

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.09	9500	4.29	21000	6.67
100	0.41	10000	4.40	22000	6.92
500	0.93	10500	4.52	23000	7.00
1000	1.33	11000	4.64	24000	7.18
1500	1.63	11500	4.76	25000	7.29
2000	1.90	12000	4.87	26000	7.55
2500	2.12	12500	4.99	27000	7.70
3000	2.33	13000	5.11	28000	7.88
3500	2.50	13500	5.20	29000	8.02
4000	2.67	14000	5.31	30000	8.15
4500	2.82	14500	5.42	31000	8.35
5000	2.99	15000	5.51	32000	8.40
5500	3.16	15500	5.58	33000	8.62
6000	3.32	16000	5.68	34000	8.73
6500	3.51	16500	5.78	35000	8.78
7000	3.65	17000	5.91	36000	8.94
7500	3.79	17500	5.99	37000	9.21
8000	3.92	18000	6.07	38000	9.37
8500	4.04	19000	6.36	39000	9.45
9000	4.18	20000	6.49	40000	9.52



13 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
A/m	ampere per meter
AM	amplitude modulation
AVRG	average (detector)
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(μ V)	decibel referred to one microvolt
dB(μ V/m)	decibel referred to one microvolt per meter
dB(μ A)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
μ s	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
Ω	Ohm
PM	pulse modulation
PS	power supply
ppm	part per million (10^{-6})
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
WB	wideband

END OF DOCUMENT