

September 17, 2007

Andrew Leimer  
Andrew.Leimer@fcc.gov  
FCC Application Processing Branch

Applicant:	Aruba Networks, Inc.
FCC ID	Q9DAP6061SDR
Correspondence Reference Number	33782
731 Confirmation Number	EA297319
Date of Original E-Mail	09/14/2007

Question:

1) If not in filing already, as part of op desc exhibit, please describe transmit operations of each antenna configuration option (location and type for all antenna elements, diversity, beamforming, MIMO, etc)

Response:

1) This FCC ID is marketed as two models: the Aruba Access Point Model 60 (external antenna connectors, RP-SMA) and Model 61 (integral antenna).

The model 60 has two RP-SMA connectors which may be attached to the Aruba external antennas detailed in the application. The two antennas operate in diversity mode only with no other transmit modes possible.

The model 61 has two integrated antennas are located in the articulating section of the access point shown in Figure 1 below. The antennas operate in diversity mode only with no other transmit modes possible. The model 61 has no external antenna connectors accessible to the user.



FIGURE 1: Articulating Integrated Antennas, Model AP-61 (Q9DAP6061SDR)

Question:

2) RF exposure exhibit indicates distances closer than 20 cm - note that FCC RF exposure limits at closer than 20 cm are in terms of SAR not field strength or power density. Please revise RF exposure exhibit accordingly.

Response:

2) The RF exposure exhibit in the test report indicates calculation distances closer than 20cm. However in the same page of the report under Note: in the Specification, Maximum Permissible Exposure Limits it specifies that the “minimum separation distance is 20cm”, see highlighted area below.

**Specification**  
**Maximum Permissible Exposure Limits**

Devices are subject to the radio frequency radiation exposure requirements specified in §1.1307 (b), 2.1091 and 2.1093 as appropriate. All equipment shall be considered to operate in a “general population/uncontrolled” environment.

Limit S = 1mW / cm<sup>2</sup> from 1.310 Table 1

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

It is understood that this presentation may be subject to misinterpretation and therefore MiCOM Labs will amend how it reports the 20cm limit.

Question:

3) Submit an expanded plot of the Channel Closing Transmission Time. The scale should not exceed 600 ms. The purpose of this is to show that all data packets stop within 200 ms. The second requirement is that the control signals must not exceed 60ms total over the 10 second period after the radar signal ends. Your plot meets this requirement but I cannot distinguish between packets and control signals without the expanded plot.

Response:

The plot identifying the Channel Closing Transmission Time in Section 6.2.5 In-Service Monitoring etc. is only to be used as back-up information as this does not provide sufficient information. The digitized data extracted from the plot identifying the exact on/off time during the Channel Closing Time is real time and precise. Should control and data packets be required to be differentiated this

can be achieved through the data provided. Not sure how control and data signals can be differentiated, if this is possible please advise.

The NTIA were satisfied with MiCOM Labs DFS test and reporting methodology and this has not changed.