


7.6 Radiated Spurious Emissions

Test Procedure

Testing was performed in a 3-meter anechoic chamber. Preliminary radiated emissions were measured on every azimuth and with the receiving antenna in both horizontal and vertical polarizations. Preliminary emissions were recorded with in Spectrum Analyzer mode, using a maximum peak detector while in peak hold mode.


Emissions nearest the limits were chosen for maximization and formal measurement using a CISPR Compliant receiver. Emissions above 1000 MHz are measured utilizing a CISPR compliant average detector with a tuned receiver, using a bandwidth of 1 MHz. Emissions from 30 MHz – 1000 MHz are measured utilizing a CISPR compliant quasi-peak detector with a tuned receiver, using a bandwidth of 120 kHz. Only the highest emissions relative to the limit are listed.

Test Measurement Set Up



Radiated Emission Measurement Setup – Above 1 GHz

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Radiated Emission Measurement Setup – Below 1 GHz

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

FS = Field Strength

R = Measured Spectrum analyzer Input Amplitude

AF = Antenna Factor



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 198 of 372

CORR = Correction Factor = CL – AG + NFL

CL = Cable Loss

AG = Amplifier Gain

FO = Distance Falloff Factor

NFL = Notch Filter Loss or Waveguide Loss

Field Strength Calculation Example:

Given receiver input reading of 51.5 dB μ V; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dB}\mu\text{V/m}$$

Conversion between dB μ V/m (or dB μ V) and μ V/m (or μ V) are done as:

$$\text{Level (dB}\mu\text{V/m)} = 20 * \text{Log (level (\mu\text{V/m}))}$$

$$40 \text{ dB}\mu\text{V/m} = 100 \mu\text{V/m}$$

$$48 \text{ dB}\mu\text{V/m} = 250 \mu\text{V/m}$$

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 199 of 372

Specification

Radiated Spurious Emissions

FCC §15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section §15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(a)).

FCC §15.205 (a) Except as shown in paragraph (d) of 15.205 (a), only spurious emissions are permitted in any of the frequency bands listed.

FCC §15.205 (a) Except as shown in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

FCC §15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 200 of 372

Table 1: FCC 15.209 Spurious Emissions Limits

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance (meters)
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

Laboratory Measurement Uncertainty for Spectrum Measurement

Measurement Uncertainty	+5.6/ -4.5 dB
--------------------------------	---------------

Traceability:

Method	Test Equipment Used
Work instruction WI-03	0088, 0158, 0134, 0304, 0311, 0315, 0310, 0312

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 201 of 372

7.6.1 Integral Antenna - Transmitter Radiated Spurious Emissions – Above 1 GHz

2400 – 2483.5 MHz: 802.11b

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	37
Power Setting	12 in ART test utility	Press. (mBars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	P o l	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4824.042	64.7	4.5	-9.4	59.7	Peak Max	H	149	360	74.0	-14.3	Pass	RB
4824.042	58.2	4.5	-9.4	53.2	Average	H	149	360	54.0	-0.8	Pass	RB
7232.505	48.6	5.4	-5.3	48.8	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
9648.076	53.4	6.3	-3.4	56.4	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 202 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	12 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4874.048	56.9	4.5	-9.3	52.1	Average Max	H	104	360	54.0	-1.9	Pass	RB
4874.048	60.5	4.5	-9.3	55.7	Peak Max	H	104	360	74.0	-18.3	Pass	RB
7313.026	34.2	5.4	-5.0	34.7	Average Max	H	98	327	54	-19.3	Pass	RB
7313.026	46.7	5.4	-5.0	47.2	Peak Max	H	98	327	74	-26.8	Pass	RB
9748.114	52.7	6.4	-3.6	55.4	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 203 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	10.5 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4924.013	61.9	4.6	-9.1	57.4	Peak Max	H	98	356	74.0	-16.6	Pass	RB
4924.01293	57.5	4.6	-9.1	52.9	Average Max	H	98	356	54.0	-1.1	Pass	RB
7388.260	34.6	5.5	-4.8	35.3	Average Max	H	98	314	54	-18.7	Pass	RB
7388.260	47.4	5.5	-4.8	48.0	Peak Max	H	98	314	74	-26.0	Pass	RB
9848.041	52.4	6.4	-3.2	55.6	Peak [Scan]	H	> 20dB below fundamental					NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2400 – 2483.5 MHz: 802.11g

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	P o l	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4824.369	63.2	4.5	-9.4	58.2	Peak Max	H	164	358	74.0	-15.8	Pass	RB
4824.369	49.6	4.5	-9.4	44.6	Average Max	H	164	358	54.0	-9.4	Pass	RB
7231.864	53.0	5.4	-5.3	53.2	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 205 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4875.541	48.3	4.5	-9.3	43.5	Average Max	H	132	360	54.0	-10.5	Pass	RB
4875.541	63.0	4.5	-9.3	58.2	Peak Max	H	132	360	74.0	-15.8	Pass	RB
7312.745	40.4	5.4	-4.9	40.9	Average Max	H	98	322	54	-13.1	Pass	RB
7312.745	56.3	5.4	-4.9	56.8	Peak Max	H	98	322	74	-17.2	Pass	RB
9754.589	47.4	6.4	-3.7	50.1	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 206 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antennas	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4926.172	66.6	4.6	-9.1	62.2	Peak Max	H	98	360	74.0	-11.9	Pass	RB
4926.172	52.3	4.6	-9.1	47.8	Average Max	H	98	360	54.0	-6.2	Pass	RB
7383.207	38.9	5.5	-4.8	39.5	Average Max	H	157	329	54	-14.5	Pass	RB
7383.207	57.5	5.5	-4.8	58.1	Peak Max	H	157	329	74	-15.9	Pass	RB
9836.874	46.7	6.4	-3.2	49.9	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 207 of 372

2400 – 2483.5 MHz: 802.11n HT-20

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antenna	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4822.255	50.7	4.5	-9.4	45.7	Average	H	167	0	54.0	-8.3	Pass	RB
4822.255	64.2	4.5	-9.4	59.3	Peak	H	167	0	74.0	-14.7	Pass	RB
7234.910	50.4	5.4	-5.2	50.6	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
9653.306	47.6	6.3	-3.5	50.4	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 208 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antenna	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4877.595	47.6	4.5	-9.3	42.7	Average Max	H	118	0	54.0	-11.3	Pass	RB
4877.595	62.1	4.5	-9.3	57.2	Peak Max	H	118	0	74.0	-16.8	Pass	RB
7311.022	40.5	5.4	-4.9	41.0	Average Max	H	98	320	54	-13.0	Pass	RB
7311.022	57.1	5.4	-4.9	57.6	Peak Max	H	98	320	74	-16.4	Pass	RB
9754.309	47.8	6.4	-3.7	50.5	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 209 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	Integral Antenna	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4925.130	51.7	4.6	-9.1	47.2	Average Max	H	98	360	54.0	-6.8	Pass	RB
4925.13	65.6	4.6	-9.1	61.1	Peak Max	H	98	360	74.0	-12.9	Pass	RB
7386.693	41.7	5.5	-4.8	42.4	Average Max	H	98	25	54	-11.6	Pass	RB
7386.693	57.9	5.5	-4.8	58.5	Peak Max	H	98	25	74	-15.5	Pass	RB
9837.916	48.7	6.4	-3.2	52.0	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 210 of 372

2400 – 2483.5 MHz: 802.11n HT-40

Test Freq.	2422 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4861.002	51.1	4.5	-9.3	46.3	Average Max	H	98	346	54.0	-7.7	Pass	RB
4861.002	63.7	4.5	-9.3	58.9	Peak Max	H	98	346	74.0	-15.1	Pass	RB
4989.259	37.8	4.6	-9.1	33.3	Average Max	H	101	338	54	-20.8	Pass	RB
4989.259	55.9	4.6	-9.1	51.4	Peak Max	H	101	338	74	-22.6	Pass	RB
7299.760	51.2	5.4	-4.9	51.7	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 211 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4892.826	52.2	4.5	-9.3	47.4	Average Max	H	98	347	54.0	-6.6	Pass	RB
4892.826	64.4	4.5	-9.3	59.6	Peak Max	H	98	347	74.0	-14.4	Pass	RB
4988.497	56.0	4.6	-9.1	51.5	Peak Max	H	98	346	74	-22.5	Pass	RB
4988.497	38.0	4.6	-9.1	33.5	Average Max	H	98	346	54	-20.5	Pass	RB
7344.970	41.0	5.5	-5.0	41.5	Average Max	H	102	343	54	-12.6	Pass	RB
7344.970	54.3	5.5	-5.0	54.8	Peak Max	H	102	343	74	-19.2	Pass	RB
9793.828	46.9	6.4	-3.4	49.8	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 212 of 372

Test Freq.	2452 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4925.491	50.8	4.6	-9.1	46.3	Average Max	H	137	360	54.0	-7.7	Pass	RB
4925.491	63.3	4.6	-9.1	58.8	Peak Max	H	137	360	74.0	-15.2	Pass	RB
4988.577	36.0	4.6	-9.1	31.5	Average Max	H	115	360	54	-22.5	Pass	RB
4988.577	51.7	4.6	-9.1	47.2	Peak Max	H	115	360	74	-26.9	Pass	RB
7383.687	43.2	5.5	-4.8	43.8	Average Max	H	119	340	54	-10.2	Pass	RB
7383.687	57.2	5.5	-4.8	57.9	Peak Max	H	119	340	74	-16.2	Pass	RB
9835.752	46.9	6.4	-3.2	50.1	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 213 of 372

5725 – 5850 MHz: 802.11a

Test Freq.	5745 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	P o l	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5100.923	71.4	4.6	-8.8	67.1	Peak Max	H	99	0	74.0	-6.9	Pass	RB
5100.923	57.7	4.6	-8.8	53.5	Average Max	V	108	27	54.0	-0.5	Pass	RB
5427.375	67.7	4.6	-9.2	63.1	Peak Max	H	98	54	74	-10.9	Pass	RB
5427.375	54.4	4.6	-9.2	49.8	Average Max	H	98	54	54	-4.2	Pass	RB
6329.218	54.8	5.1	-6.6	53.3	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	
11489.569	56.2	6.8	-1.1	61.8	Peak Max	H	126	318	74	-12.2	Pass	RB
11489.569	42.3	6.8	-1.1	47.9	Average Max	H	126	318	54	-6.1	Pass	RB
17241.603	57.4	8.6	1.6	67.7	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 214 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	13.5 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5098.455	57.5	4.6	-8.8	53.4	Average	H	98	16	54.0	-0.6	Pass	RB
5098.455	71.1	4.6	-8.8	66.9	Peak	H	98	16	74.0	-7.1	Pass	RB
6375.391	53.1	5.1	-6.7	51.5	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
11570.781	41.6	6.8	-1.2	47.2	Average Max	H	98	325	54	-6.8	Pass	RB
11570.781	56.3	6.8	-1.2	61.9	Peak Max	H	98	325	74	-12.1	Pass	RB
17348.937	53.9	8.7	1.9	64.5	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 215 of 372

Test Freq.	5825 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	14 in ART test utility	Press. (m Bars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5099.809	70.8	4.6	-8.8	66.6	Peak Max	V	104	33	74.0	-7.4	Pass	RB
5099.809	57.6	4.6	-8.8	53.4	Average Max	V	104	33	54.0	-0.6	Pass	RB
5224.449	69.0	4.6	-9.4	64.2	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB
11648.958	37.8	6.8	-1.9	42.7	Average Max	H	109	83	54	-11.3	Pass	RB
11648.958	51.4	6.8	-1.9	56.4	Peak Max	H	109	83	74	-17.7	Pass	RB
17481.884	44.2	8.8	1.6	54.6	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 216 of 372

5725 – 5850 MHz: 802.11n HT-20

Test Freq.	5745 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	26
Power Setting	14 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
2493.377	55.0	3.0	-11.1	46.9	Peak Max	H	102	58	74.0	-27.1	Pass	RB
2493.377	38.3	3.0	-11.1	30.2	Average Max	H	102	58	54.0	-23.8	Pass	RB
5137.675	58.0	4.6	-9.3	53.3	Average Max	V	100	46	54	-0.7	Pass	RB
5137.675	71.0	4.6	-9.3	66.3	Peak Max	V	100	46	74	-7.7	Pass	RB
5241.122	70.0	4.6	-9.7	64.9	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	
5985.571	54.4	4.9	-8.3	51.1	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	
11494.639	38.3	6.8	-1.2	44.0	Average Max	V	100	353	54	-10.0	Pass	RB
11494.639	53.4	6.8	-1.2	59.0	Peak Max	V	100	353	74	-15.0	Pass	RB
17238.348	52.1	8.6	1.5	62.2	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 217 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	26
Power Setting	14 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5099.125	58.0	4.6	-8.8	53.8	Average Max	H	98	342	54.0	-0.2	Pass	RB
5099.125	71.0	4.6	-8.8	66.8	Peak Max	H	98	342	74.0	-7.2	Pass	RB
5415.802	55.6	4.6	-9.2	51.0	Average Max	H	142	21	54	-3.0	Pass	RB
5415.802	68.8	4.6	-9.2	64.2	Peak Max	H	142	21	74	-9.8	Pass	RB
6348.697	52.6	5.1	-7.0	50.7	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	
11568.737	38.9	6.8	-1.2	44.5	Average Max	H	98	326	54	-9.5	Pass	RB
11568.737	54.2	6.8	-1.2	59.8	Peak Max	H	98	326	74	-14.2	Pass	RB
17349.980	53.0	8.7	1.9	63.6	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 218 of 372

Test Freq.	5825 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	26
Power Setting	13.5 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5099.857	57.7	4.6	-8.8	53.5	Average	H	98	11	54.0	-0.5	Pass	RB
5099.857	71.5	4.6	-8.8	67.3	Peak	H	98	11	74.0	-6.7	Pass	RB
5986.052	52.1	4.9	-8.3	48.7	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
11646.032	50.6	6.8	-1.8	55.6	Peak Max	H	98	84	74	-18.4	Pass	RB
11646.032	36.6	6.8	-1.8	41.6	Average Max	H	98	84	54	-12.4	Pass	RB
17478.798	43.8	8.8	1.6	54.2	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non Restricted Band, Limit is 20dB below fundamental peak												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 219 of 372

5725 – 5850 MHz: 802.11n HT-40

Test Freq.	5755 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	36
Power Setting	13.5 in ART test utility	Press. (mBars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5097.234	57.2	4.6	-8.8	53.1	Average	H	98	17	54.0	-0.9	Pass	RB
5098.036	70.3	4.6	-8.8	66.1	Peak	H	98	17	74.0	-7.9	Pass	RB
6314.629	53.6	5.0	-6.8	51.8	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	
11500.040	49.0	6.8	-1.2	54.7	Peak Max	H	101	89	74	-19.3	Pass	RB
11500.040	36.1	6.8	-1.2	41.7	Average Max	H	101	89	54	-12.3	Pass	RB
17270.140	51.1	8.6	1.5	61.2	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 220 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	36
Power Setting	13.5 in ART test utility	Press. (mBars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5138.577	58.1	4.6	-9.3	53.4	Average	V	99	42	54.0	-0.7	Pass	RB
5138.577	71.7	4.6	-9.3	67.0	Peak	V	99	42	74.0	-7.0	Pass	RB
5973.948	52.4	4.9	-8.2	49.0	Peak [Scan]	H	> 20dB below fundamental				Pass	NRB
11573.387	49.0	6.8	-1.2	54.6	Peak Max	H	109	324	74	-19.4	Pass	RB
11573.387	35.5	6.8	-1.2	41.1	Average Max	H	109	324	54	-12.9	Pass	RB
17343.968	44.0	8.7	1.7	54.3	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non Restricted Band, Limit is 20dB below fundamental peak												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 221 of 372

Test Freq.	5815 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	36
Power Setting	14 in ART test utility	Press. (mBars)	1008
Antenna	Integral Antenna	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
5099.028	71.1	4.6	-8.8	66.9	Peak	H	98	19	74.0	-7.1	Pass	RB
5099.028	57.9	4.6	-8.8	53.8	Average	H	98	19	54.0	-0.2	Pass	RB
5411.062	55.9	4.6	-9.1	51.4	Average Max	H	129	17	54	-2.6	Pass	RB
5411.062	69.5	4.6	-9.1	65.0	Peak Max	H	129	17	74	-9.0	Pass	RB
5973.948	53.4	4.9	-8.2	50.0	Peak [Scan]	H	> 20dB below fundamental			Pass	NRB	
17443.848	47.7	8.7	2.0	58.4	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



7.6.2 Integral Antenna - Transmitter Band edge spurious emissions

2412 MHz - 802.11b; 2200 - 2390 MHz




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 223 of 372

2412 MHz - 802.11g; 2200 - 2390 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	72.62 dBµV	VBW	1 MHz	
	96.2 dBµV	2.38847695 GHz	SWT	60 s	Unit dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2412 MHz - 802.11n HT-20; 2200 - 2390 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	72.87 dBµV	VBW	1 MHz	
	96.2 dBµV	2.38543086 GHz	SWT	60 s	Unit dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2422 MHz - 802.11n HT-40; 2200 - 2390 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	71.88 dBµV	VBW	1 MHz	
	96.2 dBµV	2.38276553 GHz	SWT	60 s	Unit dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 226 of 372

2462 MHz - 802.11b; 2483.5 - 2500 MHz

 Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 96.2 dBV 63.09 dBV VBW 1 MHz
2.48743487 GHz SWT 60 s Unit dBV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11g; 2483.5 - 2500 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	73.41 dBµV	VBW	1 MHz	
	96.2 dBµV	2.48571543 GHz	SWT	60 s	Unit dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11n HT-20; 2483.5 - 2500 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	73.49 dBµV	VBW	1 MHz	
	96.2 dBµV	2.48452505 GHz	SWT	60 s	Unit dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2452 MHz - 802.11n HT-40; 2483.5 - 2500 MHz

	Ref Lvl	73.11 dBµV	RBW	1 MHz	RF Att	20 dB
	96.2 dBµV	2.48350000 GHz	VBW	1 MHz		
			SWT	60 s	Unit	dBµV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



5745 MHz - 802.11a; 5350 - 5460 MHz



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 66.01 dBV VBW 1 MHz
100 dBV 5.35529058 GHz SWT 60 s Unit dBV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



5745 MHz - 802.11n HT-20; 5350 - 5460 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	Ref Lvl	66.32 dBV	VBW	1 MHz	
	100 dBV	5.36653307 GHz	SWT	60 s	Unit dBV




This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



5755 MHz - 802.11n HT-40; 5350 - 5460 MHz

 **Marker 1 [T1]** RBW 1 MHz RF Att 20 dB
Ref Lvl 65.14 dBmV VBW 1 MHz
100 dBmV 5.36587174 GHz SWT 60 s Unit dBmV



Date: 30.MAR.2010 12:30:36

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 233 of 372

7.6.3 Integral Antenna - Transmitter Peak Emissions (RSS-210/RSS-GEN)

2400 – 2483.5 MHz: 802.11b

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	12 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2414.558	58.4	13.0	32.2	103.6	Peak [Scan]	H						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 234 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	12 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2439.658	57.8	13.0	32.2	103.0	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 235 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	10.5 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2459.571	58.8	13.0	32.3	104.0	Peak [Scan]	H						PK

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 236 of 372

2400 – 2483.5 MHz: 802.11g

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2415.562	65.9	13.0	32.2	111.1	Peak [Scan]	H						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 237 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2442.838	67.0	13.0	32.3	112.2	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 238 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	19.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2467.771	67.8	13.0	32.3	113.0	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 239 of 372

2400 – 2483.5 MHz: 802.11n HT-20

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11n; HT-20; 6.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2417.570	66.1	13.0	32.2	111.2	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 240 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n; HT-20; 6.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2443.005	66.5	13.0	32.3	111.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 241 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11n; HT-20; 6.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2457.730	67.4	13.0	32.3	112.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 242 of 372

2400 – 2483.5 MHz: 802.11n HT-40

Test Freq.	2422 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2426.774	63.5	13.0	32.2	108.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 243 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2442.503	64.5	13.0	32.3	109.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 244 of 372

Test Freq.	2452 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	20
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1009
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2456.224	64.1	13.0	32.3	109.3	Peak [Scan]	H						PK

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 245 of 372

5725 – 5850 MHz: 802.11a

Test Freq.	5745 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	18 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5737.776	65.2	14.8	35.0	114.9	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 246 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	13.5 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5790.130	62.4	14.8	35.0	112.1	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 247 of 372

Test Freq.	5825 MHz	Engineer	CSB
Variant	802.11a; 6 Mbs	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	14 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5828.206	61.8	14.8	35.0	111.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 248 of 372

5725 – 5850 MHz: 802.11n HT-20

Test Freq.	5745 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	14 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5749.549	62.6	14.8	35.0	112.3	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 249 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	13.5 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5787.375	62.4	14.8	35.0	112.2	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 250 of 372

Test Freq.	5825 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	13.5 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5820.441	60.3	14.8	35.0	110.1	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 251 of 372

5725 – 5850 MHz: 802.11n HT-40

Test Freq.	5755 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	13.5 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5751.804	59.2	14.8	35.0	108.9	Peak [Scan]	H						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 252 of 372

Test Freq.	5785 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	13.5 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5770.842	58.9	14.8	35.0	108.7	Peak [Scan]	H						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak Emission of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 253 of 372

Test Freq.	5815 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	20.5
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	35
Power Setting	14 in ART test utility	Press. (m Bars)	1010
Antenna	Integral Antennas	Duty Cycle (%)	100
Test Notes 1	Peak Emissions		
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
5805.912	58.7	14.8	35.0	108.5	Peak [Scan]	H						PK

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak Emission of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 254 of 372

7.6.4 AP-ANT-2 - Transmitter Radiated Spurious Emissions – Above 1 GHz

2400 – 2483.5 MHz: 802.11b

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum.(%)	42
Power Setting	6 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4824.011	61.4	4.5	-9.4	56.4	Peak	V	98	322	74.0	-17.6	Pass	RB
4823.967	58.3	4.5	-9.4	53.3	Average	V	98	322	54.0	-0.7	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 255 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	42
Power Setting	7.5 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4874.029	61.0	4.5	-9.3	56.1	Peak Max	V	98	317	74.0	-17.9	Pass	RB
4874.029	58.6	4.5	-9.3	53.8	Average Max	V	98	317	54.0	-0.2	Pass	RB
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non Restricted Band, Limit is 20dB below fundamental peak										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 256 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	42
Power Setting	7.0 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4924.037	62.1	4.6	-9.1	57.5	Peak Max	V	172	319	74.0	-16.5	Pass	RB
4923.987	57.4	4.6	-9.1	52.9	Average	V	172	319	54.0	-1.1	Pass	RB
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission NRB = Non Restricted Band, Limit is 20dB below fundamental peak												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 257 of 372

2400 – 2483.5 MHz: 802.11g

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	P o l	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4823.608	70.7	4.5	-9.4	65.7	Peak Max	V	98	316	74.0	-8.3	Pass	RB
4823.608	56.9	4.5	-9.4	51.9	Average Max	V	98	316	54.0	-2.1	Pass	RB
7235.752	48.0	5.4	-5.2	48.2	Peak [Scan]	V	> 20 dB below fundamental				Pass	NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 258 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4873.788	55.5	4.5	-9.3	50.7	Average Max	H	190	227	54.0	-3.3	Pass	RB
4873.788	69.4	4.5	-9.3	64.6	Peak Max	H	190	227	74.0	-9.4	Pass	RB
7310.035	42.0	5.4	-4.9	42.5	Average Max	V	98	10	54	-11.5	Pass	RB
7310.035	56.8	5.4	-4.9	57.4	Peak Max	V	98	10	74	-16.7	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 259 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4923.808	53.9	4.6	-9.1	49.3	Average Max	V	190	0	54.0	-4.7	Pass	RB
4923.808	67.9	4.6	-9.1	63.4	Peak Max	V	190	0	74.0	-10.6	Pass	RB
7385.070	39.5	5.5	-4.8	40.2	Average Max	V	116	11	54	-13.9	Pass	RB
7385.070	55.1	5.5	-4.8	55.8	Peak Max	V	116	11	74	-18.3	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 260 of 372

2400 – 2483.5 MHz: 802.11n HT-20

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4818.357	71.1	4.5	-9.3	66.2	Peak	V	100	0	74.0	-7.8	Pass	RB
4818.357	57.5	4.5	-9.3	52.6	Average	V	100	0	54.0	-1.4	Pass	RB
7237.675	58.2	5.4	-5.1	58.5	Peak [Scan]	V	> 20 dB below fundamental				Pass	NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 261 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4873.547	57.9	4.5	-9.3	53.1	Average Max	V	98	26	54.0	-0.9	Pass	RB
4873.547	71.1	4.5	-9.3	66.3	Peak Max	V	98	26	74.0	-7.7	Pass	RB
7310.060	50.2	5.4	-4.9	50.8	Average Max	V	106	16	54	-3.2	Pass	RB
7310.060	64.9	5.4	-4.9	65.4	Peak Max	V	106	16	74	-8.6	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 262 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	18 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-2	Duty Cycle (%)	100%
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4923.447	58.2	4.6	-9.1	53.6	Average Max	V	157	26	54.0	-0.4	Pass	RB
4923.447	72.4	4.6	-9.1	67.9	Peak Max	V	157	26	74.0	-6.2	Pass	RB
7389.259	46.3	5.5	-4.8	47.0	Average Max	V	180	12	54	-7.0	Pass	RB
7389.259	63.0	5.5	-4.8	63.7	Peak Max	V	180	12	74	-10.3	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 263 of 372

2400 – 2483.5 MHz: 802.11n HT-40

Test Freq.	2422 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4841.924	55.9	4.5	-9.4	51.0	Average Max	H	174	229	54.0	-3.0	Pass	RB
4841.924	69.2	4.5	-9.4	64.3	Peak Max	H	174	229	74.0	-9.7	Pass	RB
7272.666	44.4	5.4	-5.1	44.8	Average Max	V	153	0	54	-9.3	Pass	RB
7272.666	59.3	5.4	-5.1	59.6	Peak Max	V	153	0	74	-14.4	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 264 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4872.926	56.1	4.5	-9.3	51.3	Average Max	V	162	336	54.0	-2.7	Pass	RB
4872.926	69.9	4.5	-9.3	65.1	Peak Max	V	162	336	74.0	-8.9	Pass	RB
7308.017	47.4	5.4	-4.9	47.9	Average Max	V	136	8	54	-6.1	Pass	RB
7308.017	62.3	5.4	-4.9	62.9	Peak Max	V	136	8	74	-11.1	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 265 of 372

Test Freq.	2452 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1	EUT vertical on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4900.601	57.1	4.5	-9.3	52.3	Average Max	H	191	236	54.0	-1.7	Pass	RB
4900.601	71.7	4.5	-9.3	67.0	Peak Max	H	191	236	74.0	-7.0	Pass	RB
7363.046	45.7	5.5	-4.9	46.2	Average Max	V	115	14	54	-7.8	Pass	RB
7363.046	61.1	5.5	-4.9	61.7	Peak Max	V	115	14	74	-12.4	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



7.6.5 AP-ANT-2 - Transmitter Band edge spurious emissions

2412 MHz - 802.11b; 2200 - 2390 MHz

	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
Ref Lvl	72.03 dBµV	VBW	1 MHz		
100 dBµV	2.38923848 GHz	SWT	60 s	Unit	dBµV



Date: 1.JAN.1997 00:32:11

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 267 of 372

2412 MHz - 802.11g; 2200 - 2390 MHz



Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
100 dBV	72.13 dBV	VBW	1 MHz		
	2.38847695 GHz	SWT	60 s	Unit	dBV




Date: 28.APR.2010 10:18:34


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 268 of 372

2412 MHz - 802.11n HT-20; 2200 - 2390 MHz

 **Marker 1 [T1]** RBW 1 MHz RF Att 20 dB
Ref Lvl 73.39 dBV VBW 1 MHz
100 dBV 2.38885772 GHz SWT 60 s Unit dBV




Date: 28.APR.2010 10:26:22


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 269 of 372

2422 MHz - 802.11n HT-40; 2200 - 2390 MHz

 **Marker 1 [T1]** RBW 1 MHz RF Att 20 dB
Ref Lvl 70.71 dBV VBW 1 MHz
100 dBV 2.3900000 GHz SWT 60 s Unit dBV




Date: 28.APR.2010 10:36:36

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11b; 2483.5 - 2500 MHz

	Ref Lvl	61.07 dBV	RBW	1 MHz	RF Att	20 dB
	100 dBV	2.48862525 GHz	VBW	1 MHz		
			SWT	60 s	Unit	dBV




Date: 28.APR.2010 10:48:59

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11g; 2483.5 - 2500 MHz

	Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	100 dBV	69.91 dBV	VBW	1 MHz		
		2.48359920 GHz	SWT	60 s	Unit	dBV



Date: 28.APR.2010 10:59:27

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 273 of 372

2452 MHz - 802.11n HT-40; 2483.5 - 2500 MHz



Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
100 dBV	73.48 dBV	VBW	1 MHz		
	2.48366533 GHz	SWT	60 s	Unit	dBV



Date: 28.APR.2010 11:06:33

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 274 of 372

7.6.6 AP-ANT-2 - Transmitter Peak Emissions (RSS-210/RSS-GEN)

2400 – 2483.5 MHz: 802.11b

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	6 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2414.752	72.7	7.1	30.4	110.2	Peak [Scan]	V						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 275 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	7.5 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2440.080	72.9	7.2	30.5	110.5	Peak [Scan]	V						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 276 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	7 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2463.878	72.5	7.2	30.6	110.3	Peak [Scan]	V						PK

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 277 of 372

2400 – 2483.5 MHz: 802.11g

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	13 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2416.283	84.0	7.1	30.4	121.6	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 278 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	13 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2442.307	81.2	7.2	30.5	118.9	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 279 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	13 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2468.888	81.0	7.2	30.6	118.8	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 280 of 372

2400 – 2483.5 MHz: 802.11n HT-20

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2406.680	87.9	7.1	30.4	125.4	Peak [Scan]	V						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 281 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2440.776	86.4	7.2	30.5	124.0	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 282 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2469.305	85.2	7.2	30.6	123.0	Peak [Scan]	V						PK

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 283 of 372

2400 – 2483.5 MHz: 802.11n HT-40

Test Freq.	2422 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	PoI	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2413.499	84.2	7.1	30.4	121.7	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 284 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2432.287	83.7	7.1	30.5	121.3	Peak [Scan]	V						PK


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 PK = Peak emissions of Fundamental

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 285 of 372

Test Freq.	2452 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	18.5
Freq. Range	2400 - 2483.5 MHz	Rel. Hum. (%)	37
Power Setting	18 in art	Press. (m Bars)	1004
Antenna	AP-ANT-2	Duty Cycle (%)	100
Test Notes 1			
Test Notes 2			



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV/m	Margin dB	Pass /Fail	Comments
2465.965	83.0	7.2	30.6	120.8	Peak [Scan]	V						PK
Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission PK = Peak emissions of Fundamental												

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.




Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 286 of 372

7.6.7 AP-ANT-7 - Transmitter Radiated Spurious Emissions – Above 1 GHz

2400 – 2483.5 MHz: 802.11b

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	42
Power Setting	6 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4824.032	60.7	4.5	-9.4	55.7	Peak	V	100	104	74.0	-18.3	Pass	RB
4824.032	58.1	4.5	-9.4	53.2	Average	V	100	104	54.0	-0.9	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 287 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	42
Power Setting	6.5 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks


Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4873.956	60.4	4.5	-9.3	55.6	Peak	V	98	103	74.0	-18.4	Pass	RB
4873.956	57.9	4.5	-9.3	53.1	Average	V	98	103	54.0	-0.9	Pass	RB
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non Restricted Band, Limit is 20dB below fundamental peak										

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 288 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11b; 1 Mbs	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	42
Power Setting	7.0 in ART test utility	Press. (m Bars)	1000
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4924.057	60.4	4.6	-9.1	55.9	Peak Max	V	98	122	74.0	-18.2	Pass	RB
4924.057	57.3	4.6	-9.1	52.8	Average Max	V	98	122	54.0	-1.3	Pass	RB
Legend:		TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission										
		NRB = Non Restricted Band, Limit is 20dB below fundamental peak										


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 289 of 372

2400 – 2483.5 MHz: 802.11g

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	P o l	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4823.568	70.6	4.5	-9.4	65.6	Peak Max	V	101	104	74.0	-8.4	Pass	RB
4823.568	56.6	4.5	-9.4	51.7	Average Max	V	101	104	54.0	-2.3	Pass	RB
7236.885	60.0	5.4	-5.2	60.2	Peak	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 290 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4873.525	57.0	4.5	-9.3	52.2	Average Max	V	102	88	54.0	-1.9	Pass	RB
4873.525	71.0	4.5	-9.3	66.1	Peak Max	V	102	88	74.0	-7.9	Pass	RB
7307.500	44.4	5.4	-4.9	45.0	Average Max	V	129	117	54	-9.0	Pass	RB
7307.500	60.7	5.4	-4.9	61.3	Peak Max	V	129	117	74	-12.8	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 291 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11g; 6 Mbs	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	13 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4923.530	57.2	4.6	-9.1	52.7	Average Max	V	98	116	54.0	-1.3	Pass	RB
4923.53	71.5	4.6	-9.1	66.9	Peak Max	V	98	116	74.0	-7.1	Pass	RB
7381.082	40.8	5.5	-4.8	41.4	Average Max	V	98	116	54	-12.6	Pass	RB
7381.082	59.7	5.5	-4.8	60.3	Peak Max	V	98	116	74	-13.7	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 292 of 372

2400 – 2483.5 MHz: 802.11n HT-20

Test Freq.	2412 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	16 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4823.136	71.2	4.5	-9.4	66.3	Peak	V	98	121	74.0	-7.7	Pass	RB
4823.136	58.0	4.5	-9.4	53.1	Average	V	98	121	54.0	-0.9	Pass	RB
7233.788	62.5	5.4	-5.2	62.7	Peak [Scan]	V	> 20dB below fundamental				Pass	NRB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 293 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	16 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4872.876	58.5	4.5	-9.3	53.7	Average Max	V	98	129	54.0	-0.3	Pass	RB
4872.876	72.9	4.5	-9.3	68.1	Peak Max	V	98	129	74.0	-5.9	Pass	RB
7310.461	48.7	5.4	-4.9	49.3	Average Max	V	98	119	54	-4.7	Pass	RB
7310.461	66.1	5.4	-4.9	66.7	Peak Max	V	98	119	74	-7.3	Pass	RB
9737.956	46.3	6.4	-3.5	49.2	Peak [Scan]	V	> 20dB below fundamental			Pass	NRB	


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 294 of 372

Test Freq.	2462 MHz	Engineer	CSB
Variant	802.11n HT-20; 6.5 MCS	Temp (°C)	21
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	37
Power Setting	15.5 in ART test utility	Press. (m Bars)	1003
Antenna	AP-ANT-7	Duty Cycle (%)	100%
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4922.555	73.1	4.6	-9.1	68.5	Peak Max	V	98	121	74.0	-5.5	Pass	RB
4922.556	58.0	4.6	-9.1	53.4	Average	V	98	121	54.0	-0.6	Pass	RB
7382.044	46.9	5.5	-4.8	47.6	Average Max	V	98	116	54	-6.4	Pass	RB
7382.044	62.9	5.5	-4.8	63.5	Peak Max	V	98	116	74	-10.5	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 295 of 372

2400 – 2483.5 MHz: 802.11n HT-40

Test Freq.	2422 MHz	Engineer	CSB
Variant	802.11n HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-7	Duty Cycle (%)	100
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4842.991	70.7	4.5	-9.4	65.8	Peak Max	V	98	124	74.0	-8.2	Pass	RB
4842.991	57.3	4.5	-9.4	52.4	Average Max	V	98	124	54.0	-1.6	Pass	RB
7275.271	47.8	5.4	-5.1	48.1	Average Max	V	106	118	54	-5.9	Pass	RB
7275.271	64.1	5.4	-5.1	64.4	Peak Max	V	106	118	74	-9.6	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 296 of 372

Test Freq.	2437 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-7	Duty Cycle (%)	100
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4870.982	67.3	4.5	-9.3	62.5	Peak Max	V	169	119	74.0	-11.5	Pass	RB
4870.982	53.5	4.5	-9.3	48.7	Average Max	V	169	119	54.0	-5.3	Pass	RB
7308.537	48.3	5.4	-4.9	48.8	Average Max	V	98	119	54	-5.2	Pass	RB
7308.537	63.3	5.4	-4.9	63.9	Peak Max	V	98	119	74	-10.1	Pass	RB


Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 297 of 372

Test Freq.	2452 MHz	Engineer	CSB
Variant	802.11n; HT-40; 13.5 MCS	Temp (°C)	19
Freq. Range	1000 MHz - 18000 MHz	Rel. Hum. (%)	36
Power Setting	18 in ART test utility	Press. (m Bars)	1008
Antenna	AP-ANT-7	Duty Cycle (%)	100
Test Notes 1	EUT Horizontal on table.		
Test Notes 2	Fundamental attenuated by notch filter		



Formally measured emission peaks

Frequency MHz	Raw dBuV	Cable Loss	AF dB	Level dBuV	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBuV	Margin dB	Pass /Fail	Comments
4902.575	57.4	4.5	-9.3	52.6	Average Max	V	110	118	54.0	-1.4	Pass	RB
4902.575	70.6	4.5	-9.3	65.8	Peak Max	V	110	118	74.0	-8.2	Pass	RB
7350.942	48.4	5.5	-4.9	48.9	Average Max	V	98	112	54	-5.1	Pass	RB
7350.942	64.6	5.5	-4.9	65.1	Peak Max	V	98	112	74	-8.9	Pass	RB

Legend: TX = Transmitter Emissions; DIG = Digital Emissions; FUND = Fundamental; WB = Wideband Emission
 NRB = Non Restricted Band, Limit is 20dB below fundamental peak


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2412 MHz - 802.11g; 2200 - 2390 MHz



Marker 1 [T1] RBW 1 MHz RF Att 20 dB
Ref Lvl 69.44 dBV VBW 1 MHz
100 dBV 2.3900000 GHz SWT 60 s Unit dBV



Date: 28.APR.2010 12:07:21


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 300 of 372

2412 MHz - 802.11n HT-20; 2200 - 2390 MHz

	Ref Lvl	70.92 dBV	RBW	1 MHz	RF Att	20 dB
	100 dBV	2.39000000 GHz	VBW	1 MHz		
			SWT	60 s	Unit	dBV





Date: 28.APR.2010 11:58:59

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2422 MHz - 802.11n HT-40; 2200 - 2390 MHz

 **Marker 1 [T1]** RBW 1 MHz RF Att 20 dB
Ref Lvl 72.47 dBV VBW 1 MHz
100 dBV 2.3900000 GHz SWT 60 s Unit dBV




Date: 28.APR.2010 12:15:01

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11b; 2483.5 - 2500 MHz

	Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	100 dBV	67.21 dBV	VBW	1 MHz		
		2.49679259 GHz	SWT	60 s	Unit	dBV




Date: 28.APR.2010 11:34:10


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



Title: Aruba AP-92/93 802.11a/b/g/n Wireless AP
To: FCC 47 CFR Part 15.247 & IC RSS-210
Serial #: ARUB51-U1 Rev A
Issue Date: 18th May 2010
Page: Page 303 of 372

2462 MHz - 802.11g; 2483.5 - 2500 MHz

 **Marker 1 [T1]** RBW 1 MHz RF Att 20 dB
Ref Lvl 68.83 dBV VBW 1 MHz
100 dBV 2.48753407 GHz SWT 60 s Unit dBV




Date: 28.APR.2010 11:39:31

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2462 MHz - 802.11n HT-20; 2483.5 - 2500 MHz

	Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	100 dBV	69.76 dBV	VBW	1 MHz		
		2.48392986 GHz	SWT	60 s	Unit	dBV




Date: 28.APR.2010 11:44:22

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.



2452 MHz - 802.11n HT-40; 2483.5 - 2500 MHz

	Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	20 dB
	100 dBV	73.20 dBV	VBW	1 MHz		
		2.48350000 GHz	SWT	60 s	Unit	dBV



Date: 28.APR.2010 11:47:33

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. Any changes will be noted in the Document History section of the report.